

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Date of issue:01/06/2018 Revision date:03/05/2019 Supersedes: 19/11/2018 Version: 2.2

SECTION 1: Identification: Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture

Trade name : 2K RAPTOR BLACK AEROSOL

Product code : RLB/AL

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : coatings

1.4. Supplier's details

Supplier

U-POL AUSTRALIA PTY LIMITED Unit A, 16 - 20 Cassola Place Penrith, NSW 2750 - Australia T 02 4731 2655 - F 02 4731 2611 info@u-pol.co.nz - www.u-pol.com.au Supplier

U-POL NEW ZEALAND LIMITED
c/o Lindsay & Associates
Unit H, 12 Amera Place, East Tamaki
Manukau City 2013 - New Zealand
T + 612 4731 2655 - F + 612 4731 2611
technicalsupport@u-pol.com - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800

764 766

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1 H222
Serious eye damage/eye irritation, Category 2A H319
Skin sensitisation, Category 1 H317

2.2. Label elements

Hazard pictograms (GHS AU)





Signal word (GHS AU) : Danger

Contains : hexamethylene diisocyanate oligomers (5 - 15 %); reaction mass of α -3-(3-(2H-benzotriazol-2-

yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (< 5 %); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (< 5

%)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Precautionary statements (GHS AU) : P210 - Keep away from heat, open flames, sparks, hot surfaces. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, spray, fume.

P280 - Wear eye protection, protective gloves, protective clothing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

03/05/2019 EN (English) 1/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
hexamethylene diisocyanate oligomers ()	28182-81-2	5 - 15	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) ()	104810-47-1	< 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ()	1065336-91-5	< 5	Acute Tox. 5 (Oral), H303 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Other substances (not contributing to the classification of this product)		99.43 - 99.61	

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes. Avoid breathing vapours, spray, fume.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid

breathing vapours, spray, fume. Wear personal protective equipment.

03/05/2019 EN (English) 2/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Hygiene measures

: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

Exposure limit values for the other components

acetone (67-64-1)			
Australia	Local name	Acetone	
Australia	TWA (mg/m³)	1185 mg/m³	
Australia	TWA (ppm)	500 ppm	
Australia	STEL (mg/m³)	2375 mg/m³	
Australia	STEL (ppm)	1000 ppm	
New Zealand	Local name	Acetone	
New Zealand	TWA (mg/m³)	1185 mg/m³	
New Zealand	TWA (ppm)	500 ppm	
New Zealand	STEL (mg/m³)	2375 mg/m³	
New Zealand	STEL (ppm)	1000 ppm	
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition	

carbon black (1333-86-4)	carbon black (1333-86-4)		
Australia	Local name	Carbon black	
Australia	TWA (mg/m³)	3 mg/m³	
New Zealand	Local name	Carbon black	
New Zealand	TWA (mg/m³)	3 mg/m³	
New Zealand	Remark (NZ)	6.7B (Suspected carcinogen)	
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition	

cristobalite, 1%≤conc respirable crystalline silica<10% (14464-46-1)			
Australia	Local name	Cristobalite (respirable dust)	
Australia	TWA (mg/m³)	0.1 mg/m³	
Australia	Remark (AU)	See Silica - Crystalline	

n-butyl acetate (123-86-4)			
Australia	Local name	n-Butyl acetate	
Australia	TWA (mg/m³)	713 mg/m³	
Australia	TWA (ppm)	150 ppm	
Australia	STEL (mg/m³)	950 mg/m³	
Australia	STEL (ppm)	200 ppm	
New Zealand	Local name	n-Butyl acetate	
New Zealand	TWA (mg/m³)	713 mg/m³	
New Zealand	TWA (ppm)	150 ppm	
New Zealand	STEL (mg/m³)	950 mg/m³	
New Zealand	STEL (ppm)	200 ppm	
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition	

ethylbenzene (100-41-4)

03/05/2019 EN (English) 3/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

according to the Model Work Hea	cording to the Model Work Health and Safety Regulations		
ethylbenzene (100-41-4)			
Australia	Local name	Ethyl benzene	
Australia	TWA (mg/m³)	434 mg/m³	
Australia	TWA (ppm)	100 ppm	
Australia	STEL (mg/m³)	543 mg/m³	
Australia	STEL (ppm)	125 ppm	
New Zealand	Local name	Ethyl benzene	
New Zealand	TWA (mg/m³)	434 mg/m³	
New Zealand	TWA (ppm)	100 ppm	
New Zealand	STEL (mg/m³)	543 mg/m³	
New Zealand	STEL (ppm)	125 ppm	
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition	
2-methoxy-1-methylethy	I acetate (108-65-6)		
Australia	Local name	1-Methoxy-2-propanol acetate	
Australia	TWA (mg/m³)	274 mg/m³	
Australia	TWA (ppm)	50 ppm	
Australia	STEL (mg/m³)	548 mg/m³	
Australia	STEL (ppm)	100 ppm	
Australia	Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.	
dimethyl ether (115-10-6))		
Australia	Local name	Dimethyl ether	
Australia	TWA (mg/m³)	760 mg/m³	
Australia	TWA (ppm)	400 ppm	
Australia	STEL (mg/m³)	950 mg/m³	
Australia	STEL (ppm)	500 ppm	
New Zealand	Local name	Dimethylether	
New Zealand	TWA (mg/m³)	766 mg/m³	
New Zealand	TWA (ppm)	400 ppm	
New Zealand	STEL (mg/m³)	958 mg/m³	
New Zealand	STEL (ppm)	500 ppm	
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition	
1,6-diisocyanatohexane	(822-06-0)		
Australia	Local name	Hexamethylene diisocyanate	
Australia	TWA (mg/m³)	0.02 mg/m³	
Australia	STEL (mg/m³)	0.07 mg/m³	
Australia	Remark (AU)	Sen - Respiratory and/or Skin Sensitiser.	
	n-butyl acetate (123-86-4)		
Australia	Local name	n-Butyl acetate	
Australia	TWA (mg/m³)	713 mg/m³	
Australia	TWA (ppm)	150 ppm	
Australia	STEL (mg/m³)	950 mg/m³	
Australia	STEL (ppm)	200 ppm	
New Zealand	Local name	n-Butyl acetate	
New Zealand	TWA (mg/m³)	713 mg/m³	

03/05/2019 EN (English) 4/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

n-butyl acetate (123-86-4)			
New Zealand	TWA (ppm)	150 ppm	
New Zealand	STEL (mg/m³)	950 mg/m³	
New Zealand	STEL (ppm)	200 ppm	
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition	

quartz (14808-60-7)			
Australia	Local name	Quartz [Silica – Crystalline]	
Australia	TWA (mg/m³)	0.1 mg/m³ respirable sizes	
Australia	Remark (AU)	See Silica - Crystalline	

calcium carbonate (471-34-1)			
Australia	Local name	Calcium carbonate (Limestone; Marble; Whiting)	
Australia	TWA (mg/m³)	10 mg/m³	
Australia	Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.	
New Zealand	Local name	Calcium carbonate (Limestone) (Marble)	
New Zealand	TWA (mg/m³)	10 mg/m³	
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition	

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

Hand protection : Protective gloves

Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Air-Purifying Respirator (APR), reusable	Filter A2/B2		

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance

Aerosol.

Colour : No data available
Odour : No data available
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available

03/05/2019 EN (English) 5/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Melting point / Freezing point : Melting point : Not applicable

Boiling point : $-24 \, ^{\circ}\text{C}$ Flash point : $< 0 \, ^{\circ}\text{C}$

Auto-ignition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative density : No data available
Density : Density : 0.947 g/cm³
Solubility : No data available
Log Pow : No data available

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : No data available Minimum ignition energy : No data available

VOC content : 526 g/l

VOC content - Regulatory : No data available

SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.Extremely flammable

aerosol. Pressurised container: May burst if heated.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)		
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)	
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)	
LC50 inhalation rat (mg/l)	5800 mg/l (OECD Guideline 403, 14d, rat)	

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)		
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)	
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across.	

examethylene diisocyanate oligomers (28182-81-2)	
LD50 oral rat	> 2500 mg/kg (OECD Test Guideline 423, rat, female)
LD50 dermal rat	> 2000 mg/kg (OECD Test Guideline 402, rat, male/female)
LC50 inhalation rat (Dust/Mist - mg/l/4h)	0.39 mg/l/4h (OECD Test Guideline 403, rat, female, inhalation, dust/mist)

Skin corrosion/irritation : Not classified

Germ cell mutagenicity

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

: Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

2K RAPTOR BLACK AEROSOL	
/aporizer	Aerosol

03/05/2019 EN (English) 6/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

eaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H- enzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- ydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)	
LC50 fish 1	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	2658 - 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Log Pow	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology

12.4. Mobility in soil

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)	
Log Pow	See section 12.1 on ecotoxicology

12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

2K RAPTOR BLACK AEROSOL

Fluorinated greenhouse gases False

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)

Fluorinated greenhouse gases False

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

Fluorinated greenhouse gases

False

hexamethylene diisocyanate oligomers (28182-81-2)

Fluorinated greenhouse gases False

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1950 UN-No. (IMDG) : 1950 UN-No. (IATA) : 1950

14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : AEROSOLS

03/05/2019 EN (English) 7/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

: AEROSOLS Proper Shipping Name (IMDG) Proper Shipping Name (IATA) : Aerosols, flammable

Transport hazard class(es) 14.3.

ADG

Transport hazard class(es) (ADG) : 2.1 Danger labels (ADG) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1 Danger labels (IMDG) 2.1



IATA

Transport hazard class(es) (IATA) : 2.1 2.1

Hazard labels (IATA)



14.4. **Packing group**

Packing group (ADG) : Not applicable Packing group (IMDG) : Not applicable : Not applicable Packing group (IATA)

14.5. **Environmental hazards**

: No Marine pollutant

Special precautions for user

Specific storage requirement : No data available Shock sensitivity : No data available

14.7. **Additional information**

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

Special provision (ADG) : 63, 190, 277, 327, 344

Limited quantities (ADG) : See SP 277 Packing instructions (ADG) : P207, LP02 Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

03/05/2019 EN (English) 8/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None

Air transport

UN-No. (IATA) : 1950 PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Y203 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 203 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchemcode : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515 Group standard : Aerosols

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 03/05/2019

Classification:

Flam. Aerosol 1	H222
Eye Irrit. 2A	H319
Skin Sens. 1	H317

Full text of H-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H222	Extremely flammable aerosol.
H303	May be harmful if swallowed
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

SDS Australia U-POL

03/05/2019 EN (English) 9/10

Safety Data Sheet

according to the Model Work Health and Safety Regulations

For professional use only.
The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive The information contained within this safety Data Sneet (SDS) is believed to be correct as of the date issued invever it is subject to change from time to time. It does not purport to be an inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.

03/05/2019 EN (English) 10/10