



DRIVING SURFACE PERFECTION

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet HIGHVGAL-US-SDS

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 08/12/2015

Revision date: 08/29/2019

Supersedes: 03/11/2019

Version: 4.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL
 UP Number : UP0791V

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coatings and paints, thinners, paint removers
 Recommended use : Primer

1.3. Supplier

U-POL US Inc
 108 Commerce Way
 Easton, PA 18040 - United States
 T 1-800-340-7824 - F 1-800-787-5150
technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 1	Extremely flammable aerosol
Gases under pressure Liquefied gas	Contains gas under pressure; may explode if heated
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Skin sensitization, Category 1	May cause an allergic skin reaction
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity — Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Extremely flammable aerosol
 Contains gas under pressure; may explode if heated
 May cause an allergic skin reaction
 Causes serious eye irritation
 May cause drowsiness or dizziness
 Suspected of causing cancer

Precautionary statements (GHS US) :

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear eye protection, protective clothing, protective gloves.
 If on skin: Wash with plenty of water.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

If exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

2.4. Unknown acute toxicity (GHS US)

33.7% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
ethyl methyl ketone	(CAS-No.) 78-93-3	23 – 43	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
methyl acetate	(CAS-No.) 79-20-9	5 – 23	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
talc	(CAS-No.) 14807-96-6	5 – 23	Carc. 2, H351
cyclohexane	(CAS-No.) 110-82-7	< 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
acetone	(CAS-No.) 67-64-1	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
carbon black	(CAS-No.) 1333-86-4	< 5	Carc. 2, H351
fatty acids, C14-18 and C16-18-unsatd., maleated	(CAS-No.) 85711-46-2	< 5	Skin Irrit. 2, H315 Skin Sens. 1, H317
Ethylbenzene	(CAS-No.) 100-41-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Reactivity : Extremely flammable aerosol.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapors, spray, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Collect spillage.
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, spray, fume. Avoid contact with skin and eyes.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Keep container tightly closed. Keep cool.
Storage temperature : < 25 °C
Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethyl methyl ketone (78-93-3)		
ACGIH	Local name	Methyl ethyl ketone (MEK)
ACGIH	ACGIH OEL TWA [ppm]	200 ppm
ACGIH	ACGIH OEL STEL [ppm]	300 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; CNS & PNS impair. Notations: BEI

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethyl methyl ketone (78-93-3)		
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	590 mg/m ³
OSHA	OSHA PEL (TWA) [2]	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	3.5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
acetone (67-64-1)		
ACGIH	Local name	Acetone
ACGIH	ACGIH OEL TWA [ppm]	250 ppm
ACGIH	ACGIH OEL STEL [ppm]	500 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	2400 mg/m ³
OSHA	OSHA PEL (TWA) [2]	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
methyl acetate (79-20-9)		
ACGIH	Local name	Methyl acetate
ACGIH	ACGIH OEL TWA [ppm]	200 ppm
ACGIH	ACGIH OEL STEL [ppm]	250 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	610 mg/m ³
OSHA	OSHA PEL (TWA) [2]	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
cyclohexane (110-82-7)		
ACGIH	Local name	Cyclohexane
ACGIH	ACGIH OEL TWA [ppm]	100 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: CNS impair
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	1050 mg/m ³
OSHA	OSHA PEL (TWA) [2]	300 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)		
Not applicable		
Ethylbenzene (100-41-4)		
ACGIH	Local name	Ethylbenzene
ACGIH	ACGIH OEL TWA [ppm]	20 ppm

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)		
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	435 mg/m ³
OSHA	OSHA PEL (TWA) [2]	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
talc (14807-96-6)		
ACGIH	Local name	Talc
ACGIH	ACGIH OEL TWA	2 mg/m ³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica)
ACGIH	ACGIH OEL TWA [ppm]	0.1 fibers/cm ³ (Containing asbestos fibers. F - Respirable fibers)
ACGIH	Remark (ACGIH)	Containing no asbestos fibers = TLV® Basis: Pulm fibrosis; pulm func. Notations: A4 Containing asbestos fibers = TLV® Basis: Pneumoconiosis; lung cancer; mesothelioma. Notations: A1 (Confirmed Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [2]	20 mppcf
OSHA	Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Materials for protective clothing:

Impermeable clothing

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: aerosol.
Color	: Gray
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Odourless Commercial/unpurified substance: unpleasant odour Fruity odour Mild odour Ether-like odour Pleasant odour Aromatic odour Peppermint odour Irritating/pungent odour Petroleum-like odour Sweet odour Acetone odour Commercial/unpurified substance: irritating/pungent odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.777 g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
No data available	Viscosity, kinematic : No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

As Packaged Regulatory VOC	: 612 g/l (5.1 lbs/gal)
As Packaged Actual VOC	: 612 g/l (5.1 lbs/gal)
As Applied Regulatory VOC	: 612 g/l (5.1 lbs/gal)
As Applied Actual VOC	: 612 g/l (5.1 lbs/gal)
Water Content	: 0 wt%
Volatiles	: 78.8 wt%
% EPA HAPS	: 33.6 wt%
Percent Solids	: 21.24 wt%
Percent Solids	: 7.77 vol %
Maximum Incremental Reactivity (MIR)	: 0.84
MIR EPA Aerosol Category	: Auto Body Primer - ABP 1.55
MIR CARB Aerosol Category	: Auto Body Primer - Specialty Coatings (A) - ABP 0.95

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Unknown acute toxicity (GHS US)	33.7% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))
ethyl methyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE US (oral)	2193 mg/kg body weight
carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l
ATE US (oral)	6482 mg/kg body weight
ATE US (vapors)	49 mg/l/4h
ATE US (dust, mist)	49 mg/l/4h
cyclohexane (110-82-7)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 32.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)	
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15432 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

talc (14807-96-6)	
IARC group	3 - Not classifiable, 2B - Possibly carcinogenic to humans

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

ethyl methyl ketone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

methyl acetate (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.

cyclohexane (110-82-7)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

methyl acetate (79-20-9)	
LOAEC (inhalation, rat, vapor, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapor, 90 days)	1057 mg/m ³

fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)	
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

ethyl methyl ketone (78-93-3)	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

methyl acetate (79-20-9)	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna

cyclohexane (110-82-7)	
LC50 - Fish [1]	4.53 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.9 mg/l Test organisms (species): Daphnia magna
ErC50 algae	9.317 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)

fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)	
LC50 - Fish [1]	≥ 1.17 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 5.3 mg/l Test organisms (species): Daphnia magna

Ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

talc (14807-96-6)	
LC50 - Fish [1]	89581 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)

12.2. Persistence and degradability

ethyl methyl ketone (78-93-3)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O ₂ /g substance
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance
ThOD	2.44 g O ₂ /g substance

carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)	
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)
methyl acetate (79-20-9)	
Persistence and degradability	Readily biodegradable in water.
cyclohexane (110-82-7)	
Persistence and degradability	Non degradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.22 g O ₂ /g substance
ThOD	3.425 g O ₂ /g substance
Ethylbenzene (100-41-4)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
talc (14807-96-6)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

ethyl methyl ketone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.
acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.
methyl acetate (79-20-9)	
BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
cyclohexane (110-82-7)	
BCF - Fish [1]	167 (Pimephales promelas, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.44 (Experimental value, Other, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Ethylbenzene (100-41-4)	
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)	
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
talC (14807-96-6)	
BCF - Other aquatic organisms [1]	3.162 l/kg (BCFBAF v3.01, Fresh water, QSAR)
Partition coefficient n-octanol/water (Log Pow)	-9.4 (QSAR, KOWWIN, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

ethyl methyl ketone (78-93-3)	
Surface tension	0.024 N/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.53 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.
carbon black (1333-86-4)	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.
acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.
methyl acetate (79-20-9)	
Surface tension	24 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.
cyclohexane (110-82-7)	
Surface tension	0.025 N/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.89 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil.
Ethylbenzene (100-41-4)	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.
talC (14807-96-6)	
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

SECTION 13: Disposal considerations

13.1. Disposal methods

- Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description (DOT) : UN1950 Aerosols (flammable), 2.1

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols
flammable
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
Emergency Response Guide (ERG) Number : 126
Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description (TDG) : UN1950 AEROSOLS (flammable), 2.1
UN-No. (TDG) : UN1950
Proper Shipping Name (TDG) : AEROSOLS
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index : 1 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

Transport by sea

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1
UN-No. (IMDG) : 1950
Proper Shipping Name (IMDG) : AEROSOLS
Class (IMDG) : 2 - Gases

Air transport

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1
UN-No. (IATA) : 1950
Proper Shipping Name (IATA) : Aerosols, flammable
Class (IATA) : 2 - Gases

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

cyclohexane	CAS-No. 110-82-7	< 5%
Ethylbenzene	CAS-No. 100-41-4	< 5%

ethyl methyl ketone (78-93-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ 5000 lb

methyl acetate (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

cyclohexane (110-82-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ 1000 lb

fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag PMN - PMN - indicates a commenced PMN substance.

Ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 1000 lb

talc (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

ethyl methyl ketone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

cyclohexane (110-82-7)

Listed on the Canadian DSL (Domestic Substances List)

fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

talc (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

Ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

⚠ WARNING: This product can expose you to carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
carbon black(1333-86-4)	X					
Ethylbenzene(100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	

Component	State or local regulations
carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
talc(14807-96-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Ethylbenzene(100-41-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
ethyl methyl ketone(78-93-3)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
cyclohexane(110-82-7)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
methyl acetate(79-20-9)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
acetone(67-64-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Revision date : 08/29/2019

HIGH #5 HIGH BUILD PRIMER FILLER GRAY AEROSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
- NFPA reactivity : 3 - Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction but that require a strong initiating source or must be heated under confinement before initiation.



SDS US GHS (GHS HazCom2012)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.