



UP2001 FISH EYE ELIMINATOR

COMMON CAUSES OF "FISH EYES"	<ol style="list-style-type: none">1. Oil, wax, grease or silicone contamination.2. Contaminated air lines.3. Polishes, aerosol spray that contain silicone (some interior cleaners).4. Contamination by overspray of an incompatible paint system.
Health and Safety Statement	IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM . FOR PROFESSIONAL USE ONLY. Read full instructions before use.
PREVENTION	Thoroughly degrease surface with good quality wax/grease remover e.g. UP2002, UP2012, UP2021, UP2022 and UP2023. Add U-POL Fish Eye Eliminator to top coat. Regular maintenance of air supply/equipment.
DIRECTIONS	U-POL Fish Eye Eliminator is for use in automotive and industrial urethanes to improve levelling and eliminate fisheyes and crater formation. For best results, mix 1 reservoir per quart (liter) of clear or topcoat, add hardener and reducer where required, mix thoroughly and leave to condition for 10 minutes.
LIMITATIONS	Do not exceed recommended levels of addition. Do not use in primer systems.

PRODUCT ORDER CODES

PRODUCT ORDER CODE	PRODUCT DESCRIPTION	UNIT QUANTITY
UP2001	Fish Eye Eliminator 8.45 fl. oz. (250ml)	10

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064
Tel: (800) 340 7824; Fax: (800) 787 5150
Email: sales-us@u-pol.com Website: www.u-pol.com