



DRIVING SURFACE PERFECTION

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 04-28-2021

Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Trade name : RAPTOR 1K TRUCK BED COATING WHITE AEROSOL
 Product code : UP8411
 UP Number : UP8411
 Product group : aerosol

1.2. Recommended use and restrictions on use

Recommended use : Coating

1.3. Supplier

U-POL Canada Limited
 P.O. Box P.O. BOX 48600
 BC V7X 1T2 Vancouver - Canada
 T 1-800-424-9300
technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable aerosol Category 1	H222
Gases under pressure Liquefied gas	H280
Serious eye damage/eye irritation Category 2	H319
Skin sensitization, Category 1	H317
Carcinogenicity Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity (repeated exposure) Category 2	H373

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) :

- H222 - Extremely flammable aerosol
- H280 - Contains gas under pressure; may explode if heated
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H336 - May cause drowsiness or dizziness
- H351 - Suspected of causing cancer
- H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS CA) :

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 - Do not spray on an open flame or other ignition source.
- P251 - Do not pierce or burn, even after use.
- P260 - Do not breathe vapors, spray, fume.
- P264 - Wash hands thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear eye protection, protective gloves, protective clothing.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

2.4. Unknown acute toxicity (GHS CA)

3.31% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

1.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
n-butyl acetate	n-butyl acetate 1-acetoxybutane / 1-butyl acetate / acetate of butyl / acetic acid n-butyl ester / acetic acid normal-butyl ester / acetic acid, butyl ester / BUAC / BuAc (=butyl acetate) / butanolacetate / butyl acetate / butyl ethanoate / n-BuAc / n-butyl acetate / normal-butylacetate / normal-butylethanoate	(CAS-No.) 123-86-4	10 – 13	Flam. Liq. 3, H226 STOT SE 3, H336
methyl acetate	methyl acetate acetate of methyl / acetic acid methyl ester / acetic acid, methyl ester / devoton / ethyl ester of monoacetyl acid / methyl acetate / methyl acetate, anhydrous / methyl acetic ester / methyl ester acetic acid / methyl ethanoate / tereton	(CAS-No.) 79-20-9	10 – 13	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
acetone	2-propanon / 2-propanone / acetone / acetone NF / acetone oil / AI3-01238 / Caswell No.004 / chevron acetone / dimethyl formaldehyde / dimethyl ketone / dimethylketal / Dimethylketon / DMK (=dimethyl ketone) / FEMA No 3326 / ketone propane / KTI acetone / methyl acetyl / methylketon / propan-2-one / propanone / pyroacetic acid / pyroacetic ether / pyroacetic spirit / STEC 4908105	(CAS-No.) 67-64-1	10 – 13	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Xylene	AMSCO / benzene, dimethyl- / byk 310 / dimethylbenzene, mixture of isomers / dimethylbenzol, mixture of isomers / formula No 00651 / mebon thinner type 2 / methyltoluene, mixture of isomers / mixed xylenes / paint / solvent xylene / violet 3 / xylene / xylene, mixed isomers, pure / xylol / xylol, mixture of isomers	(CAS-No.) 1330-20-7	3 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
ethylbenzene	benzene, ethyl- / ethylbenzene / ethylbenzene, anhydrous / phenylethane	(CAS-No.) 100-41-4	1 – 1.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) a mixture of: alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) / reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		0.1 – 0.5	Skin Sens. 1A, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		(CAS-No.) 1065336-91-5	0.1 – 0.5	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Unsuitable extinguishing media

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Extremely flammable aerosol.
-------------	--------------------------------

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapors, spray, fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl acetate (79-20-9)		
Canada (Quebec)	VECD (OEL STEL)	757 mg/m ³
Canada (Quebec)	VECD (OEL STEL) [ppm]	250 ppm
Canada (Quebec)	VEMP (OEL TWA)	606 mg/m ³
Canada (Quebec)	VEMP (OEL TWA) [ppm]	200 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	757 mg/m ³
Alberta	OEL STEL [ppm]	250 ppm
Alberta	OEL TWA	606 mg/m ³
Alberta	OEL TWA [ppm]	200 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL STEL [ppm]	250 ppm
British Columbia	OEL TWA [ppm]	200 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	250 ppm
Manitoba	OEL TWA [ppm]	200 ppm
Manitoba	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL STEL [ppm]	250 ppm
New Brunswick	OEL TWA [ppm]	200 ppm
New Brunswick	Notations and remarks	eye & URT irr
Newfoundland & Labrador	OEL STEL [ppm]	250 ppm
Newfoundland & Labrador	OEL TWA [ppm]	200 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	250 ppm

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

methyl acetate (79-20-9)		
Nova Scotia	OEL TWA [ppm]	200 ppm
Nova Scotia	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	250 ppm
Nunavut	OEL TWA [ppm]	200 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	250 ppm
Northwest Territories	OEL TWA [ppm]	200 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	250 ppm
Ontario	OEL TWA [ppm]	200 ppm
Ontario	Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	250 ppm
Prince Edward Island	OEL TWA [ppm]	200 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	250 ppm
Saskatchewan	OEL TWA [ppm]	200 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
LPG, liquefied, under pressure (68476-85-7)		
Canada (Quebec)	VEMP (OEL TWA)	1800 mg/m ³
Canada (Quebec)	VEMP (OEL TWA) [ppm]	1000 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL [ppm]	1500 ppm
Alberta	OEL TWA [ppm]	1000 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	Notations and remarks	Simple asphyxiant; EX (Substance is a flammable asphyxiant or excursions above the exposure limit could approach 10% of the lower explosive limit)
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	Notations and remarks	TLV® Basis: Simple Asphyxiant
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Simple Asphyxiant
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	Notations and remarks	TLV® Basis: Simple Asphyxiant
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	Notations and remarks	See Appendix F: Minimal Oxygen Content
Ontario	Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

LPG, liquefied, under pressure (68476-85-7)		
Prince Edward Island	Notations and remarks	TLV® Basis: Simple Asphyxiant
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
quartz (14808-60-7)		
Canada (Quebec)	VEMP (OEL TWA)	0.1 mg/m ³ Rd
Canada (Quebec)	Notations and remarks	C2, EM
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL TWA	0.025 mg/m ³
Alberta	Notations and remarks	Carcinogenicity A2
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL TWA	0.025 mg/m ³ Respirable
British Columbia	Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Manitoba	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Nova Scotia	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL TWA	0.05 mg/m ³ (respirable fraction)
Nunavut	Notations and remarks	Designated substance
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL TWA	0.05 mg/m ³ (respirable fraction)
Northwest Territories	Notations and remarks	Designated substance
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL TWA	0.1 mg/m ³ (R - Respirable fraction)
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Prince Edward Island	Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL TWA	0.05 mg/m ³ (respirable fraction)
Saskatchewan	Notations and remarks	Designated Chemical Substance
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
n-butyl acetate (123-86-4)		
Canada (Quebec)	VECD (OEL STEL) [ppm]	150 ppm
Canada (Quebec)	VEMP (OEL TWA) [ppm]	50 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

n-butyl acetate (123-86-4)		
Alberta	OEL STEL	950 mg/m ³
Alberta	OEL STEL [ppm]	200 ppm
Alberta	OEL TWA	713 mg/m ³
Alberta	OEL TWA [ppm]	150 ppm
Alberta	Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL STEL [ppm]	150 ppm
British Columbia	OEL TWA [ppm]	50 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	150 ppm
Manitoba	OEL TWA [ppm]	50 ppm
Manitoba	Notations and remarks	TLV® Basis: Eye & URT irr
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	OEL STEL [ppm]	150 ppm
Newfoundland & Labrador	OEL TWA [ppm]	50 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Eye & URT irr
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	150 ppm
Nova Scotia	OEL TWA [ppm]	50 ppm
Nova Scotia	Notations and remarks	TLV® Basis: Eye & URT irr
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	200 ppm
Nunavut	OEL TWA [ppm]	150 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	200 ppm
Northwest Territories	OEL TWA [ppm]	150 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	200 ppm
Ontario	OEL TWA [ppm]	150 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	150 ppm
Prince Edward Island	OEL TWA [ppm]	50 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: Eye & URT irr
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	200 ppm
Saskatchewan	OEL TWA [ppm]	150 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
2-methoxy-1-methylethyl acetate (108-65-6)		
British Columbia	OEL STEL [ppm]	75 ppm
British Columbia	OEL TWA [ppm]	50 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Ontario	OEL TWA	270 mg/m ³
Ontario	OEL TWA [ppm]	50 ppm

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-methoxy-1-methylethyl acetate (108-65-6)		
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)		
Canada (Quebec)	VEMP (OEL TWA)	10 mg/m ³ Td
Canada (Quebec)	Notations and remarks	Note 1: The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1%
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL TWA	10 mg/m ³
Alberta	Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL TWA	10 mg/m ³ Total dust
British Columbia	Notations and remarks	IARC group 2B carcinogen
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL TWA	10 mg/m ³
Manitoba	Notations and remarks	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL TWA	10 mg/m ³
New Brunswick	Notations and remarks	LRT irr
Newfoundland & Labrador	OEL TWA	10 mg/m ³
Newfoundland & Labrador	Notations and remarks	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL TWA	10 mg/m ³
Nova Scotia	Notations and remarks	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL TWA	10 mg/m ³
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL TWA	10 mg/m ³
Prince Edward Island	Notations and remarks	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
aluminium oxide, activated (1344-28-1)		
Canada (Quebec)	VEMP (OEL TWA)	10 mg/m ³ Td
Canada (Quebec)	Notations and remarks	Note 1: The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1%

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

aluminium oxide, activated (1344-28-1)		
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL TWA	10 mg/m ³
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
Xylene (1330-20-7)		
Canada (Quebec)	VECD (OEL STEL)	651 mg/m ³
Canada (Quebec)	VECD (OEL STEL) [ppm]	150 ppm
Canada (Quebec)	VEMP (OEL TWA)	434 mg/m ³
Canada (Quebec)	VEMP (OEL TWA) [ppm]	100 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	651 mg/m ³
Alberta	OEL STEL [ppm]	150 ppm
Alberta	OEL TWA	434 mg/m ³
Alberta	OEL TWA [ppm]	100 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL STEL [ppm]	150 ppm
British Columbia	OEL TWA [ppm]	100 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	150 ppm
Manitoba	OEL TWA [ppm]	100 ppm
Manitoba	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL STEL [ppm]	150 ppm
New Brunswick	OEL TWA [ppm]	100 ppm
New Brunswick	Notations and remarks	URT & eye irr; CNS impair
Newfoundland & Labrador	OEL STEL [ppm]	150 ppm
Newfoundland & Labrador	OEL TWA [ppm]	100 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	150 ppm
Nova Scotia	OEL TWA [ppm]	100 ppm
Nova Scotia	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	150 ppm
Nunavut	OEL TWA [ppm]	100 ppm

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Xylene (1330-20-7)		
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	150 ppm
Northwest Territories	OEL TWA [ppm]	100 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	150 ppm
Ontario	OEL TWA [ppm]	100 ppm
Ontario	Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	150 ppm
Prince Edward Island	OEL TWA [ppm]	100 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	150 ppm
Saskatchewan	OEL TWA [ppm]	100 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
ethylbenzene (100-41-4)		
Canada (Quebec)	VEMP (OEL TWA) [ppm]	20 ppm
Canada (Quebec)	Notations and remarks	C3
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	543 mg/m ³
Alberta	OEL STEL [ppm]	125 ppm
Alberta	OEL TWA	434 mg/m ³
Alberta	OEL TWA [ppm]	100 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL TWA [ppm]	20 ppm
British Columbia	Notations and remarks	IARC group 2B carcinogen
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL TWA [ppm]	20 ppm
Manitoba	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Manitoba	Regulatory reference	ACGIH
Newfoundland & Labrador	OEL TWA [ppm]	20 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL TWA [ppm]	20 ppm
Nova Scotia	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	125 ppm
Nunavut	OEL TWA [ppm]	100 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	125 ppm
Northwest Territories	OEL TWA [ppm]	100 ppm
Northwest Territories	Notations and remarks	Designated substance

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ethylbenzene (100-41-4)		
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL TWA [ppm]	20 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL TWA [ppm]	20 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	125 ppm
Saskatchewan	OEL TWA [ppm]	100 ppm
Saskatchewan	Notations and remarks	Designated Chemical Substance
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
acetone (67-64-1)		
Canada (Quebec)	VECD (OEL STEL)	2380 mg/m ³
Canada (Quebec)	VECD (OEL STEL) [ppm]	1000 ppm
Canada (Quebec)	VEMP (OEL TWA)	1190 mg/m ³
Canada (Quebec)	VEMP (OEL TWA) [ppm]	500 ppm
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL STEL	1800 mg/m ³
Alberta	OEL STEL [ppm]	750 ppm
Alberta	OEL TWA	1200 mg/m ³
Alberta	OEL TWA [ppm]	500 ppm
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL STEL [ppm]	500 ppm
British Columbia	OEL TWA [ppm]	250 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL STEL [ppm]	500 ppm
Manitoba	OEL TWA [ppm]	250 ppm
Manitoba	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL STEL [ppm]	500 ppm
New Brunswick	OEL TWA [ppm]	250 ppm
New Brunswick	Notations and remarks	eye irr; CNS impair; BEI
Newfoundland & Labrador	OEL STEL [ppm]	500 ppm
Newfoundland & Labrador	OEL TWA [ppm]	250 ppm
Newfoundland & Labrador	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL STEL [ppm]	500 ppm
Nova Scotia	OEL TWA [ppm]	250 ppm
Nova Scotia	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL [ppm]	750 ppm
Nunavut	OEL TWA [ppm]	500 ppm
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL [ppm]	750 ppm

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

acetone (67-64-1)		
Northwest Territories	OEL TWA [ppm]	500 ppm
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Ontario	OEL STEL [ppm]	500 ppm
Ontario	OEL TWA [ppm]	250 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL [ppm]	500 ppm
Prince Edward Island	OEL TWA [ppm]	250 ppm
Prince Edward Island	Notations and remarks	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL [ppm]	750 ppm
Saskatchewan	OEL TWA [ppm]	500 ppm
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1
barium sulfate (7727-43-7)		
Canada (Quebec)	VEMP (OEL TWA)	5 mg/m ³ Id
Canada (Quebec)	Notations and remarks	Note 1: The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1%
Canada (Quebec)	Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Alberta	OEL TWA	10 mg/m ³
Alberta	Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 150/2020)
British Columbia	OEL TWA	5 mg/m ³ Inhalable (E - the value is for particulate matter containing no asbestos and less than 1% crystalline silica)
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Manitoba	OEL TWA	5 mg/m ³ (I - Inhalable particulate matter, E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica)
Manitoba	Notations and remarks	TLV® Basis: Pneumoconiosis
Manitoba	Regulatory reference	ACGIH
New Brunswick	OEL TWA	5 mg/m ³
New Brunswick	Notations and remarks	Pneumoconiosis
Newfoundland & Labrador	OEL TWA	5 mg/m ³ (I - Inhalable particulate matter, E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica)
Newfoundland & Labrador	Notations and remarks	TLV® Basis: Pneumoconiosis
Newfoundland & Labrador	Regulatory reference	ACGIH
Nova Scotia	OEL TWA	5 mg/m ³ (I - Inhalable particulate matter, E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica)
Nova Scotia	Notations and remarks	TLV® Basis: Pneumoconiosis
Nova Scotia	Regulatory reference	ACGIH
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Nunavut	Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Northwest Territories	Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

barium sulfate (7727-43-7)		
Ontario	OEL TWA	5 mg/m ³ (I - Inhalable fraction) (E - The value is for particulate matter containing no asbestos and < 1 per cent crystalline silica)
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL TWA	5 mg/m ³ (I - Inhalable particulate matter, E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica)
Prince Edward Island	Notations and remarks	TLV® Basis: Pneumoconiosis
Prince Edward Island	Regulatory reference	ACGIH
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Saskatchewan	Regulatory reference	The Occupational Health and Safety Regulations, 1996. Chapter O-1.1 Reg 1

2-methoxypropyl acetate (70657-70-4)		
British Columbia	OEL STEL [ppm]	40 ppm
British Columbia	OEL TWA [ppm]	20 ppm
British Columbia	Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: aerosol.
Color	: white
Odor	: aromatic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Vapor pressure at 50 °C	: No data available
Relative density	: No data available
Density	: 0.855 kg/m ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosion limits	: No data available

9.2. Other information

Gas group	: Press. Gas (Liq.)
As Packaged Regulatory VOC	: 517 g/l (4.3 lbs/gal)
As Packaged Actual VOC	: 469 g/l (3.9 lbs/gal)
As Applied Regulatory VOC	: 517 g/l (4.3 lbs/gal)
As Applied Actual VOC	: 469 g/l (3.9 lbs/gal)
Water Content	0 wt%
Exempt Compounds by volume	: 9.2 vol %
Exempt Compounds by weight	: 10.0 wt%
Volatiles	: 64.4 wt%
% EPA HAPS	: 4.1 wt%
Percent Solids	: 35.64 wt%

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Extremely flammable aerosol.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Unknown acute toxicity (GHS CA)	3.31% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 1.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapors))
---------------------------------	--

methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l
ATE CA (oral)	6482 mg/kg body weight
ATE CA (vapors)	49 mg/l/4h
ATE CA (dust,mist)	49 mg/l/4h

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	23.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Inhalation (mixture of vapour and aerosol), 14 day(s))
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)
ATE CA (oral)	10760 mg/kg body weight
ATE CA (Dermal)	14112 mg/kg body weight

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

n-butyl acetate (123-86-4)	
ATE CA (Gases (except aerosol dispensers and lighters))	390 ppmV/4h
Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)
ATE CA (oral)	3523 mg/kg body weight
ATE CA (Dermal)	1100 mg/kg body weight
ATE CA (Gases (except aerosol dispensers and lighters))	6700 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE CA (oral)	5800 mg/kg body weight
ATE CA (Dermal)	20000 mg/kg body weight
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,
ATE CA (oral)	3230 mg/kg body weight
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)
ATE CA (vapors)	5800 mg/l/4h
ATE CA (dust,mist)	5800 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
methyl acetate (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
Xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

: May cause damage to organs through prolonged or repeated exposure.

STOT-repeated exposure

methyl acetate (79-20-9)	
LOAEC (inhalation, rat, vapor, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapor, 90 days)	1057 mg/m ³

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL	
Vaporizer	aerosol

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

methyl acetate (79-20-9)	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
EC50 72h - Algae [1]	2.2 mg/l
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)

ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

12.2. Persistence and degradability

methyl acetate (79-20-9)	
Persistence and degradability	Readily biodegradable in water.
n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance
BOD (% of ThOD)	0.46
Xylene (1330-20-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ethylbenzene (100-41-4)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ethylbenzene (100-41-4)	
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance

acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance

12.3. Bioaccumulative potential

methyl acetate (79-20-9)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

n-butyl acetate (123-86-4)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

Xylene (1330-20-7)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)

ethylbenzene (100-41-4)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)

acetone (67-64-1)	
Bioaccumulative potential	Not bioaccumulative.
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

12.4. Mobility in soil

methyl acetate (79-20-9)	
Surface tension	24 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)

n-butyl acetate (123-86-4)	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

n-butyl acetate (123-86-4)	
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
ethylbenzene (100-41-4)	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
acetone (67-64-1)	
Surface tension	23.3 N/m (20 °C)
Ecology - soil	Highly mobile in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1950
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas
Transport document description (TDG) : UN1950 AEROSOLS, 2.1
Proper Shipping Name (TDG) : AEROSOLS

Hazard labels (TDG) : 2.1 - Flammable gases



RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment). 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L

14.2. Transport information/DOT

Department of Transport

DOT NA No	: UN1950
UN-No.(DOT)	: 1950
Transport document description (DOT)	: UN1950 Aerosols, 2.1
Proper Shipping Name (DOT)	: Aerosols
Contains Statement Field Selection (DOT)	:
Class (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Division (DOT)	: 2.1
Hazard labels (DOT)	: 2.1 - Flammable gas



Marine pollutant	: NO
Dangerous for the environment	: No
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
Emergency Response Guide (ERG) Number	: 126
Other information	: No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG)	: 1950
Proper Shipping Name (IMDG)	: AEROSOLS
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Class (IMDG)	: 2 - Gases

IATA

UN-No. (IATA)	: 1950
Proper Shipping Name (IATA)	: Aerosols, flammable
Transport document description (IATA)	: UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS
Class (IATA)	: 2 - Gases

SECTION 15: Regulatory information

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

15.1. National regulations

methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

n-butyl acetate (123-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

Listed on the Canadian DSL (Domestic Substances List)

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

methyl acetate (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

n-butyl acetate (123-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

SDS Major/Minor : None

Issue date : 04-28-2021

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

RAPTOR 1K TRUCK BED COATING WHITE AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SDS Canada U-POL

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.