

RAPTOR®

TOUGH AND TINTABLE PROTECTIVE COATING

ANTI-CORROSIVE EPOXY PRIMER

RAPTOR 4:1 Anti-Corrosive Epoxy Primer is a 2K high performance primer specifically designed to be used under RAPTOR Protective Coating to further extend the protective and anti-corrosive properties of RAPTOR. Featuring a blend of anti-corrosive additives to inhibit rust and corrosion and offers excellent salt spray resistance*.

FEATURES & BENEFITS:

- Advanced resin technology improves adhesion to bare metal and most other prepared surfaces
- Promotes intercoat performance to further extend the life RAPTOR Protective Coating
- Can be applied directly onto surface rust
- Can be applied wet on wet
- 1L covers approximately 60 sq feet at 3 MIL
- Salt spray resistance test completed at >2500 hours according to ASTM B117 by an independent laboratory



SURFACE PREPARATION



P180-P240

MIXING RATIO



4:1

SPRAY TIP SIZE



1.4-1.8mm

SPRAY PATTERN



2-3

TOP COAT WITHOUT SANDING



1 hour - 7 days

DRYING TIME

SANDING



30 mins @ 140°F



P400-P600

Please refer to product TDS for full instructions

APPLY IN 3 SIMPLE STEPS



FILL



SHAKE



SHOOT



DRIVING SURFACE PERFECTION™

RAPTOR
TECHNICAL INFORMATION

RAPTOR Anti-Corrosive Epoxy Primer's advanced resin technology improves adhesion to bare metal and most other prepared surfaces and promotes intercoat performance to further extend the life of **RAPTOR** protective coating. It can also be applied directly over surface rust.



Code	Description	Color	Units Per Case
UP4831	1L Kit	Gray	8
UP4830	5L Kit	Gray	1

OTHER PRODUCTS IN THE **RAPTOR** FAMILY



AUTOMOTIVE



OFF-ROAD



HOME



INDUSTRIAL



MARINE



AGRICULTURAL



COMMERCIAL