

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Product Reference code:according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Ref. (EU): BAGDOLSG-SDS
Issue date: 28/06/2016 Revision date: 29/07/2022 Supersedes version of: 03/12/2020 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : DOLPHIN SPEED GLAZE

Product code : BAGDOLSG/1
Type of product : Fillers
Product group : Bodyfiller

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use,Professional use
Use of the substance/mixture : Fillers, putties, plasters, modelling clay

Function or use category : Fillers

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer Importer

U-POL Limited Ltd
U-POL Netherlands B.V. B.V.
Denington Road
Hoorgoorddreef 15
GB- NN8 2QH Wellingborough - Northamptonshire
NL- 1101BA Amsterdam

GB- NN8 2QH Wellingborough - Northamptonshire
United Kingdom
T +44 (0) 1933 230310

NL- 1101BA Amster
Netherlands
T +31 20 240 2216

<u>technicalsupport@u-pol.com</u> - <u>www.u-pol.com</u> - <u>www.u-pol.com</u> - <u>www.u-pol.com</u> - <u>www.u-pol.com</u>

1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.h scni.net)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Reproductive toxicity, Category 2 H361

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific target organ toxicity — Single exposure, Category 3, Respiratory H335

tract irritation

Specific target organ toxicity — Repeated exposure, Category 1 H372

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS08

Signal word (CLP) : Danger Contains : styrene

Hazard statements (CLP) : H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

H361 - Suspected of damaging the unborn child.

H372 - Causes damage to organs (hearing organs) through prolonged or repeated

exposure (Inhalation).

Precautionary statements (CLP) : P210 - Keep away from heat, open flames, sparks, hot surfaces. — No smoking.

P261 - Avoid breathing fume, vapours. P264 - Wash hands thoroughly after handling.

P280 - Wear eye protection, protective clothing, protective gloves. P308+P313 - IF exposed or concerned: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

Unknown acute toxicity (CLP) - SDS : 0.26% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

0.26% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component		
styrene (100-42-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene (Note D)	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0 REACH-no: 01-2119457861- 32	10 – 25	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379- 17	1 – 2.5	Carc. 2, H351

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Hazardous decomposition products in case of fire : Toxic fumes may be released.

29/07/2022 (Revision date) EN (English) 3/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe

vapours, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours, fume. Use only outdoors or in a

well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Storage temperature : $< 25 \, ^{\circ}\text{C}$

Storage area : Store in a well-ventilated place.
Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

29/07/2022 (Revision date) EN (English) 4/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

The state of the s			
styrene (100-42-5)	styrene (100-42-5)		
Ireland - Occupational Exposure Limits			
Local name	Styrene [Phenylethylene, Vinyl benzene]		
OEL TWA [1]	85 mg/m³		
OEL TWA [2]	20 ppm		
OEL STEL	170 mg/m³		
OEL STEL [ppm]	40 ppm		
Regulatory reference	Chemical Agents Code of Practice 2020		
United Kingdom - Occupational Exposure Limits			
Local name	Styrene		
WEL TWA (OEL TWA) [1]	430 mg/m³		
WEL TWA (OEL TWA) [2]	100 ppm		
WEL STEL (OEL STEL)	1080 mg/m³		
WEL STEL (OEL STEL) [ppm]	250 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)			
Ireland - Occupational Exposure Limits			
Local name	Titanium dioxide		
OEL TWA [1]	10 mg/m³ total inhalable dust 4 mg/m³ respirable dust		
Regulatory reference	Chemical Agents Code of Practice 2020		
United Kingdom - Occupational Exposure Limits			
Local name	Titanium dioxide		
WEL TWA (OEL TWA) [1]	10 mg/m³ 4 mg/m³		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

styrene (100-42-5)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation 289 mg/m³	
Acute - local effects, inhalation	306 mg/m³
Long-term - systemic effects, dermal	406 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	85 mg/m³

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

styrene (100-42-5)		
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	174.25 mg/m³	
Acute - local effects, inhalation	182.75 mg/m³	
Long-term - systemic effects,oral	2.1 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	10.2 mg/m³	
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.028 mg/l	
PNEC aqua (marine water)	0.014 mg/l	
PNEC aqua (intermittent, freshwater)	0.04 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.614 mg/kg dwt	
PNEC sediment (marine water)	0.307 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.2 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	5 mg/l	

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Personal protective equipment symbol(s):









8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection				
Туре	Field of application	Characteristics	Standard	
Safety glasses	Dust	clear		

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Protective gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR), Polyvinylalcohol (PVA), Viton	6 (> 480 minutes)	0.4		EN 374-3

Other skin protection

Materials for protective clothing:

Impermeable clothing

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Respiratory protection				
Device	Filter type	Condition	Standard	
Breathing apparatus, Gas filters	Type A - High-boiling (>65 °C) organic compounds	Vapour protection	EN 140, EN 136, EN 143, EN 145, EN 149	

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Blue. Appearance : Paste. Odour : aromatic. Odour threshold : Not available Melting point : Not applicable Freezing point : Not available Boiling point : 145 °C Flammability : Not applicable Explosive limits : Not available : Not available Lower explosion limit : Not available Upper explosion limit : 32 °C Flash point Auto-ignition temperature : Not available : Not available Decomposition temperature : Not available рΗ Viscosity, kinematic $> 20.5 \text{ mm}^2/\text{s}$

Viscosity, dynamic : 51250 (47500 – 55000) cP

Solubility : insoluble in water. Soluble in aromatic hydrocarbons.

Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50 °C : Not available

Density : $1.225 (1.2 - 1.25) \text{ g/cm}^3$

29/07/2022 (Revision date) EN (English) 7/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

: Not available Relative density Relative vapour density at 20 °C : Not available Particle size : Not applicable Particle size distribution : Not applicable Particle shape : Not applicable Particle aspect ratio : Not applicable Particle aggregation state : Not applicable Particle agglomeration state : Not applicable Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 193 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

riodic toxioity (iliidiation)	Not diaddined
styrene (100-42-5)	
LD50 oral rat	5000 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	11.8 mg/l (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours))
2-phenoxyethanol (122-99-6)	
LD50 oral rat	1850 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-phenoxyethanol (122-99-6)		
LD50 dermal rat	14391 mg/kg bodyweight Animal: rat	
LD50 dermal rabbit	> 2214 mg/kg bodyweight Animal: rabbit, Guideline: other:Draft IRLG (Interagency Regulatory Liaison Group) Guidelines for Selected Acute Toxicity Tests (August. 1979)	
LC50 Inhalation - Rat	> 1 mg/l air Animal: rat, Guideline: other:OECD 412	
ethyl acetate (141-78-6)		
LD50 oral rat	10200 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral, 14 day(s))	
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male	
1,4-dihydroxybenzene; hydroquinone; quinol	(123-31-9)	
LD50 oral rat	> 375 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))	
hydrocarbons, C9-C10, n-alkanes, isoalkanes	, cyclics, <2% aromatics (1174921-73-3)	
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg	
LC50 Inhalation - Rat (Vapours)	> 4.951 mg/l/4h (OECD Guideline 403 (Acute Inhalation Toxicity), 4h, rat, male/female, inhalation (vapours))	
parrafin waxes and hydrocarbon waxes (8002	-74-2)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)	
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))	
dolomite (16389-88-1)		
LD50 oral rat	> 2000 mg/kg (OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), rat, female, Experimental value)	
talc (14807-96-6)		
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))	
(112926-00-8)		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

silicon dioxide, amorphous (7631-86-9)	
LD50 oral rat	> 10000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Dermal)
Calcium carbonate (1317-65-3)	
LD50 oral rat	6450 mg/kg (Rat, Literature study, Oral)
oxirane, 2-methyl-, polymer with oxirane, mor	no[(diethylamino)alkyl] ether (68511-96-6)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000
Unknown acute toxicity (CLP) - SDS :	0.26% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 0.26% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
Skin corrosion/irritation :	Causes skin irritation.
Serious eye damage/irritation :	Causes serious eye irritation.
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	Not classified.
styrene (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity :	Suspected of damaging the unborn child.
2-phenoxyethanol (122-99-6)	
LOAEL (animal/male, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
LOAEL (animal/female, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
NOAEL (animal/female, F0/P)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
STOT-single exposure :	May cause respiratory irritation.
styrene (100-42-5)	
STOT-single exposure	May cause respiratory irritation.
ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
hydrocarbons, C9-C10, n-alkanes, isoalkanes	, cyclics, <2% aromatics (1174921-73-3)
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure :	Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation).
styrene (100-42-5)	
LOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight Animal: rat
LOAEC (inhalation, rat, vapour, 90 days)	0.21 mg/l air Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

styrene (100-42-5)		
NOAEL (subchronic, oral, animal/male, 90 days)	10 mg/kg bodyweight Animal: mouse, Animal sex: male	
STOT-repeated exposure	Causes damage to organs (hearing sense) through prolonged or repeated exposure (if inhaled).	
2-phenoxyethanol (122-99-6)		
LOAEL (oral, rat, 90 days)	> 700 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)	
LOAEL (dermal, rat/rabbit, 90 days)	> 500 mg/kg bodyweight Animal: rabbit	
NOAEL (oral, rat, 90 days)	700 mg/kg bodyweight/day	
NOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rabbit	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0482 mg/l/6h/day	
ethyl acetate (141-78-6)		
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)	
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)	
Aspiration hazard : Not classified		
DOLPHIN SPEED GLAZE		
Viscosity, kinematic	> 20.5 mm²/s	
Viscosity, kinematic	> 20.5 mm²/s	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

 $\label{thm:local_equation} \mbox{Hazardous to the aquatic environment, short-term}$

(acute)

: Not classified

Hazardous to the aquatic environment, long-term :

: Not classified

(chronic)

styrene (100-42-5)	
LC50 - Fish [1]	10 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	4.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	6.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
LOEC (chronic)	2.06 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	1.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

styrene (100-42-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Chemical oxygen demand (COD)	2.8 g O ₂ /g substance
ThOD	3.07 g O ₂ /g substance
BOD (% of ThOD)	0.42 (Literature study)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Persistence and degradability Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

styrene (100-42-5)	
BCF - Fish [1]	74 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.96 (Practical experience/observation, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

styrene (100-42-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.55 (log Koc, Estimated value)
Ecology - soil	Low potential for adsorption in soil.
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Ecology - soil	Low potential for mobility in soil.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

Component	
styrene (100-42-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

 UN-No. (ADR)
 : UN 1866

 UN-No. (IMDG)
 : UN 1866

 UN-No. (IATA)
 : UN 1866

 UN-No. (ADN)
 : UN 1866

 UN-No. (RID)
 : UN 1866

14.2. UN proper shipping name

Proper Shipping Name (ADR) : RESIN SOLUTION
Proper Shipping Name (IMDG) : RESIN SOLUTION
Proper Shipping Name (IATA) : Resin solution
Proper Shipping Name (ADN) : RESIN SOLUTION
Proper Shipping Name (RID) : RESIN SOLUTION

Transport document description (ADR)

Transport document description (IMDG)

Transport document description (IMDG)

Transport document description (IATA)

Transport document description (ADN)

Transport document description (RID)

Transport document description (RID)

UN 1866 RESIN SOLUTION, 3, III

UN 1866 RESIN SOLUTION, 3, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

IMDG

Transport hazard class(es) (IMDG) : 3 Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3 3 Danger labels (IATA)



ADN

Transport hazard class(es) (ADN) : 3 3 Danger labels (ADN)



RID

Transport hazard class(es) (RID) 3 3

Danger labels (RID)



14.4. Packing group

Packing group (ADR) : 111 : 111 Packing group (IMDG) Packing group (IATA) : 111 Packing group (ADN) : 111 Packing group (RID) : 111

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

: No supplementary information available Other information

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1 Special provisions (ADR) : 640E Limited quantities (ADR) : 51 Excepted quantities (ADR) : E1

: P001, IBC03, LP01, R001 Packing instructions (ADR)

Special packing provisions (ADR) : PP1 Mixed packing provisions (ADR) : MP19 Portable tank and bulk container instructions (ADR) : T2 Portable tank and bulk container special provisions : TP1

(ADR)

: LGBF Tank code (ADR) Vehicle for tank carriage : FL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30

Orange plates : T

30 1866

Tunnel restriction code (ADR) : D/E EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 223, 955 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : P001, LP01 Special packing provisions (IMDG) : PP1 IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T2 Tank special provisions (IMDG) : TP1 EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-E Stowage category (IMDG) : A

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L PCA packing instructions (IATA) : 355 PCA max net quantity (IATA) : 60L CAO packing instructions (IATA) : 366 CAO max net quantity (IATA) : 220L Special provisions (IATA) : A3 ERG code (IATA) : 31

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 640E

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 640E
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions : TP1

(RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	styrene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	styrene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	styrene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	styrene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 193 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.