



DRIVING SURFACE PERFECTION

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 Product Reference code: according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 SDS Ref. (EU): CCFOUPAL-SDS  
 Issue date: 09/07/2015 Revision date: 20/12/2022 Supersedes version of: 20/08/2019 Version: 3.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL  
 UFI : MR51-Y03D-X00N-5XPA  
 Product code : CCFOUP/AL  
 Vaporizer : aerosol  
 Product group : aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
 Use of the substance/mixture : Coatings and paints, thinners, paint removers  
 Function or use category : Topcoat

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

U-POL Limited Ltd  
 Denington Road  
 GB- NN8 2QH Wellingborough – Northamptonshire  
 United Kingdom  
 T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### Importer

U-POL Netherlands B.V. B.V.  
 Hoorgoordreef 15  
 NL- 1101BA Amsterdam  
 Netherlands  
 T +31 20 240 2216  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours ( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
 Serious eye damage/eye irritation, Category 2 H319

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

No additional information available

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

Contains

: acetone

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. — No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Pressurized container: Do not pierce or burn, even after use.

P261 - Avoid breathing spray, vapours, fume.

P280 - Wear eye protection, protective clothing, protective gloves.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
dimethyl ether (115-10-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether substance with a Community workplace exposure limit (Note U)	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128-37	≥ 75	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
acetone substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Cough. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Direct contact with the eyes is likely to be irritating. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing spray, vapours.
- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released product. Collect spillage.
- Methods for cleaning up : Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing spray, vapours. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition source.
- Hygiene measures : Wash hands thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, Ignition sources, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
- Storage temperature : < 25 °C
- Storage area : Store in a well-ventilated place.
- Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

acetone (67-64-1)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Acetone
IOEL TWA	1210 mg/m <sup>3</sup>
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA [1]	1210 mg/m <sup>3</sup>
OEL TWA [2]	500 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Acetone
BLV	50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>dimethyl ether (115-10-6)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Dimethylether
IOEL TWA	1920 mg/m <sup>3</sup>
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Dimethyl ether
OEL TWA [1]	1920 mg/m <sup>3</sup>
OEL TWA [2]	1000 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>dimethyl ether (115-10-6)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Dimethyl ether
WEL TWA (OEL TWA) [1]	766 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	958 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>acetone (67-64-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	2420 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	10.6 mg/l
PNEC aqua (marine water)	1.06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	30.4 mg/kg dwt
PNEC sediment (marine water)	3.04 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	29.5 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective clothing. Safety glasses.

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Chemical goggles or safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Wear protective gloves.

##### Other skin protection

##### Materials for protective clothing:

Impermeable clothing

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

##### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable,Extremely flammable aerosol.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Immiscible with water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0.695 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 100

#### 9.2.2. Other safety characteristics

Gas group : Press. Gas (Liq.)  
VOC content : 763 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4

#### dimethyl ether (115-10-6)

LC50 Inhalation - Rat [ppm]	164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 - 203000
-----------------------------	---

Skin corrosion/irritation : Not classified  
Additional information : Based on available data, the classification criteria are not met  
Serious eye damage/irritation : Causes serious eye irritation.



# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met

### acetone (67-64-1)

LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)

STOT-single exposure	: May cause drowsiness or dizziness.
Additional information	: May cause drowsiness or dizziness.

### acetone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

## CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

Vaporizer	aerosol
-----------	---------

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

No additional information available

### 11.2.2. Other information

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met
---	--

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

### acetone (67-64-1)

LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### dimethyl ether (115-10-6)

LC50 - Fish [1]	> 4.1 g/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	154.917 mg/l Test organisms (species): other:green algae

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.2. Persistence and degradability

#### CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

Persistence and degradability	Not established.
-------------------------------	------------------

#### acetone (67-64-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
-------------------------------	--

Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
---------------------------------	------------------------------------

Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
------------------------------	------------------------------------

ThOD	2.2 g O <sub>2</sub> /g substance
------	-----------------------------------

#### dimethyl ether (115-10-6)

Persistence and degradability	Non degradable in the soil. Not readily biodegradable in water.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

Bioaccumulative potential	Not established.
---------------------------	------------------

#### acetone (67-64-1)

Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
---	-------------------

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

#### dimethyl ether (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
---	--------------------------

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

### 12.4. Mobility in soil

#### acetone (67-64-1)

Surface tension	23300 mN/m (20 °C)
-----------------	--------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

Ecology - soil	Highly mobile in soil.
----------------	------------------------

#### dimethyl ether (115-10-6)

Surface tension	No data available in the literature
-----------------	-------------------------------------

Ecology - soil	Not applicable (gas).
----------------	-----------------------

### 12.5. Results of PBT and vPvB assessment

#### Component

dimethyl ether (115-10-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---------------------------	---

acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
-------------------	---

### 12.6. Endocrine disrupting properties

No additional information available

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Remove waste in accordance with local and/or national regulations. Container under pressure. Do not drill or burn even after use.  
Additional information : Flammable vapours may accumulate in the container.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number or ID number

UN-No. (ADR) : UN 1950  
UN-No. (IMDG) : UN 1950  
UN-No. (IATA) : UN 1950  
UN-No. (ADN) : UN 1950  
UN-No. (RID) : UN 1950

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable  
Proper Shipping Name (ADN) : AEROSOLS  
Proper Shipping Name (RID) : AEROSOLS  
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)  
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1  
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1  
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1  
Transport document description (RID) : UN 1950 AEROSOLS, 2.1

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 2.1  
Danger labels (ADR) : 2.1  
:



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1  
:



#### IATA

Transport hazard class(es) (IATA) : 2.1

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danger labels (IATA) : 2.1

:



### ADN

Transport hazard class(es) (ADN) : 2.1

Danger labels (ADN) : 2.1

:



### RID

Transport hazard class(es) (RID) : 2.1

Danger labels (RID) : 2.1

:



## 14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

## 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

## 14.6. Special precautions for user

### Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP02

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12

Special provisions for carriage - Operation (ADR) : S2

Tunnel restriction code (ADR) : D

### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Segregation (IMDG) : SG69

### Air transport

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

### Inland waterway transport

Classification code (ADN) : 5F  
Special provisions (ADN) : 19, 327, 344, 625  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01, VE04  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : 5F  
Special provisions (RID) : 190, 327, 344, 625  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E0  
Packing instructions (RID) : P207, LP02  
Special packing provisions (RID) : PP87, RR6, L2  
Mixed packing provisions (RID) : MP9  
Transport category (RID) : 2  
Special provisions for carriage – Packages (RID) : W14  
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12  
Colis express (express parcels) (RID) : CE2  
Hazard identification number (RID) : 23

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL ; acetone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL ; acetone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
40.	dimethyl ether ; acetone	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see [https://ec.europa.eu/home-affairs/sites/default/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/sites/default/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list_of_competent_authorities_and_national_contact_points_en.pdf)

VOC content : 763 g/l

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H319	Causes serious eye irritation.

# CUSTOM CAN FILL-ONE SOLVENT BASED AEROSOL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H336	May cause drowsiness or dizziness.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).