



DRIVING SURFACE PERFECTION

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Date of issue: 27/07/2016

Revision date: 03/05/2019

Supersedes: 02/11/2017

Version: 2.1

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture
Trade name : U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL
Product code : CCFOWP/AL

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

1.4. Supplier's details

Supplier

U-POL AUSTRALIA PTY LIMITED
Unit A, 16 - 20 Cassola Place
Penrith, NSW 2750 - Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.co.nz - www.u-pol.com.au

Supplier

U-POL NEW ZEALAND LIMITED
c/o Lindsay & Associates
Unit H, 12 Amara Place, East Tamaki
Manukau City 2013 - New Zealand
T + 612 4731 2655 - F + 612 4731 2611
technicalsupport@u-pol.com - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1 H222
Serious eye damage/eye irritation, Category 2A H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) :

Danger

Contains :

acetone (5 - 23 %); propan-2-ol (< 5 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing fume, spray, vapours.
P264 - Wash hands thoroughly after handling.
P280 - Wear eye protection, protective clothing, protective gloves.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
acetone ()	67-64-1	5 - 23	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
propan-2-ol ()	67-63-0	< 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Other substances (not contributing to the classification of this product)		74.77	

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

- Symptoms/effects : May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable aerosol. Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, fume, spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

- Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released product, pump into suitable containers. Collect spillage.
Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, fume, spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: < 25 °C
Special rules on packaging	: Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

propan-2-ol (67-63-0)		
Australia	Local name	Isopropyl alcohol
Australia	TWA (mg/m ³)	983 mg/m ³
Australia	TWA (ppm)	400 ppm
Australia	STEL (mg/m ³)	1230 mg/m ³
Australia	STEL (ppm)	500 ppm
New Zealand	Local name	Isopropyl alcohol
New Zealand	TWA (mg/m ³)	983 mg/m ³
New Zealand	TWA (ppm)	400 ppm
New Zealand	STEL (mg/m ³)	1230 mg/m ³
New Zealand	STEL (ppm)	500 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 8th Edition

acetone (67-64-1)		
Australia	Local name	Acetone
Australia	TWA (mg/m ³)	1185 mg/m ³
Australia	TWA (ppm)	500 ppm
Australia	STEL (mg/m ³)	2375 mg/m ³
Australia	STEL (ppm)	1000 ppm
New Zealand	Local name	Acetone
New Zealand	TWA (mg/m ³)	1185 mg/m ³
New Zealand	TWA (ppm)	500 ppm
New Zealand	STEL (mg/m ³)	2375 mg/m ³
New Zealand	STEL (ppm)	1000 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

Personal protective equipment	: Gloves. Protective clothing. Safety glasses.
Materials for protective clothing	: Impermeable clothing
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment
Personal protective equipment symbol(s)	

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density : 0.696 g/cm ³
Solubility	: Immiscible with water.
Log Pow	: No data available
Viscosity, dynamic	: ≈
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content - Regulatory	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated. Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

propan-2-ol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (ppm)	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male/female, Experimental value, Inhalation (vapours), 14 day(s))
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Vaporizer	Aerosol
-----------	---------

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

propan-2-ol (67-63-0)

LC50 fish 1	9640 - 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
Log Pow	0.05 (Weight of evidence approach, 25 °C)
Log Koc	0.185 - 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

acetone (67-64-1)

LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)

12.2. Persistence and degradability

propan-2-ol (67-63-0)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

acetone (67-64-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

12.3. Bioaccumulative potential

propan-2-ol (67-63-0)

Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

acetone (67-64-1)

BCF fish 1	See section 12.1 on ecotoxicology
BCF other aquatic organisms 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Not bioaccumulative.

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

12.4. Mobility in soil

propan-2-ol (67-63-0)	
Surface tension	0.021 N/m (25 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil.
acetone (67-64-1)	
Surface tension	0.0237 N/m
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL	
Fluorinated greenhouse gases	False
propan-2-ol (67-63-0)	
Fluorinated greenhouse gases	False
acetone (67-64-1)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1
Danger labels (ADG) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Hazard labels (IATA) : 2.1

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations



14.4. Packing group

Packing group (ADG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

14.5. Environmental hazards

Marine pollutant	: No
------------------	------

14.6. Special precautions for user

Specific storage requirement	: No data available
Shock sensitivity	: No data available

14.7. Additional information

Other information	: No supplementary information available
-------------------	--

Transport by road and rail

UN-No. (ADG)	: 1950
Special provision (ADG)	: 63, 190, 277, 327, 344
Limited quantities (ADG)	: See SP 277
Packing instructions (ADG)	: P207, LP02
Special packing provisions (ADG)	: PP87, L2

Transport by sea

UN-No. (IMDG)	: 1950
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None

Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.8. Hazchem or Emergency Action Code

Hazchemcode	: Not applicable
-------------	------------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number	: HSR002515
Group standard	: Aerosols

U-POL CUSTOM CAN - FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 03/05/2019

Classification:

Flam. Aerosol 1	H222
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements:

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

SDS Australia U-POL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.