



DRIVING SURFACE PERFECTION

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 05-25-2018

Revision date: 01-06-2020

Supersedes: 08-13-2019

Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Trade name : CUSTOM CAN FILL-ONE WATER BASED AEROSOL
 Product code : CCFOWP/AL
 UP Number : UP0852
 Product group : Aerosol

1.2. Recommended use and restrictions on use

Recommended use : Coating

1.3. Supplier

U-POL CANADA LIMITED
 P.O. Box P.O. BOX 48600
 BC V7X 1T2 VANCOUVER - CANADA
 T 1-800-424-9300
technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable aerosol Category 1 H222
 Gases under pressure Liquefied gas H280
 Serious eye damage/eye irritation Category 2 H319
 Specific target organ toxicity (single exposure) Category 3 H336

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : H222 - Extremely flammable aerosol
 H280 - Contains gas under pressure; may explode if heated
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness

Precautionary statements (GHS CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P261 - Avoid breathing vapors, spray, fume.
 P264 - Wash hands thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves, protective clothing, eye protection.
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 - Call a POISON CENTER if you feel unwell.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
acetone	2-propanon / 2-propanone / acetone / acetone NF / acetone oil / A13-01238 / Caswell No.004 / chevron acetone / dimethyl formaldehyde / dimethyl ketone / dimethylketal / Dimethylketon / DMK (=dimethyl ketone) / FEMA No 3326 / ketone propane / KTI acetone / methyl acetyl / pyroacetic acid / pyroacetic ether / pyroacetic spirit / STEC 4908105	(CAS-No.) 67-64-1	15 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
propan-2-ol	propan-2-ol 1-methylethanol / 1-methylethyl alcohol / 2-hydroxypropane / 2-propanol / 2-propanol, anhydrous / 2-propyl alcohol / A13-01636 / alcojel / alcosolve / AVANTIN / AVANTINE / caswell No 507 / chromar (=2-propanol) / combi-schutz / CORONA WIRE CLEANER (=2-propanol) / CTL R-53 reducer / dimethyl carbinol / DISK DRIVE HEAD CLEANING KIT (=2-propanol) / ethyl carbinol / hartosol / hydroxypropane / imsol A / IPA SGL / IPA T1 / IPA USP / IPA, anhydrous / IPA-EG / isoethylcarbinol / isohol / isopropanol, anhydrous / isopropyl alcohol / isopropyl alcohol, anhydrous / KENCO #880-T FLUX THINNER (=2-propanol) / LENS CLENS #3 (=2-propanol) / lutosol / normal-propan-2-ol / n-propan-2-ol / perspirit / persprit / petrohol / PRO / productcode S1155 / propan-2-ol / propyl alcohol (=sec-propyl alcohol) / pseudo-propyl alcohol / secondary-propyl alcohol / sec-propanol / sec-propyl alcohol / spectrar / STCC 4904205 / sterisol hand disinfectant / takineocol / TEXPADS / visco 1152 / XEROX FILM REMOVER	(CAS-No.) 67-63-0	1.5 – 3	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurized container: may burst if heated.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Collect spillage.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, spray, fume.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.
Storage temperature : < 25 °C
Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propan-2-ol (67-63-0)		
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (ppm)	200 ppm
Alberta	Notations and remarks	Eye & URT irr; CNS impair
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OEL TWA (ppm)	200 ppm
British Columbia	Notations and remarks	Eye & URT irr; CNS impair
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OEL TWA (ppm)	200 ppm
Manitoba	Notations and remarks	Eye & URT irr; CNS impair
New Brunswick	OEL STEL (ppm)	400 ppm
New Brunswick	OEL TWA (ppm)	200 ppm
New Brunswick	Notations and remarks	Eye & URT irr; CNS impair
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

propan-2-ol (67-63-0)		
Newfoundland & Labrador	Notations and remarks	Eye & URT irr; CNS impair
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nova Scotia	Notations and remarks	Eye & URT irr; CNS impair
Nunavut	OEL STEL (ppm)	400 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Nunavut	Notations and remarks	Eye & URT irr; CNS impair
Northwest Territories	OEL STEL (ppm)	400 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Northwest Territories	Notations and remarks	Eye & URT irr; CNS impair
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Prince Edward Island	Notations and remarks	Eye & URT irr; CNS impair
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
acetone (67-64-1)		
Alberta	OEL STEL (ppm)	500 ppm
Alberta	OEL TWA (ppm)	250 ppm
Alberta	Notations and remarks	eye irr; CNS impair; BEI
British Columbia	OEL STEL (ppm)	500 ppm
British Columbia	OEL TWA (ppm)	250 ppm
British Columbia	Notations and remarks	eye irr; CNS impair; BEI
Manitoba	OEL STEL (ppm)	500 ppm
Manitoba	OEL TWA (ppm)	250 ppm
Manitoba	Notations and remarks	eye irr; CNS impair; BEI
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (ppm)	250 ppm
New Brunswick	Notations and remarks	eye irr; CNS impair; BEI
Newfoundland & Labrador	OEL STEL (ppm)	500 ppm
Newfoundland & Labrador	OEL TWA (ppm)	250 ppm
Newfoundland & Labrador	Notations and remarks	eye irr; CNS impair; BEI
Nova Scotia	OEL STEL (ppm)	500 ppm
Nova Scotia	OEL TWA (ppm)	250 ppm
Nova Scotia	Notations and remarks	eye irr; CNS impair; BEI
Nunavut	OEL STEL (ppm)	500 ppm
Nunavut	OEL TWA (ppm)	250 ppm
Nunavut	Notations and remarks	eye irr; CNS impair; BEI
Northwest Territories	OEL STEL (ppm)	500 ppm
Northwest Territories	OEL TWA (ppm)	250 ppm
Northwest Territories	Notations and remarks	eye irr; CNS impair; BEI
Ontario	OEL STEL (ppm)	750 ppm
Ontario	OEL TWA (ppm)	500 ppm
Ontario	Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Prince Edward Island	OEL STEL (ppm)	500 ppm
Prince Edward Island	OEL TWA (ppm)	250 ppm
Prince Edward Island	Notations and remarks	eye irr; CNS impair; BEI
Saskatchewan	OEL STEL (ppm)	750 ppm

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

acetone (67-64-1)

Saskatchewan	OEL TWA (ppm)	500 ppm
--------------	---------------	---------

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Materials for protective clothing:

Impermeable clothing

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Colorless
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Vapor pressure at 50 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.696 g/cm ³
Solubility	: Immiscible with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosive properties	: Pressurized container: may burst if heated.
Explosion limits	: No data available

9.2. Other information

Gas group	: Press. Gas (Liq.)
As Packaged Regulatory VOC	: 696 g/l (5.8 lbs/gal)

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

As Packaged Actual VOC	: 696 g/l (5.8 lbs/gal)
As Applied Regulatory VOC	: 696 g/l (5.8 lbs/gal)
As Applied Actual VOC	: 696 g/l (5.8 lbs/gal)
Water Content	0 wt%
Volatiles	: 100 wt%
Percent Solids	: 0 wt%

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

propan-2-ol (67-63-0)	
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (ppm)	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE CA (oral)	5840 mg/kg body weight
ATE CA (Dermal)	16400 mg/kg body weight

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
ATE CA (oral)	5800 mg/kg body weight
ATE CA (Dermal)	20000 mg/kg body weight
ATE CA (vapors)	76 mg/l/4h
ATE CA (dust,mist)	76 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

propan-2-ol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

: Not classified

STOT-repeated exposure

Aspiration hazard : Not classified

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Vaporizer	Aerosol
-----------	---------

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

propan-2-ol (67-63-0)

LC50 fish 1	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

acetone (67-64-1)

LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 96h algae (1)	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)

12.2. Persistence and degradability

propan-2-ol (67-63-0)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

acetone (67-64-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

12.3. Bioaccumulative potential

propan-2-ol (67-63-0)

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

acetone (67-64-1)

Bioaccumulative potential	Not bioaccumulative.
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)

12.4. Mobility in soil

propan-2-ol (67-63-0)

Surface tension	0.021 N/m (25 °C)
Ecology - soil	Highly mobile in soil.
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1950
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas.
Transport document description : UN1950 AEROSOLS (flammable), 2.1
Proper Shipping Name (Transportation of Dangerous Goods) : AEROSOLS
flammable

Hazard labels (TDG) : 2.1 - Flammable gases



TDG Special Provisions : 80 - Despite section 1.17 of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with section 5.11 of Part 5, Means of Containment, except that the requirement for aerosol containers to be tightly packed in a wood, fibreboard or plastic box does not apply to a user or purchaser who transports no more than six aerosol containers. For a similar rule respecting aerosol containers, see subparagraph 1.15(1)(a)(i) of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases. SOR/2012-245
107 - (1)These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2, (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a ship on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2)Subsection (1) does not apply to self-defence spray. SOR/2014-306

Explosive Limit and Limited Quantity Index : 1 L

14.2. Transport information/DOT

Department of Transport

DOT NA No : UN1950
UN-No.(DOT) : 1950
Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)
Contains Statement Field Selection (DOT) :
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Division (DOT) : 2.1

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazard labels (DOT) : 2.1 - Flammable gas



Dangerous for the environment : No
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
Other information : No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1950
Proper Shipping Name (IMDG) : AEROSOLS
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1
Class (IMDG) : 2 - Gases

IATA

UN-No. (IATA) : 1950
Proper Shipping Name (IATA) : Aerosols, flammable
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. National regulations

No additional information available

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

propan-2-ol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

SDS Major/Minor : None
Date of issue : 05-25-2018
Revision date : 01-06-2020
Supersedes : 08-13-2019

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

SDS Canada U-POL

CUSTOM CAN FILL-ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.