



EGC62 FIBREGLASS FILLER

EGC62

Version: 2.0 Date of issue: 15/02/2018 Revision date: 15/10/2019 Supersedes: 15/02/2018



DRIVING SURFACE PERFECTION

TECHNICAL DATASHEET

Manufactured using high quality European resins, EGC62 Fibreglass Filler takes the place of both short and long strand products. Its lightweight formula can be easily shaped and sanded once cured.

- Spreads like a short strand yet bridges holes like a long strand.
- Non-sagging even on vertical surfaces - spreads, adheres, and finishes like a polyester filler.
- Forms a hard, durable surface that is still smooth and very easy to sand.
- Water resistant.
- Can be finished with putty or glaze or directly primed.
- Spreads, adheres, and finishes like a polyester filler.

Typical Use

For the bridging of holes and rust in surfaces such as steel and GRP.



Application Guide

Tools Required



Bodyfiller Applicator (UP0738), GUIDE #7 Guide Coat Aerosol, MAXIMUM Abrasives, MAXIMUM Painters Overalls, MAXIMUM Premium Masks, Onion Board Mixing Palette (UP0737), U-POL System 20 Degreaser (UP2002, UP2012, UP2022), EGC89 Solvent Based Degreaser.

Surface Preparation



Bare Steel

Original Paint

Fiberglass

Degreaser

EGC89 Solvent Based Degreaser

EGC89 Solvent Based Degreaser

UP2002 Water-Based Degreaser

Abrasion

P80

P180

P180

EGC62 FIBREGLASS FILLER has superb adhesion to all the substrates above.

For best results, good preparation is essential.

Clean and degrease removing dirt, oil, grease and wax with a cleaning solution, like EGC89 Solvent Based Degreaser or SYSTEM 20 Water Based Degreaser (UP2002) (please check local VOC regulations).

Abrade with grit paper as stated above for each respective substrate.

Re-clean, dry and degrease the abraded substrate ready for application.

Application



Mixing ratio (BPO Hardener):

50°F

4%

70°F

3%

85°F

2%

Gel Time:

7 - 8 minutes

4 - 7 minutes

4 - 5 minutes

Sandable after:

20 minutes

15 - 20 minutes

15 minutes

Maximum Fill Depth

4 - 7 mm

Apply with a pressing action to reduce air entrapment.

Follow mix ratio carefully. Do not under or over catalyze.

Mix thoroughly on an Onion Board Mixing Palette.

Not recommended for applications below 40°F

Sanding



Initial Sanding

P80 - P120

Final Sanding

P180 - P240

A U-POL Finishing Filler such as EGC52 PREMIUM GLAZE can be used to fill imperfections such as pin holes and scratches prior to painting.

Over-Painting



U-POL recommends an EGC Primer to achieve the perfect surface for the color of your choice.

Technical information

Physical properties

Appearance

Fibrous, Paste.

Color

Yellow

Specific gravity / density

≈ 1.275 (1.26 - 1.29) g/cm³

U-POL US, Inc.
108 Commerce Way
Stockertown, PA 18083
WWW.U-POL.COM

US Sales
T: (610) 746 7081
F: (610) 743 8654
sales-us@u-pol.com

International
T: +44 (0)20 8492 5900
F: +44 (0)20 8150 5605
sales@u-pol.com

Technical
T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicalsupport@u-pol.com



EGC62 FIBREGLASS FILLER

EGC62

Version: 2.0 Date of issue: 15/02/2018 Revision date: 15/10/2019 Supersedes: 15/02/2018



DRIVING SURFACE PERFECTION

TECHNICAL DATASHEET



VOC Information



As Packaged Regulatory VOC	332 g/l (2.77 lb/gal)
As Packaged Actual VOC	332 g/l (2.77 lb/gal)
As Applied Regulatory VOC	70 g/l (0.58 lb/gal)
As Applied Actual VOC	70 g/l (0.58 lb/gal)
Percent Solids	75.83 wt%
Volatiles	24.2 wt%
Water Content	0 wt%
Exempt Compounds by weight	0 wt%
Exempt Compounds by volume	0 vol %
% HAPS	42.98 wt%

Shelf Life & Storage



Order Code	Format	Shelf Life	Batch Coding System
EGC62	0.8 Gallon Can	4 years	C

- A Date of manufacture, unique 5-digit batch code and expiry date printed on base of tin.
- B Date of manufacture and/or 5-digit batch code printed on base of tin/adhesive label/adhesive label on kit box. e.g. 93822 = 2019, week 38, batch 22
- C Date of manufacture and unique 5-digit batch code and printed on base of tin/adhesive label.
- D Date of manufacture and unique 5-digit batch code printed on cartridge.
- E Date of manufacture and unique 7-digit code printed on lid.
- F Date of manufacture and unique 6-digit batch number printed on packaging.
- G Date of manufacture and unique 4-digit batch code and printed on base of tin.
- H Date of manufacture and batch number incorporated into 8-digit code e.g. 18071234 = (18) 2018, (07) July, batch number 1234
- I Date of manufacture printed on tin.
- J Date and time of manufacture printed on neck of aerosol.
- K Date of manufacture and weight of sachet embossed on seal. e.g. 40G 110717
- L Unique 5-digit batch code printed on packaging/adhesive label/embossed on seal. For the date of manufacture, please quote this code to technicalsupport@u-pol.com.
- M Unique 5-digit batch number followed by weight printed on tube. e.g. 17149GR78 = batch number 17149GR, weight 78 g. For the date of manufacture, please quote this code to technicalsupport@u-pol.com.
- N Date of filling and unique 7 digit batch code stamped on adhesive label.
- O LOT number ending in a unique 5-digit code printed on sachet. For the date of manufacture, please quote this code to technicalsupport@u-pol.com.
- P Date of aerosol manufacture and 5-digit aerosol base batch code printed on base of tin. e.g. 93822 = 2019, week 38, batch 22
- Q Date of aerosol manufacture and unique 5-8 digit batch code printed on base of tin.

Recommended storage temperature 40 °F - 75 °F
 Store locked up. Store in a well-ventilated place. Keep cool. Keep only in original container.

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL US, Inc.
 108 Commerce Way
 Stockertown, PA 18083
 WWW.U-POL.COM

US Sales
 T: (610) 746 7081
 F: (610) 743 8654
 sales-us@u-pol.com

International
 T: +44 (0)20 8492 5900
 F: +44 (0)20 8150 5605
 sales@u-pol.com

Technical
 T: +44 (0)1933 230 310
 F: +44 (0)1933 425 797
 technicalsupport@u-pol.com