



DRIVING SURFACE PERFECTION™

CLEAR #1

CLEAR #1 UV Resistant Clearcoat Aerosol



DESCRIPTION

An advanced clearcoat that gives an excellent high gloss finish with UV resistance and durability. Ideal for spot repairs, wing mirror covers, door handles and mouldings.

FEATURES

- Excellent flow and depth of gloss
- Easy to use and fast drying
- Compatible with solvent and water-based basecoats






TECHNICAL DATA SHEET

CLEAR #1

CLEAR #1 UV Resistant Clearcoat

Aerosol

Product preparation - application Spray can

| | | |
|--|---|--|
|  | It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation. | |
|  | Old or original paintwork - thoroughly clean and degrease surfaces with precleaner or panel prep. Sand P800 - P1000 and reclean with degreaser. For freshly applied coatings such as water or solvent based basecoat, follow manufacturers TDS guidelines for overcoat times. Generally solvent based basecoat should be flashed of for at least 20 minutes before application of clearcoat. | |
|  | Ready to use | |
|  | Not applicable | |
|  | 1 - 2 coats sprayed 15-25cm away from the object | with intermediate flash-off: 5 min - 10 min at 20°C Handleable: 30 min at 20°C Final airdry time: 1 hr at 20°C depending on film build |

VOC compliant

2004/42/IIB/e(840) 680: The EU limit value for this product (product category: e) in ready to use form is maximum 840 g/l of VOC. The VOC content of this product in ready to use form is maximum 680 g/l.



TECHNICAL DATA SHEET

CLEAR #1

CLEAR #1 UV Resistant Clearcoat

Aerosol

Products

| | |
|--|--|
| | U-POL CLEAR #1 UV Resistant Clearcoat |
|  | 35 µm 2 coats |
|  | After use, hold aerosol can upside down and spray briefly to clean nozzle. If the nozzle becomes blocked, remove from the can and soak in gentle thinners before replacing. |

Remarks

- Theoretical coverage 1.6m² per unit, assuming 100% transfer efficiency at the recommended film build.
- Aerosol cans should be stored for 2 hours at room temperature before use. For long term storage keep in a dry well ventilated area and away from direct sunlight and frost. Recommended storage temperature 5 - 25°C, recommended application temperature 20°C

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our brand product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our brand product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.