



DRIVING SURFACE PERFECTION™

GRIP #4

GRIP #4 Universal Adhesion Promotor Aerosol



DESCRIPTION

A ready to use universal adhesion promotor for paints, adhesives and sealants. Ideal for all automotive surfaces such as plastics, aluminium, fibreglass, galvanised and painted surfaces. Improves surface preparation in difficult to access areas.

FEATURES

- Sprays flat - no sanding required
- Can be overcoated with most water or solvent based paint systems
- Helps to prevent lifting in hard to sand areas






TECHNICAL DATA SHEET

GRIP #4

GRIP #4 Universal Adhesion Promotor

Aerosol

Product preparation - application

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.	
	Thoroughly clean the area with detergent and water and allow to dry completely. Where possible, abrade surface P180 - P320 for metals, P320 - P500 for plastics, P800 - P1000 for original or OEM paintwork. Clean or degrease thoroughly after abrading to remove dust. Suitable for use on most plastics, Original paint, fibreglass, SMC, lightly abraded E-Coat, DTM including Aluminium and Galvanised steel.	
	Ready to use	
	Not applicable	
	1 - 2 Light coats 15-25 cm from the object	with intermediate flash-off: 10 min at 20°C Final flash-off to overcoat with most solvent and water based paint systems: 20 min at 20°C

VOC compliant

2004/42/IIIB/e(840) 763: The EU limit value for this product (product category: e) in ready to use form is maximum 840 g/l of VOC. The VOC content of this product in ready to use form is maximum 763 g/l.



TECHNICAL DATA SHEET

GRIP #4

GRIP #4 Universal Adhesion Promotor

Aerosol

Products

GRIP #4 1K Universal Adhesion Promoter	
	2 µm
	After use, hold aerosol can upside down and spray briefly to clean nozzle. If the nozzle becomes blocked, remove from the can and soak in gentle thinners before replacing.

Remarks

- Theoretical coverage 2m² per unit, assuming 100% transfer efficiency and at the indicated film build.
- Aerosol cans should be stored for 2 hours at room temperature before use. For long term storage keep in a dry well ventilated area and away from direct sunlight and frost. Recommended storage temperature 5 - 25°C, recommended application temperature 20°C

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our brand product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our brand product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.