



DRIVING SURFACE PERFECTION™

# GUARD #10

## GUARD #10 Gravi-Gard Stone Chip Protector Aerosol



### DESCRIPTION

A textured, durable coating to protect against stone chips, salt, damp and rust. Supplied with two nozzles for either a fine or coarse finish.

### FEATURES







- Sound dampening - ideal for body panels and inside engine compartments
- Fast drying and can be over painted
- High build formulation covers weld marks and seams

# TECHNICAL DATA SHEET

## GUARD #10

### GUARD #10 Gravi-Gard Stone Chip Protector Aerosol

#### Product preparation - application

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.	
	<p>For steel, thoroughly clean and degrease surfaces, abrade with P80 - P240, reclean to remove dust. For optimum results on bare metal, aluminium surfaces and galvanized steel abrade P180 - P320, apply 1-2 light coats ACID #8 Etch Primer, allowing 30 minutes drying time before priming. Old or original paintwork - thoroughly clean and degrease surfaces with precleaner or panel prep. Sand P240 - P320 and reclean with degreaser. Can be applied over sanded SMC, polyester bodyfillers and Fibreglass when abraded P180 - P240 and degreased, or lightly sanded E-Coat</p>	
	Ready to use	
	Not applicable	
	1 - 2 coats at a distance 25-40 cm to create the desired texture	with intermediate flash-off: 10 min - 15 min at 20°C Overpaintable without sanding: 3 hr - 4 hr Depending on film thickness.
	Scuff before overcoating if left more than 16 hours. Can be overcoated with most paint systems, for optimum gloss holdout use a 2K primer to seal the surface first.	

VOC compliant



2004/42/IB/e(840) 567: The EU limit value for this product (product category: e) in ready to use form is maximum 840 g/l of VOC. The VOC content of this product in ready to use form is maximum 567 g/l.

# TECHNICAL DATA SHEET

## GUARD #10

### GUARD #10 Gravi-Gard Stone Chip Protector Aerosol

#### Products

GUARD #10 Gravi-Gard™ Stone Chip Protector	
	40 - 50 µm 2 coats
	After use, hold aerosol can upside down and spray briefly to clean nozzle. If the nozzle becomes blocked, remove from the can and soak in gentle thinners before replacing.

#### Remarks

- Applying more than 2 coats increases the drying time for overcoating.
- Theoretical coverage up to 2m² per unit, assuming 100% transfer efficiency at the specified film build.
- Aerosol cans should be stored for 2 hours at room temperature before use. For long term storage keep in a dry well ventilated area and away from direct sunlight and frost. Recommended storage temperature 5 - 25°C, recommended application temperature 20°C

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our brand product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our brand product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.