



DRIVING SURFACE PERFECTION™

MICF/200

MicroFill Pinhole Eliminator and Sealer



DESCRIPTION

A wipe-on pinhole eliminator and sealer for use over filled surfaces prior to priming to help reduce re-work. It Eliminates micro pinholes and scratches after sanding and seals the filled repair surface reducing primer consumption by up to 30%. It also contains an adhesion promoter which improves adhesion between the surface and primer. The 1K paste dries within 15 minutes and is ready for painting with no sanding required.

FEATURES







- Reduces primer consumption by up to 30%
- Reduces re-work
- Promotes adhesion between surface and primer
- Easy to use 1K paste
- Ready to overpaint in 15 mins (@ 20°C)
- Free from microplastics

TECHNICAL DATA SHEET

MICF/200

MicroFill Pinhole Eliminator and Sealer

Product preparation - application Surface conditioner

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.
	Existing bodyfiller - cleaned with solvent based degreaser and sanded with P80-P180 grit. Re-clean the abraded substrate before application. Existing finishes: Surfaces must be sanded and precleaned before application Most automotive exterior plastic parts.
	Ready For Use Apply a small amount of MIC onto the surface to be treated and work into the surface using a lint free cloth. Buff the surface to remove excess MIC. Repeat as necessary.
	Not applicable
	When using waterborne primers, allow to dry for 20-minutes. Sand with P320 or finer, then apply primer as per manufacturers' instructions.
	Primer Primer-Surfacer

VOC compliant

2004/42/IIB(c)(540) 540: The EU limit value for this product (product category: IIB(c)) in ready to use form is maximum 540 g/l of VOC. The VOC content of this product in ready to use form is maximum 540 g/l.

TECHNICAL DATA SHEET

MICF/200

MicroFill Pinhole Eliminator and Sealer

Products

	U-POL MicroFill
--	-----------------

Waste treatment	Dispose of contents / container to approved disposal companies or municipal collection points. Do not empty into drains.
-----------------	--

Remarks

- Large pinholes should be filled with a glazing putty such as U-POL Dolphin Glaze.
- Recommended storage temperature at 5°C to 25°C.
- At high temperature product may become liquid. This does not affect performance.

Shelf Life	2 years

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our brand product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our brand product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.