



# FIBRAL LITE FIBREGLASS FILLER

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

DRIVING SURFACE PERFECTION

Date of issue:19/01/2017

Revision date:03/05/2019

Supersedes: 20/03/2018

Version: 2.4

### SECTION 1: Identification : Product identifier and chemical identity

#### 1.1. Product identifier

Product form : Mixture  
Trade name : FIBRAL LITE FIBREGLASS FILLER  
Product code : FIBL/2, FIBL/3

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Fillers

#### 1.4. Supplier's details

##### Supplier

U-POL AUSTRALIA PTY LIMITED  
Unit A, 16 - 20 Cassola Place  
Penrith, NSW 2750 - Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com.au](http://www.u-pol.com.au)

##### Supplier

U-POL NEW ZEALAND LIMITED  
c/o Lindsay & Associates  
Unit H, 12 Amera Place, East Tamaki  
Manukau City 2013 - New Zealand  
T + 612 4731 2655 - F + 612 4731 2611  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazards identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2A H319  
Reproductive toxicity, Category 2 H361  
Specific target organ toxicity — Repeated exposure, Category 1 H372

#### 2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger  
Contains : styrene (5-23 %)  
Hazard statements (GHS AU) : H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H361 - Suspected of damaging the unborn child.  
H372 - Causes damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).  
Precautionary statements (GHS AU) : P260 - Do not breathe fume, vapours.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P302+P352 - IF ON SKIN: Wash with plenty of water  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

# FIBRAL LITE FIBREGLASS FILLER

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
styrene ( )	100-42-5	5-23	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)		66.35 - 79.89	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Symptoms caused by exposure

- Symptoms/effects after skin contact : Irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

#### 5.2. Special hazards arising from the substance or mixture

- General measures : Remove ignition sources. No open flames. No smoking.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Hazchemcode : \* 3Y

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Protective clothing. Safety glasses. Gloves.
- Emergency procedures : Ventilate spillage area. Do not breathe vapours. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Avoid breathing vapours. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

- Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released product. Collect spillage.
- Methods for cleaning up : Mechanically recover the product. This material and its container must be disposed of in a safe way, and as per local legislation. Notify authorities if product enters sewers or public waters.

### SECTION 7: Handling and storage, including how the chemical may be safely used

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

# FIBRAL LITE FIBREGLASS FILLER

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.  
Storage temperature : < 25 °C  
Storage area : Store in well ventilated area.  
Special rules on packaging : Keep only in original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters - exposure standards

styrene (100-42-5)		
Australia	Local name	Styrene, monomer (Phenylethylene; Vinyl benzene)
Australia	TWA (mg/m <sup>3</sup> )	213 mg/m <sup>3</sup>
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m <sup>3</sup> )	426 mg/m <sup>3</sup>
Australia	STEL (ppm)	100 ppm
New Zealand	Local name	Phenylethylene (Styrene, monomer) (Vinyl benzene)
New Zealand	TWA (mg/m <sup>3</sup> )	213 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	50 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	426 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	100 ppm
New Zealand	Remark (NZ)	skin (Skin absorption), 6.7A (Confirmed carcinogen)
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

### Exposure limit values for the other components

### 8.2. Monitoring

No additional information available

### 8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Personal protective equipment

Personal protective equipment : Gloves. Protective clothing. Safety glasses.  
Materials for protective clothing : Impermeable clothing  
Hand protection : Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Protective gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR), Polyvinylalcohol (PVA), Viton	6 (> 480 minutes)	0.4		EN 374-3

Eye protection : Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Dust	clear	

Skin and body protection : Wear suitable protective clothing

Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Device	Filter type	Condition	Standard
Breathing apparatus, Gas filters	Type A - High-boiling (>65 °C) organic compounds	Vapour protection	EN 140, EN 136, EN 143, EN 145, EN 149

Personal protective equipment symbol(s)

# FIBRAL LITE FIBREGLASS FILLER

## Safety Data Sheet

according to the Model Work Health and Safety Regulations



Environmental exposure controls : Avoid release to the environment.

### SECTION 9: Physical and chemical properties

Physical state	: Solid
Appearance	: Fibrous. Paste.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Freezing point : Not applicable
Boiling point	: No data available
Flash point	: 31 °C
Auto-ignition temperature	: Not applicable
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density : $\approx 1.275$ (1.26 - 1.29) g/cm <sup>3</sup> Relative density : Not applicable
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Viscosity, dynamic	: $\approx$
Explosive properties	: No data available
Explosive limits	: Not applicable
Minimum ignition energy	: No data available
VOC content	: 332 g/l
VOC content - Regulatory	: No data available
Percent Solids	: 75.83 wt%

### SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport. The product is non-reactive under normal conditions of use, storage and transport
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

styrene (100-42-5)	
LD50 oral rat	> 6000 mg/kg bodyweight (Rat, Male, Weight of evidence, Oral)
LD50 oral	> 6000 mg/kg bodyweight (Hamster, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	11.8 mg/l air (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours))
LC50 inhalation rat (Vapours - mg/l/4h)	< 6000 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

# FIBRAL LITE FIBREGLASS FILLER

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).
Aspiration hazard	: Not classified

### SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

#### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

styrene (100-42-5)	
LC50 fish 1	10 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	4.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, GLP)
ErC50 (algae)	4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	35.5 (Carassius auratus, Literature study)
Log Pow	2.96 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Log Koc	2.55 (log Koc, Estimated value)

#### 12.2. Persistence and degradability

styrene (100-42-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Chemical oxygen demand (COD)	2.8 g O <sub>2</sub> /g substance
ThOD	3.07 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.42 (Literature study)

#### 12.3. Bioaccumulative potential

styrene (100-42-5)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### 12.4. Mobility in soil

styrene (100-42-5)	
Surface tension	0.032 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

#### 12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

FIBRAL LITE FIBREGLASS FILLER	
Fluorinated greenhouse gases	False
styrene (100-42-5)	
Fluorinated greenhouse gases	False

# FIBRAL LITE FIBREGLASS FILLER

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

#### 14.1. UN number

UN-No. (ADG) : 1866

#### 14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : RESIN SOLUTION

#### 14.3. Transport hazard class(es)

##### ADG

Transport hazard class(es) (ADG) : 3  
Danger labels (ADG) : 3



##### IMDG

Transport hazard class(es) (IMDG) : Not applicable

##### IATA

Transport hazard class(es) (IATA) : Not applicable

#### 14.4. Packing group

Packing group (ADG) : III  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

#### 14.5. Environmental hazards

Marine pollutant : No

#### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

#### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1866  
Special provision (ADG) : 223  
Limited quantities (ADG) : 5I  
Packing instructions (ADG) : P001, IBC03, LP01  
Special packing provisions (ADG) : PP1  
Portable tank and bulk container instructions (ADG) : T2  
Portable tank and bulk container special provisions (ADG) : TP1

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### 14.8. Hazchem or Emergency Action Code

Hazchemcode : \* 3Y

# FIBRAL LITE FIBREGLASS FILLER

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

#### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002670

Group standard : Surface coatings and colourants

#### 15.2. International agreements

No additional information available

### SECTION 16: Any other relevant information

Revision date : 03/05/2019

Classification:

Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Repr. 2	H361
STOT RE 1	H372

Full text of H-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

SDS Australia U-POL

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.*