

U-POL Application Guide

Recommended Procedure for Obtaining Consistent Results

UP0799 GRIP#4™ Universal Adhesion Promoter

UP0799 GRIP#4 Adhesion Promoter is an effective tie coat for use on the following substrates:

- All plastics including TPO
- Body side and trim molding
- Fiberglass / SMC
- Painted surfaces
- Aluminum, Galvanized, Zinc
- Polyester fillers and putties

Process Tools Required:		
UP0799 GRIP#4		

1. SURFACE PREPARATION



Thoroughly clean area with soap and water, let dry. Degrease with solvent or water based wax and grease remover. Blow off with clean compressed air.

2. SHAKE UP0799



Shake can thoroughly for 2 minutes

3. APPLICATION



Apply 2 light even coats over area or component to be painted. Allowing a 5 minute flash time between coats.

4. DRY TIME



Allow Grip#4 to dry 10 - 20 minutes before applying primer, color or clear. Top coat within 60 minutes of application. Due to possible surface contamination, if left for longer than 60 minutes, clean and re-apply.

5. SANDING



Sanding of Grip#4 is not necessary.

U-POL®

U-POL Technical Support:
1-800-340-7824

U-POL US, 630 Municipal Drive, Suite 300, Nazareth, PA 18064
T: 800-340-7824 F: 610-743-8654 sales-us@u-pol.com www.u-pol.com