

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Product Reference code:according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 SDS Ref. (EU): GUARDAL-SDS Issue date: 24/02/2015 Revision date: 22/12/2022 Supersedes version of: 14/08/2020 Version: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| Product group : Aerosol | Product form Trade name Product code Vaporizer Product group | : Mixture : GUARD #10 GRAVI-GARD BLACK AEROSOL : GUARD/AL : Aerosol : Aerosol |
|-------------------------|--|---|
|-------------------------|--|---|

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

| Main use category | : Industrial use, Professional use |
|------------------------------|---|
| Use of the substance/mixture | : Coatings and paints, thinners, paint removers |
| Function or use category | : Topcoat |

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

U-POL Limited Ltd Denington Road GB– NN8 2QH Wellingborough – Northamptonshire United Kingdom T +44 (0) 1933 230310 technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number

: CHEMTREC: +44 (0) 870 8200418 (24 hrs)

| Country | Organisation/Company | Address | Emergency number | Comment |
|----------------|--|--|--|---|
| Ireland | National Poisons Information Centre Beaumont Hospital | PO Box 1297 Beaumont Road 9 Dublin | +353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7) | |
| United Kingdom | NHS England, Scotland & Wales | - | Call 111 or a Doctor | In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.h scni.net) |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

| Classification according to Regulation (EC) No. 1272/2008 [CLP] | |
|--|-----------|
| Aerosol, Category 1 | H222;H229 |
| Skin corrosion/irritation, Category 2 | H315 |
| Serious eye damage/eye irritation, Category 2 | H319 |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336 |
| Specific target organ toxicity – Repeated exposure, Category 2 | H373 |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

| Labelling according to Regulation (EC) No. 1272 | /2008 [CLP] |
|---|--|
| Hazard pictograms (CLP) | : GHS02 GHS07 GHS08 |
| Signal word (CLP) | : Danger |
| Contains | : acetone, reaction mass of ethylbenzene, m-xylene and p-xylene |
| Hazard statements (CLP) | H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H373 - May cause damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled). |
| Precautionary statements (CLP) | P210 - Keep away from heat, hot surfaces, open flames, sparks. – No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Pressurized container: Do not pierce or burn, even after use. P261 - Avoid breathing vapours, fume, spray. P264 - Wash hands thoroughly after handling. P280 - Wear eye protection, protective clothing, protective gloves. P337+P313 - If eye irritation persists: Get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|---------|--|
| acetone substance with a Community workplace exposure limit | CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330- 49 | 20 – 25 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| reaction mass of ethylbenzene, m-xylene and p- xylene | EC-No.: 905-562-9 REACH-no: 01-2119555267- 33 | 5 – 20 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|---------|--|
| Xylene substance with a Community workplace exposure limit (Note C) | CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32 | 5 – 10 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| kieselguhr, soda ash flux calcined | CAS-No.: 68855-54-9 EC-No.: 272-489-0 REACH-no: 01-2119488518- 22 | < 5 | STOT RE 2, H373 |
| ethylbenzene substance with a Community workplace exposure limit | CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370- 35 | 1 – 2.5 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 |

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

| SECTION 4: First aid measures | |
|---|--|
| 4.1. Description of first aid measures | |
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |
| 4.2. Most important symptoms and eff | ects, both acute and delayed |
| Symptoms/effects after skin contact Symptoms/effects after eye contact | Irritation. Repeated exposure may cause skin dryness or cracking. Eye irritation. |
| 4.3. Indication of any immediate media | cal attention and special treatment needed |

Treat symptomatically.

| SECTION 5: Firefighting measures | |
|---|---|
| 5.1. Extinguishing media | |
| Suitable extinguishing media | : Water spray. Dry powder. Foam. |
| 5.2. Special hazards arising from the subst | ance or mixture |
| Fire hazard Explosion hazard Hazardous decomposition products in case of fire | Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic fumes may be released. |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| 5.3. Advice for firefighters | |
|---------------------------------------|---|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
| SECTION 6: Accidental release n | neasures |
| 6.1. Personal precautions, protective | e equipment and emergency procedures |
| 6.1.1. For non-emergency personnel | |
| Protective equipment | : Safety glasses. Protective clothing. Gloves. |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, fume, spray. Avoid contact with skin and eyes. |
| 6.1.2. For emergency responders | |
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| 6.2. Environmental precautions | |
| Avoid release to the environment. | |
| 6.3. Methods and material for contai | nment and cleaning up |
| For containment | : Contain released product. Collect spillage. |
| Methods for cleaning up | : Mechanically recover the product. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

For further information refer to section 13.

| SECTION 7: Handling and storage | | | |
|---|---|--|--|
| 7.1. Precautions for safe handling | | | |
| Precautions for safe handling Hygiene measures | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, fume, spray. Avoid contact with skin and eyes. Wear personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. | | |
| 7.2. Conditions for safe storage, including any incompatibilities | | | |
| Storage conditions Storage temperature Special rules on packaging | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool. < 25 °C Keep only in original container. | | |
| 7.3. Specific end use(s) | | | |

No additional information available

| SECTION 8: | Exposure | controls/ | personal | protection |
|------------|----------|-----------|----------|------------|
|------------|----------|-----------|----------|------------|

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Safety Data Sheet

| acetone (67-64-1) | | |
|--|---|--|
| EU - Indicative Occupational Exposure Limit (IOEL) | | |
| Local name | Acetone | |
| IOEL TWA | 1210 mg/m ³ | |
| IOEL TWA [ppm] | 500 ppm | |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC | |
| Ireland - Occupational Exposure Limits | | |
| Local name | Acetone | |
| OEL TWA [1] | 1210 mg/m ³ | |
| OEL TWA [2] | 500 ppm | |
| Remark | IOELV (Indicative Occupational Exposure Limit Values) | |
| Regulatory reference | Chemical Agents Code of Practice 2020 | |
| Ireland - Biological limit values | | |
| Local name | Acetone | |
| BLV | 50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific) | |
| Regulatory reference | Biological Monitoring Guidelines (HSA, 2011) | |
| United Kingdom - Occupational Exposure Limits | | |
| Local name | Acetone | |
| WEL TWA (OEL TWA) [1] | 1210 mg/m ³ | |
| WEL TWA (OEL TWA) [2] | 500 ppm | |
| WEL STEL (OEL STEL) | 3620 mg/m ³ | |
| WEL STEL (OEL STEL) [ppm] | 1500 ppm | |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE | |
| kieselguhr, soda ash flux calcined (68855-54- | 9) | |
| Ireland - Occupational Exposure Limits | | |
| Local name | Diatomaceous earth, natural, respirable dust | |
| OEL TWA [1] | 1.2 mg/m ³ | |
| Regulatory reference | Chemical Agents Code of Practice 2020 | |
| United Kingdom - Occupational Exposure Limits | | |
| WEL TWA (OEL TWA) [1] | 1.2 mg/m ³ | |
| Xylene (1330-20-7) | | |
| EU - Indicative Occupational Exposure Limit (IOEL) | | |
| Local name | Xylene, mixed isomers, pure | |
| IOEL TWA | 221 mg/m ³ | |
| IOEL TWA [ppm] | 50 ppm | |
| IOEL STEL | 442 mg/m ³ | |
| IOEL STEL [ppm] | 100 ppm | |
| Remark | Skin | |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC | |

Safety Data Sheet

| Xylene (1330-20-7) | |
|--|--|
| Ireland - Occupational Exposure Limits | |
| Local name | Xylene, mixed isomers |
| OEL TWA [1] | 221 mg/m³ |
| OEL TWA [2] | 50 ppm |
| OEL STEL | 442 mg/m ³ |
| OEL STEL [ppm] | 100 ppm |
| Remark | Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values) |
| Regulatory reference | Chemical Agents Code of Practice 2020 |
| Ireland - Biological limit values | |
| Local name | Xylene |
| BLV | 1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift |
| Regulatory reference | Biological Monitoring Guidelines (HSA, 2011) |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Xylene |
| WEL TWA (OEL TWA) [1] | 220 mg/m³ |
| WEL TWA (OEL TWA) [2] | 50 ppm |
| WEL STEL (OEL STEL) | 441 mg/m³ |
| WEL STEL (OEL STEL) [ppm] | 100 ppm |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| United Kingdom - Biological limit values | |
| Local name | Xylene, o-, m-, p- or mixed isomers |
| BMGV | 650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| ethylbenzene (100-41-4) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Ethylbenzene |
| IOEL TWA | 442 mg/m ³ |
| IOEL TWA [ppm] | 100 ppm |
| IOEL STEL | 884 mg/m³ |
| IOEL STEL [ppm] | 200 ppm |
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| Ireland - Occupational Exposure Limits | • |
| Local name | Ethylbenzene |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| ethylbenzene (100-41-4) | | |
|---|---|--|
| OEL TWA [1] | 442 mg/m ³ | |
| OEL TWA [2] | 100 ppm | |
| OEL STEL | 884 mg/m ³ | |
| OEL STEL [ppm] | 200 ppm | |
| Remark | Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values) | |
| Regulatory reference | Chemical Agents Code of Practice 2020 | |
| Ireland - Biological limit values | | |
| Local name | Ethyl benzene | |
| BLV | 0.7 g/g creatinine Parameter: mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift at end of workweek - Notations: Ns (Non-specific), Sq (Semi- quantitative) Parameter: ethylbenzene - Medium: end-exhaled air - Sampling time: Not critical - Notations: Sq (Semi-quantitative) | |
| Regulatory reference | Biological Monitoring Guidelines (HSA, 2011) | |
| United Kingdom - Occupational Exposure Limits | | |
| Local name | Ethylbenzene | |
| WEL TWA (OEL TWA) [1] | 441 mg/m ³ | |
| WEL TWA (OEL TWA) [2] | 100 ppm | |
| WEL STEL (OEL STEL) | 552 mg/m³ | |
| WEL STEL (OEL STEL) [ppm] | 125 ppm | |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) | |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE | |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses

8.2.2.2. Skin protection

Skin and body protection: Wear suitable protective clothing

Hand protection: Protective gloves

Other skin protection

Materials for protective clothing:

Impermeable clothing

8.2.2.3. Respiratory protection

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. [In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | : Liquid |
|---|---|
| Appearance | : Aerosol. |
| Colour | : Black. |
| Odour | : No data available |
| Odour threshold | : No data available |
| рН | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Vapour pressure | : No data available |
| Relative vapour density at 20°C | : No data available |
| Relative density | : No data available |
| Density | : 0.969 g/cm ³ |
| Solubility | : insoluble in water. soluble in most organic solvents. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Viscosity, kinematic | : 31.3 mm²/s |
| Viscosity, dynamic | : No data available |
| Explosive properties | : Pressurised container: May burst if heated. |
| Oxidising properties | No data available |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Explosive limits | : No data available |
|--------------------------|----------------------------------|
| 9.2. Other information | |
| VOC content Gas group | : 571 g/l : Press. Gas (Liq.) |

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

| SECTION 11: Toxicological information | |
|--|---|
| 11.1 Information on toxicological effects | |
| Acute toxicity (dermal) | Not classified Not classified Not classified |
| 2-methylpropan-1-ol; iso-butanol (78-83-1) | |
| LD50 oral rat | > 2830 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 18.18 mg/l air (6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s)) |
| LC50 Inhalation - Rat (Vapours) | 24.6 mg/l/4h (Other, 4 h, Rat, Male/female, Experimental value, Inhalation (vapours)) |
| cyclohexanone oxime (100-64-1) | |
| LD50 oral rat | 883 mg/kg (rat, female) |
| LD50 dermal rabbit | > 5000 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), rabbit, male/female) |
| naphtha (petroleum), hydrotreated heavy (64742-48-9) | |
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rabbit | > 5000 mg/kg |
| LC50 Inhalation - Rat | > 4951 mg/m³ |

Safety Data Sheet

| acetone (67-64-1) | |
|--|--|
| LD50 oral rat | 5800 mg/kg bodyweight Animal: rat, Animal sex: female |
| LD50 dermal rabbit | > 15800 mg/kg bodyweight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | 76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4 |
| dolomite (16389-88-1) | |
| LD50 oral rat | > 2000 mg/kg (OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), rat, female, Experimental value) |
| magnesium carbonate (546-93-0) | |
| LD50 oral rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure) |
| quartz (14808-60-7) | |
| LD50 oral rat | > 500 mg/kg |
| carbon black (1333-86-4) | |
| LD50 oral rat | > 8000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LC50 Inhalation - Rat | > 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust)) |
| castor oil, sulphated, sodium salt (68187-76-8 |) |
| LD50 oral rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity) |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity) |
| kieselguhr, soda ash flux calcined (68855-54- | 9) |
| LD50 oral rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LC50 Inhalation - Rat | > 2.6 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) |
| LC50 Inhalation - Rat (Dust/Mist) | > 2.6 mg/l/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, Experimental value) |
| reaction mass of ethylbenzene, m-xylene and | p-xylene |
| LD50 oral rat | 3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral), rat, male) |
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
| LC50 Inhalation - Rat [ppm] | 6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours) |
| calcium carbonate (471-34-1) | |
| LD50 oral rat | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure) |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)) |

Safety Data Sheet

| calcium carbonate (471-34-1) | | |
|---|---|--|
| LC50 Inhalation - Rat | > 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity) | |
| LC50 Inhalation - Rat (Dust/Mist) | > 3 mg/l/4h (4 h, OECD Guidelines 403 (Acute Toxicity Inhalation), rat, male/female, Experimental value) | |
| Xylene (1330-20-7) | | |
| LD50 oral rat | 3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s)) | |
| LD50 dermal rat | 12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days) | |
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male | |
| LC50 Inhalation - Rat [ppm] | 6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male) | |
| ethylbenzene (100-41-4) | | |
| LD50 oral rat | 3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s)) | |
| LD50 dermal rabbit | 15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal) | |
| LC50 Inhalation - Rat | 17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours)) | |
| talc (14807-96-6) | I | |
| LD50 oral rat | > 5000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s)) | |
| LD50 dermal rat | > 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s)) | |
| LC50 Inhalation - Rat | > 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s)) | |
| | Causes skin irritation. | |
| | Causes serious eye irritation. Not classified | |
| | Not classified | |
| Carcinogenicity : | Not classified | |
| reaction mass of ethylbenzene, m-xylene and | p-xylene | |
| IARC group | 2B - Possibly carcinogenic to humans | |
| Xylene (1330-20-7) | | |
| IARC group | 3 - Not classifiable | |
| ethylbenzene (100-41-4) | | |
| IARC group | 2B - Possibly carcinogenic to humans | |
| Reproductive toxicity : | Not classified | |
| acetone (67-64-1) | | |
| LOAEL (animal/female, F0/P) | 11298 mg/kg bodyweight Animal: mouse, Animal sex: female | |
| NOAEL (animal/male, F0/P) | 900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information) | |
| STOT-single exposure : | May cause drowsiness or dizziness. | |
| 2-methylpropan-1-ol; iso-butanol (78-83-1) | | |
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. | |

Safety Data Sheet

| naphtha (petroleum), hydrotreated heavy (64742-48-9) | | |
|--|---|--|
| STOT-single exposure | May cause drowsiness or dizziness. | |
| acetone (67-64-1) | | |
| STOT-single exposure | May cause drowsiness or dizziness. | |
| reaction mass of ethylbenzene, m-xylene and | p-xylene | |
| STOT-single exposure | May cause respiratory irritation. | |
| Xylene (1330-20-7) | | |
| STOT-single exposure | May cause respiratory irritation. | |
| | May cause damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled). | |
| 2-methylpropan-1-ol; iso-butanol (78-83-1) | | |
| NOAEL (oral, rat, 90 days) | > 1450 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) | |
| cyclohexanone oxime (100-64-1) | | |
| NOAEL (oral, rat, 90 days) | 2.5 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) | |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. | |
| castor oil, sulphated, sodium salt (68187-76-8 |) | |
| NOAEL (oral, rat, 90 days) | 5780 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents) | |
| kieselguhr, soda ash flux calcined (68855-54- | 9) | |
| NOAEL (oral, rat, 90 days) | 3737.9 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) | |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure (inhalation). | |
| reaction mass of ethylbenzene, m-xylene and | p-xylene | |
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) | |
| NOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight/day (OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female) | |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. | |
| calcium carbonate (471-34-1) | | |
| NOAEL (oral, rat, 90 days) | 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) | |
| Xylene (1330-20-7) | | |
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) | |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. | |
| ethylbenzene (100-41-4) | ethylbenzene (100-41-4) | |
| NOAEL (oral, rat, 90 days) | 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents) | |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| ethylbenzene (100-41-4) | | |
|------------------------------------|--|--|
| STOT-repeated exposure | May cause damage to organs (hearing sense) through prolonged or repeated exposure. | |
| Aspiration hazard : | Not classified | |
| GUARD #10 GRAVI-GARD BLACK AEROSOL | | |
| Vaporizer | Aerosol | |
| Viscosity, kinematic | 31.3 mm²/s | |
| Not able to form a pool | Yes | |

SECTION 12: Ecological information

12.1. Toxicity

| Hazardous to the aquatic environment, short-term : (acute) | The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Not classified |
|--|---|
| acetone (67-64-1) | |
| LC50 - Fish [1] | 6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow- through system, Fresh water, Experimental value, Measured concentration) |
| LOEC (chronic) | > 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | ≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| reaction mass of ethylbenzene, m-xylene and | l p-xylene |
| LC50 - Fish [1] | 2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia |
| EC50 72h - Algae [1] | 1.3 mg/l |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |
| Xylene (1330-20-7) | |
| LC50 - Fish [1] | 2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia |
| EC50 72h - Algae [1] | 2.2 mg/l |
| ErC50 algae | 4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |
| ethylbenzene (100-41-4) | |
| LC50 - Fish [1] | 5.1 mg/l Test organisms (species): Menidia menidia |
| EC50 - Crustacea [1] | 1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| EC50 72h - Algae [1] | 4.9 mg/l Test organisms (species): Skeletonema costatum |
| EC50 72h - Algae [2] | 5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| ethylbenzene (100-41-4) | |
|-------------------------|--|
| EC50 96h - Algae [1] | 7.7 mg/l Test organisms (species): Skeletonema costatum |
| EC50 96h - Algae [2] | 3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| LOEC (chronic) | 1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d' |
| NOEC (chronic) | 0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d' |

12.2. Persistence and degradability

| acetone (67-64-1) | | | |
|---|--|--|--|
| Persistence and degradability | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. | | |
| Biochemical oxygen demand (BOD) | 1.43 g O ₂ /g substance | | |
| Chemical oxygen demand (COD) | 1.92 g O ₂ /g substance | | |
| ThOD | 2.2 g O ₂ /g substance | | |
| kieselguhr, soda ash flux calcined (68855-54-9) | | | |
| Persistence and degradability | Biodegradability: not applicable. | | |
| Chemical oxygen demand (COD) | Not applicable | | |
| ThOD | Not applicable | | |
| BOD (% of ThOD) | Not applicable | | |
| Xylene (1330-20-7) | | | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. | | |
| ethylbenzene (100-41-4) | | | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. | | |
| Biochemical oxygen demand (BOD) | 1.44 g O ₂ /g substance | | |
| Chemical oxygen demand (COD) | 2.1 g O ₂ /g substance | | |
| ThOD | 3.17 g O₂/g substance | | |

12.3. Bioaccumulative potential

| acetone (67-64-1) | | |
|---|--|--|
| Partition coefficient n-octanol/water (Log Pow) | -0.23 (Test data) | |
| Bioaccumulative potential | Not bioaccumulative. | |
| kieselguhr, soda ash flux calcined (68855-54-9) | | |
| Bioaccumulative potential No test data of component(s) available. | | |
| Xylene (1330-20-7) | | |
| BCF - Fish [1] | 7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read- across) | |
| Partition coefficient n-octanol/water (Log Pow) | 3.2 (Read-across, 20 °C) | |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). | |
| ethylbenzene (100-41-4) | | |
| BCF - Fish [1] | 1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value) | |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| - (hull | |
|---|---|
| ethylbenzene (100-41-4) | |
| Partition coefficient n-octanol/water (Log Pow) | 3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |
| 12.4. Mobility in soil | |
| acetone (67-64-1) | |
| Surface tension | 23300 mN/m (20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |
| Xylene (1330-20-7) | |
| Surface tension | 28.01 – 29.76 mN/m (25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across) |
| Ecology - soil | Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation. |
| ethylbenzene (100-41-4) | |
| Surface tension | 71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.71 (log Koc, PCKOCWIN v1.66, QSAR) |
| Ecology - soil | Low potential for adsorption in soil. Toxic to soil organisms. |

12.5. Results of PBT and vPvB assessment

| Component | |
|-------------------------|---|
| acetone (67-64-1) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |
| Xylene (1330-20-7) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |
| ethylbenzene (100-41-4) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |

12.6. Other adverse effects

No additional information available

| SECTION 13: Disposal considerations | |
|---|--|
| 13.1. Waste treatment methods | |
| Regional legislation (waste) Waste treatment methods | Disposal must be done according to official regulations.Dispose of contents/container in accordance with licensed collector's sorting instructions. |

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1 UN number UN-No. (ADR)

: UN 1950

: UN 1950

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| UN-No. (IATA) UN-No. (ADN) UN-No. (RID) | : UN 1950 : UN 1950 : UN 1950 |
|--|---|
| 14.2. UN proper shipping name | |
| Proper Shipping Name (ADR) Proper Shipping Name (IMDG) Proper Shipping Name (IATA) Proper Shipping Name (ADN) Proper Shipping Name (RID) Transport document description (ADR) Transport document description (IMDG) Transport document description (IATA) Transport document description (ADN) Transport document description (RID) | AEROSOLS AEROSOLS Aerosols, flammable AEROSOLS AEROSOLS UN 1950 AEROSOLS, 2.1, (D) UN 1950 AEROSOLS, 2.1 |
| 14.3. Transport hazard class(es) | |
| ADR Transport hazard class(es) (ADR) Danger labels (ADR) | : 2.1 : 2.1 : |



Transport hazard class(es) (IMDG) Danger labels (IMDG)



: 2.1

: 2.1 :

IATA

Transport hazard class(es) (IATA) Danger labels (IATA)



Transport hazard class(es) (ADN) Danger labels (ADN)

RID

Transport hazard class(es) (RID) Danger labels (RID)





Safety Data Sheet

| 14.4. Packing group | |
|--|--|
| Packing group (ADR) | : Not applicable |
| Packing group (IMDG) | : Not applicable |
| Packing group (IATA) | : Not applicable |
| Packing group (ADN) | : Not applicable |
| Packing group (RID) | : Not applicable |
| 14.5. Environmental hazards | |
| Dangerous for the environment | : No |
| Marine pollutant | : No |
| Other information | No supplementary information available |
| 14.6. Special precautions for user | |
| Overland transport | |
| Classification code (ADR) | : 5F |
| Special provisions (ADR) | : 190, 327, 344, 625 |
| Limited quantities (ADR) | : 190, 527, 544, 625 : 11 |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P207 |
| Special packing provisions (ADR) | : PP87, RR6, L2 |
| Mixed packing provisions (ADR) | : MP9 |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Packages (ADR) | : V14 |
| Special provisions for carriage - Loading, unloading | |
| and handling (ADR) | |
| Special provisions for carriage - Operation (ADR) | : \$2 |
| Tunnel restriction code (ADR) | : D |
| | |
| Transport by sea | |
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 381, 959 |
| Packing instructions (IMDG) | : P207, LP200 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D |
| EmS-No. (Spillage) | : S-U |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |
| | |
| Air transport | |
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |
| Inland waterway transport | |
| Classification code (ADN) | : 5F |
| Special provisions (ADN) | : 190, 327, 344, 625 |
| Limited quantities (ADN) | : 1L |
| Excepted quantities (ADN) | : E0 |
| Equipment required (ADN) | : PP, EX, A |
| Ventilation (ADN) | : VE01, VE04 |
| Number of blue cones/lights (ADN) | : 1 |
| | |
| Rail transport | |
| Classification code (RID) | : 5F |
| · · | |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Special provisions (RID) Limited quantities (RID) | | 190, 327, 344, 625 1L |
|--|---|--------------------------|
| Excepted quantities (RID) | : | E0 |
| Packing instructions (RID) | : | P207, LP200 |
| Special packing provisions (RID) | : | PP87, RR6, L2 |
| Mixed packing provisions (RID) | : | MP9 |
| Transport category (RID) | : | 2 |
| Special provisions for carriage – Packages (RID) | : | W14 |
| Special provisions for carriage - Loading, unloading | : | CW9, CW12 |
| and handling (RID) | | |
| Colis express (express parcels) (RID) | : | CE2 |
| Hazard identification number (RID) | : | 23 |
| | | |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

| EU restriction list (REACH Annex XVII) | | |
|--|--|--|
| Reference code | Applicable on | Entry title or description |
| 3. | GUARD #10 GRAVI- GARD BLACK AEROSOL ; acetone | Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008 |
| 3(a) | GUARD #10 GRAVI- GARD BLACK AEROSOL ; acetone ; reaction mass of ethylbenzene, m-xylene and p-xylene | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F |
| 3(b) | GUARD #10 GRAVI- GARD BLACK AEROSOL ; acetone ; reaction mass of ethylbenzene, m-xylene and p-xylene | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10 |
| 40. | acetone | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not. |

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors) ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

| Name | | Nomenclature | Combined Nomenclature code for mixture without constituents which would determine classification under another CN code |
|---------|---------|--------------|--|
| Acetone | 67-64-1 | 2914 11 00 | ex 3824 99 92 |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf VOC content : 571 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

| Full text of H- and EUH | Full text of H- and EUH-statements: | | |
|---------------------------|--|--|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 | | |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 | | |
| Aerosol 1 | Aerosol, Category 1 | | |
| Asp. Tox. 1 | Aspiration hazard, Category 1 | | |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 | | |
| Flam. Liq. 2 | Flammable liquids, Category 2 | | |
| Flam. Liq. 3 | Flammable liquids, Category 3 | | |
| H222 | Extremely flammable aerosol. | | |
| H225 | Highly flammable liquid and vapour. | | |
| H226 | Flammable liquid and vapour. | | |
| H229 | Pressurised container: May burst if heated. | | |
| H304 | May be fatal if swallowed and enters airways. | | |
| H312 | Harmful in contact with skin. | | |
| H315 | Causes skin irritation. | | |
| H319 | Causes serious eye irritation. | | |
| H332 | Harmful if inhaled. | | |
| H335 | May cause respiratory irritation. | | |
| H336 | May cause drowsiness or dizziness. | | |
| H373 | May cause damage to organs through prolonged or repeated exposure. | | |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 | | |
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 | | |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis | | |

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.