



DRIVING SURFACE PERFECTION

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Product Reference code: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
SDS Ref. (EU): MXMCL-SDS  
Issue date: 14/11/2019 Revision date: 21/04/2022 Supersedes version of: 08/02/2022 Version: 4.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : MAXIMUM 2:1 CLEARCOAT  
UFI : Y0G1-M0N9-1003-MTM9  
Product code : MXMCL/1, MXMCL/5  
Product group : Clearcoat

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
Use of the substance/mixture : Coatings and paints, thinners, paint removers  
Function or use category : Topcoat

##### 1.2.2. Uses advised against

Restrictions on use : Consumer uses: Private households (= general public = consumers)

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

U-POL Limited Ltd  
Denington Road  
GB- NN8 2QH Wellingborough – Northamptonshire  
United Kingdom  
T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### Supplier

U-POL Netherlands B.V. B.V.  
Hoogoorddreef 15  
NL- 1101BA Amsterdam  
Netherlands  
T +31 20 240 2216  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours ( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Skin sensitisation, Category 1 H317

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412
Full text of H- and EUH-statements: see section 16	

### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: Xylene, n-butyl acetate, reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene), reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, n-butyl acrylate, 2-hydroxyethyl methacrylate

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P261 - Avoid breathing vapours, spray, fume.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear face protection, protective clothing, protective gloves.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Unknown acute toxicity (CLP) - SDS : 0.24% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336
Xylene substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	20 – 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
ethylbenzene substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	5 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
solvent naphtha (petroleum), light aromatic (Note H)(Note 5)(Note P)	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4 REACH-no: 01-2119455851-35	3 – 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
n-butyl acrylate substance with a Community workplace exposure limit	CAS-No.: 141-32-2 EC-No.: 205-480-7 EC Index-No.: 607-062-00-3 REACH-no: 01-2119453155-43	0.3 – 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
2-hydroxyethyl methacrylate (Note D)	CAS-No.: 868-77-9 EC-No.: 212-782-2 EC Index-No.: 607-124-00-X REACH-no: 01-2119490169-29	0.3 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: 104810-48-2 EC-No.: 400-830-7 EC Index-No.: 607-176-00-3 REACH-no: 01-0000015075-76	0.3 – 1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: 1065336-91-5 EC-No.: 915-687-0 REACH-no: 01-2119491304-40	0.1 – 0.25	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Note 5 : The concentration limits for gaseous mixtures are expressed as volume per volume percentage.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Note H : The classification and labelling shown for this substance applies to the hazardous property(ies) indicated by the hazard statement(s) in combination with the hazard class(es) and category(ies) shown. The requirements of Article 4 for manufacturers, importers or downstream users of this substance apply to all other hazard classes and categories. For hazard classes where the route of exposure or the nature of the effects leads to a differentiation of the classification of the hazard class, the manufacturer, importer or downstream user is required to consider the routes of exposure or the nature of the effects not already considered.

Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe fume, spray, vapours. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe fume, spray, vapours. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>n-butyl acetate (123-86-4)</b>	
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Butyl acetate
OEL TWA [1]	710 mg/m <sup>3</sup>
OEL TWA [2]	150 ppm
OEL STEL	950 mg/m <sup>3</sup>
OEL STEL [ppm]	200 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Xylene (1330-20-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Xylene, mixed isomers
OEL TWA [1]	221 mg/m <sup>3</sup>
OEL TWA [2]	50 ppm
OEL STEL	442 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Xylene
BLV	1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Xylene (1330-20-7)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	441 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>ethylbenzene (100-41-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Ethylbenzene
IOEL TWA	442 mg/m <sup>3</sup>
IOEL TWA [ppm]	100 ppm
IOEL STEL	884 mg/m <sup>3</sup>
IOEL STEL [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Ethylbenzene
OEL TWA [1]	442 mg/m <sup>3</sup>
OEL TWA [2]	100 ppm
OEL STEL	884 mg/m <sup>3</sup>
OEL STEL [ppm]	200 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Ethyl benzene
BLV	0.7 g/g creatinine Parameter: mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift at end of workweek - Notations: Ns (Non-specific), Sq (Semi-quantitative) Parameter: ethylbenzene - Medium: end-exhaled air - Sampling time: Not critical - Notations: Sq (Semi-quantitative)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ethylbenzene (100-41-4)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethylbenzene
WEL TWA (OEL TWA) [1]	441 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	552 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>n-butyl acrylate (141-32-2)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butylacrylate
IOEL TWA	11 mg/m <sup>3</sup>
IOEL TWA [ppm]	2 ppm
IOEL STEL	53 mg/m <sup>3</sup>
IOEL STEL [ppm]	10 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	n-Butyl acrylate
OEL TWA [1]	11 mg/m <sup>3</sup>
OEL TWA [2]	2 ppm
OEL STEL	53 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	n-Butyl acrylate
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1 ppm
WEL STEL (OEL STEL)	26 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	5 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available



# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 140 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.964 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	:

### 9.2. Other information

VOC content : 551 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	23.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)</b>	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)
<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,
<b>2-phenoxyethanol (122-99-6)</b>	
LD50 oral rat	1850 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	14391 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 2214 mg/kg bodyweight Animal: rabbit, Guideline: other:Draft IRLG (Interagency Regulatory Liaison Group) Guidelines for Selected Acute Toxicity Tests (August. 1979)
LC50 Inhalation - Rat	> 1 mg/l air Animal: rat, Guideline: other:OECD 412
<b>toluene (108-88-3)</b>	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	25.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	25.7 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
<b>octamethylcyclotetrasiloxane (556-67-2)</b>	
LD50 oral rat	> 4800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2400 mg/kg bodyweight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	36 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
<b>dibutyltin dilaurate (77-58-7)</b>	
LD50 oral rat	2071 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1207 - 5106

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>dibutyltin dilaurate (77-58-7)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg (OECD Test Guideline 402)
LC50 Inhalation - Rat (Vapours)	> 6.193 mg/l/4h (4 h, OECD Test Guideline 403, vapours)
<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
<b>2-hydroxyethyl methacrylate (868-77-9)</b>	
LD50 oral rat	5564 mg/kg bodyweight Animal: rat, Guideline: other:Appraisal of the safety of chem by the Staff of the Division of Pharmacology, FDA, 1959 in food, drugs and cosmetics
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male
<b>n-butyl acrylate (141-32-2)</b>	
LD50 oral rat	9050 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male, Weight of evidence)
LD50 dermal rabbit	2000 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value)
LC50 Inhalation - Rat	14.6 mg/l (4 h, Rat, Literature study)
Unknown acute toxicity (CLP) - SDS	: 0.24% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
<b>Xylene (1330-20-7)</b>	
IARC group	3 - Not classifiable
<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>n-butyl acrylate (141-32-2)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
<b>2-phenoxyethanol (122-99-6)</b>	
LOAEL (animal/male, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
LOAEL (animal/female, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>2-phenoxyethanol (122-99-6)</b>	
NOAEL (animal/female, F0/P)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
<b>dibutyltin dilaurate (77-58-7)</b>	
NOAEL (animal/male, F0/P)	1.9 – 2.3 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
NOAEL (animal/female, F0/P)	1.7 – 2.4 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Xylene (1330-20-7)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>toluene (108-88-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>dibutyltin dilaurate (77-58-7)</b>	
STOT-single exposure	Causes damage to organs (thymus).
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>n-butyl acrylate (141-32-2)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>2-phenoxyethanol (122-99-6)</b>	
LOAEL (oral, rat, 90 days)	> 700 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	> 500 mg/kg bodyweight Animal: rabbit
NOAEL (oral, rat, 90 days)	700 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rabbit
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0482 mg/l/6h/day
<b>toluene (108-88-3)</b>	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>toluene (108-88-3)</b>	
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>dibutyltin dilaurate (77-58-7)</b>	
STOT-repeated exposure	Causes damage to organs (thymus) through prolonged or repeated exposure.
<b>ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing sense) through prolonged or repeated exposure.
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

<b>Xylene (1330-20-7)</b>	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	2.2 mg/l
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)</b>	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)</b>	
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
<b>ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
<b>2-hydroxyethyl methacrylate (868-77-9)</b>	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	380 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	836 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	345 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	49.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	24.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>n-butyl acrylate (141-32-2)</b>	
LC50 - Fish [1]	5.2 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	8.2 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	2.65 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	1.71 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
<b>12.2. Persistence and degradability</b>	
<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46
<b>Xylene (1330-20-7)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.
<b>ethylbenzene (100-41-4)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance
<b>n-butyl acrylate (141-32-2)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.91 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.674 g O <sub>2</sub> /g substance
ThOD	2.25 g O <sub>2</sub> /g substance
<b>12.3. Bioaccumulative potential</b>	
<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Xylene (1330-20-7)</b>	
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)</b>	
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6
Bioaccumulative potential	Not established.
<b>ethylbenzene (100-41-4)</b>	
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>n-butyl acrylate (141-32-2)</b>	
BCF - Other aquatic organisms [1]	17.3 l/kg (BCFBAF v3.01, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.38 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)



# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-butyl acrylate (141-32-2)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

n-butyl acetate (123-86-4)	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

ethylbenzene (100-41-4)	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.

n-butyl acrylate (141-32-2)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.6 – 2.2 (log Koc, EPA OTS 796.2750: Sediment and Soil Adsorption Isotherm, Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

### 12.5. Results of PBT and vPvB assessment

Component	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acrylate (141-32-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

#### 14.1 UN number

UN-No. (ADR)	: UN 1263
UN-No. (IMDG)	: UN 1263
UN-No. (IATA)	: UN 1263
UN-No. (ADN)	: UN 1263
UN-No. (RID)	: UN 1263

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: PAINT
Proper Shipping Name (IMDG)	: PAINT
Proper Shipping Name (IATA)	: Paint
Proper Shipping Name (ADN)	: PAINT
Proper Shipping Name (RID)	: PAINT
Transport document description (ADR)	: UN 1263 PAINT, 3, III, (D/E)
Transport document description (IMDG)	: UN 1263 PAINT, 3, III
Transport document description (IATA)	: UN 1263 Paint, 3, III
Transport document description (ADN)	: UN 1263 PAINT, 3, III
Transport document description (RID)	: UN 1263 PAINT, 3, III

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



##### IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



##### IATA

Transport hazard class(es) (IATA)	: 3
Danger labels (IATA)	: 3



##### ADN

Transport hazard class(es) (ADN)	: 3
Danger labels (ADN)	: 3



# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### RID

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3  
:



### 14.4. Packing group

Packing group (ADR) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III  
Packing group (ADN) : III  
Packing group (RID) : III


### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
Special provisions (ADR) : 163, 367, 650  
Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E1  
Packing instructions (ADR) : P001, IBC03, LP01, R001  
Special packing provisions (ADR) : PP1  
Mixed packing provisions (ADR) : MP19  
Portable tank and bulk container instructions (ADR) : T2  
Portable tank and bulk container special provisions (ADR) : TP1, TP29  
Tank code (ADR) : LGBF  
Vehicle for tank carriage : FL  
Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V12  
Special provisions for carriage - Operation (ADR) : S2  
Hazard identification number (Kemler No.) : 30  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3Y

#### Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : A  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	MAXIMUM 2:1 CLEARCOAT ; Xylene ; ethylbenzene ; solvent naphtha (petroleum), light aromatic ; n-butyl acetate ; n-butyl acrylate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	MAXIMUM 2:1 CLEARCOAT ; Xylene ; ethylbenzene ; solvent naphtha (petroleum), light aromatic ; n-butyl acetate ; reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxy poly(oxyethylene) ; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; n-butyl acrylate ; 2-hydroxyethyl methacrylate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	MAXIMUM 2:1 CLEARCOAT ; solvent naphtha (petroleum), light aromatic ; reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxy poly(oxyethylene) ; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Xylene ; ethylbenzene ; solvent naphtha (petroleum), light aromatic ; n-butyl acetate ; n-butyl acrylate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list  $\geq 0,1\%$  / SCL

Contains organic solvents ( $\geq 1\%$ )

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 551 g/l

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Abbreviations and acronyms:

STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

# MAXIMUM 2:1 CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Full text of H- and EUH-statements:

Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).