



MAXIMUM HARDENER

MXMH/25

Version: 1.0

Date of issue: 25/02/2022 Revision date: 25/03/2022



DRIVING SURFACE PERFECTION

TECHNICAL DATASHEET

Product	Order Code	Format	Shelf Life
MAXIMUM HARDENER	MXMH/25	2.5L Tin	2 years

APPLICATION INFORMATION



FOR PPE RECOMMENDATIONS REFER TO SDS

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information.

Additional information



Important Remarks

This 2K hardener contains isocyanates. Please refer to the safety data sheet prior to use.
Keep hardeners sealed and away from moisture.
2K hardeners must not be used on their own. They must always be mixed with a clear coat, primer or solid colour.

TECHNICAL INFORMATION

Physical properties



Appearance	Clear, colorless liquid.
Colour	Colourless
Density	0.946 g/cm ³
Percent Solids	30 wt%

VOC Information



The VOC content of this product as received is 652 g/l. The VOC content of this product in ready to use form is



Storage

Recommended storage temperature 5 °C - 25 °C

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Associated Products



Product	Order Code	Format
For additional technical assistance, please contact the U-POL Technical Department at technicalsupport@u-pol.com		

U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits. U-POL is not liable for mis-use or abuse of its products and no application warranty is expressed or implied.

U-POL Limited
Denington Road
NN8 2QH Wellingborough - United Kingdom
T +44 (0) 1933 230310
technicalsupport@u-pol.com - www.u-pol.com

U-POL Netherlands B.V.
Hoogoorddreef 15
1101BA Amsterdam - Netherlands
T +31 20 240 2216
technicalsupport@u-pol.com - www.u-pol.com