



ISOPON PLASTIC BUMPER FILLER TUBE

PBF/100

Version:

Date of issue: Revision date:







DRIVING SURFACE PERFECTION

TECHNICAL DATASHEET





Specialy formulated to repair scratches and scuffs in most types of plastic. Simple to mix, easily sanded and shaped, highly flexible with excellent adhesion.

Product	Order Code	Format	Shelf Life
ISOPON PLASTIC BUMPER FILLER TUBE	PBF/100	100ml Tube 1 x 5g BPO Sachet 1 x Bodyfiller Applicator	5 years

APPLICATION INFORMATION

 FOR PPE RECOMMENDATIONS REFER TO SDS	This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information.			
Surface Preparation 	Substrate PP EPDM EPDM/PP TPO ABS	Degreaser PLAST-X 1 Plastic Pre-Cleaner Aerosol PLAST-X 1 Plastic Pre-Cleaner Aerosol PLAST-X 1 Plastic Pre-Cleaner Aerosol PLAST-X 1 Plastic Pre-Cleaner Aerosol PLAST-X 1 Plastic Pre-Cleaner Aerosol	Abrasion P180 P180 P180 P180 P180	
Application 	Mixing ratio (BPO Hardener) Gel Time Sandable after	10°C	20°C	30°C
Sanding 	Maximum Fill Depth Infrared Bake	1 - 2 mm 50 – 80 cm, 80 °C, 5 minutes		
Over-Painting 	Initial Sanding	P180		

TECHNICAL INFORMATION

Physical properties 	Appearance Colour Density	Paste. Black 1.775 (1.75 – 1.8) g/cm ³		
VOC Information 	VOC Category (2004/42/CE)	Bodyfiller/Stopper, product category IIB(b), max. limit 250 g/l The VOC content of this product as received is 240 g/l. The VOC content of this product in ready to use form is 100 g/l.		
Storage 	Recommended storage temperature	< 25 °C Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Keep only in original container.		
Associated Products 	Product WIPE #6 Solvent-Based Degreaser Aerosol	Order Code WIPE/AL	Format 450ml Aerosol	

U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits. U-POL is not liable for mis-use or abuse of its products and no application warranty is expressed or implied.



ISOPON PLASTIC BUMPER FILLER TUBE

PBF/100

Version:

Date of issue: Revision date:

DRIVING SURFACE PERFECTION

TECHNICAL DATASHEET

For additional technical assistance, please contact the U-POL Technical Department at technicalsupport@u-pol.com

U-POL Limited
Denington Road
NN8 2QH Wellingborough - United Kingdom
T +44 (0) 1933 230310
technicalsupport@u-pol.com - www.u-pol.com

U-POL Netherlands B.V.
Hoogoorddreef 15
1101BA Amsterdam - Netherlands
T +31 20 240 2216
technicalsupport@u-pol.com - www.u-pol.com