



DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

# POWER CAN

Topcoat Colour

## DESCRIPTION

High build topcoat for finishing primed surfaces to achieve a matt, satin or high gloss finish

- Easy to use and flexible
- Convenience of a spray can reduces paint consumption
- Economic, durable topcoats

## TECHNICAL DATA



### Substrates

- Primed substrates
- Prepared OEM paint surfaces

## APPLICATION GUIDE



### Tools Required

- SYSTEM 20™ Degreaser
- MAXIMUM Abrasives



### Substrate Preparation And Instruction For Use

Thoroughly clean and degrease surfaces with Precleaner or panel prep. Abrade primed surfaces wet with 600-800 or dry with 400-600 abrasive, re-clean, dry and degrease



### Mixing

Shake the aerosol can for at least 2 minutes before use.



### Coats

1 - 2 coats at a distance of approx. 25 cm from the surface.

Build / microns 10μ

\*Theoretical Coverage approx. m<sup>2</sup>/unit 2

*\*Theoretical Coverage per unit assuming 100% transfer efficiency and giving the dry film thickness between indicated values.*



### Flash-off / min @ 20°C

between coats 20 - 30 mins



### Drying Times

Handleable @ 20°C / min 30



DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

# POWER CAN

Topcoat Colour

## STORAGE & VOC INFORMATION



### Shelf Life

2 years subject to good storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature                      5°C - 25°C

Recommended Application Temperature                      20°C



### VOC Information

The EU limit for this product (product category: IIB.e) in ready to use form is 840g/litre. The VOC content of this product in ready to use form is detailed in the table below.

Order Code	Format	Colour	VOC g/l
PCGB/AL	500ml Aerosol	Gloss Black	661
PCGW/AL	500ml Aerosol	Gloss White	654
PCMB/AL	500ml Aerosol	Matt Black	657
PCSB/AL	500ml Aerosol	Satin Black	656

### IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

#### U-POL Ltd

The Grange, 100 High Street  
Southgate, London, N14 6BN  
WWW.U-POL.COM

#### UK Sales

T: +44 (0)20 8492 5920  
F: +44 (0)20 8150 5605  
uk.sales@u-pol.com

#### International

T: +44 (0)20 8492 5900  
F: +44 (0)20 8150 5605  
sales@u-pol.com

#### Technical

T: +44 (0)1933 230 310  
F: +44 (0)1933 425 797  
technicaldepartment@u-pol.com