



DRIVING SURFACE PERFECTION

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Product Reference code: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
SDS Ref. (EU): PCGWAL-SDS
Issue date: 02/03/2015 Revision date: 25/02/2021 Supersedes version of: 03/12/2020 Version: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : POWERCAN GLOSS WHITE AEROSOL
UFI : NFA1-T027-S00V-JQQV
Product code : PCGW/AL
Type of product : Aerosol
Vaporizer : Aerosol
Product group : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Coatings and paints, thinners, paint removers
Function or use category : Topcoat

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

U-POL Limited
Denington Road
NN8 2QH Wellingborough - United Kingdom
T +44 (0) 1933 230310
technicalsupport@u-pol.com - www.u-pol.com

Importer

U-POL Netherlands B.V.
Hoorgoorddreef 15
1101BA Amsterdam - Netherlands
T +31 20 240 2216
technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.hscni.net)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reproductive toxicity, Category 2 H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Full text of H statements : see section 16


Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Danger
Contains : acetone; toluene
Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, open flames, sparks. — No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P261 - Avoid breathing fume, spray, vapours.
P280 - Wear eye protection, protective clothing, protective gloves.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements : EUH071 - Corrosive to the respiratory tract.
EUH208 - Contains maleic anhydride. May produce an allergic reaction.
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Unknown acute toxicity (CLP) - SDS : 0.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

2.3. Other hazards

Component	
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
toluene (108-88-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexanone (108-94-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
maleic anhydride (108-31-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone substance with a Community workplace exposure limit	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	20 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336
toluene substance with a Community workplace exposure limit	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (EC Index-No.) 022-006-002 (REACH-no) 01-2119489379-17	5 – 10	Carc. 2, H351
reaction mass of ethylbenzene, m-xylene and p-xylene	(EC-No.) 905-562-9 (REACH-no) 01-2119555267-33	1 – 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
hydrocarbons, C9, aromatics	(CAS-No.) 64742-95-6 (EC-No.) 918-668-5 (REACH-no) 01-2119455851-35	1 – 2.5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
cyclohexanone substance with a Community workplace exposure limit	(CAS-No.) 108-94-1 (EC-No.) 203-631-1 (EC Index-No.) 606-010-00-7 (REACH-no) 01-2119453616-35	1 – 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

maleic anhydride	(CAS-No.) 108-31-6 (EC-No.) 203-571-6 (EC Index-No.) 607-096-00-9 (REACH-no) 01-2119472428-21	< 0.1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372
------------------	--	-------	---

Specific concentration limits:

Name	Product identifier	Specific concentration limits
maleic anhydride	(CAS-No.) 108-31-6 (EC-No.) 203-571-6 (EC Index-No.) 607-096-00-9 (REACH-no) 01-2119472428-21	(0.001 ≤ C ≤ 100) Skin Sens. 1A, H317

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a physician immediately. Call a doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product. Collect spillage.
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature : < 25 °C
Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Toluene
IOEL TWA	192 mg/m ³

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

toluene (108-88-3)	
IOEL TWA [ppm]	50 ppm
IOEL STEL	384 mg/m ³
IOEL STEL [ppm]	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Ireland - Occupational Exposure Limits	
Local name	Toluene
OEL TWA [1]	192 mg/m ³
OEL TWA [2]	50 ppm
OEL STEL	384 mg/m ³
OEL STEL [ppm]	100 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
Ireland - Biological limit values	
Local name	Toluene
BLV	0.02 mg/l Parameter: toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: toluene - Medium: urine - Sampling time: End of shift 0.3 mg/g creatinine Parameter: o-cresol - Medium: urine - Sampling time: End of shift - Notations: B (Background)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Toluene
WEL TWA (OEL TWA) [1]	191 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Acetone
OEL TWA [1]	1210 mg/m ³

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone (67-64-1)	
OEL TWA [2]	500 ppm
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
Ireland - Biological limit values	
Local name	Acetone
BLV	50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m ³
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
cyclohexanone (108-94-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Cyclohexanone
IOEL TWA	40.8 mg/m ³
IOEL TWA [ppm]	10 ppm
IOEL STEL	81.6 mg/m ³
IOEL STEL [ppm]	20 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Cyclohexanone
OEL TWA [1]	40.8 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	81.6 mg/m ³
OEL STEL [ppm]	20 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
Ireland - Biological limit values	
Local name	Cyclohexanone
BLV	8 mg/l Parameter: cyclohexanol - Medium: urine - Sampling time: End of shift - Notations: Cyclohexanol= metabolite; Ns (Non-specific) 80 mg/l Parameter: 1,2-Cyclohexanediol - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexanone (108-94-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Cyclohexanone
WEL TWA (OEL TWA) [1]	41 mg/m ³
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	82 mg/m ³
WEL STEL (OEL STEL) [ppm]	20 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Cyclohexanone
BMGV	2 mmol/mol Creatinine Parameter: cyclohexanol - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
maleic anhydride (108-31-6)	
Ireland - Occupational Exposure Limits	
Local name	Maleic anhydride
OEL TWA [2]	0.01 ppm IFV (Inhlabl Fraction and Vapour)
Notes (IE)	Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom - Occupational Exposure Limits	
Local name	Maleic anhydride
WEL TWA (OEL TWA) [1]	1 mg/m ³
WEL STEL (OEL STEL)	3 mg/m ³
Remark (WEL)	Sen (Capable of causing occupational asthma)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-butyl acetate (123-86-4)	
Ireland - Occupational Exposure Limits	
Local name	Butyl acetate
OEL TWA [1]	710 mg/m ³
OEL TWA [2]	150 ppm
OEL STEL	950 mg/m ³
OEL STEL [ppm]	200 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m ³
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Ireland - Occupational Exposure Limits	
Local name	Titanium dioxide
OEL TWA [1]	10 mg/m ³ total inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	Chemical Agents Code of Practice 2020
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	10 mg/m ³ 4 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

toluene (108-88-3)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	384 mg/m ³
Acute - local effects, inhalation	384 mg/m ³
Long-term - systemic effects, dermal	384 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	192 mg/m ³
Long-term - local effects, inhalation	192 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	226 mg/m ³
Acute - local effects, inhalation	226 mg/m ³

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Long-term - systemic effects, oral	8.13 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	56.5 mg/m ³
Long-term - systemic effects, dermal	226 mg/kg bodyweight/day
Long-term - local effects, inhalation	56.5 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.68 mg/l
PNEC aqua (marine water)	0.68 mg/l
PNEC aqua (intermittent, freshwater)	0.68 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	16.39 mg/kg dwt
PNEC sediment (marine water)	16.39 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.89 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	13.61 mg/l

acetone (67-64-1)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	2420 mg/m ³
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m ³
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	10.6 mg/l
PNEC aqua (marine water)	1.06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	30.4 mg/kg dwt
PNEC sediment (marine water)	3.04 mg/kg dwt
PNEC (Soil)	
PNEC soil	29.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

cyclohexanone (108-94-1)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	100 mg/kg bodyweight/day
Acute - systemic effects, inhalation	100 mg/m ³
Acute - local effects, inhalation	100 mg/m ³

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Long-term - systemic effects, dermal	10 mg/kg bw/day
Long-term - systemic effects, inhalation	20 mg/m ³
Long-term - local effects, inhalation	20 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	30 mg/kg bw/day
Acute - systemic effects, inhalation	50 mg/m ³
Acute - systemic effects, oral	10 mg/kg bw/day
Acute - local effects, inhalation	50 mg/m ³
Long-term - systemic effects, oral	5 mg/kg bw/day
Long-term - systemic effects, inhalation	50 mg/m ³
Long-term - systemic effects, dermal	20 mg/kg bw/day
Long-term - local effects, inhalation	20 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.033 mg/l
PNEC aqua (marine water)	0.003 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.168 mg/kg dwt
PNEC sediment (marine water)	0.017 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.014 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

n-butyl acetate (123-86-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	11 mg/kg bw/day
Acute - systemic effects, inhalation	600 mg/m ³
Acute - local effects, inhalation	600 mg/m ³
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m ³
Long-term - local effects, inhalation	300 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	6 mg/kg bw/day
Acute - systemic effects, inhalation	300 mg/m ³
Acute - systemic effects, oral	2 mg/kg bw/day
Acute - local effects, inhalation	300 mg/m ³
Long-term - systemic effects, oral	2 mg/kg bw/day
Long-term - systemic effects, inhalation	35.7 mg/m ³
Long-term - systemic effects, dermal	6 mg/kg bw/day
Long-term - local effects, inhalation	35.7 mg/m ³

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Other skin protection

Materials for protective clothing:

Impermeable clothing

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0.727 g/cm ³
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

VOC content	: 633
Gas group	: Press. Gas (Liq.)

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients	: 87.86478638349994
----------------------------	---------------------

9.2.2. Other safety characteristics

Gas group	: Press. Gas (Liq.)
VOC content	: 633

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

LPG, liquefied, under pressure (68476-85-7)

LC50 Inhalation - Rat	658 mg/l (4 h, Rat, Inhalation)
-----------------------	---------------------------------

toluene (108-88-3)

LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	25.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	25.7 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))

acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4

cyclohexanone (108-94-1)

LD50 oral rat	1890 mg/kg bodyweight (BASF test, Rat, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	1100 mg/kg (BRENNTAG test)
LC50 Inhalation - Rat	> 6.2 mg/l air Animal: rat
LC50 Inhalation - Rat (Vapours)	8000 mg/l/4h

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-methoxy-1-methylethyl acetate (108-65-6)	
LD50 oral rat	6190 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	1728 ppm/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, Inhalation, vapours)

maleic anhydride (108-31-6)	
LD50 oral rat	1090 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	2620 mg/kg bodyweight Animal: rabbit, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

cellulose acetate butyrate (9004-36-8)	
LD50 oral rat	> 3200 mg/kg
LD50 dermal	> 1000 mg/kg (Guinea pig)

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)	
LD50 oral rat	301 mg/kg (OECD 423)
LD50 dermal rabbit	2750 mg/kg

solvent naphtha (petroleum), light aromatic (64742-95-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg (OECD Test Guideline 402)
LC50 Inhalation - Rat (Vapours)	> 6.193 mg/l/4h (4 h, OECD Test Guideline 403, vapours)

butyl glycoether (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value)

bis(2-ethylhexyl) terephthalate (6422-86-2)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: other:TSCA FHSA Regulations (1979): 16 CFR Part 1500.40 (Hazardous Substances and Articles, Administration and Enforcement Regulations)
---------------	---

2-phenoxyethanol (122-99-6)

LD50 oral rat	1850 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	14391 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 2214 mg/kg bodyweight Animal: rabbit, Guideline: other:Draft IRLG (Interagency Regulatory Liaison Group) Guidelines for Selected Acute Toxicity Tests (August. 1979)
LC50 Inhalation - Rat	> 1 mg/l air Animal: rat, Guideline: other:OECD 412

C22-30 chlorinated paraffin (chlorination: 42-48%) (63449-39-8)

LD50 oral rat	> 11700 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-1 (Acute Oral Toxicity)
LD50 oral	> 23400 mg/kg bodyweight Animal: mouse, Guideline: EPA OPP 81-1 (Acute Oral Toxicity)
LD50 dermal rabbit	> 13900 mg/kg

hydrogen peroxide solution... % (7722-84-1)

LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:US EPA Toxic Substance Health Effects Test Guidelines (PB82-232984, 1982), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	---

carbon black (1333-86-4)

LD50 oral rat	> 8000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))

Xylene (1330-20-7)

LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)

octamethylcyclotetrasiloxane (556-67-2)

LD50 oral rat	> 4800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50 dermal rat	> 2400 mg/kg bodyweight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	36 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

reaction mass of ethylbenzene, m-xylene and p-xylene

LD50 oral rat	3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral), rat, male)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours)

hydrocarbons, C9, aromatics (64742-95-6)

LD50 oral rat	8400 ml/kg
LD50 dermal rabbit	3160 mg/kg bodyweight (OECD Guideline 402 (Acute Dermal Toxicity), rat, male/female)
LC50 Inhalation - Rat [ppm]	3400 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 5 mg/l/4h

decamethylcyclopentasiloxane (541-02-6)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	8.67 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EPA OTS 798.1150 (Acute inhalation toxicity), 95% CL: 7,3 - 10,32

Dodecamethylcyclohexasiloxane (540-97-6)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))

(77-99-6)

LD50 oral rat	≈ 14700 mg/kg bodyweight Animal: rat, Animal sex: male
LD50 dermal rabbit	> 10000 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 0.85 mg/l air Animal: rat, Animal sex: male

Unknown acute toxicity (CLP) - SDS : 0.49% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

toluene (108-88-3)	
IARC group	3 - Not classifiable

cyclohexanone (108-94-1)	
IARC group	3 - Not classifiable

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

reaction mass of ethylbenzene, m-xylene and p-xylene	
IARC group	2B - Possibly carcinogenic to humans

C22-30 chlorinated paraffin (chlorination: 42-48%) (63449-39-8)	
NOAEL (chronic, oral, animal/male, 2 years)	> 3750 mg/kg bodyweight Animal: rat, Animal sex: male
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)

phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)	
NOAEL (animal/male, F0/P)	> 500

2-phenoxyethanol (122-99-6)	
LOAEL (animal/male, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
LOAEL (animal/female, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
NOAEL (animal/female, F0/P)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP

hydrocarbons, C9, aromatics (64742-95-6)	
NOAEL (animal/male, F0/P)	7500 mg/kg
NOAEL (animal/female, F0/P)	7500 mg/kg

STOT-single exposure : May cause drowsiness or dizziness.

toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

solvent naphtha (petroleum), light aromatic (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

Xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.

reaction mass of ethylbenzene, m-xylene and p-xylene	
STOT-single exposure	May cause respiratory irritation.

hydrocarbons, C9, aromatics (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : Not classified

toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

cyclohexanone (108-94-1)	
NOAEL (oral, rat, 90 days)	143 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

maleic anhydride (108-31-6)	
NOAEL (oral, rat, 90 days)	≈ 10 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
NOAEC (inhalation, rat, vapour, 90 days)	≈ 0.0033 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	Causes damage to organs (respiratory system) through prolonged or repeated exposure (inhalation).

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

butyl glycoether (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

2-phenoxyethanol (122-99-6)	
LOAEL (oral, rat, 90 days)	> 700 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	> 500 mg/kg bodyweight Animal: rabbit
NOAEL (oral, rat, 90 days)	700 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rabbit
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0482 mg/l/6h/day

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

reaction mass of ethylbenzene, m-xylene and p-xylene	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day (OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

hydrocarbons, C9, aromatics (64742-95-6)	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight/day
NOAEC (inhalation, rat, vapour, 90 days)	900 – 1800 mg/m ³

decamethylcyclopentasiloxane (541-02-6)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 1600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Dodecamethylcyclohexasiloxane (540-97-6)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing sense) through prolonged or repeated exposure.

(77-99-6)	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, gas, 90 days)	≈ 3.5 ppm Animal: rat

Aspiration hazard : Not classified

POWERCAN GLOSS WHITE AEROSOL	
Vaporizer	Aerosol

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'

acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 96h - Algae [1]	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

cyclohexanone (108-94-1)	
LC50 - Fish [1]	527 – 732 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Read-across, GLP)
-------------	--

maleic anhydride (108-31-6)	
LC50 - Fish [1]	75 mg/l Test organisms (species): Lepomis macrochirus
LC50 - Fish [2]	75 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	330 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 150 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

reaction mass of ethylbenzene, m-xylene and p-xylene	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	1.3 mg/l
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

hydrocarbons, C9, aromatics (64742-95-6)	
LC50 - Fish [1]	9.22 mg/l (Oncorhynchus mykiss)
EC50 - Crustacea [1]	6.14 mg/l 48 h, Daphnia magna
ErC50 algae	2.9 mg/l

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

toluene (108-88-3)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69

acetone (67-64-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

cyclohexanone (108-94-1)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.232 g O ₂ /g substance
Chemical oxygen demand (COD)	2.605 g O ₂ /g substance
ThOD	2.605 g O ₂ /g substance

maleic anhydride (108-31-6)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.4 – 0.6 g O ₂ /g substance
ThOD	0.97 g O ₂ /g substance

n-butyl acetate (123-86-4)

Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance
BOD (% of ThOD)	0.46

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

hydrocarbons, C9, aromatics (64742-95-6)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

toluene (108-88-3)

BCF - Fish [1]	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
----------------	---

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

acetone (67-64-1)

BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.

cyclohexanone (108-94-1)

BCF - Other aquatic organisms [1]	2.4 (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

maleic anhydride (108-31-6)

Partition coefficient n-octanol/water (Log Pow)	-2.61 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 19.8 °C)
Bioaccumulative potential	Not bioaccumulative.

n-butyl acetate (123-86-4)

BCF - Fish [1]	15.3 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

12.4. Mobility in soil

toluene (108-88-3)

Surface tension	27.73 N/m (25 °C)
Ecology - soil	Low potential for adsorption in soil.

acetone (67-64-1)

Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.

cyclohexanone (108-94-1)

Surface tension	0.034 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Highly mobile in soil.

maleic anhydride (108-31-6)

Surface tension	No data available in the literature
-----------------	-------------------------------------

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Partition coefficient n-octanol/water (Log Koc)	1.63 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

n-butyl acetate (123-86-4)	
Surface tension	0.0163 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
Ecology - soil	Low potential for mobility in soil.

12.5. Results of PBT and vPvB assessment

Component	
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
toluene (108-88-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
cyclohexanone (108-94-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
maleic anhydride (108-31-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR)	: UN 1950
UN-No. (IMDG)	: UN 1950
UN-No. (IATA)	: UN 1950
UN-No. (ADN)	: UN 1950

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

UN-No. (RID) : UN 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable
Proper Shipping Name (ADN) : AEROSOLS
Proper Shipping Name (RID) : AEROSOLS
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1
Transport document description (RID) : UN 1950 AEROSOLS, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1



ADN

Transport hazard class(es) (ADN) : 2.1
Danger labels (ADN) : 2.1



RID

Transport hazard class(es) (RID) : 2.1
Danger labels (RID) : 2.1



POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:		
Reference code	Applicable on	Entry title or description
3(a)	POWERCAN GLOSS WHITE AEROSOL ; acetone ; toluene ; n-butyl acetate ; reaction mass of ethylbenzene, m-xylene and p-xylene ; hydrocarbons, C9, aromatics ; cyclohexanone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	POWERCAN GLOSS WHITE AEROSOL ; acetone ; toluene ; n-butyl acetate ; reaction mass of ethylbenzene, m-xylene and p-xylene ; hydrocarbons, C9, aromatics ; cyclohexanone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	hydrocarbons, C9, aromatics	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	acetone ; toluene ; n-butyl acetate ; reaction mass of ethylbenzene, m-xylene and p-xylene ; hydrocarbons, C9, aromatics ; cyclohexanone	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
48.	toluene	Toluene

Contains no substance on the REACH candidate list $\geq 0,1\%$ / SCL

Contains organic solvents ($\geq 1\%$)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 633

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
	Packing instructions (RID)	Modified	
	Packing instructions (ADR)	Modified	
	Type of product	Added	
	Contains	Added	
1.2	Function or use category	Modified	
1.2	Industrial/Professional use spec	Removed	
1.2	Main use category	Added	
2.1	Adverse physicochemical, human health and environmental effects	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.2	EUH-statements	Added	
2.2	Hazard pictograms (CLP)	Modified	
4.1	First-aid measures after inhalation	Modified	
9.2	VOC content	Modified	
14.6	Special provisions (ADN)	Modified	
15.1	VOC content	Modified	
16	Abbreviations and acronyms	Added	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.

POWERCAN GLOSS WHITE AEROSOL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains maleic anhydride. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.