



DRIVING SURFACE PERFECTION

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
SDS Ref. (EU): PCLCAL-SDS  
Issue date: 3/13/2015 Revision date: 8/13/2020 Supersedes version of: 8/20/2019 Version: 4.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : POWERCAN CLEARCOAT AEROSOL  
UFI : 92N0-S06D-H00N-UQMT  
Product code : PCLC/AL  
Vaporizer : aerosol  
Product group : aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
Use of the substance/mixture : Coatings and paints, thinners, paint removers  
Function or use category : Topcoat

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

U-POL Limited  
Denington Road  
NN8 2QH Wellingborough - United Kingdom  
T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### Importer

U-POL Netherlands B.V.  
Hoorgoordreef 15  
1101BA Amsterdam - Netherlands  
T +31 20 240 2216  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours ( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Serious eye damage/eye irritation, Category 2 H319  
Skin sensitisation, Category 1 H317  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Full text of H-statements: see section 16

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

Contains

: reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; acetone

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing spray, vapours, fume.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P312 - Call doctor if you feel unwell.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

Unknown acute toxicity (CLP) - SDS

: 12.01% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## 2.3. Other hazards

Component	
dimethyl ether (115-10-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethyl methyl ketone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--	---

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether substance with a Community workplace exposure limit (Note U)	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8 (REACH-no) 01-2119472128-37	25 – 50	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
acetone substance with a Community workplace exposure limit	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	20 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336
ethyl methyl ketone substance with a Community workplace exposure limit	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
4-methylpentan-2-one; isobutyl methyl ketone substance with a Community workplace exposure limit	(CAS-No.) 108-10-1 (EC-No.) 203-550-1 (EC Index-No.) 606-004-00-4 (REACH-no) 01-2119473980-30	3 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 (REACH-no) 01-2119475791-29	1 – 2.5	Flam. Liq. 3, H226
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	(EC-No.) 400-830-7 (EC Index-No.) 607-176-00-3 (REACH-no) 01-0000015075-76	0.1 – 0.25	Skin Sens. 1A, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5 (EC-No.) 915-687-0 (REACH-no) 01-2119491304-40	< 0.1	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No flames, no sparks. Eliminate all sources of ignition.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Contain released product. Collect spillage.
Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Storage temperature : < 25 °C
- Special rules on packaging : Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

dimethyl ether (115-10-6)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Dimethylether
IOEL TWA	1920 mg/m <sup>3</sup>
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Dimethyl ether
OEL TWA [1]	1920 mg/m <sup>3</sup>
OEL TWA [2]	1000 ppm
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Dimethyl ether
WEL TWA (OEL TWA) [1]	766 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	958 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

#### ethyl methyl ketone (78-93-3)

##### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Butanone
------------	----------

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ethyl methyl ketone (78-93-3)</b>	
IOEL TWA	600 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m <sup>3</sup>
IOEL STEL [ppm]	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Methyl ethyl ketone (MEK)
OEL TWA [1]	600 mg/m <sup>3</sup>
OEL TWA [2]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Butan-2-one
BLV	70 µmol/l Parameter: butan-2- one - Medium: urine - Sampling time: Post shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butan-2-one (methyl ethyl ketone)
WEL TWA (OEL TWA) [1]	600 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	899 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	300 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Butan-2-one (methyl ethyl ketone)
BMGV	70 µmol/l Parameter: butan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	4-Methylpentan-2-one
IOEL TWA	83 mg/m <sup>3</sup>
IOEL TWA [ppm]	20 ppm
IOEL STEL	208 mg/m <sup>3</sup>
IOEL STEL [ppm]	50 ppm

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Methyl isobutyl ketone (MIBK) [Hexone, Isobutyl methyl keton, 4-Methylpentan-2-one)
OEL TWA [1]	83 mg/m <sup>3</sup>
OEL TWA [2]	20 ppm
OEL STEL	208 mg/m <sup>3</sup>
OEL STEL [ppm]	50 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Methyl isobutyl ketone (MIBK)/ 4-methylpentan-2-one
BLV	1 mg/l Parameter: MIBK - Medium: urine - Sampling time: End of shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	4-Methylpentan-2-one
WEL TWA (OEL TWA) [1]	208 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	4-methylpentan-2-one
BMGV	20 µmol/l Parameter: 4-methylpentan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Notes	Skin Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>Ireland - Occupational Exposure Limits</b>	
Local name	2-Methoxy-1-methylethylacetate
OEL TWA [1]	275 mg/m <sup>3</sup>
OEL TWA [2]	50 ppm
OEL STEL	550 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>n-butyl acetate (123-86-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup> 723 mg/m <sup>3</sup>
IOEL STEL [ppm]	150 ppm 150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831 COMMISSION DIRECTIVE (EU) 2019/1831
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Butyl acetate
OEL TWA [1]	710 mg/m <sup>3</sup>
OEL TWA [2]	150 ppm
OEL STEL	950 mg/m <sup>3</sup>
OEL STEL [ppm]	200 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm



# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>n-butyl acetate (123-86-4)</b>	
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

<b>acetone (67-64-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Acetone
IOEL TWA	1210 mg/m <sup>3</sup>
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC

<b>Ireland - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA [1]	1210 mg/m <sup>3</sup>
OEL TWA [2]	500 ppm
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020

<b>Ireland - Biological limit values</b>	
Local name	Acetone
BLV	50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)

<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>dimethyl ether (115-10-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, inhalation	1894 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, inhalation	471 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.155 mg/l

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC aqua (marine water)	0.016 mg/l
PNEC aqua (intermittent, freshwater)	1.549 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.681 mg/kg dwt
PNEC sediment (marine water)	0.069 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.045 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	160 mg/l

### reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.05 mg/kg bw/day
Long-term - systemic effects, inhalation	0.35 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.025 mg/kg bw/day
Long-term - systemic effects, inhalation	0.085 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.25 mg/kg bw/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.0023 mg/l
PNEC aqua (marine water)	0.00023 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3.37 mg/kg dwt
PNEC sediment (marine water)	0.337 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	10 mg/l

### reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, inhalation	0.68 mg/m <sup>3</sup> (DGUV DNEL List 2019)

### ethyl methyl ketone (78-93-3)

<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	1161 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	600 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	31 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	106 mg/m <sup>3</sup>

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Long-term - systemic effects, dermal	412 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	55.8 mg/l
PNEC aqua (marine water)	55.8 mg/l
PNEC aqua (intermittent, freshwater)	55.8 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	284.74 mg/kg dwt
PNEC sediment (marine water)	284.7 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	22.5 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	1000 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	709 mg/l

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	208 mg/m <sup>3</sup>
Acute - local effects, inhalation	208 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11.8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	83 mg/m <sup>3</sup>
Long-term - local effects, inhalation	83 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	155.2 mg/m <sup>3</sup>
Acute - local effects, inhalation	155.2 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4.2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4.2 mg/kg bodyweight/day
Long-term - local effects, inhalation	14.7 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.6 mg/l
PNEC aqua (marine water)	0.06 mg/l
PNEC aqua (intermittent, freshwater)	1.5 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	8.27 mg/kg dwt
PNEC sediment (marine water)	0.83 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1.3 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	27.5 mg/l

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	550 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.635 mg/l
PNEC aqua (marine water)	0.0635 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3.29 mg/kg dwt
PNEC sediment (marine water)	0.329 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.29 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l

  

<b>n-butyl acetate (123-86-4)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	11 mg/kg bw/day
Acute - systemic effects, inhalation	600 mg/m <sup>3</sup>
Acute - local effects, inhalation	600 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m <sup>3</sup>
Long-term - local effects, inhalation	300 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	6 mg/kg bw/day
Acute - systemic effects, inhalation	300 mg/m <sup>3</sup>
Acute - systemic effects, oral	2 mg/kg bw/day
Acute - local effects, inhalation	300 mg/m <sup>3</sup>
Long-term - systemic effects, oral	2 mg/kg bw/day
Long-term - systemic effects, inhalation	35.7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	6 mg/kg bw/day
Long-term - local effects, inhalation	35.7 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.18 mg/l

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.0903 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	35.6 mg/l

<b>acetone (67-64-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	2420 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	186 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1210 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	62 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	200 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	62 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	10.6 mg/l
PNEC aqua (marine water)	1.06 mg/l
PNEC aqua (intermittent, freshwater)	21 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	30.4 mg/kg dwt
PNEC sediment (marine water)	3.04 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	29.5 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

**Personal protective equipment symbol(s):**

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

**Other skin protection****Materials for protective clothing:**

Impermeable clothing

### 8.2.2.3. Respiratory protection

**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0.784 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

VOC content	: 701 g/l
Gas group	: Press. Gas (Liq.)

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients	: 88.46005292806115
----------------------------	---------------------

#### 9.2.2. Other safety characteristics

Gas group	: Press. Gas (Liq.)
VOC content	: 701 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### dimethyl ether (115-10-6)

LC50 Inhalation - Rat	309 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (gases))
LC50 Inhalation - Rat [ppm]	164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 - 203000

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)

<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,

<b>toluene (108-88-3)</b>	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	25.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	25.7 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))

<b>ethyl methyl ketone (78-93-3)</b>	
LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
LD50 oral rat	2080 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1,91 - 2,27
LD50 dermal rat	$\geq$ 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat (Vapours)	10 – 20 mg/l/4h

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 oral rat	6190 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	1728 ppm/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, Inhalation, vapours)



# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

<b>acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4

<b>2-phenoxyethanol (122-99-6)</b>	
LD50 oral rat	1850 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	14391 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 2214 mg/kg bodyweight Animal: rabbit, Guideline: other:Draft IRLG (Interagency Regulatory Liaison Group) Guidelines for Selected Acute Toxicity Tests (August. 1979)
LC50 Inhalation - Rat	> 1 mg/l air Animal: rat, Guideline: other:OECD 412

<b>Xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)

<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))

<b>octamethylcyclotetrasiloxane (556-67-2)</b>	
LD50 oral rat	> 4800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2400 mg/kg bodyweight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	36 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

<b>cellulose acetate butyrate (9004-36-8)</b>	
LD50 oral rat	> 3200 mg/kg
LD50 dermal	> 1000 mg/kg (Guinea pig)

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### mixed dibasic acid polyester plasticizer

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Unknown acute toxicity (CLP) - SDS : 12.01% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified

### acetone (67-64-1)

LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
-----------------------------	--

NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
---------------------------	--

### 2-phenoxyethanol (122-99-6)

LOAEL (animal/male, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
-------------------------	---

LOAEL (animal/female, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
---------------------------	---

NOAEL (animal/female, F0/P)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
-----------------------------	---

STOT-single exposure : May cause drowsiness or dizziness.

### toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### ethyl methyl ketone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### 2-methoxypropyl acetate (70657-70-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### n-butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>Xylene (1330-20-7)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

<b>toluene (108-88-3)</b>	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

<b>2-phenoxyethanol (122-99-6)</b>	
LOAEL (oral, rat, 90 days)	> 700 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	> 500 mg/kg bodyweight Animal: rabbit
NOAEL (oral, rat, 90 days)	700 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rabbit
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0482 mg/l/6h/day

<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing sense) through prolonged or repeated exposure.

Aspiration hazard : Not classified

POWERCAN CLEARCOAT AEROSOL	
Vaporizer	aerosol

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	154.917 mg/l Test organisms (species): other:green algae

reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

ethyl methyl ketone (78-93-3)	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
LC50 - Fish [1]	> 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

<b>acetone (67-64-1)</b>	
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 96h - Algae [1]	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

## 12.2. Persistence and degradability

<b>dimethyl ether (115-10-6)</b>	
Persistence and degradability	Non degradable in the soil. Not readily biodegradable in water.

<b>ethyl methyl ketone (78-93-3)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Biochemical oxygen demand (BOD)	2.06 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.16 g O <sub>2</sub> /g substance
ThOD	2.72 g O <sub>2</sub> /g substance

### 2-methoxy-1-methylethyl acetate (108-65-6)

Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
-------------------------------	--

### n-butyl acetate (123-86-4)

Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

### acetone (67-64-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

## 12.3. Bioaccumulative potential

### dimethyl ether (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylpoly(oxyethylene)

BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

### ethyl methyl ketone (78-93-3)

Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 2-methoxy-1-methylethyl acetate (108-65-6)

Partition coefficient n-octanol/water (Log Pow)	1.2 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>n-butyl acetate (123-86-4)</b>	
BCF - Fish [1]	15.3 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>acetone (67-64-1)</b>	
BCF - Fish [1]	0.69 (Pisces)
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

<b>dimethyl ether (115-10-6)</b>	
Surface tension	0.02 N/m (-40 °C)
Ecology - soil	Not applicable (gas).

<b>ethyl methyl ketone (78-93-3)</b>	
Surface tension	0.024 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.53 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
Partition coefficient n-octanol/water (Log Koc)	2.008 (log Koc, Weight of evidence, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Surface tension	29.4 mN/m (20 °C, 100 vol %, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	0.264 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.

<b>n-butyl acetate (123-86-4)</b>	
Surface tension	0.0163 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

<b>acetone (67-64-1)</b>	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Results of PBT and vPvB assessment

<b>Component</b>	
dimethyl ether (115-10-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethyl methyl ketone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number or ID number

UN-No. (ADR) : UN 1950  
UN-No. (IMDG) : UN 1950  
UN-No. (IATA) : UN 1950  
UN-No. (ADN) : UN 1950  
UN-No. (RID) : UN 1950

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable  
Proper Shipping Name (ADN) : AEROSOLS  
Proper Shipping Name (RID) : AEROSOLS  
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)  
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1  
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1  
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1  
Transport document description (RID) : UN 1950 AEROSOLS, 2.1

### 14.3. Transport hazard class(es)

**ADR**  
Transport hazard class(es) (ADR) : 2.1  
Danger labels (ADR) : 2.1



# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1



### IATA

Transport hazard class(es) (IATA) : 2.1  
Danger labels (IATA) : 2.1



### ADN

Transport hazard class(es) (ADN) : 2.1  
Danger labels (ADN) : 2.1



### RID

Transport hazard class(es) (RID) : 2.1  
Danger labels (RID) : 2.1



## 14.4. Packing group

Packing group (ADR) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable  
Packing group (ADN) : Not applicable  
Packing group (RID) : Not applicable

## 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

## 14.6. Special precautions for user

### Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207  
Special packing provisions (ADR) : PP87, RR6, L2

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
Special provisions for carriage - Operation (ADR) : S2  
Tunnel restriction code (ADR) : D

### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

### Air transport

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

### Inland waterway transport

Classification code (ADN) : 5F  
Special provisions (ADN) : 190, 327, 344, 625  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01, VE04  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : 5F  
Special provisions (RID) : 190, 327, 344, 625  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E0  
Packing instructions (RID) : P207, LP200  
Special packing provisions (RID) : PP87, RR6, L2  
Mixed packing provisions (RID) : MP9  
Transport category (RID) : 2  
Special provisions for carriage – Packages (RID) : W14  
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12  
Colis express (express parcels) (RID) : CE2  
Hazard identification number (RID) : 23

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
----------------	---------------	----------------------------

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3(a)	POWERCAN CLEARCOAT AEROSOL ; isobutyl methyl ketone ; ethyl methyl ketone ; 2-methoxy-1-methylethyl acetate ; acetone ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	POWERCAN CLEARCOAT AEROSOL ; isobutyl methyl ketone ; ethyl methyl ketone ; reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) ; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; acetone ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) ; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	dimethyl ether ; isobutyl methyl ketone ; ethyl methyl ketone ; 2-methoxy-1-methylethyl acetate ; acetone ; n-butyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list  $\geq 0,1\%$  / SCL

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 701 g/l

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2

# POWERCAN CLEARCOAT AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).