



# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

DRIVING SURFACE PERFECTION

Date of issue:10/01/2017

Revision date:03/05/2019

Supersedes: 26/10/2017

Version: 2.1

### SECTION 1: Identification : Product identifier and chemical identity

#### 1.1. Product identifier

Product form : Mixture  
Trade name : U-POL POWERCAN PRIMER GREY AEROSOL  
Product code : PCPG/AL

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Primer

#### 1.4. Supplier's details

##### Supplier

U-POL AUSTRALIA PTY LIMITED  
Unit A, 16 - 20 Cassola Place  
Penrith, NSW 2750 - Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com.au](http://www.u-pol.com.au)

##### Supplier

U-POL NEW ZEALAND LIMITED  
c/o Lindsay & Associates  
Unit H, 12 Amara Place, East Tamaki  
Manukau City 2013 - New Zealand  
T + 612 4731 2655 - F + 612 4731 2611  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazards identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1 H222  
Serious eye damage/eye irritation, Category 2A H319  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

#### 2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger

Contains : ethyl methyl ketone (23 - 43 %); ethyl acetate (< 5 %); 1-butanol (< 5 %); n-butyl acetate (< 5 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing fume, spray, vapours.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

Additional hazard statements (GHS AU) : AUH066 - Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
ethyl methyl ketone ( )	78-93-3	23 - 43	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Eye Irrit. 2A, H319 STOT SE 3, H336
ethyl acetate ( )	141-78-6	< 5	Flam. Liq. 2, H225 STOT SE 3, H336
1-butanol ( )	71-36-3	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336
castor oil, sulfated, sodium salt ( )	68187-76-8	< 5	Eye Irrit. 2A, H319
n-butyl acetate ( )	123-86-4	< 5	Flam. Liq. 3, H226 STOT SE 3, H336
Other substances (not contributing to the classification of this product)		99.96 - 99.99	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Symptoms caused by exposure

- Symptoms/effects : May cause drowsiness or dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, fume, spray.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

- Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released product. Collect spillage.  
Methods for cleaning up : Mechanically recover the product.

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### SECTION 7: Handling and storage, including how the chemical may be safely used

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, fume, spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Storage temperature : < 25 °C
- Special rules on packaging : Keep only in original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters - exposure standards

ethyl methyl ketone (78-93-3)		
Australia	Local name	Methyl ethyl ketone (MEK) (2-Butanone)
Australia	TWA (mg/m <sup>3</sup> )	445 mg/m <sup>3</sup>
Australia	TWA (ppm)	150 ppm
Australia	STEL (mg/m <sup>3</sup> )	890 mg/m <sup>3</sup>
Australia	STEL (ppm)	300 ppm
New Zealand	Local name	Methyl ethyl ketone (2-Butanone) (MEK)
New Zealand	TWA (mg/m <sup>3</sup> )	445 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	150 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	890 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	300 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

n-butyl acetate (123-86-4)		
Australia	Local name	n-Butyl acetate
Australia	TWA (mg/m <sup>3</sup> )	713 mg/m <sup>3</sup>
Australia	TWA (ppm)	150 ppm
Australia	STEL (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
Australia	STEL (ppm)	200 ppm
New Zealand	Local name	n-Butyl acetate
New Zealand	TWA (mg/m <sup>3</sup> )	713 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	150 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	200 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

1-butanol (71-36-3)		
Australia	Local name	n-Butyl alcohol (n-Butanol)
Australia	OEL - Ceilings (mg/m <sup>3</sup> )	152 mg/m <sup>3</sup>
Australia	OEL - Ceilings (ppm)	50 ppm
Australia	Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
New Zealand	Local name	n-Butyl alcohol
New Zealand	Remark (NZ)	skin (Skin absorption)
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

ethyl acetate (141-78-6)		
Australia	Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
Australia	TWA (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

ethyl acetate (141-78-6)		
Australia	TWA (ppm)	200 ppm
Australia	STEL (mg/m <sup>3</sup> )	1440 mg/m <sup>3</sup>
Australia	STEL (ppm)	400 ppm
New Zealand	Local name	Ethyl acetate
New Zealand	TWA (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	200 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

### Exposure limit values for the other components

#### 8.2. Monitoring

No additional information available

#### 8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

#### 8.4. Personal protective equipment

Personal protective equipment : Gloves. Protective clothing. Safety glasses.

Materials for protective clothing : Impermeable clothing

Hand protection : Protective gloves

Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

### SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point : Not applicable
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density : 0.731 g/cm <sup>3</sup>
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Viscosity, dynamic	: ≈
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Minimum ignition energy	: No data available
VOC content - Regulatory	: No data available
Gas group	: Press. Gas (Liq.)

### SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated. Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ethyl methyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male/female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 - 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male/female, Experimental value, Dermal)
LC50 inhalation rat (ppm)	390 ppm/4h
LC50 inhalation rat (Vapours - mg/l/4h)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

1-butanol (71-36-3)	
LD50 oral rat	2292 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	3430 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)

ethyl acetate (141-78-6)	
LD50 oral rat	10200 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	> 20000 mg/kg bodyweight (24 hour cuff method, 24 h, Rabbit, Male, Experimental value, Dermal)

castor oil, sulfated, sodium salt (68187-76-8)	
LD50 oral rat	> 15600 mg/kg
LD50 dermal rat	> 2000 mg/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

U-POL POWERCAN PRIMER GREY AEROSOL	
Vaporizer	Aerosol

### SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

ethyl methyl ketone (78-93-3)	
LC50 fish 1	2993 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	308 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Log Koc	1.53 (log Koc, Calculated value)

n-butyl acetate (123-86-4)	
LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
LC50 fish 2	62 mg/l (Leuciscus idus, static system)
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)
NOEC chronic crustacea	23 mg/l
BCF fish 1	15.3 (Calculated value)
Log Pow	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	1.268 - 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)

1-butanol (71-36-3)	
LC50 fish 1	1376 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1328 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
NOEC chronic crustacea	4.1 mg/l
BCF other aquatic organisms 1	3.16 (BCFWIN, Calculated value)
Log Pow	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	0.388 (log Koc, PCKOCWIN v1.66, Calculated value)

ethyl acetate (141-78-6)	
LC50 fish 1	230 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	154 mg/l (48 h, Daphnia magna, Literature)
BCF fish 1	30 (3 day(s), Leuciscus idus, Static system, Experimental value)
Log Pow	0.68 (Experimental value, EPA OPPTS 830.7560, 25 °C)

castor oil, sulfated, sodium salt (68187-76-8)	
LC50 fish 1	550 mg/l (Danio rerio)
NOEC chronic crustacea	100 mg/l
NOEC chronic algae	10 mg/l
Log Pow	1

### 12.2. Persistence and degradability

ethyl methyl ketone (78-93-3)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

1-butanol (71-36-3)	
Persistence and degradability	Readily biodegradable in water.

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

<b>1-butanol (71-36-3)</b>	
Biochemical oxygen demand (BOD)	1.1 - 1.92 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.46 g O <sub>2</sub> /g substance
ThOD	2.59 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.33 - 0.79

<b>ethyl acetate (141-78-6)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.293 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.69 g O <sub>2</sub> /g substance
ThOD	1.82 g O <sub>2</sub> /g substance

<b>castor oil, sulfated, sodium salt (68187-76-8)</b>	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>ethyl methyl ketone (78-93-3)</b>	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>n-butyl acetate (123-86-4)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>1-butanol (71-36-3)</b>	
BCF other aquatic organisms 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>ethyl acetate (141-78-6)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>castor oil, sulfated, sodium salt (68187-76-8)</b>	
Log Pow	See section 12.1 on ecotoxicology

### 12.4. Mobility in soil

<b>ethyl methyl ketone (78-93-3)</b>	
Surface tension	0.024 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.

<b>n-butyl acetate (123-86-4)</b>	
Surface tension	0.0163 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

<b>1-butanol (71-36-3)</b>	
Surface tension	0.07 N/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil. May be harmful to plant growth, blooming and fruit formation.

<b>ethyl acetate (141-78-6)</b>	
Surface tension	0.024 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

<b>castor oil, sulfated, sodium salt (68187-76-8)</b>	
Log Pow	See section 12.1 on ecotoxicology

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

U-POL POWERCAN PRIMER GREY AEROSOL	
Fluorinated greenhouse gases	False
ethyl methyl ketone (78-93-3)	
Fluorinated greenhouse gases	False
n-butyl acetate (123-86-4)	
Fluorinated greenhouse gases	False
1-butanol (71-36-3)	
Fluorinated greenhouse gases	False
ethyl acetate (141-78-6)	
Fluorinated greenhouse gases	False
castor oil, sulfated, sodium salt (68187-76-8)	
Fluorinated greenhouse gases	False

### SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

#### 14.1. UN number

UN-No. (ADG) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

#### 14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable

#### 14.3. Transport hazard class(es)

##### ADG

Transport hazard class(es) (ADG) : 2.1  
Danger labels (ADG) : 2.1



##### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1



##### IATA

Transport hazard class(es) (IATA) : 2.1  
Hazard labels (IATA) : 2.1





# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 14.4. Packing group

Packing group (ADG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

### 14.5. Environmental hazards

Marine pollutant	: No
------------------	------

### 14.6. Special precautions for user

Specific storage requirement	: No data available
Shock sensitivity	: No data available

### 14.7. Additional information

Other information	: No supplementary information available
-------------------	--

### Transport by road and rail

UN-No. (ADG)	: 1950
Special provision (ADG)	: 63, 190, 277, 327, 344
Limited quantities (ADG)	: See SP 277
Packing instructions (ADG)	: P207, LP02
Special packing provisions (ADG)	: PP87

### Transport by sea

UN-No. (IMDG)	: 1950
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None

### Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.8. Hazchem or Emergency Action Code

Hazchemcode	: Not applicable
-------------	------------------

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	: HSR002515
Group standard	: Aerosols

### 15.2. International agreements

No additional information available

## SECTION 16: Any other relevant information

Revision date	: 03/05/2019
Classification:	

# U-POL POWERCAN PRIMER GREY AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Flam. Aerosol 1	H222
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. 5 (Dermal)	Acute toxicity (dermal), Category 5
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

SDS Australia U-POL

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).*