



# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

DRIVING SURFACE PERFECTION

Date of issue:21/03/2017

Revision date:03/05/2019

Supersedes: 05/12/2017

Version: 3.1

### SECTION 1: Identification : Product identifier and chemical identity

#### 1.1. Product identifier

Product form : Mixture  
Trade name : U-POL PLASTX TEXTURECOAT - COARSE  
Product code : PLAS/4C

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

#### 1.4. Supplier's details

##### Supplier

U-POL AUSTRALIA PTY LIMITED  
Unit A, 16 - 20 Cassola Place  
Penrith, NSW 2750 - Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com.au](http://www.u-pol.com.au)

##### Supplier

U-POL NEW ZEALAND LIMITED  
c/o Lindsay & Associates  
Unit H, 12 Amara Place, East Tamaki  
Manukau City 2013 - New Zealand  
T + 612 4731 2655 - F + 612 4731 2611  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazards identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1 H222  
Serious eye damage/eye irritation, Category 2A H319  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

#### 2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger

Contains : acetone (23 - 43 %); hydrocarbons C9 – 10 n-alkanes, isoalkanes, cyclics, <2% aromatics (5 - 23 %); cyclohexane (< 5 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing vapours, spray, fume.  
P264 - Wash hands thoroughly after handling.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
acetone ( )	67-64-1	23 - 43	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
hydrocarbons C9 – 10 n-alkanes, isoalkanes, cyclics, <2% aromatics ( )	1174921-73-3	5 - 23	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
cyclohexane ( )	110-82-7	< 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
C22-30 chlorinated paraffin (chlorination: 42-48%) ( )	63449-39-8	< 5	Not classified
Other substances (not contributing to the classification of this product)		53.67	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Symptoms caused by exposure

- Symptoms/effects : May cause drowsiness or dizziness.

#### 4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
General measures : Remove ignition sources. No open flames. No smoking.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, spray, fume.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

- Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released product, pump into suitable containers. Collect spillage.  
Methods for cleaning up : Mechanically recover the product.

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### SECTION 7: Handling and storage, including how the chemical may be safely used

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray, fume.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Storage temperature : < 25 °C
- Special rules on packaging : Keep only in original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters - exposure standards

acetone (67-64-1)		
Australia	Local name	Acetone
Australia	TWA (mg/m <sup>3</sup> )	1185 mg/m <sup>3</sup>
Australia	TWA (ppm)	500 ppm
Australia	STEL (mg/m <sup>3</sup> )	2375 mg/m <sup>3</sup>
Australia	STEL (ppm)	1000 ppm
New Zealand	Local name	Acetone
New Zealand	TWA (mg/m <sup>3</sup> )	1185 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	500 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	2375 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	1000 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

cyclohexane (110-82-7)		
Australia	Local name	Cyclohexane
Australia	TWA (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
Australia	TWA (ppm)	100 ppm
Australia	STEL (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
Australia	STEL (ppm)	300 ppm
New Zealand	Local name	Cyclohexane
New Zealand	TWA (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	100 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	300 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 8th Edition

#### Exposure limit values for the other components

#### 8.2. Monitoring

No additional information available

#### 8.3. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

#### 8.4. Personal protective equipment

- Personal protective equipment : Gloves. Protective clothing. Safety glasses.
- Materials for protective clothing : Impermeable clothing
- Hand protection : Protective gloves
- Eye protection : Safety glasses

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment
- Personal protective equipment symbol(s)



- Environmental exposure controls : Avoid release to the environment.

### SECTION 9: Physical and chemical properties

- Physical state : Liquid
- Appearance : Aerosol.
- Colour : No data available
- Odour : No data available
- Odour threshold : No data available
- pH : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Melting point / Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Auto-ignition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapour pressure : No data available
- Relative density : No data available
- Density : Density : 0.809 g/cm<sup>3</sup>
- Solubility : insoluble in water. soluble in most organic solvents.
- Log Pow : No data available
- Viscosity, dynamic : ≈
- Explosive properties : Pressurised container: May burst if heated.
- Explosive limits : No data available
- Minimum ignition energy : No data available
- VOC content - Regulatory : No data available
- Gas group : Press. Gas (Liq.)

### SECTION 10: Stability and reactivity

- Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated. Extremely flammable aerosol. Pressurised container: May burst if heated.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.
- Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
- Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

- Acute toxicity (oral) : Not classified
- Acute toxicity (dermal) : Not classified
- Acute toxicity (inhalation) : Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

<b>hydrocarbons C9 – 10 n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (1174921-73-3)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	> 4.951 mg/l/4h (OECD Guideline 403 (Acute Inhalation Toxicity), 4h, rat, male/female, inhalation (vapours))

<b>cyclohexane (110-82-7)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male/female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	> 32.88 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value)
LC50 inhalation rat (Vapours - mg/l/4h)	> 32.88 mg/l/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), Rat, male/female, Experimental value, Inhalation (vapours))

<b>C22-30 chlorinated paraffin (chlorination: 42-48%) (63449-39-8)</b>	
LD50 oral rat	> 11700 mg/kg (EPA OPP 81-1 (Acute Oral Toxicity), rat, male/female)
LD50 dermal rabbit	> 13900 mg/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

<b>U-POL PLASTX TEXTURECOAT - COARSE</b>	
Vaporizer	Aerosol

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

<b>acetone (67-64-1)</b>	
LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)

<b>hydrocarbons C9 – 10 n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (1174921-73-3)</b>	
LC50 fish 1	10 - 100 mg/l
NOEC chronic fish	1 mg/l

<b>cyclohexane (110-82-7)</b>	
LC50 fish 1	4.53 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
EC50 Daphnia 1	0.9 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	9.317 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)
BCF fish 1	167 (Pimephales promelas, QSAR)
Log Pow	3.44 (Experimental value, Other, 25 °C)
Log Koc	2.89 (log Koc, Other, QSAR)

### 12.2. Persistence and degradability

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

<b>acetone (67-64-1)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

<b>cyclohexane (110-82-7)</b>	
Persistence and degradability	Non degradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.22 g O <sub>2</sub> /g substance
ThOD	3.425 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>acetone (67-64-1)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
BCF other aquatic organisms 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Not bioaccumulative.

<b>cyclohexane (110-82-7)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

<b>acetone (67-64-1)</b>	
Surface tension	0.0237 N/m
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	No (test)data on mobility of the substance available.

<b>cyclohexane (110-82-7)</b>	
Surface tension	0.025 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

<b>U-POL PLASTX TEXTURECOAT - COARSE</b>	
Fluorinated greenhouse gases	False

<b>acetone (67-64-1)</b>	
Fluorinated greenhouse gases	False

<b>hydrocarbons C9 – 10 n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (1174921-73-3)</b>	
Fluorinated greenhouse gases	False

<b>cyclohexane (110-82-7)</b>	
Fluorinated greenhouse gases	False

<b>C22-30 chlorinated paraffin (chlorination: 42-48%) (63449-39-8)</b>	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable

### 14.3. Transport hazard class(es)

#### ADG

Transport hazard class(es) (ADG) : 2.1  
Danger labels (ADG) : 2.1



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1



#### IATA

Transport hazard class(es) (IATA) : 2.1  
Hazard labels (IATA) : 2.1



### 14.4. Packing group

Packing group (ADG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Marine pollutant : No

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344  
Limited quantities (ADG) : See SP 277  
Packing instructions (ADG) : P207, LP02  
Special packing provisions (ADG) : PP87, L2

### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None

### Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.8. Hazchem or Emergency Action Code

Hazchemcode	: Not applicable
-------------	------------------

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	: HSR002515
Group standard	: Aerosols

### 15.2. International agreements

No additional information available

## SECTION 16: Any other relevant information

Revision date	: 03/05/2019
---------------	--------------

Classification:

Flam. Aerosol 1	H222
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS Australia U-POL

# U-POL PLASTX TEXTURECOAT - COARSE

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

---

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).*