



DRIVING SURFACE PERFECTION

TECHNICAL DATA SHEET

# PLAST-X #5

Trim Topcoat colours

## DESCRIPTION

- Topcoat for suitably primed plastic components
- Achieves a satin, durable finish
- Excellent coverage and fast drying

## TECHNICAL DATA



### Substrates

- PLAST-X #3 or #3HB
- Prepared OEM paint surfaces

## APPLICATION GUIDE



### Tools Required

- PLAST-X Range
- MAXIMUM Abrasives



### Substrate Preparation And Instruction For Use

Thoroughly clean and degrease surfaces with PLAS/1 aerosol plastic cleaner.  
Abrade primed surfaces wet with 600-800 or dry with 400-600 abrasive, re-clean, dry and degrease



### Mixing

Shake the aerosol can for at least 2 minutes before use.



### Coats

1 - 2 coats at a distance of approx. 25 cm from the surface.

Build / microns 15μ

\*Theoretical Coverage approx. m<sup>2</sup>/unit 2

*\*Theoretical Coverage per unit assuming 100% transfer efficiency and giving the dry film thickness between indicated values.*



### Flash-off / min @ 20°C

between coats 2 - 5 mins



### Drying Times

Handleable @ 20°C / min 60 mins

Drying time is dependant on film thickness, humidity and temperature.



DRIVING SURFACE PERFECTION

TECHNICAL DATA SHEET

# PLAST-X #5

Trim Topcoat colours

## STORAGE & VOC INFORMATION



### Shelf Life

2 years subject to good storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature 5°C - 25°C

Recommended Application Temperature 20°C



### VOC Information

The EU limit for this product (product category: IIB.e) in ready to use form is 840g/litre. The VOC content of this product in ready to use form is 680 g/litre.

Order Code	Format	Colour	VOC g/l
PLAS/5B	400ml Aerosol	Black	644
PLAS/5BG	400ml Aerosol	Basalt Grey	637
PLAS/5DG	400ml Aerosol	Dark Grey	640
PLAS/5GG	400ml Aerosol	Graphite	636
PLAS/5LG	400ml Aerosol	Light Grey	642
PLAS/5MG	400ml Aerosol	Medium Grey	641
PLAS/5SB	400ml Aerosol	Signal Black	633
PLAS/5TB	400ml Aerosol	Traffic Black	633

### IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM). U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

**U-POL AUSTRALIA PTY Ltd.**  
Unit A, 16-20 Cassola Place,  
Penrith, NSW 2750.  
Australia

Tel: 02 4731 2655  
Emergency Tel: +61 290 372 994  
Fax: +61 290 372 994

Email: [info@u-pol.com.au](mailto:info@u-pol.com.au)  
Web: [www.u-pol.com.au](http://www.u-pol.com.au)