



DRIVING SURFACE PERFECTION™

334

TECHNICAL DATA SHEET

Fine Finishing Compound

Version: 1.0

DESCRIPTION

A liquid compound to remove fine abrasive marks, P2000 grit or finer, restores dull oxidized paintwork and blends in dry edges of a repair. Suitable for all finishes including dark colours

- Scratch resistant, swirl eliminator
- Free from silicone and ammonia
- For use with orange foam mop (QWMFFF)

Typical Use - U-POL 334 Fine Finishing Compound is a finer liquid abrasive designed to rectify modern paintwork to a high gloss finish.

STORAGE & VOC INFORMATION

Storage Information



It is recommended that U-POL 334 is stored in a frost free environment.

VOC Information



VOC content 258g/l

Order Code	Format	Colour
QW334/1	1L Bottle	Cream

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL Ltd

4th Floor, The Grange, 100 High Street
London, N14 6BN
WWW.U-POL.COM

UK Sales

T: +44 (0)20 8492 5920
F: +44 (0)20 8181 6911
uk.sales@u-pol.com

International

T: +44 (0)20 8492 5900
F: +44 (0)20 8150 5605
sales@u-pol.com

Technical

T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicaldepartment@u-pol.com

APPLICATION GUIDE

Tools Required



By Machine:

QWMS - Soft Polishing Foam Mop (Fast Fix or Backing Plate) for a high gloss immaculate finish on dark colours.

QWMF - Firm Compounding Foam Mop (Fast Fix or Backing Plate) for faster results on hard aged, ceramic and scratch resistant coatings.

By Hand:

QWCMF - Micro Fibre Polishing Cloth





DRIVING SURFACE PERFECTION™

334

TECHNICAL DATA SHEET

Version: 1.0

Fine Finishing Compound

Surface Preparation



Old paintwork should be cleaned thoroughly to remove road traffic film and dirt. Wipe down surface with System 2000, 2001 or 2002 degreaser.

New paint should be fully cured in accordance with paint manufacturers' drying schedule. Minor orange peel, runs, scratches and dirt nibs should be removed using U-POL Maximum Film-backed ABD7/VP1500 P1500 grit abrasive disc or finer. Use of a soft interface pad is recommended to further refine the scratch pattern. Remove sanding debris from surface with U-POL Tack Cloth and degrease.

Application



Use with either a U-POL Firm Compounding Foam Mop or a Soft Polishing Foam Mop depending on the degree of cutting action required. Ensure the mop is clean and free from dust and dirt which may scratch paint surface. Soak the mop in clean water then squeeze out any excessive water. Fit mop to a polishing machine and spin off to remove any excess water.

Shake U-POL 334 before use. Working a small area at a time, apply product to mop or directly to panel and spread over the area using the foam pad. Begin compounding at buffer speed of 1200-1500 RPM and medium pressure; always start polisher with the mop head flat on the surface.

Reduce speed and/or pressure when compounding panel edges or ridges. Gradually decrease the pressure and buff until desired finish is achieved.

More compound and/or water can be added if required. Wipe clean using a U-POL Micro Fibre Polishing Cloth. Clean mop heads regularly to avoid build-up of paint that may impair future work.

U-POL 334 may also be applied by hand with a soft polishing cloth using a buffing action. Do not use cotton or mutton cloths as these are too coarse and can scratch surface.

Additional Information

The finish can be further enhanced using 335 High Gloss Final Glaze and/or 336 Ultra Gloss Wax Protector from the U-POL Automotive Polishing System. Other products in the system are U-POL 333 Cutting Compound where a more aggressive cutting action is required, available in paste or liquid form. All products are 100% bodyshop safe.