



DRIVING SURFACE PERFECTION™

335

TECHNICAL DATA SHEET

High Gloss Final Glaze

Version: 1.0

DESCRIPTION

Recreate a durable professional high gloss finish. Suitable for all modern paintwork whether aged or new.

- Eliminates holograms and swirl marks
- Easy to apply and remove
- Water miscible, free from silicone and ammonia

Typical Use - U-POL 335 High Gloss Final Glaze delivers that showroom finish demanded by discerning customers.

STORAGE & VOC INFORMATION

Storage Information



It is recommended that U-POL 335 is stored in a frost free environment.

VOC Information



VOC content 115g/l

Order Code	Format	Colour
QW335/1	1L Bottle	White

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL Ltd

4th Floor, The Grange, 100 High Street
London, N14 6BN
WWW.U-POL.COM

UK Sales

T: +44 (0)20 8492 5920
F: +44 (0)20 8181 6911
uk.sales@u-pol.com

International

T: +44 (0)20 8492 5900
F: +44 (0)20 8150 5605
sales@u-pol.com

Technical

T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicaldepartment@u-pol.com

APPLICATION GUIDE

Tools Required



By Machine:

QWMS - Soft Polishing Foam Mop (Fast Fix or Backing Plate)

By Hand:

QWCMF - Micro Fibre Polishing Cloth





DRIVING SURFACE PERFECTION™

335

TECHNICAL DATA SHEET

High Gloss Final Glaze

Version: 1.0

Surface Preparation



Old paintwork should be cleaned thoroughly to remove road traffic film and dirt. Wipe down surface with System 2000, 2001 or 2002 degreaser.

New paint should be fully cured in accordance with paint manufacturers' drying schedule. Paintwork should be washed and dried before applying U-POL 335.

Application



By Machine: Use with a U-POL Soft Polishing Foam Mop. Ensure the mop is clean and free from dust and dirt which may scratch paint surface. Soak the mop in clean water then squeeze out any excessive water. Fit compounding mop to a polishing machine and spin off to remove any excess water.

Shake U-POL 335 before use. Working a small area at a time apply product to mop or directly to panel and spread over the area using the foam pad. Begin polishing at buffer speed of 1200-1500 RPM and applying light/medium pressure; always start polisher with the mop head flat on the surface. Buff until desired finish is achieved. If any residue remains this should be removed with a U-POL Micro Fibre Polishing Cloth. Clean mop heads regularly for optimal performance.

By Hand: Shake U-POL 335 bottle before use. Apply a small amount of product to a clean U-POL Micro Fibre Polishing Cloth. Using a light even pressure, apply product to the surface using an overlapping motion to ensure complete coverage. Buff until the desired finish is achieved.

Additional Information

For extra surface protection use in conjunction with 336 Ultra Gloss Wax Protector from the U-POL Automotive Polishing System.

Other products in the system include 333 Cutting Compound Paste and 333 Liquid Cutting Compound for regular compounding and 334 Fine Finishing Compound for minor defect correction and paint restoring. All products are 100% bodyshop safe.