

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing vapours, spray, fume.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear eye protection, face protection, protective gloves.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
hexamethylene diisocyanate oligomers	28182-81-2	5 - 15	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5	< 10	Acute Tox. 5 (Oral), H303 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	-	< 10	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Other substances (not contributing to the classification of this product)	-	92.71	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing fume, spray, vapours.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing fume, spray, vapours. Wear personal protective equipment.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Exposure limit values for the other components

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

quartz (14808-60-7)		
Australia - Occupational Exposure Limits		
Local name	Quartz [Silica – Crystalline]	
OES TWA [1]	0.05 mg/m ³ respirable dust	
Remark (AU)	Carcinogenicity Category 1A – Known to have carcinogenic potential for humans. The classification of a chemical into this category is based largely on human evidence from studies that have established a causal relationship between human exposure and the development of cancer.	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
crystalite, 1%≤conc respirable crystalline silica<10% (14464-46-1)		
Australia - Occupational Exposure Limits		
Local name	Cristobalite [Silica – Crystalline]	
OES TWA [1]	0.05 mg/m ³ respirable dust	
Remark (AU)	Carcinogenicity Category 1A – Known to have carcinogenic potential for humans. The classification of a chemical into this category is based largely on human evidence from studies that have established a causal relationship between human exposure and the development of cancer.	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
calcium carbonate (471-34-1)		
Australia - Occupational Exposure Limits		
Local name	Calcium carbonate (Limestone; Marble; Whiting)	
OES TWA [1]	10 mg/m ³	
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
New Zealand - Occupational Exposure Limits		
Local name	Marble (Calcium carbonate)	
WES-TWA (OEL TWA) [1]	10 mg/m ³	
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition	
n-butyl acetate (123-86-4)		
Australia - Occupational Exposure Limits		
Local name	n-Butyl acetate	
OES TWA [1]	713 mg/m ³	
OES TWA [2]	150 ppm	

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

n-butyl acetate (123-86-4)		
OES STEL	950 mg/m ³	
OES STEL [ppm]	200 ppm	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
New Zealand - Occupational Exposure Limits		
Local name	n-Butyl acetate	
WES-TWA (OEL TWA) [1]	713 mg/m ³	
WES-TWA (OEL TWA) [2]	150 ppm	
WES-STEL (OEL STEL)	950 mg/m ³	
WES-STEL (OEL STEL) [ppm]	200 ppm	
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition	
2-methoxy-1-methylethyl acetate (108-65-6)		
Australia - Occupational Exposure Limits		
Local name	1-Methoxy-2-propanol acetate	
OES TWA [1]	274 mg/m ³	
OES TWA [2]	50 ppm	
OES STEL	548 mg/m ³	
OES STEL [ppm]	100 ppm	
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
acetone (67-64-1)		
Australia - Occupational Exposure Limits		
Local name	Acetone	
OES TWA [1]	1185 mg/m ³	
OES TWA [2]	500 ppm	
OES STEL	2375 mg/m ³	
OES STEL [ppm]	1000 ppm	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
New Zealand - Occupational Exposure Limits		
Local name	Acetone	
WES-TWA (OEL TWA) [1]	1185 mg/m ³	
WES-TWA (OEL TWA) [2]	500 ppm	
WES-STEL (OEL STEL)	2375 mg/m ³	
WES-STEL (OEL STEL) [ppm]	1000 ppm	
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition	

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

acetone (67-64-1)		
New Zealand - Biological Exposure Indices		
Local name	Acetone	
BEI	50 mg/l Parameter: Acetone - Medium: Urine - Sampling time: End of shift	
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition	
carbon black (1333-86-4)		
Australia - Occupational Exposure Limits		
Local name	Carbon black	
OES TWA [1]	3 mg/m ³	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
New Zealand - Occupational Exposure Limits		
Local name	Carbon black	
WES-TWA (OEL TWA) [1]	3 mg/m ³	
Remark (NZ)	6.7B (Suspected carcinogen)	
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition	
dimethyl ether (115-10-6)		
Australia - Occupational Exposure Limits		
Local name	Dimethyl ether	
OES TWA [1]	760 mg/m ³	
OES TWA [2]	400 ppm	
OES STEL	950 mg/m ³	
OES STEL [ppm]	500 ppm	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)	
New Zealand - Occupational Exposure Limits		
Local name	Dimethylether	
WES-TWA (OEL TWA) [1]	766 mg/m ³	
WES-TWA (OEL TWA) [2]	400 ppm	
WES-STEEL (OEL STEL)	958 mg/m ³	
WES-STEEL (OEL STEL) [ppm]	500 ppm	
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition	

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Air-Purifying Respirator (APR), reusable	Filter A2/B2		

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance : aerosol.
Colour : Black
Odour : characteristic
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point / Freezing point : No data available
Boiling point : -24 °C
Flash point : No data available
Auto-ignition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative density : No data available
Density : Density: 0.947 g/cm³
Solubility : No data available
Partition coefficient n-octanol/water (Log Pow) : No data available
Explosive properties : Pressurised container: May burst if heated.
Explosive limits : No data available
Minimum ignition energy : No data available
VOC content : 526 g/l
VOC content - Regulatory : No data available
Percent Solids : 44.39 wt%

SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.
Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials : No additional information available
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)
ATE AU (vapours)	5800 mg/l/4h
ATE AU (dust,mist)	5800 mg/l/4h

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,
ATE AU (oral)	3230 mg/kg bodyweight

hexamethylene diisocyanate oligomers (28182-81-2)	
LD50 oral rat	> 2500 mg/kg (OECD Test Guideline 423, rat, female)
LD50 dermal rat	> 2000 mg/kg (OECD Test Guideline 402, rat, male/female)
LC50 Inhalation - Rat (Dust/Mist)	0.39 mg/l/4h (OECD Test Guideline 403, rat, female, inhalation, dust/mist)
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	0.39 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

hexamethylene diisocyanate oligomers (28182-81-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

RAPTOR 2K BLACK BED LINER AEROSOL	
Vaporizer	aerosol

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

12.4. Mobility in soil

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

RAPTOR 2K BLACK BED LINER AEROSOL	
Fluorinated greenhouse gases	False
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	
Fluorinated greenhouse gases	False
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
Fluorinated greenhouse gases	False
hexamethylene diisocyanate oligomers (28182-81-2)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1
Danger labels (ADG) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1



14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Special provision (ADG) : 63, 190, 277, 327, 344
Limited quantities (ADG) : See SP 277
Packing instructions (ADG) : P207, LP02
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515
Group standard : Aerosols

hexamethylene diisocyanate oligomers (28182-81-2)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR003565
----------------------	-----------

Xylene (1330-20-7)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR000983
----------------------	-----------

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 20/12/2021

Classification

Aerosol 1	H222;H229
-----------	-----------

RAPTOR 2K BLACK BED LINER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Classification	
Eye Irrit. 2A	H319
Skin Sens. 1	H317

Full text of H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H303	May be harmful if swallowed
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.