



S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

DRIVING SURFACE PERFECTION

Date of issue:20/01/2017

Revision date:03/05/2019

Supersedes: 07/12/2017

Version: 2.1

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture
Trade name : S2003 PLASTIC PRIMER AEROSOL
Product code : S2003/AL

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesion promoter

1.4. Supplier's details

Supplier

U-POL AUSTRALIA PTY LIMITED
Unit A, 16 - 20 Cassola Place
Penrith, NSW 2750 - Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.co.nz - www.u-pol.com.au

Supplier

U-POL NEW ZEALAND LIMITED
c/o Lindsay & Associates
Unit H, 12 Amera Place, East Tamaki
Manukau City 2013 - New Zealand
T + 612 4731 2655 - F + 612 4731 2611
technicalsupport@u-pol.com - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1 H222
Skin corrosion/irritation, Category 2 H315
Reproductive toxicity, Category 2 H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Specific target organ toxicity — Repeated exposure, Category 2 H373

2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger

Contains : toluene (43 - 63 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe fume, spray, vapours.
P264 - Wash hands thoroughly after handling.
P280 - Wear eye protection, protective clothing, protective gloves.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
toluene ()	108-88-3	43 - 63	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)		52.04	

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
General measures	: Remove ignition sources. No open flames. No smoking. No flames, no sparks. Eliminate all sources of ignition.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. No open flames. No smoking. No flames, no sparks. Eliminate all sources of ignition.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapours, fume, spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released product. Collect spillage.
Methods for cleaning up	: Mechanically recover the product. Notify authorities if product enters sewers or public waters.

S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapours, fume, spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Storage temperature : < 25 °C
- Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

toluene (108-88-3)		
Australia	Local name	Toluene
Australia	TWA (mg/m ³)	191 mg/m ³
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m ³)	574 mg/m ³
Australia	STEL (ppm)	150 ppm
Australia	Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
New Zealand	Local name	Toluene (Toluol)
New Zealand	TWA (mg/m ³)	188 mg/m ³
New Zealand	TWA (ppm)	50 ppm
New Zealand	Remark (NZ)	skin (Skin absorption)
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 8th Edition

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

- Personal protective equipment : Gloves. Protective clothing. Safety glasses.
- Materials for protective clothing : Impermeable clothing
- Hand protection : Protective gloves
- Eye protection : Safety glasses
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)



- Environmental exposure controls : Avoid release to the environment.

S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point : Not applicable
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density : 0.779 g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Viscosity, dynamic	: ≈
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content - Regulatory	: No data available
Gas group	: Press. Gas (Liq.)

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated. Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

toluene (108-88-3)	
LD50 oral rat	5580 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral (one dose))
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Other, 24 h, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (Vapours - mg/l/4h)	25.7 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).
Aspiration hazard	: Not classified

S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

S2003 PLASTIC PRIMER AEROSOL	
Vaporizer	Aerosol

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

toluene (108-88-3)	
LC50 fish 1	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value)
BCF fish 1	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Log Pow	2.73 (Experimental value, 20 °C)

12.2. Persistence and degradability

toluene (108-88-3)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69

12.3. Bioaccumulative potential

toluene (108-88-3)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

toluene (108-88-3)	
Surface tension	27.73 N/m (25 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

S2003 PLASTIC PRIMER AEROSOL	
Fluorinated greenhouse gases	False
toluene (108-88-3)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG)	: 1950
UN-No. (IMDG)	: 1950
UN-No. (IATA)	: 1950

14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG)	: AEROSOLS
Proper Shipping Name (IMDG)	: AEROSOLS
Proper Shipping Name (IATA)	: Aerosols, flammable

S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1
Danger labels (ADG) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Hazard labels (IATA) : 2.1



14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950
Special provision (ADG) : 63, 190, 277, 327, 344
Limited quantities (ADG) : See SP 277
Packing instructions (ADG) : P207, LP02
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950
Special provisions (IMDG) : 63, 190, 277, 327, 344, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP02
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None

S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Stowage and segregation (IMDG) : Protected from sources of heat For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but 'Separated from' class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167
ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchemcode : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515
Group standard : Aerosols

ethylbenzene (100-41-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001151

xylene (1330-20-7)

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR000983

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 03/05/2019

Classification:

Flam. Aerosol 1	H222
Skin Irrit. 2	H315
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373

Full text of H-statements:

Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Aerosol 1	Flammable aerosols, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

S2003 PLASTIC PRIMER AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

SDS Australia U-POL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.