



DRIVING SURFACE PERFECTION

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date: 20/01/2017 Revision date: 20/12/2021 Supersedes: 7/02/2021 Version: 4.0

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL  
Product code : S2003/AL

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

#### 1.4. Details of manufacturer or importer

##### Supplier

U-POL Australia Pty Limited Ltd  
Unit A, 16 - 20 Cassola Place  
Penrith NSW 2750  
Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.au](mailto:info@u-pol.co.au) - [www.u-pol.com](http://www.u-pol.com)

##### Supplier

U-POL New Zealand Limited Ltd  
c/o Lindsay & Associates Unit H, 12 Amara Place, East Tamaki  
Manukau City Auckland 2013  
New Zealand  
T + 612 4731 2655 - F + 612 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Health hazard

Signal word (GHS AU) :

Danger

Contains :

toluene (30 – 60 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs (hearing organs) through prolonged or repeated exposure (inhalation)

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Precautionary statements (GHS AU)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P260 - Do not breathe fume, spray, vapours. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear eye protection, face protection, protective gloves. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
-----------------------------------	---

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
toluene	108-88-3	30 – 60	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)	-	52.04	-

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

### 4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

General measures	: Remove ignition sources. No open flames. No smoking. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. No open flames. No smoking. No flames, no sparks. Eliminate all sources of ignition.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe fume, spray, vapours. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

For containment	: Contain released product. Collect spillage.
Methods for cleaning up	: Mechanically recover the product. Notify authorities if product enters sewers or public waters.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe fume, spray, vapours. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: < 25 °C
Special rules on packaging	: Keep only in original container.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

toluene (108-88-3)	
Australia - Occupational Exposure Limits	
Local name	Toluene

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

toluene (108-88-3)	
OES TWA [1]	191 mg/m <sup>3</sup>
OES TWA [2]	50 ppm
OES STEL	574 mg/m <sup>3</sup>
OES STEL [ppm]	150 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
New Zealand - Occupational Exposure Limits	
Local name	Toluene (Toluol)
WES-TWA (OEL TWA) [1]	188 mg/m <sup>3</sup>
WES-TWA (OEL TWA) [2]	50 ppm
Remark (NZ)	skin (Skin absorption)
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
New Zealand - Biological Exposure Indices	
Local name	Toluene
BEI	0.03 mg/l Parameter: Toluene - Medium: Urine - Sampling time: End of exposure or end of shift 0.3 mg/g creatinine Parameter: o-Cresol (following hydrolysis) - Medium: Urine - Sampling time: End of exposure or end of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Gloves. Protective clothing. Safety glasses.
Materials for protective clothing	: Impermeable clothing
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: aerosol.
Colour	: dark orange
Odour	: characteristic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Melting point / Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: 0.799 g/l
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 756 g/l
VOC content - Regulatory	: No data available
Gas group	: Press. Gas (Liq.)
Percent Solids	: 0 wt%

### SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### toluene (108-88-3)

LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	25.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	25.7 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE AU (oral)	5580 mg/kg bodyweight
ATE AU (vapours)	25.7 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.

#### toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure (inhalation).

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL	
Vaporizer	aerosol

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
BCF - Fish [1]	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)

### 12.2. Persistence and degradability

toluene (108-88-3)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.69

### 12.3. Bioaccumulative potential

toluene (108-88-3)	
BCF - Fish [1]	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 12.4. Mobility in soil

#### toluene (108-88-3)

Surface tension	27.73 N/m (25 °C)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

#### SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

Fluorinated greenhouse gases	False
------------------------------	-------

#### toluene (108-88-3)

Fluorinated greenhouse gases	False
------------------------------	-------

## SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

### 14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable

### 14.3. Transport hazard class(es)

#### ADG

Transport hazard class(es) (ADG) : 2.1  
Danger labels (ADG) : 2.1  
:



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1  
:



#### IATA

Transport hazard class(es) (IATA) : 2.1  
Danger labels (IATA) : 2.1

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations



### 14.4. Packing group

Packing group (ADG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable

### 14.5. Environmental hazards

Marine pollutant	: No
Dangerous for the environment	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

Specific storage requirement	: No data available
Shock sensitivity	: No data available

### 14.7. Additional information

Other information	: No supplementary information available
-------------------	--

#### Transport by road and rail

UN-No. (ADG)	: 1950
Special provision (ADG)	: 63, 190, 277, 327, 344
Limited quantities (ADG)	: See SP 277
Packing instructions (ADG)	: P207, LP02
Special packing provisions (ADG)	: PP87, L2

#### Transport by sea

UN-No. (IMDG)	: 1950
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None

#### Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code	: Not applicable
--------------	------------------

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available



# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515

Group standard : Aerosols

#### toluene (108-88-3)

### Hazardous Substances and New Organisms Act

HSNO Approval Number HSR001227

#### chlorobenzene (108-90-7)

### Hazardous Substances and New Organisms Act

HSNO Approval Number HSR001108

#### dimethyl ether (115-10-6)

### Hazardous Substances and New Organisms Act

HSNO Approval Number HSR000995

#### Xylene (1330-20-7)

### Hazardous Substances and New Organisms Act

HSNO Approval Number HSR000983

#### ethylbenzene (100-41-4)

### Hazardous Substances and New Organisms Act

HSNO Approval Number HSR001151

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Revision date : 20/12/2021

### Classification

Aerosol 1	H222;H229
Skin Irrit. 2	H315
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373

### Full text of H-statements

Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2

# SYSTEM 20 PLASTIC PRIMER ADHESION PROMOTER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Full text of H-statements	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).