



DRIVING SURFACE PERFECTION

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS Ref. (EU): S2021BL

Date of issue: 07/08/2019 Revision date: 07/08/2019 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : S2021 UHS HIGH BUILD PRIMER BLACK (5:1)  
 Product code : S2021B/1, S2021B/3, S2021B/5  
 Product group : 2K Primer

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Function or use category : Primer

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

U-POL LIMITED  
 Denington Road, Wellingborough  
 Northants. NN8 2QH - UK  
 T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours ( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225  
 Serious eye damage/eye irritation, Category 2 H319  
 Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411  
 Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Causes serious eye irritation.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

: Danger

Hazard statements (CLP) :

: H225 - Highly flammable liquid and vapour.  
 H319 - Causes serious eye irritation.  
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P264 - Wash hands thoroughly after handling.  
 P280 - Wear face protection, protective clothing, protective gloves.  
 P337+P313 - If eye irritation persists: Get medical advice/attention.  
 P391 - Collect spillage.  
 P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	10 - 20	Flam. Liq. 3, H226 STOT SE 3, H336
4-methylpentan-2-one; isobutyl methyl ketone	(CAS-No.) 108-10-1 (EC-No.) 203-550-1 (EC Index-No.) 606-004-00-4 (REACH-no) 01-2119473980-30	5 - 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335
xylene (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	5 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
trizinc bis(orthophosphate)	(CAS-No.) 7779-90-0 (EC-No.) 231-944-3 (EC Index-No.) 030-011-00-6 (REACH-no) 01-2119485044-40	3 - 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	1 - 2.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact : Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapours, spray, fume. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain released product. Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours, spray, fume. Avoid contact with skin and eyes.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.  
Storage temperature : < 25 °C  
Storage area : Keep container in a well-ventilated place.  
Special rules on packaging : Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### n-butyl acetate (123-86-4)

EU	Local name	n-butyl acetate
EU	IOELV TWA (mg/m <sup>3</sup> )	241 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	723 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	150 ppm
EU	Notes	(Year of adoption 2016)
EU	Regulatory reference	SCOEL Recommendations
Ireland	Local name	Butyl acetate
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	710 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	150 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	200 ppm
Ireland	Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
United Kingdom	Local name	Butyl acetate

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-butyl acetate (123-86-4)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	724 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	966 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	200 ppm
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland	Local name	Ethylbenzene
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	884 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	200 ppm
Ireland	Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
United Kingdom	Local name	Ethylbenzene
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	552 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	125 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)		
EU	Local name	4-Methylpentan-2-one
EU	IOELV TWA (mg/m <sup>3</sup> )	83 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	208 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	50 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland	Local name	Methyl isobutyl ketone (MIBK)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	83 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	20 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	208 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	50 ppm

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)		
Ireland	Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
United Kingdom	Local name	4-Methylpentan-2-one
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	208 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	416 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland	Local name	Xylene, mixed isomers
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Ireland	Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
United Kingdom	Local name	Xylene
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	441 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Materials for protective clothing:

Impermeable clothing

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Hand protection:

Protective gloves

### Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed

### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous. Liquid.
Colour	: Black.
Odour	: aromatic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 35 °C
Flash point	: 18 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.49 g/cm <sup>3</sup>
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Viscosity, kinematic	: 2684.564 mm <sup>2</sup> /s
Viscosity, dynamic	: 4000 (3500 - 4500) cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 453 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### ethyl 3-ethoxypropionate (763-69-9)

LD50 oral rat	5000 mg/kg (Rat, Oral)
LD50 dermal rabbit	4076 mg/kg (Rabbit, Dermal)
LC50 inhalation rat (ppm)	> 998 ppm (OECD Guideline 403 (Acute Inhalation Toxicity), non-GLP, 6h, rat, male)

#### trizinc bis(orthophosphate) (7779-90-0)

LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Experimental value, Oral)
LC50 inhalation rat (mg/l)	> 5.41 mg/l/4h (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Read-across, Inhalation (dust))

#### n-butyl acetate (123-86-4)

LD50 oral rat	10760 - 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male/female, Experimental value, Dermal)
LC50 inhalation rat (ppm)	390 ppm/4h
LC50 inhalation rat (Vapours - mg/l/4h)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

#### calcium isononanoate (53988-05-9)

LD50 oral rat	1160 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Read-across, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)

#### hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LD50 oral rat	> 5000 mg/kg (OECD Guideline 401 (Acute Oral Toxicity), rat, male/female)
LD50 dermal rabbit	> 5000 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), rat, male/female)
LC50 inhalation rat (mg/l)	> 5000 mg/m <sup>3</sup> (OECD Guideline 403 (Acute Inhalation Toxicity), 8h, rat, male, vapours)

#### dolomite (16389-88-1)

LD50 oral rat	> 2000 mg/kg (OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), rat, female, Experimental value)
---------------	---

#### magnesium carbonate (546-93-0)

LD50 oral rat	> 2000 mg/kg bodyweight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
---------------	--

#### barium sulfate (7727-43-7)

LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value, Oral)
---------------	---

#### carbon black (1333-86-4)

LD50 oral rat	> 8000 mg/kg (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit, Literature study, Dermal)
LC50 inhalation rat (mg/l)	> 4.6 mg/l air (4 h, Rat, Experimental value, Inhalation)

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>silicon dioxide, amorphous (7631-86-9)</b>	
LD50 oral rat	> 10000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Dermal)

<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
LD50 oral rat	2080 mg/kg (Equivalent or similar to OECD 401, Rat, Experimental value, Oral)
LD50 dermal rat	>= 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	8.2 - 16.4 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (vapours))

<b>dibutyltin dilaurate (77-58-7)</b>	
LD50 oral rat	2071 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal, 14 day(s))

<b>talca (14807-96-6)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 2.1 mg/l/4h (OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, experimental value)

<b>calcium carbonate (471-34-1)</b>	
LD50 oral rat	> 2000 mg/kg (OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), rat, female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), rat, male/female, Experimental value)
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 3 mg/l/4h (4 h, OECD Guidelines 403 (Acute Toxicity Inhalation), rat, male/female, Experimental value)

<b>quartz (14808-60-7)</b>	
LD50 oral rat	> 500 mg/kg

<b>xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LC50 inhalation rat (ppm)	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)

<b>cellulose acetate butyrate (9004-36-8)</b>	
LD50 oral rat	> 3200 mg/kg
LD50 dermal	> 1000 mg/kg (Guinea pig)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.



# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

### ethylbenzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

### xylene (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

### S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

Viscosity, kinematic	2684.564 mm <sup>2</sup> /s
----------------------	-----------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.

### trizinc bis(orthophosphate) (7779-90-0)

LC50 fish 1	0.169 mg/l (ASTM E729-88, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Read-across, Nominal concentration)
-------------	--

### n-butyl acetate (123-86-4)

LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
LC50 fish 2	62 mg/l (Leuciscus idus, static system)
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)
EC50 72h algae (1)	674.7 mg/l (Desmodesmus subspicatus, Static system, Fresh water, Experimental value)
NOEC chronic crustacea	23 mg/l

### ethylbenzene (100-41-4)

LC50 fish 1	4.2 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Salmo gairdneri, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	2.1 (1.8 - 2.4) mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h algae (1)	5.4 mg/l (US EPA, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Cell numbers)

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

LC50 fish 1	600 mg/l (96 h, Salmo gairdneri, Fresh water, Literature study)
LC50 fish 2	> 179 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	> 200 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 96h algae (1)	400 mg/l (Selenastrum capricornutum, Literature study, Growth rate)

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>xylene (1330-20-7)</b>	
LC50 fish 1	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)
EC50 72h algae (1)	2.2 mg/l
ErC50 (algae)	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

### 12.2. Persistence and degradability

<b>trizinc bis(orthophosphate) (7779-90-0)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### **n-butyl acetate (123-86-4)**

Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

### **ethylbenzene (100-41-4)**

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance

### **4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)**

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.06 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.16 g O <sub>2</sub> /g substance
ThOD	2.72 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.76

### **xylene (1330-20-7)**

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
-------------------------------	--

### 12.3. Bioaccumulative potential

<b>trizinc bis(orthophosphate) (7779-90-0)</b>	
BCF other aquatic organisms 1	116 - 60960 (21 day(s), Gammarus sp., Semi-static system, Salt water, Read-across, Fresh weight)
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).

### **n-butyl acetate (123-86-4)**

BCF fish 1	15.3 (Calculated value)
Log Pow	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### **ethylbenzene (100-41-4)**

BCF fish 1	1 - 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
------------	---

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Log Pow	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

BCF fish 1	2 - 5 (Pisces, Estimated value)
Log Pow	1.9 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### xylene (1330-20-7)

BCF fish 1	7.2 - 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Log Pow	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

#### trizinc bis(orthophosphate) (7779-90-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

### n-butyl acetate (123-86-4)

Surface tension	0.0163 N/m (20 °C)
Log Koc	1.268 - 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

### ethylbenzene (100-41-4)

Surface tension	0.071 N/m (23 °C, 0.0582 g/l, EU Method A.5: Surface tension)
Log Koc	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

Surface tension	0.024 N/m (20 °C)
Log Koc	2.008 (log Koc, Weight of evidence, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

### xylene (1330-20-7)

Surface tension	28.01 - 29.76 mN/m (25 °C)
Log Koc	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

### 12.5. Results of PBT and vPvB assessment

#### Component

ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
trizinc bis(orthophosphate) (7779-90-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.6. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1263	1263	1263	1263	1263
<b>14.2. UN proper shipping name</b>				
PAINT	PAINT	Paint	PAINT	PAINT
<b>Transport document description</b>				
UN 1263 PAINT, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640D, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Orange plates



Tunnel restriction code (ADR)

: D/E

EAC code

: •3YE

### Transport by sea

Special provisions (IMDG)

: 163, 367

Limited quantities (IMDG)

: 5 L

Excepted quantities (IMDG)

: E2

Packing instructions (IMDG)

: P001

Special packing provisions (IMDG)

: PP1

IBC packing instructions (IMDG)

: IBC02

Tank instructions (IMDG)

: T4

Tank special provisions (IMDG)

: TP1, TP8, TP28

EmS-No. (Fire)

: F-E

EmS-No. (Spillage)

: S-E

Stowage category (IMDG)

: B

Properties and observations (IMDG)

: Miscibility with water depends upon the composition.

### Air transport

PCA Excepted quantities (IATA)

: E2

PCA Limited quantities (IATA)

: Y341

PCA limited quantity max net quantity (IATA)

: 1L

PCA packing instructions (IATA)

: 353

PCA max net quantity (IATA)

: 5L

CAO packing instructions (IATA)

: 364

CAO max net quantity (IATA)

: 60L

Special provisions (IATA)

: A3, A72, A192

ERG code (IATA)

: 3L

### Inland waterway transport

Classification code (ADN)

: F1

Special provisions (ADN)

: 163, 367, 640D, 650

Limited quantities (ADN)

: 5 L

Excepted quantities (ADN)

: E2

Equipment required (ADN)

: PP, EX, A

Ventilation (ADN)

: VE01

Number of blue cones/lights (ADN)

: 1

### Rail transport

Classification code (RID)

: F1

Special provisions (RID)

: 163, 367, 640D, 650

Limited quantities (RID)

: 5L

Excepted quantities (RID)

: E2

Packing instructions (RID)

: P001, IBC02, R001

Special packing provisions (RID)

: PP1

Mixed packing provisions (RID)

: MP19

Portable tank and bulk container instructions (RID)

: T4

Portable tank and bulk container special provisions (RID)

: TP1, TP8, TP28

Tank codes for RID tanks (RID)

: LGBF

Transport category (RID)

: 2

Colis express (express parcels) (RID)

: CE7

Hazard identification number (RID)

: 33

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	S2021 UHS HIGH BUILD PRIMER BLACK (5:1) ; ethylbenzene ; xylene, mixture of isomers ; isobutyl methyl ketone ; n-butyl acetate
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	S2021 UHS HIGH BUILD PRIMER BLACK (5:1) ; ethylbenzene ; xylene, mixture of isomers ; isobutyl methyl ketone ; n-butyl acetate
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	S2021 UHS HIGH BUILD PRIMER BLACK (5:1)
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	S2021 UHS HIGH BUILD PRIMER BLACK (5:1) ; ethylbenzene ; xylene, mixture of isomers ; isobutyl methyl ketone ; n-butyl acetate

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 453 g/l

Directive 2012/18/EU (SEVESO III)

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

# S2021 UHS HIGH BUILD PRIMER BLACK (5:1)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II) U-POL

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).*