



S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

DRIVING SURFACE PERFECTION

Date of issue:20/01/2017

Revision date:07/08/2019

Supersedes: 09/07/2019

Version: 3.1

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture
Trade name : S2025 HIGH BUILD PRIMER GREY (4:1)
Product code : S2025/1, S2025/4

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Primer

1.4. Supplier's details

Supplier

U-POL AUSTRALIA PTY LIMITED
Unit A, 16 - 20 Cassola Place
Penrith, NSW 2750 - Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.co.nz - www.u-pol.com.au

Supplier

U-POL NEW ZEALAND LIMITED
c/o Lindsay & Associates
Unit H, 12 Amera Place, East Tamaki
Manukau City 2013 - New Zealand
T + 612 4731 2655 - F + 612 4731 2611
technicalsupport@u-pol.com - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2A H319

2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Warning
Contains : xylene (5 - 23 %); reaction mass of ethylbenzene, m-xylene and p-xylene (< 5 %)
Hazard statements (GHS AU) : H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P264 - Wash hands thoroughly after handling.
P280 - Wear face protection, protective clothing, protective gloves.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
Unknown acute toxicity (GHS AU) : 4.34% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
xylene ()	1330-20-7	5 - 23	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
reaction mass of ethylbenzene, m-xylene and p-xylene ()		< 5	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)		95.07 - 97.04	

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

- Symptoms/effects after skin contact : Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Hazchem Code : 3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Protective clothing. Safety glasses. Gloves.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

- Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released product. Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Storage temperature : < 25 °C
- Storage area : Store in well ventilated area.
- Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

xylene (1330-20-7)		
New Zealand	Local name	Xylene (Dimethylbenzene)
New Zealand	TWA (mg/m ³)	217 mg/m ³
New Zealand	TWA (ppm)	50 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 8th Edition

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

- Personal protective equipment : Gas mask. Gloves. Protective clothing. Safety glasses.
- Materials for protective clothing : Impermeable clothing
- Hand protection : Protective gloves
- Eye protection : Safety glasses
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : Air-fed respiratory protective equipment should be worn when this product is sprayed
- Personal protective equipment symbol(s)



- Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

- Physical state : Liquid
- Appearance : Viscous. Liquid.
- Colour : No data available
- Odour : No data available
- Odour threshold : No data available

S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point : Not applicable
Boiling point	: No data available
Flash point	: 28 °C
Auto-ignition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density : 1.69 (1.67 - 1.71) g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Viscosity, kinematic	: 4142.012 mm ² /s
Viscosity, dynamic	: 7000 (6500 - 7500) cP
Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content - Regulatory	: No data available
Percent Solids	: 76.23 wt%

SECTION 10: Stability and reactivity

Reactivity	: Flammable liquid and vapour. Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

reaction mass of ethylbenzene, m-xylene and p-xylene

LD50 oral rat	3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral), rat, male)
LD50 dermal rabbit	12126 mg/kg (Weight of evidence, New Zealand White)
LC50 inhalation rat (ppm)	6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours)

xylene (1330-20-7)

LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LC50 inhalation rat (ppm)	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)

Unknown acute toxicity (GHS AU)	: 4.34% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

reaction mass of ethylbenzene, m-xylene and p-xylene

NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day (OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female)
----------------------------	--

S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Aspiration hazard : Not classified.

S2025 HIGH BUILD PRIMER GREY (4:1)

Viscosity, kinematic	4142.012 mm ² /s
----------------------	-----------------------------

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

reaction mass of ethylbenzene, m-xylene and p-xylene

LC50 fish 1	3300 - 4093 µg/l
-------------	------------------

EC50 Daphnia 1	2930 - 4000 µg/l
----------------	------------------

xylene (1330-20-7)

LC50 fish 1	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)
-------------	---

ErC50 (algae)	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
---------------	--

BCF fish 1	7.2 - 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
------------	--

Log Pow	3.2 (Read-across, 20 °C)
---------	--------------------------

Log Koc	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
---------	--

12.2. Persistence and degradability

xylene (1330-20-7)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
-------------------------------	--

12.3. Bioaccumulative potential

xylene (1330-20-7)

BCF fish 1	See section 12.1 on ecotoxicology
------------	-----------------------------------

Log Pow	See section 12.1 on ecotoxicology
---------	-----------------------------------

Log Koc	See section 12.1 on ecotoxicology
---------	-----------------------------------

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

12.4. Mobility in soil

xylene (1330-20-7)

Surface tension	28.01 - 29.76 mN/m (25 °C)
-----------------	----------------------------

Log Pow	See section 12.1 on ecotoxicology
---------	-----------------------------------

Log Koc	See section 12.1 on ecotoxicology
---------	-----------------------------------

Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
----------------	---

12.5. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available

S2025 HIGH BUILD PRIMER GREY (4:1)

Fluorinated greenhouse gases	False
------------------------------	-------

reaction mass of ethylbenzene, m-xylene and p-xylene

Fluorinated greenhouse gases	False
------------------------------	-------

xylene (1330-20-7)

Fluorinated greenhouse gases	False
------------------------------	-------

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1263
UN-No. (IMDG) : 1263
UN-No. (IATA) : 1263

14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : PAINT
Proper Shipping Name (IMDG) : PAINT
Proper Shipping Name (IATA) : Paint

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 3
Danger labels (ADG) : 3
:



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3
:



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3
:



14.4. Packing group

Packing group (ADG) : III
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1263
Special provision (ADG) : 163, 223
Limited quantities (ADG) : 5l
Packing instructions (ADG) : P001, IBC03, LP01
Special packing provisions (ADG) : PP1

S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Portable tank and bulk container instructions (ADG) : T2
Portable tank and bulk container special provisions (ADG) : TP1, TP29

Transport by sea

UN-No. (IMDG) : 1263
Special provisions (IMDG) : 163, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8, TP28
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : B
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

UN-No. (IATA) : 1263
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002662
Group standard : Surface coatings and colourants

ethylbenzene (100-41-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001151

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 07/08/2019

Classification:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2A	H319

Full text of H-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5

S2025 HIGH BUILD PRIMER GREY (4:1)

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

SDS Australia U-POL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.