



DRIVING SURFACE PERFECTION

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
 SDS Ref. (EU): S2045-SDS  
 Issue date: 2/25/2015 Revision date: 8/28/2020 Supersedes version of: 8/2/2019 Version: 5.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : SYSTEM 20 STANDARD UNIVERSAL THINNER  
 UFI : VYV0-A0PW-Q006-Q47R  
 Product code : S2045/1, S2045/5  
 Product group : Thinners

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
 Use of the substance/mixture : Coatings and paints, thinners, paint removers  
 Function or use category : Thinner

##### 1.2.2. Uses advised against

Restrictions on use : Consumer uses: Private households (= general public = consumers)

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

U-POL Limited  
 Denington Road  
 NN8 2QH Wellingborough - United Kingdom  
 T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### Importer

U-POL Netherlands B.V.  
 Hoogoorddreef 15  
 1101BA Amsterdam - Netherlands  
 T +31 20 240 2216  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours ( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225  
 Skin corrosion/irritation, Category 2 H315  
 Serious eye damage/eye irritation, Category 2 H319  
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335  
 Specific target organ toxicity — Repeated exposure, Category 2 H373

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Aspiration hazard, Category 1 H304  
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412  
Full text of H-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Danger  
Contains : Xylene; Ethylbenzene; solvent naphtha (petroleum), light aromatic; n-butyl acetate  
Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P261 - Avoid breathing vapours, spray, fume.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear face protection, protective clothing, protective gloves.  
P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting.  
P337+P313 - If eye irritation persists: Get medical advice/attention.

## 2.3. Other hazards

Component	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336
Xylene substance with a Community workplace exposure limit (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	25 – 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 (REACH-no) 01-2119475791-29	5 – 20	Flam. Liq. 3, H226
solvent naphtha (petroleum), light aromatic (Note H)(Note 5)(Note P)	(CAS-No.) 64742-95-6 (EC-No.) 265-199-0 (EC Index-No.) 649-356-00-4 (REACH-no) 01-2119455851-35	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Ethylbenzene substance with a Community workplace exposure limit	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	10 – 20	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Note 5 : The concentration limits for gaseous mixtures are expressed as volume per volume percentage.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note H : The classification and labelling shown for this substance applies to the hazardous property(ies) indicated by the hazard statement(s) in combination with the hazard class(es) and category(ies) shown. The requirements of Article 4 for manufacturers, importers or downstream users of this substance apply to all other hazard classes and categories. For hazard classes where the route of exposure or the nature of the effects leads to a differentiation of the classification of the hazard class, the manufacturer, importer or downstream user is required to consider the routes of exposure or the nature of the effects not already considered.

Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapours, spray, fume. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe vapours, spray, fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup> 723 mg/m <sup>3</sup>
IOEL STEL [ppm]	150 ppm 150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831 COMMISSION DIRECTIVE (EU) 2019/1831
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Butyl acetate
OEL TWA [1]	710 mg/m <sup>3</sup>
OEL TWA [2]	150 ppm
OEL STEL	950 mg/m <sup>3</sup>
OEL STEL [ppm]	200 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

#### 2-methoxy-1-methylethyl acetate (108-65-6)

EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
IOEL STEL	550 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Notes	Skin Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	2-Methoxy-1-methylethylacetate
OEL TWA [1]	275 mg/m <sup>3</sup>
OEL TWA [2]	50 ppm
OEL STEL	550 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Xylene (1330-20-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Notes	Skin Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Xylene, mixed isomers
OEL TWA [1]	221 mg/m <sup>3</sup>
OEL TWA [2]	50 ppm
OEL STEL	442 mg/m <sup>3</sup>

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Xylene (1330-20-7)</b>	
OEL STEL [ppm]	100 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Xylene
BLV	1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	441 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Ethylbenzene (100-41-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Ethylbenzene
IOEL TWA	442 mg/m <sup>3</sup>
IOEL TWA [ppm]	100 ppm
IOEL STEL	884 mg/m <sup>3</sup>
IOEL STEL [ppm]	200 ppm
Notes	Skin Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Ethylbenzene
OEL TWA [1]	442 mg/m <sup>3</sup>
OEL TWA [2]	100 ppm
OEL STEL	884 mg/m <sup>3</sup>
OEL STEL [ppm]	200 ppm

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Ethylbenzene (100-41-4)</b>	
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Ethyl benzene
BLV	0.7 g/g creatinine Parameter: mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift at end of workweek - Notations: Ns (Non-specific), Sq (Semi-quantitative) Parameter: ethylbenzene - Medium: end-exhaled air - Sampling time: Not critical - Notations: Sq (Semi-quantitative)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethylbenzene
WEL TWA (OEL TWA) [1]	441 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	552 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	125 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>n-butyl acetate (123-86-4)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	11 mg/kg bw/day
Acute - systemic effects, inhalation	600 mg/m <sup>3</sup>
Acute - local effects, inhalation	600 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m <sup>3</sup>
Long-term - local effects, inhalation	300 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	6 mg/kg bw/day
Acute - systemic effects, inhalation	300 mg/m <sup>3</sup>
Acute - systemic effects, oral	2 mg/kg bw/day
Acute - local effects, inhalation	300 mg/m <sup>3</sup>
Long-term - systemic effects, oral	2 mg/kg bw/day
Long-term - systemic effects, inhalation	35.7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	6 mg/kg bw/day



# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Long-term - local effects, inhalation	35.7 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.0903 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	35.6 mg/l

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	550 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.635 mg/l
PNEC aqua (marine water)	0.0635 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3.29 mg/kg dwt
PNEC sediment (marine water)	0.329 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.29 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l

<b>Xylene (1330-20-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	289 mg/m <sup>3</sup>
Acute - local effects, inhalation	289 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m <sup>3</sup>
Long-term - local effects, inhalation	77 mg/m <sup>3</sup>

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	174 mg/m <sup>3</sup>
Acute - local effects, inhalation	174 mg/m <sup>3</sup>
Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.8 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day
Long-term - local effects, inhalation	65.3 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12.46 mg/kg dwt
PNEC sediment (marine water)	12.46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2.31 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6.58 mg/l

### solvent naphtha (petroleum), light aromatic (64742-95-6)

#### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	150 mg/m <sup>3</sup>

#### DNEL/DMEL (General population)

Long-term - systemic effects, oral	11 mg/kg bodyweight/day
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day

### Ethylbenzene (100-41-4)

#### DNEL/DMEL (Workers)

Acute - local effects, inhalation	293 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m <sup>3</sup>

#### DNEL/DMEL (General population)

Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	15 mg/m <sup>3</sup>

#### PNEC (Water)

PNEC aqua (freshwater)	0.1 mg/l
PNEC aqua (marine water)	0.01 mg/l
PNEC aqua (intermittent, freshwater)	0.1 mg/l

#### PNEC (Sediment)

PNEC sediment (freshwater)	13.7 mg/kg dwt
PNEC sediment (marine water)	1.37 mg/kg dwt

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC (Soil)	
PNEC soil	2.68 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.02 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	9.6 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

#### 8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

#### 8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Liquid.
Odour	: Solvent-like odour.

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: > 114 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: < 23 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: ≈ 1 mm <sup>2</sup> /s
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0.886 g/l
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

VOC content : 886 g/l

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 886 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 oral rat	6190 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	1728 ppm/4h (4 h, OECD Guideline 403 (Acute Inhalation Toxicity), rat, male/female, Inhalation, vapours)

<b>Xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)

<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg (OECD Test Guideline 402)
LC50 Inhalation - Rat (Vapours)	> 6.193 mg/l/4h (4 h, OECD Test Guideline 403, vapours)

<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Xylene (1330-20-7)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

2-methoxypropyl acetate (70657-70-4)	
STOT-single exposure	May cause respiratory irritation.

Xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.

solvent naphtha (petroleum), light aromatic (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing sense) through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

SYSTEM 20 STANDARD UNIVERSAL THINNER	
Viscosity, kinematic	≈ 1 mm <sup>2</sup> /s

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

#### n-butyl acetate (123-86-4)

LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

#### 2-methoxy-1-methylethyl acetate (108-65-6)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

#### Xylene (1330-20-7)

LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	2.2 mg/l
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

#### Ethylbenzene (100-41-4)

LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

### 12.2. Persistence and degradability

#### n-butyl acetate (123-86-4)

Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

#### 2-methoxy-1-methylethyl acetate (108-65-6)

Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
-------------------------------	--

#### Xylene (1330-20-7)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
-------------------------------	--

#### solvent naphtha (petroleum), light aromatic (64742-95-6)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

#### Ethylbenzene (100-41-4)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

#### n-butyl acetate (123-86-4)

BCF - Fish [1]	15.3 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

#### 2-methoxy-1-methylethyl acetate (108-65-6)

Partition coefficient n-octanol/water (Log Pow)	1.2 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### Xylene (1330-20-7)

BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).



# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6
Bioaccumulative potential	Not established.

Ethylbenzene (100-41-4)	
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

n-butyl acetate (123-86-4)	
Surface tension	0.0163 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

2-methoxy-1-methylethyl acetate (108-65-6)	
Surface tension	29.4 mN/m (20 °C, 100 vol %, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	0.264 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.

Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

Ethylbenzene (100-41-4)	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.

### 12.5. Results of PBT and vPvB assessment

Component	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Endocrine disrupting properties

No additional information available

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number or ID number

UN-No. (ADR) : UN 1263  
UN-No. (IMDG) : UN 1263  
UN-No. (IATA) : UN 1263  
UN-No. (ADN) : UN 1263  
UN-No. (RID) : UN 1263

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : PAINT RELATED MATERIAL  
Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL  
Proper Shipping Name (IATA) : Paint  
Proper Shipping Name (ADN) : PAINT RELATED MATERIAL  
Proper Shipping Name (RID) : PAINT RELATED MATERIAL  
Transport document description (ADR) : UN 1263 PAINT RELATED MATERIAL, 3, II, (D/E)  
Transport document description (IMDG) : UN 1263 PAINT RELATED MATERIAL, 3, II  
Transport document description (IATA) : UN 1263 Paint, 3, II  
Transport document description (ADN) : UN 1263 PAINT RELATED MATERIAL, 3, II  
Transport document description (RID) : UN 1263 PAINT RELATED MATERIAL, 3, II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Danger labels (IATA) : 3

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



### ADN

Transport hazard class(es) (ADN) : 3  
Danger labels (ADN) : 3



### RID

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3



## 14.4. Packing group

Packing group (ADR) : II  
Packing group (IMDG) : II  
Packing group (IATA) : II  
Packing group (ADN) : II  
Packing group (RID) : II

## 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

## 14.6. Special precautions for user

### Overland transport

Classification code (ADR) : F1  
Special provisions (ADR) : 163, 367, 640D, 650  
Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E2  
Packing instructions (ADR) : P001, IBC02, R001  
Special packing provisions (ADR) : PP1  
Mixed packing provisions (ADR) : MP19  
Portable tank and bulk container instructions (ADR) : T4  
Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28  
Tank code (ADR) : LGBF  
Vehicle for tank carriage : FL  
Transport category (ADR) : 2  
Special provisions for carriage - Operation (ADR) : S2, S20  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

### Transport by sea

Special provisions (IMDG) : 163, 367

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640D, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 640D, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
----------------	---------------	----------------------------

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3(a)	SYSTEM 20 STANDARD UNIVERSAL THINNER ; Xylene ; Ethylbenzene ; 2-methoxy-1-methylethyl acetate ; solvent naphtha (petroleum), light aromatic ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	SYSTEM 20 STANDARD UNIVERSAL THINNER ; Xylene ; Ethylbenzene ; solvent naphtha (petroleum), light aromatic ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	SYSTEM 20 STANDARD UNIVERSAL THINNER ; solvent naphtha (petroleum), light aromatic	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	SYSTEM 20 STANDARD UNIVERSAL THINNER ; Xylene ; Ethylbenzene ; 2-methoxy-1-methylethyl acetate ; solvent naphtha (petroleum), light aromatic ; n-butyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains organic solvents ( $\geq 1\%$ )

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 886 g/l

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# SYSTEM 20 STANDARD UNIVERSAL THINNER

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

---

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).