



DRIVING SURFACE PERFECTION

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
SDS ID: SMCB-US-SDS
Issue date: 8/17/2015 Revision date: 11/17/2022 Supersedes: 2/14/2020 Version: 4.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : SMC CARBON FIBRE REINFORCED FILLER - BLACK
Product code : SMCB/2
UP Number : UP0777

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Fillers, putties, plasters, modeling clay
Recommended use : Fillers

1.3. Supplier

U-POL US Inc Inc.
50 Applied Bank Blvd., Suite 300 Glen Mills
Pennsylvania, PA 19342
United States
T (610) 746 7081
technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

SECTION 2: Hazard(s) identification


2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Carcinogenicity Category 2	Suspected of causing cancer
Reproductive toxicity Category 2	Suspected of damaging the unborn child
Specific target organ toxicity (repeated exposure) Category 1	Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) : 

Signal word (GHS US) : Danger

Hazard statements (GHS US) : Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
Suspected of damaging the unborn child
Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS US) : Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Do not breathe fume, vapors.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear eye protection, protective clothing, protective gloves.
If on skin: Wash with plenty of water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
talc	CAS-No.: 14807-96-6	23 – 43	Carc. 2, H351
styrene	CAS-No.: 100-42-5	5 – 23	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 Repr. 2, H361 STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
carbon black	CAS-No.: 1333-86-4	< 5	Carc. 2, H351

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.
Emergency procedures : Ventilate spillage area. Do not breathe vapors, spray, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Collect spillage.
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapors, spray, fume. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature	: < 25 °C
Storage area	: Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SMC CARBON FIBRE REINFORCED FILLER - BLACK

No additional information available

talC (14807-96-6)

USA - ACGIH - Occupational Exposure Limits

Local name	Talc
ACGIH OEL TWA	2 mg/m ³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica)
ACGIH OEL TWA [ppm]	0.1 fibers/cm ³ (Containing asbestos fibers. F - Respirable fibers)
Remark (ACGIH)	Containing no asbestos fibers = TLV® Basis: Pulm fibrosis; pulm func. Notations: A4 Containing asbestos fibers = TLV® Basis: Pneumoconiosis; lung cancer; mesothelioma. Notations: A1 (Confirmed Human Carcinogen)
Regulatory reference	ACGIH 2021

USA - OSHA - Occupational Exposure Limits

Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))
OSHA PEL (TWA) [2]	20 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

carbon black (1333-86-4)

USA - ACGIH - Occupational Exposure Limits

Local name	Carbon black
ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2021

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)	
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon black
OSHA PEL (TWA) [1]	3.5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
styrene (100-42-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Styrene
ACGIH OEL TWA [ppm]	10 ppm
ACGIH OEL STEL [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: CNS & hearing impair; URT irr; peripheral neuropathy; visual disorders. Notations: OTO; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	STYRENE
BEI (BLV)	400 mg/g Kreatinin Parameter: Mandelic acid plus phenylglyoxylic acid - Medium: urine - Sampling time: End of shift - Notations: Ns 40 µg/l Parameter: Styrene - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Styrene
OSHA PEL (TWA) [2]	100 ppm
OSHA PEL C [ppm]	200 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	600 ppm 5 mins. in any 3 hrs.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Materials for protective clothing:

Impermeable clothing

Hand protection:

Protective gloves

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Type	Material	Permeation	Thickness (mm)	Penetration
Protective gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR), Polyvinylalcohol (PVA), Viton	6 (> 480 minutes)	0.4	

Eye protection:

Safety glasses

Type	Field of application	Characteristics
Safety glasses	Dust	clear

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Device	Filter type	Condition
Breathing apparatus, Gas filters	Type A - High-boiling (>65 °C) organic compounds	vapor protection

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Fibrous. Paste.
Color	: Black
Odor	: aromatic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: 32 °C (does not sustain combustion)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.66 (1.64 – 1.68) g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: No data available

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content	: 187 g/l
As Packaged Regulatory VOC	: 187 g/l (1.5 lb/gal)
As Packaged Actual VOC	: 187 g/l (1.5 lb/gal)
As Applied Regulatory VOC	: 39 g/l (0.32 lb/gal)
As Applied Actual VOC	: 39 g/l (0.32 lb/gal)
Percent Solids	: 89.43 wt%
Percent Solids	: 48.74 vol %
Volatiles	: 10.6 wt%
Water Content	: 0 wt%
Water Content	: 0 vol %
Exempt Compounds by weight	: 0 wt%
Exempt Compounds by volume	: 0 vol %
% EPA HAPS	: 10.08 wt%

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

talC (14807-96-6)

LD50 oral rat	> 5000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

talca (14807-96-6)	
LC50 Inhalation - Rat	> 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))
carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))
styrene (100-42-5)	
LD50 oral rat	5000 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	11.8 mg/l (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours))
ATE US (oral)	5000 mg/kg body weight
ATE US (vapors)	11.8 mg/l/4h
ATE US (dust, mist)	11.8 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
talca (14807-96-6)	
IARC group	3 - Not classifiable, 2B - Possibly carcinogenic to humans
carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
styrene (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified
styrene (100-42-5)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation).
styrene (100-42-5)	
LOAEL (oral,rat,90 days)	2000 mg/kg body weight Animal: rat
LOAEC (inhalation,rat,vapor,90 days)	0.21 mg/l air Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat
NOAEL (subchronic,oral,animal/male,90 days)	10 mg/kg body weight Animal: mouse, Animal sex: male
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: > 20.5 mm ² /s

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

talca (14807-96-6)	
LC50 - Fish [1]	89581 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)
carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
styrene (100-42-5)	
LC50 - Fish [1]	10 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	4.7 mg/l Test organisms (species): Daphnia magna
ErC50 algae	4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
LOEC (chronic)	2.06 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	1.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

talca (14807-96-6)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
styrene (100-42-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Chemical oxygen demand (COD)	2.8 g O ₂ /g substance
ThOD	3.07 g O ₂ /g substance
BOD (% of ThOD)	0.42 (Literature study)

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

talc (14807-96-6)	
BCF - Other aquatic organisms [1]	3.162 l/kg (BCFBAF v3.01, Fresh water, QSAR)
Partition coefficient n-octanol/water (Log Pow)	-9.4 (QSAR, KOWWIN, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.
styrene (100-42-5)	
BCF - Fish [1]	74 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.96 (Practical experience/observation, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

talc (14807-96-6)	
Ecology - soil	Adsorbs into the soil.
carbon black (1333-86-4)	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.
styrene (100-42-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.55 (log Koc, Estimated value)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

TDG
Transport hazard class(es) (TDG) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT
No data available

TDG
No data available

IMDG
No data available

IATA
No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
talc	14807-96-6	Present	Active	
carbon black	1333-86-4	Present	Active	
styrene	100-42-5	Present	Active	

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
styrene	CAS-No. 100-42-5	5 – 23%

styrene (100-42-5)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb

15.2. International regulations

CANADA

talc (14807-96-6)
Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)
Listed on the Canadian DSL (Domestic Substances List)

styrene (100-42-5)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations


No additional information available

National regulations

carbon black (1333-86-4)
Listed on IARC (International Agency for Research on Cancer) Listed on INSQ (Mexican National Inventory of Chemical Substances)

styrene (100-42-5)
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

 **WARNING:** This product can expose you to carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
styrene(100-42-5)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
tal(14807-96-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SMC CARBON FIBRE REINFORCED FILLER - BLACK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/17/2022

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.