



DRIVING SURFACE PERFECTION

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date: 4/05/2017 Revision date: 20/12/2021 Supersedes: 19/04/2021 Version: 4.0

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL  
Product code : SPOT/AL

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Primer

#### 1.4. Details of manufacturer or importer

##### Supplier

U-POL Australia Pty Limited Ltd  
Unit A, 16 - 20 Cassola Place  
Penrith NSW 2750  
Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.au](mailto:info@u-pol.co.au) - [www.u-pol.com](http://www.u-pol.com)

##### Supplier

U-POL New Zealand Limited Ltd  
c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki  
Manukau City Auckland 2013  
New Zealand  
T + 612 4731 2655 - F + 612 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

|  |           |
|--|-----------|
| Aerosol, Category 1  | H222;H229 |
| Serious eye damage/eye irritation, Category 2A                         | H319      |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis | H336      |

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger

Contains : acetone (30 – 60 %); hydrocarbons, C9, aromatics (< 10 %); ethyl methyl ketone (< 10 %); ethyl acetate (< 10 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing fume, spray, vapours.  
P264 - Wash hands thoroughly after handling.

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, face protection, protective gloves.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.  
Additional hazard statements (GHS AU) : AUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

| Name  | CAS-No.    | %       | Classification according to the model Work Health and Safety Regulations (WHS Regulations) |
|---|------------|---------|--|
| acetone   | 67-64-1    | 30 – 60 | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336                               |
| hydrocarbons, C9, aromatics   | 64742-95-6 | < 10    | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>STOT SE 3, H335<br>Asp. Tox. 1, H304              |
| ethyl methyl ketone   | 78-93-3    | < 10    | Flam. Liq. 2, H225<br>Acute Tox. 5 (Oral), H303<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336  |
| ethyl acetate   | 141-78-6   | < 10    | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336                               |
| Other substances (not contributing to the classification of this product) | -          | 60.32   | -  |

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

- For containment : Contain released product, collect/pump into suitable containers. Collect spillage.  
Methods for cleaning up : Mechanically recover the product.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Storage temperature : < 25 °C  
Special rules on packaging : Keep only in original container.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

#### acetone (67-64-1)

##### Australia - Occupational Exposure Limits

|             |            |
|-------------|------------|
| Local name  | Acetone    |
| OES TWA [1] | 1185 mg/m³ |
| OES TWA [2] | 500 ppm    |

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

|   |  |
|---|--|
| <b>acetone (67-64-1)</b>                          |  |
| OES STEL  | 2375 mg/m <sup>3</sup>   |
| OES STEL [ppm]                                    | 1000 ppm   |
| Regulatory reference                              | Workplace exposure standards for airborne contaminants (2019)              |
| <b>New Zealand - Occupational Exposure Limits</b> |  |
| Local name  | Acetone  |
| WES-TWA (OEL TWA) [1]                             | 1185 mg/m <sup>3</sup>   |
| WES-TWA (OEL TWA) [2]                             | 500 ppm  |
| WES-STEL (OEL STEL)                               | 2375 mg/m <sup>3</sup>   |
| WES-STEL (OEL STEL) [ppm]                         | 1000 ppm   |
| Regulatory reference                              | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>New Zealand - Biological Exposure Indices</b>  |  |
| Local name  | Acetone  |
| BEI   | 50 mg/l Parameter: Acetone - Medium: Urine - Sampling time: End of shift   |
| Regulatory reference                              | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>ethyl methyl ketone (78-93-3)</b>              |  |
| <b>Australia - Occupational Exposure Limits</b>   |  |
| Local name  | Methyl ethyl ketone (MEK; 2-Butanone)                                      |
| OES TWA [1]                                       | 445 mg/m <sup>3</sup>  |
| OES TWA [2]                                       | 150 ppm  |
| OES STEL  | 890 mg/m <sup>3</sup>  |
| OES STEL [ppm]                                    | 300 ppm  |
| Regulatory reference                              | Workplace exposure standards for airborne contaminants (2019)              |
| <b>New Zealand - Occupational Exposure Limits</b> |  |
| Local name  | Methyl ethyl ketone (MEK, 2-Butanone)                                      |
| WES-TWA (OEL TWA) [1]                             | 445 mg/m <sup>3</sup>  |
| WES-TWA (OEL TWA) [2]                             | 150 ppm  |
| WES-STEL (OEL STEL)                               | 890 mg/m <sup>3</sup>  |
| WES-STEL (OEL STEL) [ppm]                         | 300 ppm  |
| Regulatory reference                              | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>New Zealand - Biological Exposure Indices</b>  |  |
| Local name  | Methyl ethyl ketone (MEK)  |
| BEI   | 2 mg/l Parameter: MEK - Medium: Urine - Sampling time: End of shift        |
| Regulatory reference                              | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>ethyl acetate (141-78-6)</b>                   |  |
| <b>Australia - Occupational Exposure Limits</b>   |  |
| Local name  | Ethyl acetate (Acetic acid ethyl ester; Acetic ester)                      |
| OES TWA [1]                                       | 720 mg/m <sup>3</sup>  |
| OES TWA [2]                                       | 200 ppm  |
| OES STEL  | 1440 mg/m <sup>3</sup>   |

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

| ethyl acetate (141-78-6)                   |  |
|--|--|
| OES STEL [ppm]                             | 400 ppm  |
| Regulatory reference                       | Workplace exposure standards for airborne contaminants (2019)              |
| New Zealand - Occupational Exposure Limits |  |
| Local name                                 | Ethyl acetate  |
| WES-TWA (OEL TWA) [1]                      | 720 mg/m <sup>3</sup>  |
| WES-TWA (OEL TWA) [2]                      | 200 ppm  |
| Regulatory reference                       | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |

### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

|                                   |  |
|-----------------------------------|--|
| Personal protective equipment     | : Gloves. Protective clothing. Safety glasses.                             |
| Materials for protective clothing | : Impermeable clothing   |
| Hand protection                   | : Protective gloves  |
| Eye protection                    | : Safety glasses   |
| Skin and body protection          | : Wear suitable protective clothing  |
| Respiratory protection            | : In case of insufficient ventilation, wear suitable respiratory equipment |

#### Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

|   |   |
|---|---|
| Physical state                                  | : Liquid  |
| Appearance                                      | : aerosol.  |
| Colour  | : Grey  |
| Odour   | : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.<br>Mixture contains one or more component(s) which have the following odour:<br>Odourless Pleasant odour Aromatic odour Petroleum-like odour Sweet odour Peppermint odour Irritating/pungent odour Fruity odour Mild odour Ether-like odour Alcohol odour Acetone odour Commercial/unpurified substance: unpleasant odour |
| Odour threshold                                 | : No data available   |
| pH  | : No data available   |
| Relative evaporation rate (butylacetate=1)      | : No data available   |
| Melting point / Freezing point                  | : No data available   |
| Boiling point                                   | : No data available   |
| Flash point                                     | : No data available   |
| Auto-ignition temperature                       | : No data available   |
| Flammability (solid, gas)                       | : No data available   |
| Vapour pressure                                 | : No data available   |
| Relative density                                | : No data available   |
| Density   | : Density: 0.731 g/cm <sup>3</sup>  |
| Solubility                                      | : insoluble in water. soluble in most organic solvents.   |
| Partition coefficient n-octanol/water (Log Pow) | : No data available   |
| Explosive properties                            | : Pressurised container: May burst if heated.   |
| Explosive limits                                | : No data available   |

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

|                          |                     |
|--------------------------|---------------------|
| Minimum ignition energy  | : No data available |
| VOC content              | : 615 g/l           |
| VOC content - Regulatory | : No data available |
| Gas group                | : Press. Gas (Liq.) |
| Percent Solids           | : 13.62 wt%         |

### SECTION 10: Stability and reactivity

|                                    |  |
|------------------------------------|--|
| Reactivity                         | : Extremely flammable aerosol. Pressurised container: May burst if heated.                             |
| Chemical stability                 | : Stable under normal conditions.  |
| Possibility of hazardous reactions | : No dangerous reactions known under normal conditions of use.   |
| Conditions to avoid                | : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.      |
| Incompatible materials             | : No additional information available  |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

### SECTION 11: Toxicological information

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

#### acetone (67-64-1)

|                       |  |
|-----------------------|--|
| LD50 oral rat         | 5800 mg/kg bodyweight Animal: rat, Animal sex: female                                |
| LD50 dermal rabbit    | > 15800 mg/kg bodyweight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | 76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4                     |
| ATE AU (oral)         | 5800 mg/kg bodyweight  |

#### ethyl methyl ketone (78-93-3)

|                    |  |
|--------------------|--|
| LD50 oral rat      | 2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))          |
| ATE AU (oral)      | 2193 mg/kg bodyweight  |

#### ethyl acetate (141-78-6)

|                    |  |
|--------------------|--|
| LD50 oral rat      | 10200 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral, 14 day(s)) |
| LD50 oral          | 4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)                    |
| LD50 dermal rabbit | > 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male  |
| ATE AU (oral)      | 10200 mg/kg bodyweight   |

#### hydrocarbons, C9, aromatics (64742-95-6)

|                                 |  |
|---------------------------------|--|
| LD50 oral rat                   | 8400 ml/kg   |
| LD50 dermal rabbit              | 3160 mg/kg bodyweight (OECD Guideline 402 (Acute Dermal Toxicity), rat, male/female) |
| LC50 Inhalation - Rat [ppm]     | 3400 ppm/4h  |
| LC50 Inhalation - Rat (Vapours) | > 5 mg/l/4h  |

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Skin corrosion/irritation         | : Not classified                 |
| Serious eye damage/irritation     | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified                 |
| Germ cell mutagenicity            | : Not classified                 |

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

|                       |                                      |
|-----------------------|--------------------------------------|
| Carcinogenicity       | : Not classified                     |
| Reproductive toxicity | : Not classified                     |
| STOT-single exposure  | : May cause drowsiness or dizziness. |

|                          |                                    |
|--------------------------|------------------------------------|
| <b>acetone (67-64-1)</b> |                                    |
| STOT-single exposure     | May cause drowsiness or dizziness. |

|                                      |                                    |
|--------------------------------------|------------------------------------|
| <b>ethyl methyl ketone (78-93-3)</b> |                                    |
| STOT-single exposure                 | May cause drowsiness or dizziness. |

|                                 |                                    |
|---------------------------------|------------------------------------|
| <b>ethyl acetate (141-78-6)</b> |                                    |
| STOT-single exposure            | May cause drowsiness or dizziness. |

|   |  |
|---|--|
| <b>hydrocarbons, C9, aromatics (64742-95-6)</b> |  |
| STOT-single exposure                            | May cause drowsiness or dizziness. May cause respiratory irritation. |

STOT-repeated exposure : Not classified

|                                 |  |
|---------------------------------|--|
| <b>ethyl acetate (141-78-6)</b> |  |
| LOAEL (oral, rat, 90 days)      | 3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test) |
| NOAEL (oral, rat, 90 days)      | 900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)  |

|   |                              |
|---|------------------------------|
| <b>hydrocarbons, C9, aromatics (64742-95-6)</b> |                              |
| NOAEL (oral, rat, 90 days)                      | 600 mg/kg bodyweight/day     |
| NOAEC (inhalation, rat, vapour, 90 days)        | 900 – 1800 mg/m <sup>3</sup> |

Aspiration hazard : Not classified

|  |         |
|--|---------|
| <b>SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL</b> |         |
| Vaporizer                                    | aerosol |

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

|   |   |
|---|---|
| Ecology - general   | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute)  | : Not classified  |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified  |

|  |   |
|--|---|
| <b>acetone (67-64-1)</b>                                   |   |
| LC50 - Fish [1]  | 6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration) |
| LOEC (chronic)   | > 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'  |
| NOEC (chronic)   | ≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'  |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)  |

|                                      |   |
|--------------------------------------|---|
| <b>ethyl methyl ketone (78-93-3)</b> |   |
| LC50 - Fish [1]                      | 2993 mg/l Test organisms (species): Pimephales promelas |

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

| ethyl methyl ketone (78-93-3)                              |  |
|--|--|
| EC50 - Crustacea [1]                                       | 308 mg/l Test organisms (species): Daphnia magna   |
| ErC50 algae  | 1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate) |
| Partition coefficient n-octanol/water (Log Pow)            | 0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)   |

| ethyl acetate (141-78-6)                        |   |
|---|---|
| LC50 - Fish [1]                                 | 230 mg/l Test organisms (species): Pimephales promelas            |
| NOEC (chronic)                                  | 2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| BCF - Fish [1]                                  | 30 (3 day(s), Leuciscus idus, Static renewal, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | 0.68 (Experimental value, EPA OPPTS 830.7560, 25 °C)              |

| hydrocarbons, C9, aromatics (64742-95-6) |                                 |
|--|---------------------------------|
| LC50 - Fish [1]                          | 9.22 mg/l (Oncorhynchus mykiss) |
| EC50 - Crustacea [1]                     | 6.14 mg/l 48 h, Daphnia magna   |
| ErC50 algae                              | 2.9 mg/l                        |

### 12.2. Persistence and degradability

| acetone (67-64-1)               |  |
|---------------------------------|--|
| Persistence and degradability   | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.43 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 1.92 g O <sub>2</sub> /g substance   |
| ThOD                            | 2.2 g O <sub>2</sub> /g substance  |

| ethyl methyl ketone (78-93-3)   |  |
|---------------------------------|--|
| Persistence and degradability   | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 2.03 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 2.31 g O <sub>2</sub> /g substance   |
| ThOD                            | 2.44 g O <sub>2</sub> /g substance   |

| ethyl acetate (141-78-6)        |  |
|---------------------------------|--|
| Persistence and degradability   | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.293 g O <sub>2</sub> /g substance                        |
| Chemical oxygen demand (COD)    | 1.69 g O <sub>2</sub> /g substance                         |
| ThOD                            | 1.82 g O <sub>2</sub> /g substance                         |

| hydrocarbons, C9, aromatics (64742-95-6) |                                 |
|--|---------------------------------|
| Persistence and degradability            | Readily biodegradable in water. |

### 12.3. Bioaccumulative potential

| acetone (67-64-1)                               |                   |
|---|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | -0.23 (Test data) |



# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

| acetone (67-64-1)  |   |
|--|---|
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)                                    |
| Bioaccumulative potential                                  | Not bioaccumulative.  |
| ethyl methyl ketone (78-93-3)                              |   |
| Partition coefficient n-octanol/water (Log Pow)            | 0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)                                    |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (Log Kow < 4).  |
| ethyl acetate (141-78-6)                                   |   |
| BCF - Fish [1]   | 30 (3 day(s), Leuciscus idus, Static renewal, Experimental value)                               |
| Partition coefficient n-octanol/water (Log Pow)            | 0.68 (Experimental value, EPA OPPTS 830.7560, 25 °C)  |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (BCF < 500).  |

### 12.4. Mobility in soil

| acetone (67-64-1)  |   |
|--|---|
| Surface tension  | 23300 mN/m (20 °C)  |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)   |
| Ecology - soil   | Highly mobile in soil.  |
| ethyl methyl ketone (78-93-3)                              |   |
| Surface tension  | No data available in the literature   |
| Partition coefficient n-octanol/water (Log Pow)            | 0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)   |
| Ecology - soil   | Highly mobile in soil. Slightly harmful to plants.  |
| ethyl acetate (141-78-6)                                   |   |
| Surface tension  | No data available in the literature   |
| Partition coefficient n-octanol/water (Log Pow)            | 0.68 (Experimental value, EPA OPPTS 830.7560, 25 °C)  |
| Ecology - soil   | Low potential for adsorption in soil.   |

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

| SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL |       |
|---------------------------------------|-------|
| Fluorinated greenhouse gases          | False |
| acetone (67-64-1)                     |       |
| Fluorinated greenhouse gases          | False |
| ethyl methyl ketone (78-93-3)         |       |
| Fluorinated greenhouse gases          | False |

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### ethyl acetate (141-78-6)

Fluorinated greenhouse gases

False

### hydrocarbons, C9, aromatics (64742-95-6)

Fluorinated greenhouse gases

False

## SECTION 13: Disposal considerations

Regional legislation (waste)

: Disposal must be done according to official regulations.

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG)

: 1950

UN-No. (IMDG)

: 1950

UN-No. (IATA)

: 1950

### 14.2. UN Proper Shipping Name

Proper Shipping Name (ADG)

: AEROSOLS

Proper Shipping Name (IMDG)

: AEROSOLS

Proper Shipping Name (IATA)

: Aerosols, flammable

### 14.3. Transport hazard class(es)

#### ADG

Transport hazard class(es) (ADG)

: 2.1

Danger labels (ADG)

: 2.1

:



#### IMDG

Transport hazard class(es) (IMDG)

: 2.1

Danger labels (IMDG)

: 2.1

:



#### IATA

Transport hazard class(es) (IATA)

: 2.1

Danger labels (IATA)

: 2.1

:



### 14.4. Packing group

Packing group (ADG)

: Not applicable

Packing group (IMDG)

: Not applicable

Packing group (IATA)

: Not applicable

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 14.5. Environmental hazards

Marine pollutant : No  
Dangerous for the environment : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344  
Limited quantities (ADG) : See SP 277  
Packing instructions (ADG) : P207, LP02  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None

#### Air transport

UN-No. (IATA) : 1950  
PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

#### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515  
Group standard : Aerosols

#### acetone (67-64-1)

#### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001070 |
|----------------------|-----------|

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

|   |           |
|---|-----------|
| <b>ethyl methyl ketone (78-93-3)</b>              |           |
| <b>Hazardous Substances and New Organisms Act</b> |           |
| HSNO Approval Number                              | HSR001190 |

|  |           |
|--|-----------|
| <b>2,6-dimethylheptan-4-one; di-isobutyl ketone (108-83-8)</b> |           |
| <b>Hazardous Substances and New Organisms Act</b>              |           |
| HSNO Approval Number   | HSR001130 |

|   |           |
|---|-----------|
| <b>n-butyl acetate (123-86-4)</b>                 |           |
| <b>Hazardous Substances and New Organisms Act</b> |           |
| HSNO Approval Number                              | HSR001091 |

|   |           |
|---|-----------|
| <b>2-methoxy-1-methylethyl acetate (108-65-6)</b> |           |
| <b>Hazardous Substances and New Organisms Act</b> |           |
| HSNO Approval Number                              | HSR001219 |

|   |           |
|---|-----------|
| <b>carbon black (1333-86-4)</b>                   |           |
| <b>Hazardous Substances and New Organisms Act</b> |           |
| HSNO Approval Number                              | HSR002801 |

|  |  |
|--|--|
| <b>phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)</b> |  |
| <b>Hazardous Substances and New Organisms Act</b>                    |  |
| HSNO Approval Number   | HSR001545(dilution)<br>HSR001571(dilution) |

|   |           |
|---|-----------|
| <b>1-butanol (71-36-3)</b>                        |           |
| <b>Hazardous Substances and New Organisms Act</b> |           |
| HSNO Approval Number                              | HSR001096 |

|   |           |
|---|-----------|
| <b>ethyl acetate (141-78-6)</b>                   |           |
| <b>Hazardous Substances and New Organisms Act</b> |           |
| HSNO Approval Number                              | HSR001041 |

|  |           |
|--|-----------|
| <b>LPG, liquefied, under pressure (68476-85-7)</b> |           |
| <b>Hazardous Substances and New Organisms Act</b>  |           |
| HSNO Approval Number                               | HSR001009 |

|   |           |
|---|-----------|
| <b>hydrocarbons, C9, aromatics (64742-95-6)</b>   |           |
| <b>Hazardous Substances and New Organisms Act</b> |           |
| HSNO Approval Number                              | HSR001503 |

# SPOT #3 UNIVERSAL SPOT PRIMER AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number

HSR002495

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Revision date

: 20/12/2021

### Classification

Aerosol 1

H222;H229

Eye Irrit. 2A

H319

STOT SE 3

H336

### Full text of H-statements

Acute Tox. 5 (Oral)

Acute toxicity (oral), Category 5

Aerosol 1

Aerosol, Category 1

Asp. Tox. 1

Aspiration hazard, Category 1

Eye Irrit. 2A

Serious eye damage/eye irritation, Category 2A

Flam. Liq. 2

Flammable liquids, Category 2

Flam. Liq. 3

Flammable liquids, Category 3

STOT SE 3

Specific target organ toxicity — Single exposure, Category 3, Narcosis

STOT SE 3

Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

H225

Highly flammable liquid and vapour

H226

Flammable liquid and vapour

H303

May be harmful if swallowed

H304

May be fatal if swallowed and enters airways

H319

Causes serious eye irritation

H335

May cause respiratory irritation

H336

May cause drowsiness or dizziness

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).