



DRIVING SURFACE PERFECTION

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Issue date: 6/09/2017 Revision date: 3/05/2019 Supersedes: 6/09/2017 Version: 1.1

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
 Trade name : PLAST X 3 PRIMER FILLER AEROSOL
 Product code : PLAS/3

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

1.4. Details of manufacturer or importer

Supplier

U-POL Australia Pty Limited Ltd
 55 Leland Street
 Penrith NSW 2750
 Australia
 T 02 4731 2655 - F 02 4731 2611
info@u-pol.com.au - www.u-pol.com

Supplier

U-POL New Zealand Limited Ltd
 c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki
 Manukau City Auckland 2013
 New Zealand
 T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611
info@u-pol.co.nz - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1	H222
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)



Signal word (GHS AU)

: Danger

Contains

: ethyl methyl ketone (30 – 60 %); ethyl acetate (< 10 %); 1-butanol (< 10 %); n-butyl acetate (< 10 %)

Hazard statements (GHS AU)

: H222 - Extremely flammable aerosol
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS AU)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking, heat, hot surfaces, open flames, sparks
 P251 - Do not pierce or burn, even after use.
 P261 - Avoid breathing vapours, spray.
 P280 - Wear eye protection, protective clothing, protective gloves.

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

P337+P313 - If eye irritation persists: Get medical attention.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
ethyl methyl ketone	78-93-3	30 – 60	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Eye Irrit. 2A, H319 STOT SE 3, H336
Other substances (not contributing to the classification of this product)	-	65.99	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

- For containment : Contain released product, collect/pump into suitable containers. Collect spillage.
- Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Storage temperature : < 25 °C
- Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

ethyl methyl ketone (78-93-3)

Australia - Occupational Exposure Limits

Local name	Methyl ethyl ketone (MEK; 2-Butanone)
OES TWA [1]	445 mg/m ³
OES TWA [2]	150 ppm
OES STEL	890 mg/m ³
OES STEL [ppm]	300 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

New Zealand - Occupational Exposure Limits

Local name	Methyl ethyl ketone (MEK, 2-Butanone)
WES-TWA (OEL TWA) [1]	445 mg/m ³
WES-TWA (OEL TWA) [2]	150 ppm

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

ethyl methyl ketone (78-93-3)	
WES-STEL (OEL STEL)	890 mg/m ³
WES-STEL (OEL STEL) [ppm]	300 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
New Zealand - Biological Exposure Indices	
Local name	Methyl ethyl ketone (MEK)
BEI	2 mg/l Parameter: MEK - Medium: Urine - Sampling time: End of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing	: Impermeable clothing
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: dark grey
Odour	: characteristic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: 0.736 g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 636 g/l
VOC content - Regulatory	: No data available
Gas group	: Press. Gas (Liq.)
Percent Solids	: 16.64 wt%

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ethyl methyl ketone (78-93-3)

LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 8100 mg/kg bw/day (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
ATE AU (oral)	2193 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

ethyl methyl ketone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

PLAST X 3 PRIMER FILLER AEROSOL

Vaporizer	Aerosol
-----------	---------

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

ethyl methyl ketone (78-93-3)

LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

ethyl methyl ketone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

12.2. Persistence and degradability

ethyl methyl ketone (78-93-3)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O ₂ /g substance
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance
ThOD	2.44 g O ₂ /g substance

12.3. Bioaccumulative potential

ethyl methyl ketone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

ethyl methyl ketone (78-93-3)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

PLAST X 3 PRIMER FILLER AEROSOL	
Fluorinated greenhouse gases	False
ethyl methyl ketone (78-93-3)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1
Danger labels (ADG) : 2.1
:



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1
:



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1
:



14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Special provision (ADG)	: 63, 190, 277, 327, 344
Limited quantities (ADG)	: See SP 277
Packing instructions (ADG)	: P207, LP02
Special packing provisions (ADG)	: PP87, L2

Transport by sea

UN-No. (IMDG)	: 1950
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None

Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code	: Not applicable
--------------	------------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number	: HSR002515
Group standard	: Aerosols

ethyl methyl ketone (78-93-3)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001190
----------------------	-----------

LPG, liquefied, under pressure (68476-85-7)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001009
----------------------	-----------

2,6-dimethylheptan-4-one; di-isobutyl ketone (108-83-8)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001130
----------------------	-----------

n-butyl acetate (123-86-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001091
----------------------	-----------

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

2-methoxy-1-methylethyl acetate (108-65-6)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001219
----------------------	-----------

carbon black (1333-86-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR002801
----------------------	-----------

phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001545(dilution) HSR001571(dilution)
----------------------	--

1-butanol (71-36-3)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001096
----------------------	-----------

ethyl acetate (141-78-6)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001041
----------------------	-----------

hydrocarbons, C9, aromatics (64742-95-6)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001503
----------------------	-----------

fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR002495
----------------------	-----------

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 03/05/2019

Classification

Flam. Aerosol 1	H222
Eye Irrit. 2A	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

Full text of H-statements

Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
---------------------	-----------------------------------

PLAST X 3 PRIMER FILLER AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Full text of H-statements	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H303	May be harmful if swallowed
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H412	Harmful to aquatic life with long lasting effects

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.