



DRIVING SURFACE PERFECTION

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations  
Issue date: 2/02/2017 Revision date: 19/04/2021 Supersedes: 3/05/2019 Version: 4.0

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY  
Product code : PLAS/5LG

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

#### 1.4. Details of manufacturer or importer

##### Supplier

U-POL Australia Pty Limited Ltd  
55 Leland Street  
Penrith NSW 2750  
Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.com.au](mailto:info@u-pol.com.au) - [www.u-pol.com](http://www.u-pol.com)

##### Supplier

U-POL New Zealand Limited Ltd  
c/o Lindsay & Associates Unit H, 12 Amara Place, East Tamaki  
Manukau City Auckland 2013  
New Zealand  
T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

|  |      |
|--|------|
| Flammable aerosols, Category 1   | H222 |
| Skin corrosion/irritation, Category 3                                  | H316 |
| Serious eye damage/eye irritation, Category 2A                         | H319 |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336 |

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Signal word (GHS AU) :

Danger

Contains :

acetone (30 – 60 %); 4-methylpentan-2-one; isobutyl methyl ketone (< 10 %); n-butyl acetate (< 10 %); hydrocarbons, C9, aromatics (< 10 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol  
H316 - Causes mild skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking. heat, hot surfaces, open flames, sparks  
P251 - Do not pierce or burn, even after use.

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

P261 - Avoid breathing fume, spray, vapours.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P337+P313 - If eye irritation persists: Get medical attention.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

| Name  | CAS-No.  | %       | Classification according to the model Work Health and Safety Regulations (WHS Regulations)  |
|---|----------|---------|---|
| acetone   | 67-64-1  | 30 – 60 | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336  |
| 4-methylpentan-2-one; isobutyl methyl ketone                              | 108-10-1 | < 10    | Flam. Liq. 2, H225<br>Acute Tox. 5 (Oral), H303<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Eye Irrit. 2A, H319<br>Carc. 2, H351<br>STOT SE 3, H335 |
| Other substances (not contributing to the classification of this product) | -        | 66.75   | -   |

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : Irritation.

### 4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

For containment : Contain released product, collect/pump into suitable containers. Collect spillage.  
Methods for cleaning up : Mechanically recover the product.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Storage temperature : < 25 °C  
Special rules on packaging : Keep only in original container.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

| acetone (67-64-1)                        |   |
|--|---|
| Australia - Occupational Exposure Limits |   |
| Local name                               | Acetone   |
| OES TWA [1]                              | 1185 mg/m³  |
| OES TWA [2]                              | 500 ppm   |
| OES STEL                                 | 2375 mg/m³  |
| OES STEL [ppm]                           | 1000 ppm  |
| Regulatory reference                     | Workplace exposure standards for airborne contaminants (2019) |

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

|  |  |
|--|--|
| <b>acetone (67-64-1)</b>                                       |  |
| <b>New Zealand - Occupational Exposure Limits</b>              |  |
| Local name   | Acetone  |
| WES-TWA (OEL TWA) [1]  | 1185 mg/m <sup>3</sup>   |
| WES-TWA (OEL TWA) [2]  | 500 ppm  |
| WES-STEL (OEL STEL)  | 2375 mg/m <sup>3</sup>   |
| WES-STEL (OEL STEL) [ppm]                                      | 1000 ppm   |
| Regulatory reference   | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>New Zealand - Biological Exposure Indices</b>               |  |
| Local name   | Acetone  |
| BEI  | 50 mg/l Parameter: Acetone - Medium: Urine - Sampling time: End of shift   |
| Regulatory reference   | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b> |  |
| <b>Australia - Occupational Exposure Limits</b>                |  |
| Local name   | Methyl isobutyl ketone (MIBK; 4-Methyl-2-pentanone; Hexone)                |
| OES TWA [1]  | 205 mg/m <sup>3</sup>  |
| OES TWA [2]  | 50 ppm   |
| OES STEL   | 307 mg/m <sup>3</sup>  |
| OES STEL [ppm]   | 75 ppm   |
| Regulatory reference   | Workplace exposure standards for airborne contaminants (2019)              |
| <b>New Zealand - Occupational Exposure Limits</b>              |  |
| Local name   | Methyl isobutyl ketone (Hexone)  |
| WES-TWA (OEL TWA) [1]  | 205 mg/m <sup>3</sup>  |
| WES-TWA (OEL TWA) [2]  | 50 ppm   |
| WES-STEL (OEL STEL)  | 307 mg/m <sup>3</sup>  |
| WES-STEL (OEL STEL) [ppm]                                      | 75 ppm   |
| Regulatory reference   | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>New Zealand - Biological Exposure Indices</b>               |  |
| Local name   | Methyl isobutyl ketone (MIBK)  |
| BEI  | 0.7 mg/l Parameter: MIBK - Medium: Urine - Sampling time: End of shift     |
| Regulatory reference   | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |

### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Gloves. Protective clothing. Safety glasses.  
Materials for protective clothing : Impermeable clothing  
Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

### Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

|   |   |
|---|---|
| Physical state                                  | : Liquid  |
| Appearance                                      | : Aerosol.  |
| Colour  | : Light grey  |
| Odour   | : Odour threshold is subjective and inadequate to warn for overexposure.<br>Mixture contains one or more component(s) which have the following odour:<br>Aromatic odour Sweet odour Fruity odour Odourless Commercial/unpurified substance:<br>unpleasant odour Almost odourless Pleasant odour Camphor odour Mild odour Ether-like<br>odour Petroleum-like odour |
| Odour threshold                                 | : No data available   |
| pH  | : No data available   |
| Relative evaporation rate (butylacetate=1)      | : No data available   |
| Melting point / Freezing point                  | : No data available   |
| Boiling point                                   | : No data available   |
| Flash point                                     | : No data available   |
| Auto-ignition temperature                       | : No data available   |
| Flammability                                    | : No data available   |
| Vapour pressure                                 | : No data available   |
| Relative density                                | : No data available   |
| Density   | : Density: 0.724 g/cm <sup>3</sup>  |
| Solubility                                      | : insoluble in water. soluble in most organic solvents.   |
| Partition coefficient n-octanol/water (Log Pow) | : No data available   |
| Explosive properties                            | : Pressurised container: May burst if heated.   |
| Explosive limits                                | : No data available   |
| Minimum ignition energy                         | : No data available   |
| VOC content                                     | : 639   |
| VOC content - Regulatory                        | : No data available   |
| Gas group                                       | : Press. Gas (Liq.)   |
| Percent Solids                                  | : 11.67 wt%   |

## SECTION 10: Stability and reactivity

|                                    |  |
|------------------------------------|--|
| Reactivity                         | : Extremely flammable aerosol. Pressurised container: May burst if heated.                             |
| Chemical stability                 | : Stable under normal conditions.  |
| Possibility of hazardous reactions | : No dangerous reactions known under normal conditions of use.   |
| Conditions to avoid                | : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.      |
| Incompatible materials             | : No additional information available  |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## SECTION 11: Toxicological information

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

### acetone (67-64-1)

|               |   |
|---------------|---|
| LD50 oral rat | 5800 mg/kg bodyweight Animal: rat, Animal sex: female |
|---------------|---|

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

|  |  |
|--|--|
| <b>acetone (67-64-1)</b>                                       |  |
| LD50 dermal rabbit   | > 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))                                       |
| LC50 Inhalation - Rat  | 76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4   |
| ATE AU (oral)  | 5800 mg/kg bodyweight  |
| <b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b> |  |
| LD50 oral rat  | 2080 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1,91 - 2,27                |
| LD50 dermal rat  | ≥ 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat (Vapours)                                | 10 – 20 mg/l/4h  |
| ATE AU (oral)  | 2080 mg/kg bodyweight  |
| ATE AU (gases)   | 4500 ppmv/4h   |
| ATE AU (vapours)   | 10 mg/l/4h   |
| ATE AU (dust,mist)   | 1.5 mg/l/4h  |
| Skin corrosion/irritation                                      | : Causes mild skin irritation.   |
| Serious eye damage/irritation                                  | : Causes serious eye irritation.   |
| Respiratory or skin sensitisation                              | : Not classified   |
| Germ cell mutagenicity   | : Not classified   |
| Carcinogenicity  | : Not classified   |
| Reproductive toxicity  | : Not classified   |
| STOT-single exposure   | : May cause drowsiness or dizziness.   |
| <b>acetone (67-64-1)</b>                                       |  |
| STOT-single exposure   | May cause drowsiness or dizziness.   |
| <b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b> |  |
| STOT-single exposure   | May cause respiratory irritation.  |
| STOT-repeated exposure   | : Not classified   |
| <b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b> |  |
| LOAEL (oral, rat, 90 days)                                     | 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)           |
| NOAEL (oral, rat, 90 days)                                     | 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)            |
| NOAEC (inhalation, rat, vapour, 90 days)                       | 4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)                   |
| Aspiration hazard  | : Not classified   |
| <b>PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY</b>              |  |
| Vaporizer  | Aerosol  |

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

|   |  |
|---|--|
| Ecology - general   | : Harmful to aquatic life with long lasting effects. |
| Hazardous to the aquatic environment, short-term (acute)  | : Not classified                                     |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified                                     |

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| acetone (67-64-1)  |   |
|--|---|
| LC50 - Fish [1]  | 6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration) |
| LOEC (chronic)   | > 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'  |
| NOEC (chronic)   | ≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'  |
| BCF - Fish [1]   | 0.69 (Pisces, Literature study)   |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)  |

| 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)    |   |
|--|---|
| LC50 - Fish [1]  | > 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) |
| EC50 - Crustacea [1]                                       | > 200 mg/l Test organisms (species): Daphnia magna                                  |
| Partition coefficient n-octanol/water (Log Pow)            | 1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)                  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.008 (log Koc, Weight of evidence, Calculated value)                               |

### 12.2. Persistence and degradability

| acetone (67-64-1)               |  |
|---------------------------------|--|
| Persistence and degradability   | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.43 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 1.92 g O <sub>2</sub> /g substance   |
| ThOD                            | 2.2 g O <sub>2</sub> /g substance  |

| 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1) |  |
|---|--|
| Persistence and degradability                           | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD)                         | 2.06 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)                            | 2.16 g O <sub>2</sub> /g substance   |
| ThOD  | 2.72 g O <sub>2</sub> /g substance   |

### 12.3. Bioaccumulative potential

| acetone (67-64-1)  |  |
|--|--|
| BCF - Fish [1]   | 0.69 (Pisces, Literature study)                              |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (BCF < 500).               |

| 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)    |  |
|--|--|
| Partition coefficient n-octanol/water (Log Pow)            | 1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.008 (log Koc, Weight of evidence, Calculated value)              |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (Log Kow < 4).                   |

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 12.4. Mobility in soil

#### acetone (67-64-1)

|  |  |
|--|--|
| Surface tension  | 23.3 mN/m (20 °C)  |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil   | Highly mobile in soil.   |

#### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

|  |   |
|--|---|
| Surface tension  | No data available in the literature   |
| Partition coefficient n-octanol/water (Log Pow)            | 1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)                      |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 2.008 (log Koc, Weight of evidence, Calculated value) |
| Ecology - soil   | Low potential for adsorption in soil.   |

### 12.5. Other adverse effects

|                       |                                       |
|-----------------------|---------------------------------------|
| Ozone                 | : Not classified                      |
| Other adverse effects | : No additional information available |

#### PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### acetone (67-64-1)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

## SECTION 13: Disposal considerations

|                              |   |
|------------------------------|---|
| Regional legislation (waste) | : Disposal must be done according to official regulations.                                    |
| Waste treatment methods      | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |

## SECTION 14: Transport information

### 14.1. UN number

|               |        |
|---------------|--------|
| UN-No. (ADG)  | : 1950 |
| UN-No. (IMDG) | : 1950 |
| UN-No. (IATA) | : 1950 |

### 14.2. UN Proper Shipping Name

|                             |                       |
|-----------------------------|-----------------------|
| Proper Shipping Name (ADG)  | : AEROSOLS            |
| Proper Shipping Name (IMDG) | : AEROSOLS            |
| Proper Shipping Name (IATA) | : Aerosols, flammable |

### 14.3. Transport hazard class(es)

#### ADG

|                                  |       |
|----------------------------------|-------|
| Transport hazard class(es) (ADG) | : 2.1 |
| Danger labels (ADG)              | : 2.1 |



# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations



### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1



### IATA

Transport hazard class(es) (IATA) : 2.1  
Danger labels (IATA) : 2.1



## 14.4. Packing group

Packing group (ADG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

## 14.5. Environmental hazards

Marine pollutant : No  
Dangerous for the environment : No  
Other information : No supplementary information available

## 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

## 14.7. Additional information

Other information : No supplementary information available

### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344  
Limited quantities (ADG) : See SP 277  
Packing instructions (ADG) : P207, LP02  
Special packing provisions (ADG) : PP87, L2

### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None

### Air transport

UN-No. (IATA) : 1950  
PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

|                                 |                    |
|---------------------------------|--------------------|
| PCA packing instructions (IATA) | : 203              |
| PCA max net quantity (IATA)     | : 75kg             |
| CAO packing instructions (IATA) | : 203              |
| CAO max net quantity (IATA)     | : 150kg            |
| Special provisions (IATA)       | : A145, A167, A802 |
| ERG code (IATA)                 | : 10L              |

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

#### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515  
Group standard : Aerosols

#### acetone (67-64-1)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001070

#### LPG, liquefied, under pressure (68476-85-7)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001009

#### 2-phenoxyethanol (122-99-6)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR003045

#### toluene (108-88-3)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001227

#### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001194

#### solvent naphtha (petroleum), light aromatic (64742-95-6)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001503

#### 2-methoxy-1-methylethyl acetate (108-65-6)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001219

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)

#### Hazardous Substances and New Organisms Act

|                      |  |
|----------------------|--|
| HSNO Approval Number | HSR001545(dilution)<br>HSR001571(dilution) |
|----------------------|--|

### n-butyl acetate (123-86-4)

#### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001091 |
|----------------------|-----------|

### butyl glycolether (111-76-2)

#### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001154 |
|----------------------|-----------|

### Xylene (1330-20-7)

#### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR000983 |
|----------------------|-----------|

### hydrocarbons, C9, aromatics (64742-95-6)

#### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001503 |
|----------------------|-----------|

### ethylbenzene (100-41-4)

#### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001151 |
|----------------------|-----------|

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Revision date : 19/04/2021

### Classification

|                 |      |
|-----------------|------|
| Flam. Aerosol 1 | H222 |
| Skin Irrit. 3   | H316 |
| Eye Irrit. 2A   | H319 |
| STOT SE 3       | H336 |

### Full text of H-statements

|                                  |  |
|----------------------------------|--|
| Acute Tox. 4 (Inhalation)        | Acute toxicity (inhal.), Category 4            |
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4  |
| Acute Tox. 5 (Oral)              | Acute toxicity (oral), Category 5              |
| Carc. 2                          | Carcinogenicity, Category 2                    |
| Eye Irrit. 2A                    | Serious eye damage/eye irritation, Category 2A |

# PLAST X 5 COLOUR COAT AEROSOL - LIGHT GREY

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| Full text of H-statements |  |
|---------------------------|--|
| Flam. Aerosol 1           | Flammable aerosols, Category 1   |
| Flam. Liq. 2              | Flammable liquids, Category 2  |
| Skin Irrit. 3             | Skin corrosion/irritation, Category 3  |
| STOT SE 3                 | Specific target organ toxicity – Single exposure, Category 3, Narcosis                     |
| STOT SE 3                 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |
| H222                      | Extremely flammable aerosol  |
| H225                      | Highly flammable liquid and vapour   |
| H303                      | May be harmful if swallowed  |
| H316                      | Causes mild skin irritation  |
| H319                      | Causes serious eye irritation  |
| H332                      | Harmful if inhaled   |
| H335                      | May cause respiratory irritation   |
| H336                      | May cause drowsiness or dizziness  |
| H351                      | Suspected of causing cancer  |

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).