



DRIVING SURFACE PERFECTION

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
Issue date: 3/08/2016 Revision date: 4/05/2023 Supersedes: 3/05/2019 Version: 3.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Trade name : SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)
Product code : S2080/1, S2080/5

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating
Restrictions on use : Consumer uses: Private households (= general public = consumers)

1.4. Details of manufacturer or importer

Supplier

U-POL Australia Pty Limited Ltd
55 Leland Street
Penrith NSW 2750
Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.com.au - www.u-pol.com

Supplier

U-POL New Zealand Limited Ltd
c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki
Manukau City Auckland 2013
New Zealand
T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611
info@u-pol.co.nz - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame



Exclamation mark



Health hazard

Signal word (GHS AU) : Warning

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Contains	: n-butyl acetate (< 30 %); hydrocarbons, C9, aromatics (< 30 %); Xylene (10 – 30 %); 4-methylpentan-2-one; isobutyl methyl ketone (< 10 %); reaction mass of ethylbenzene, m-xylene and p-xylene (< 10 %); reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (< 10 %); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (< 10 %)
Hazard statements (GHS AU)	: H226 - Flammable liquid and vapour H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H351 - Suspected of causing cancer H373 - May cause damage to organs through prolonged or repeated exposure
Precautionary statements (GHS AU)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing fume, spray, vapours. P264 - Wash hands thoroughly after handling. P280 - Wear face protection, protective clothing, protective gloves. P337+P313 - If eye irritation persists: Get medical attention. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
n-butyl acetate	123-86-4	< 30	Flam. Liq. 3, H226 STOT SE 3, H336
hydrocarbons, C9, aromatics	64742-95-6	< 30	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304
Xylene	1330-20-7	10 – 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	< 10	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
Other substances (not contributing to the classification of this product)	-	68.35 – 88.03	-

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.

4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: * 3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, fume, spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment	: Collect spillage. Contain released product, collect/pump into suitable containers.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, fume, spray. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Ignition sources, Heat sources, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.
- Storage temperature : < 25 °C
- Storage area : Store in a well-ventilated place.
- Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

n-butyl acetate (123-86-4)	
Australia - Occupational Exposure Limits	
Local name	n-Butyl acetate
OES TWA [1]	713 mg/m ³
OES TWA [2]	150 ppm
OES STEL	950 mg/m ³
OES STEL [ppm]	200 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
New Zealand - Occupational Exposure Limits	
Local name	n-Butyl acetate
WES-TWA (OEL TWA) [1]	713 mg/m ³
WES-TWA (OEL TWA) [2]	150 ppm
WES-STEEL (OEL STEL)	950 mg/m ³
WES-STEEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Australia - Occupational Exposure Limits	
Local name	Methyl isobutyl ketone (MIBK; 4-Methyl-2-pentanone; Hexone)
OES TWA [1]	205 mg/m ³
OES TWA [2]	50 ppm
OES STEL	307 mg/m ³
OES STEL [ppm]	75 ppm

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
New Zealand - Occupational Exposure Limits	
Local name	Methyl isobutyl ketone (Hexone)
WES-TWA (OEL TWA) [1]	205 mg/m ³
WES-TWA (OEL TWA) [2]	50 ppm
WES-STEL (OEL STEL)	307 mg/m ³
WES-STEL (OEL STEL) [ppm]	75 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
New Zealand - Biological Exposure Indices	
Local name	Methyl isobutyl ketone (MIBK)
BEI	0.7 mg/l Parameter: MIBK - Medium: Urine - Sampling time: End of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
Xylene (1330-20-7)	
New Zealand - Occupational Exposure Limits	
Local name	Xylene (Dimethylbenzene)
WES-TWA (OEL TWA) [1]	217 mg/m ³
WES-TWA (OEL TWA) [2]	50 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
New Zealand - Biological Exposure Indices	
Local name	Xylene
BEI	1.5 g/l Parameter: Methylhippuric acid - Medium: Urine - Sampling time: End of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Gas mask. Gloves. Protective clothing. Safety glasses.
Materials for protective clothing	: Impermeable clothing
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Air-fed respiratory protective equipment should be worn when this product is sprayed

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Appearance	: Liquid.
Colour	: Colourless
Odour	: characteristic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: 115 °C
Flash point	: 16 °C
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: 0.967 g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s
Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 518 g/l
VOC content - Regulatory	: No data available
Percent Solids	: 45.55 wt%

SECTION 10: Stability and reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

n-butyl acetate (123-86-4)

LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	23.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)
ATE AU (oral)	10760 mg/kg bodyweight
ATE AU (gases)	390 ppmv/4h
ATE AU (vapours)	23.4 mg/l/4h
ATE AU (dust,mist)	23.4 mg/l/4h

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
LD50 oral rat	2080 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1,91 - 2,27
LD50 dermal rat	≥ 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat (Vapours)	10 – 20 mg/l/4h
ATE AU (oral)	2080 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	10 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h
Xylene (1330-20-7)	
LD50 oral rat	> 4000 mg/kg bodyweight (Equivalent or similar to EU Method B.1, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	29.09 mg/l (Equivalent or similar to EU Method B.2, 4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)
ATE AU (dermal)	1100 mg/kg bodyweight
ATE AU (gases)	6700 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h
hydrocarbons, C9, aromatics (64742-95-6)	
LD50 oral rat	8400 ml/kg
LD50 dermal rabbit	3160 mg/kg bodyweight (OECD Guideline 402 (Acute Dermal Toxicity), rat, male/female)
LC50 Inhalation - Rat [ppm]	3400 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 5 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
STOT-single exposure	May cause respiratory irritation.
Xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
hydrocarbons, C9, aromatics (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

hydrocarbons, C9, aromatics (64742-95-6)	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight/day
NOAEC (inhalation, rat, vapour, 90 days)	900 – 1800 mg/m ³

Aspiration hazard : Not classified.

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)	
Viscosity, kinematic	> 20.5 mm ² /s

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
LC50 - Fish [1]	> 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna
Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.008 (log Koc, Weight of evidence, Calculated value)
Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
hydrocarbons, C9, aromatics (64742-95-6)	
LC50 - Fish [1]	9.22 mg/l (Oncorhynchus mykiss)
EC50 - Crustacea [1]	6.14 mg/l 48 h, Daphnia magna
ErC50 algae	2.9 mg/l
12.2. Persistence and degradability	
n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.06 g O ₂ /g substance
Chemical oxygen demand (COD)	2.16 g O ₂ /g substance
ThOD	2.72 g O ₂ /g substance
Xylene (1330-20-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
hydrocarbons, C9, aromatics (64742-95-6)	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.008 (log Koc, Weight of evidence, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Xylene (1330-20-7)	
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

n-butyl acetate (123-86-4)	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. Not toxic to plants.

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology2.008 (log Koc, Weight of evidence, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)	
Fluorinated greenhouse gases	False
n-butyl acetate (123-86-4)	
Fluorinated greenhouse gases	False
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Fluorinated greenhouse gases	False

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Xylene (1330-20-7)	
Fluorinated greenhouse gases	False
hydrocarbons, C9, aromatics (64742-95-6)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG)	: 1263
UN-No. (IMDG)	: 1263
UN-No. (IATA)	: 1263

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG)	: PAINT
Proper Shipping Name (IMDG)	: PAINT
Proper Shipping Name (IATA)	: Paint

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG)	: 3
Danger labels (ADG)	: 3
	:



IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3
	:



IATA

Transport hazard class(es) (IATA)	: 3
Danger labels (IATA)	: 3
	:



14.4. Packing group

Packing group (ADG)	: III - Substances presenting low danger
Packing group (IMDG)	: III
Packing group (IATA)	: III

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

14.5. Environmental hazards

Marine pollutant	: No
Dangerous for the environment	: No
Other information	: No supplementary information available

14.6. Special precautions for user

Specific storage requirement	: No data available
Shock sensitivity	: No data available

14.7. Additional information

Other information	: No supplementary information available
-------------------	--

Transport by road and rail

UN-No. (ADG)	: 1263
Special provision (ADG)	: 163, 223, 367
Limited quantities (ADG)	: 5L
Packing instructions (ADG)	: P001, IBC03, LP01
Special packing provisions (ADG)	: PP1
Portable tank and bulk container instructions (ADG)	: T2
Portable tank and bulk container special provisions (ADG)	: TP1, TP29

Transport by sea

UN-No. (IMDG)	: 1263
Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

UN-No. (IATA)	: 1263
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code	: * 3Y
--------------	--------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number	: HSR002662
Group standard	: Surface coatings and colourants

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

n-butyl acetate (123-86-4)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR001091

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR001194

2-methoxy-1-methylethyl acetate (108-65-6)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR001219

dibutyltin dilaurate (77-58-7)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR003610

Xylene (1330-20-7)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR000983

hydrocarbons, C9, aromatics (64742-95-6)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR001503

ethylbenzene (100-41-4)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR001151

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 04/05/2023

Classification	
Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H336
STOT SE 3	H335

SYSTEM 20 SUPERIOR HS CLEARCOAT (2:1)

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Classification	
STOT RE 2	H373

Full text of H-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.