



DRIVING SURFACE PERFECTION

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Issue date: 27/07/2016 Revision date: 9/12/2021 Supersedes: 8/06/2021 Version: 4.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Trade name : CUSTOM CAN FILL ONE WATER BASED AEROSOL
Product code : CCFOWP/AL

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

1.4. Details of manufacturer or importer

Supplier

U-POL Australia Pty Limited Ltd
55 Leland Street
Penrith NSW 2750
Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.com.au - www.u-pol.com

Supplier

U-POL New Zealand Limited Ltd
c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki
Manukau City Auckland 2013
New Zealand
T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611
info@u-pol.co.nz - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)



Signal word (GHS AU)

: Danger

Contains

: acetone (10 – 30 %); propan-2-ol (< 10 %)

Hazard statements (GHS AU)

: H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing fume, spray, vapours.

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, protective clothing, protective gloves.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical attention.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
acetone	67-64-1	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Other substances (not contributing to the classification of this product)	-	77.29	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable aerosol. Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

- For containment : Contain released product, collect/pump into suitable containers. Collect spillage.
- Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Storage temperature : < 25 °C
- Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

acetone (67-64-1)

Australia - Occupational Exposure Limits

Local name	Acetone
OES TWA [1]	1185 mg/m³
OES TWA [2]	500 ppm
OES STEL	2375 mg/m³
OES STEL [ppm]	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

New Zealand - Occupational Exposure Limits

Local name	Acetone
WES-TWA (OEL TWA) [1]	1185 mg/m³
WES-TWA (OEL TWA) [2]	500 ppm

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

acetone (67-64-1)	
WES-STEL (OEL STEL)	2375 mg/m ³
WES-STEL (OEL STEL) [ppm]	1000 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
New Zealand - Biological Exposure Indices	
Local name	Acetone
BEI	50 mg/l Parameter: Acetone - Medium: Urine - Sampling time: End of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Gloves. Protective clothing. Safety glasses.
Materials for protective clothing	: Impermeable clothing
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Colourless
Odour	: Odour threshold is subjective and inadequate to warn for overexposure. Mixture contains one or more component(s) which have the following odour: Mild odour Alcohol odour Stuffy odour Aromatic odour Sweet odour Fruity odour Ether-like odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not applicable
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: 0.696 g/cm ³
Solubility	: Immiscible with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 763 g/l

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

VOC content - Regulatory	: No data available
Gas group	: Press. Gas (Liq.)
Percent Solids	: 0 wt%

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE AU (oral)	5800 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

acetone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Vaporizer	Aerosol
-----------	---------

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

12.2. Persistence and degradability

acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance

12.3. Bioaccumulative potential

acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

acetone (67-64-1)	
Surface tension	23.3 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

CUSTOM CAN FILL ONE WATER BASED AEROSOL	
Fluorinated greenhouse gases	False
acetone (67-64-1)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1
Danger labels (ADG) : 2.1
:



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1
:



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1
:



14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Transport by road and rail

UN-No. (ADG)	: 1950
Special provision (ADG)	: 63, 190, 277, 327, 344
Limited quantities (ADG)	: See SP 277
Packing instructions (ADG)	: P207, LP02
Special packing provisions (ADG)	: PP87, L2

Transport by sea

UN-No. (IMDG)	: 1950
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None

Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code	: Not applicable
--------------	------------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number	: HSR002515
Group standard	: Aerosols

propan-2-ol (67-63-0)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001180
----------------------	-----------

acetone (67-64-1)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001070
----------------------	-----------

dimethyl ether (115-10-6)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR000995
----------------------	-----------

15.2. International agreements

No additional information available

CUSTOM CAN FILL ONE WATER BASED AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 16: Other information

Revision date : 09/12/2021

Classification

Aerosol 1	H222;H229
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements

Aerosol 1	Aerosol, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.