



DRIVING SURFACE PERFECTION

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 Product Reference code: according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 SDS Ref. (EU): TOPG-SDS  
 Issue date: 30/03/2015 Revision date: 17/11/2022 Supersedes version of: 17/03/2022 Version: 5.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : TOPSTOP GOLD EASY SANDING STOPPER  
 UFI : FM11-N0YC-700W-EJQ7  
 Product code : TOPG/BL, TOPG/BM, TOPG/2, DIS/TOPG  
 Type of product : Fillers  
 Product group : Bodyfiller

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
 Use of the substance/mixture : Fillers, putties, plasters, modelling clay  
 Function or use category : Fillers

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

U-POL Limited Ltd  
 Denington Road  
 GB- NN8 2QH Wellingborough – Northamptonshire  
 United Kingdom  
 T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### Importer

U-POL Netherlands B.V. B.V.  
 Hoogoorddreef 15  
 NL- 1101BA Amsterdam  
 Netherlands  
 T +31 20 240 2216  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

| Country        | Organisation/Company                                     | Address                                  | Emergency number   | Comment   |
|----------------|--|--|--|---|
| Ireland        | National Poisons Information Centre<br>Beaumont Hospital | PO Box 1297<br>Beaumont Road<br>9 Dublin | +353 1 809 2566<br>(Healthcare professionals-<br>24/7)<br>+353 1 809 2166 (public,<br>8am - 10pm, 7/7) |   |
| United Kingdom | NHS<br>England, Scotland & Wales                         | -  | Call 111 or a Doctor   | In Northern Ireland,<br>contact your local GP<br>or pharmacist during<br>normal hours<br>( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> ) |

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315  
 Serious eye damage/eye irritation, Category 2 H319  
 Reproductive toxicity, Category 2 H361  
 Specific target organ toxicity — Repeated exposure, Category 1 H372

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Causes skin irritation. Causes serious eye irritation.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: styrene

Hazard statements (CLP)

: H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H361 - Suspected of damaging fertility or the unborn child.  
H372 - Causes damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).  
Precautionary statements (CLP) : P201 - Obtain special instructions before use.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.

## 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

| Component  |   |
|--|---|
| styrene (100-42-5)   | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 3.2. Mixtures

| Name  | Product identifier   | %       | Classification according to Regulation (EC) No. 1272/2008 [CLP]  |
|---|--|---------|--|
| styrene<br>(Note D)   | CAS-No.: 100-42-5<br>EC-No.: 202-851-5<br>EC Index-No.: 601-026-00-0<br>REACH-no: 01-2119457861-32   | 10 – 20 | Flam. Liq. 3, H226<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 4 (Inhalation:vapour), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Repr. 2, H361d<br>STOT SE 3, H335<br>STOT RE 1, H372<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | CAS-No.: 13463-67-7<br>EC-No.: 236-675-5<br>EC Index-No.: 022-006-00-2<br>REACH-no: 01-2119489379-17 | 1 – 2.5 | Carc. 2, H351  |

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                                       |  |
|---------------------------------------|--|
| First-aid measures general            | : IF exposed or concerned: Get medical advice/attention.   |
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing.   |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.   |
| First-aid measures after eye contact  | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion    | : Call a poison center or a doctor if you feel unwell.   |

### 4.2. Most important symptoms and effects, both acute and delayed

|                                     |                   |
|-------------------------------------|-------------------|
| Symptoms/effects after skin contact | : Irritation.     |
| Symptoms/effects after eye contact  | : Eye irritation. |

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.

Emergency procedures : Ventilate spillage area. Do not breathe vapours, fume. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain released product, collect/pump into suitable containers. Collect spillage.

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapours, fume. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Storage temperature : < 25 °C

Storage area : Store in a well-ventilated place.

Special rules on packaging : Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

| styrene (100-42-5)                     |   |
|--|---|
| Ireland - Occupational Exposure Limits |   |
| Local name                             | Styrene [Phenylethylene, Vinyl benzene] |
| OEL TWA [1]                            | 85 mg/m <sup>3</sup>                    |
| OEL TWA [2]                            | 20 ppm                                  |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| styrene (100-42-5)  |  |
|---|--|
| OEL STEL  | 170 mg/m <sup>3</sup>  |
| OEL STEL [ppm]  | 40 ppm   |
| Regulatory reference  | Chemical Agents Code of Practice 2020  |
| United Kingdom - Occupational Exposure Limits   |  |
| Local name  | Styrene  |
| WEL TWA (OEL TWA) [1]   | 430 mg/m <sup>3</sup>  |
| WEL TWA (OEL TWA) [2]   | 100 ppm  |
| WEL STEL (OEL STEL)   | 1080 mg/m <sup>3</sup>   |
| WEL STEL (OEL STEL) [ppm]   | 250 ppm  |
| Regulatory reference  | EH40/2005 (Fourth edition, 2020). HSE  |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7) |  |
| Ireland - Occupational Exposure Limits  |  |
| Local name  | Titanium dioxide   |
| OEL TWA [1]   | 10 mg/m <sup>3</sup> total inhalable dust<br>4 mg/m <sup>3</sup> respirable dust |
| Regulatory reference  | Chemical Agents Code of Practice 2020  |
| United Kingdom - Occupational Exposure Limits   |  |
| Local name  | Titanium dioxide   |
| WEL TWA (OEL TWA) [1]   | 10 mg/m <sup>3</sup><br>4 mg/m <sup>3</sup>                                      |
| Regulatory reference  | EH40/2005 (Fourth edition, 2020). HSE  |

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

| styrene (100-42-5)                       |                          |
|--|--------------------------|
| DNEL/DMEL (Workers)                      |                          |
| Acute - systemic effects, inhalation     | 289 mg/m <sup>3</sup>    |
| Acute - local effects, inhalation        | 306 mg/m <sup>3</sup>    |
| Long-term - systemic effects, dermal     | 406 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 85 mg/m <sup>3</sup>     |
| DNEL/DMEL (General population)           |                          |
| Acute - systemic effects, inhalation     | 174.25 mg/m <sup>3</sup> |
| Acute - local effects, inhalation        | 182.75 mg/m <sup>3</sup> |
| Long-term - systemic effects, oral       | 2.1 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 10.2 mg/m <sup>3</sup>   |
| Long-term - systemic effects, dermal     | 343 mg/kg bodyweight/day |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| <b>styrene (100-42-5)</b>                     |                          |
|---|--------------------------|
| <b>PNEC (Water)</b>                           |                          |
| PNEC aqua (freshwater)                        | 0.028 mg/l               |
| PNEC aqua (marine water)                      | 0.014 mg/l               |
| PNEC aqua (intermittent, freshwater)          | 0.04 mg/l                |
| <b>PNEC (Sediment)</b>                        |                          |
| PNEC sediment (freshwater)                    | 0.614 mg/kg dwt          |
| PNEC sediment (marine water)                  | 0.307 mg/kg dwt          |
| <b>PNEC (Soil)</b>                            |                          |
| PNEC soil                                     | 0.2 mg/kg dwt            |
| <b>PNEC (STP)</b>                             |                          |
| PNEC sewage treatment plant                   | 5 mg/l                   |
| <b>phthalic anhydride (85-44-9)</b>           |                          |
| <b>DNEL/DMEL (Workers)</b>                    |                          |
| Long-term - systemic effects, dermal          | 10 mg/kg bodyweight/day  |
| Long-term - systemic effects, inhalation      | 32.2 mg/m <sup>3</sup>   |
| <b>DNEL/DMEL (General population)</b>         |                          |
| Long-term - systemic effects, oral            | 5 mg/kg bodyweight/day   |
| Long-term - systemic effects, inhalation      | 8.6 mg/m <sup>3</sup>    |
| Long-term - systemic effects, dermal          | 5 mg/kg bodyweight/day   |
| <b>PNEC (Water)</b>                           |                          |
| PNEC aqua (freshwater)                        | 1 mg/l                   |
| PNEC aqua (marine water)                      | 0.1 mg/l                 |
| PNEC aqua (intermittent, freshwater)          | 5.6 mg/l                 |
| <b>PNEC (Sediment)</b>                        |                          |
| PNEC sediment (freshwater)                    | 3.8 mg/kg dwt            |
| PNEC sediment (marine water)                  | 0.38 mg/kg dwt           |
| <b>PNEC (Soil)</b>                            |                          |
| PNEC soil                                     | 0.173 mg/kg dwt          |
| <b>PNEC (STP)</b>                             |                          |
| PNEC sewage treatment plant                   | 10 mg/l                  |
| <b>ethanediol; ethylene glycol (107-21-1)</b> |                          |
| <b>DNEL/DMEL (Workers)</b>                    |                          |
| Long-term - systemic effects, dermal          | 106 mg/kg bodyweight/day |
| Long-term - local effects, inhalation         | 35 mg/m <sup>3</sup>     |
| <b>DNEL/DMEL (General population)</b>         |                          |
| Long-term - systemic effects, dermal          | 53 mg/kg bodyweight/day  |
| Long-term - local effects, inhalation         | 7 mg/m <sup>3</sup>      |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| <b>ethanediol; ethylene glycol (107-21-1)</b>           |                          |
|---|--------------------------|
| <b>PNEC (Water)</b>                                     |                          |
| PNEC aqua (freshwater)                                  | 10 mg/l                  |
| PNEC aqua (marine water)                                | 1 mg/l                   |
| PNEC aqua (intermittent, freshwater)                    | 10 mg/l                  |
| <b>PNEC (Sediment)</b>                                  |                          |
| PNEC sediment (freshwater)                              | 37 mg/kg dwt             |
| PNEC sediment (marine water)                            | 3.7 mg/kg dwt            |
| <b>PNEC (Soil)</b>                                      |                          |
| PNEC soil   | 1.53 mg/kg dwt           |
| <b>PNEC (STP)</b>                                       |                          |
| PNEC sewage treatment plant                             | 199.5 mg/l               |
| <b>1-methoxy-2-propanol (107-98-2)</b>                  |                          |
| <b>DNEL/DMEL (Workers)</b>                              |                          |
| Acute - systemic effects, inhalation                    | 553.5 mg/m <sup>3</sup>  |
| Acute - local effects, inhalation                       | 553.5 mg/m <sup>3</sup>  |
| Long-term - systemic effects, dermal                    | 183 mg/m <sup>3</sup>    |
| Long-term - systemic effects, inhalation                | 369 mg/m <sup>3</sup>    |
| <b>DNEL/DMEL (General population)</b>                   |                          |
| Long-term - systemic effects, oral                      | 33 mg/kg bw/day          |
| Long-term - systemic effects, inhalation                | 43.9 mg/m <sup>3</sup>   |
| Long-term - systemic effects, dermal                    | 78 mg/kg bw/day          |
| <b>PNEC (Water)</b>                                     |                          |
| PNEC aqua (freshwater)                                  | 10 mg/l                  |
| PNEC aqua (marine water)                                | 1 mg/l                   |
| PNEC aqua (intermittent, freshwater)                    | 100 mg/l                 |
| <b>PNEC (Sediment)</b>                                  |                          |
| PNEC sediment (freshwater)                              | 52.3 mg/kg dwt           |
| PNEC sediment (marine water)                            | 5.2 mg/kg dwt            |
| <b>PNEC (Soil)</b>                                      |                          |
| PNEC soil   | 4.59 mg/kg dwt           |
| <b>PNEC (STP)</b>                                       |                          |
| PNEC sewage treatment plant                             | 100 mg/l                 |
| <b>dipropylene glycol monomethyl ether (34590-94-8)</b> |                          |
| <b>DNEL/DMEL (Workers)</b>                              |                          |
| Long-term - systemic effects, dermal                    | 283 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation                | 308 mg/m <sup>3</sup>    |
| <b>DNEL/DMEL (General population)</b>                   |                          |
| Long-term - systemic effects, oral                      | 36 mg/kg bodyweight/day  |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| <b>dipropylene glycol monomethyl ether (34590-94-8)</b> |                          |
|---|--------------------------|
| Long-term - systemic effects, inhalation                | 37.2 mg/m <sup>3</sup>   |
| Long-term - systemic effects, dermal                    | 121 mg/kg bodyweight/day |
| <b>PNEC (Water)</b>                                     |                          |
| PNEC aqua (freshwater)                                  | 19 mg/l                  |
| PNEC aqua (marine water)                                | 1.9 mg/l                 |
| PNEC aqua (intermittent, freshwater)                    | 190 mg/l                 |
| <b>PNEC (Sediment)</b>                                  |                          |
| PNEC sediment (freshwater)                              | 70.2 mg/kg dwt           |
| PNEC sediment (marine water)                            | 7.02 mg/kg dwt           |
| <b>PNEC (Soil)</b>                                      |                          |
| PNEC soil   | 2.74 mg/kg dwt           |
| <b>PNEC (STP)</b>                                       |                          |
| PNEC sewage treatment plant                             | 4168 mg/l                |
| <b>Xylene (1330-20-7)</b>                               |                          |
| <b>DNEL/DMEL (Workers)</b>                              |                          |
| Acute - systemic effects, inhalation                    | 289 mg/m <sup>3</sup>    |
| Acute - local effects, inhalation                       | 289 mg/m <sup>3</sup>    |
| Long-term - systemic effects, dermal                    | 180 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation                | 77 mg/m <sup>3</sup>     |
| Long-term - local effects, inhalation                   | 77 mg/m <sup>3</sup>     |
| <b>DNEL/DMEL (General population)</b>                   |                          |
| Acute - systemic effects, inhalation                    | 174 mg/m <sup>3</sup>    |
| Acute - local effects, inhalation                       | 174 mg/m <sup>3</sup>    |
| Long-term - systemic effects, oral                      | 1.6 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation                | 14.8 mg/m <sup>3</sup>   |
| Long-term - systemic effects, dermal                    | 108 mg/kg bodyweight/day |
| Long-term - local effects, inhalation                   | 65.3 mg/m <sup>3</sup>   |
| <b>PNEC (Water)</b>                                     |                          |
| PNEC aqua (freshwater)                                  | 0.327 mg/l               |
| PNEC aqua (marine water)                                | 0.327 mg/l               |
| PNEC aqua (intermittent, freshwater)                    | 0.327 mg/l               |
| <b>PNEC (Sediment)</b>                                  |                          |
| PNEC sediment (freshwater)                              | 12.46 mg/kg dwt          |
| PNEC sediment (marine water)                            | 12.46 mg/kg dwt          |
| <b>PNEC (Soil)</b>                                      |                          |
| PNEC soil   | 2.31 mg/kg dwt           |
| <b>PNEC (STP)</b>                                       |                          |
| PNEC sewage treatment plant                             | 6.58 mg/l                |



# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| ethylbenzene (100-41-4)                  |                          |
|--|--------------------------|
| <b>DNEL/DMEL (Workers)</b>               |                          |
| Acute - local effects, inhalation        | 293 mg/m <sup>3</sup>    |
| Long-term - systemic effects, dermal     | 180 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 77 mg/m <sup>3</sup>     |
| <b>DNEL/DMEL (General population)</b>    |                          |
| Long-term - systemic effects, oral       | 1.6 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 15 mg/m <sup>3</sup>     |
| <b>PNEC (Water)</b>                      |                          |
| PNEC aqua (freshwater)                   | 0.1 mg/l                 |
| PNEC aqua (marine water)                 | 0.01 mg/l                |
| PNEC aqua (intermittent, freshwater)     | 0.1 mg/l                 |
| <b>PNEC (Sediment)</b>                   |                          |
| PNEC sediment (freshwater)               | 13.7 mg/kg dwt           |
| PNEC sediment (marine water)             | 1.37 mg/kg dwt           |
| <b>PNEC (Soil)</b>                       |                          |
| PNEC soil                                | 2.68 mg/kg dwt           |
| <b>PNEC (Oral)</b>                       |                          |
| PNEC oral (secondary poisoning)          | 0.02 g/kg food           |
| <b>PNEC (STP)</b>                        |                          |
| PNEC sewage treatment plant              | 9.6 mg/l                 |

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses

| Eye protection |                      |                 |          |
|----------------|----------------------|-----------------|----------|
| Type           | Field of application | Characteristics | Standard |
| Safety glasses | Dust                 | clear           |          |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

| Hand protection   |  |                   |                |             |          |
|-------------------|--|-------------------|----------------|-------------|----------|
| Type              | Material   | Permeation        | Thickness (mm) | Penetration | Standard |
| Protective gloves | Nitrile rubber (NBR),<br>Neoprene rubber (HNBR),<br>Polyvinylalcohol (PVA),<br>Viton | 6 (> 480 minutes) | 0.4            |             | EN 374-3 |

#### Other skin protection

#### Materials for protective clothing:

Impermeable clothing

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

| Respiratory protection           |   |                   |  |
|----------------------------------|---|-------------------|--|
| Device                           | Filter type   | Condition         | Standard                                     |
| Breathing apparatus, Gas filters | Type A - High-boiling (>65 °C)<br>organic compounds | Vapour protection | EN 140, EN 136,<br>EN 143, EN 145,<br>EN 149 |

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                           |                                       |
|---------------------------|---------------------------------------|
| Physical state            | : Solid                               |
| Colour                    | : Beige.                              |
| Appearance                | : Paste.                              |
| Odour                     | : aromatic.                           |
| Odour threshold           | : Not available                       |
| Melting point             | : Not available                       |
| Freezing point            | : Not applicable                      |
| Boiling point             | : Not available                       |
| Flammability              | : Non flammable.                      |
| Explosive limits          | : Not applicable                      |
| Lower explosion limit     | : Not applicable                      |
| Upper explosion limit     | : Not applicable                      |
| Flash point               | : 32 °C (does not sustain combustion) |
| Auto-ignition temperature | : Not applicable                      |
| Decomposition temperature | : Not available                       |
| pH                        | : Not available                       |
| pH solution               | : Not available                       |
| Viscosity, kinematic      | : > 20.5 mm <sup>2</sup> /s           |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

|   |   |
|---|---|
| Solubility                                      | : insoluble in water. soluble in most organic solvents. |
| Partition coefficient n-octanol/water (Log Kow) | : Not available   |
| Vapour pressure                                 | : Not available   |
| Vapour pressure at 50 °C                        | : Not available   |
| Density   | : 1.81 (1.79 – 1.83) g/cm <sup>3</sup>                  |
| Relative density                                | : Not applicable  |
| Relative vapour density at 20 °C                | : Not applicable  |
| Particle size                                   | : Not available   |
| Particle size distribution                      | : Not available   |
| Particle shape                                  | : Not available   |
| Particle aspect ratio                           | : Not available   |
| Particle aggregation state                      | : Not available   |
| Particle agglomeration state                    | : Not available   |
| Particle specific surface area                  | : Not available   |
| Particle dustiness                              | : Not available   |

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Not sustained combustibility : Yes

#### 9.2.2. Other safety characteristics

VOC content : 221 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| styrene (100-42-5)    |  |
|-----------------------|--|
| LD50 oral rat         | 5000 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 14 day(s))            |
| LD50 dermal rat       | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat | 11.8 mg/l (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours))                |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| <b>oxirane, 2-methyl-, polymer with oxirane, mono[(diethylamino)alkyl] ether (68511-96-6)</b> |  |
|---|--|
| LD50 oral rat   | > 5000 mg/kg   |
| LD50 dermal rabbit  | > 2000   |
| <b>iron(III) oxide (1309-37-1)</b>  |  |
| LD50 oral rat   | > 10000 mg/kg bodyweight (Rat, Male, Experimental value, Oral)   |
| <b>bisphenol-A-(epichlorhydrin), epoxy resin (25068-38-6)</b>                                 |  |
| LD50 oral rat   | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)                 |
| LD50 dermal rat   | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))   |
| <b>phthalic anhydride (85-44-9)</b>   |  |
| LD50 oral rat   | 1530 mg/kg bodyweight Animal: rat, Animal sex: male  |
| LD50 dermal rabbit  | > 3160 mg/kg (Rabbit, Experimental value, Dermal, 14 day(s))   |
| LC50 Inhalation - Rat   | > 2.14 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)   |
| <b>1,4-naphthoquinone (130-15-4)</b>  |  |
| LD50 oral rat   | 190 mg/kg bodyweight (Rat, Literature study, Oral)   |
| LD50 dermal rat   | 202 mg/kg  |
| LC50 Inhalation - Rat (Vapours)   | 0.046 mg/l/4h  |
| <b>ethanediol; ethylene glycol (107-21-1)</b>   |  |
| LD50 oral rat   | 7712 mg/kg bodyweight Animal: rat  |
| LD50 dermal   | > 3500 mg/kg bodyweight (Mouse, Male / female, Experimental value, Dermal)   |
| LC50 Inhalation - Rat   | > 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))   |
| <b>1-methoxy-2-propanol (107-98-2)</b>  |  |
| LD50 oral rat   | 4016 mg/kg bodyweight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rat   | 13 g/kg  |
| <b>dipropylene glycol monomethyl ether (34590-94-8)</b>                                       |  |
| LD50 oral rat   | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)   |
| LD50 dermal rat   | > 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)  |
| LD50 dermal rabbit  | 9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)                                    |
| <b>Xylene (1330-20-7)</b>   |  |
| LD50 oral rat   | 3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))            |
| LD50 dermal rat   | 12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)             |
| LD50 dermal rabbit  | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male  |
| LC50 Inhalation - Rat [ppm]   | 6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)   |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| <b>ethylbenzene (100-41-4)</b>   |  |
|--|--|
| LD50 oral rat  | 3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))   |
| LD50 dermal rabbit   | 15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)  |
| LC50 Inhalation - Rat  | 17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))   |
| <b>barium sulfate (7727-43-7)</b>  |  |
| LD50 oral rat  | > 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))   |
| LD50 dermal rat  | > 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, Rat, Read-across, Dermal)  |
| <b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b> |  |
| LD50 oral rat  | > 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)   |
| LC50 Inhalation - Rat  | > 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))  |
| <b>dolomite (16389-88-1)</b>   |  |
| LD50 oral rat  | > 2000 mg/kg (OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), rat, female, Experimental value)  |
| <b>talc (14807-96-6)</b>   |  |
| LD50 oral rat  | > 5000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))   |
| LD50 dermal rat  | > 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))   |
| LC50 Inhalation - Rat  | > 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))   |
| <b>magnesium carbonate (546-93-0)</b>  |  |
| LD50 oral rat  | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)  |
| <b>Calcium carbonate (1317-65-3)</b>   |  |
| LD50 oral rat  | 6450 mg/kg (Rat, Literature study, Oral)   |
| Skin corrosion/irritation  | : Causes skin irritation.  |
| Serious eye damage/irritation  | : Causes serious eye irritation.   |
| Respiratory or skin sensitisation  | : Not classified   |
| Germ cell mutagenicity   | : Not classified   |
| Carcinogenicity  | : Not classified.  |
| <b>styrene (100-42-5)</b>  |  |
| IARC group   | 2B - Possibly carcinogenic to humans   |
| <b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b> |  |
| IARC group   | 2B - Possibly carcinogenic to humans   |
| <b>bisphenol-A-(epichlorhydrin), epoxy resin (25068-38-6)</b>  |  |
| NOAEL (chronic, oral, animal/male, 2 years)  | 15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information) |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| <b>bisphenol-A-(epichlorhydrin), epoxy resin (25068-38-6)</b> |   |
|---|---|
| NOAEL (chronic, oral, animal/female, 2 years)                 | 100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information) |
| <b>phthalic anhydride (85-44-9)</b>                           |   |
| NOAEL (chronic, oral, animal/male, 2 years)                   | 3570 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)  |
| NOAEL (chronic, oral, animal/female, 2 years)                 | 1785 mg/kg bodyweight Animal: mouse, Animal sex: female, Remarks on results: other:Effect type: carcinogenicity (migrated information)  |
| <b>ethanediol; ethylene glycol (107-21-1)</b>                 |   |
| NOAEL (chronic, oral, animal/male, 2 years)                   | 1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)  |
| <b>barium sulfate (7727-43-7)</b>                             |   |
| NOAEL (chronic, oral, animal/male, 2 years)                   | 60 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)  |
| NOAEL (chronic, oral, animal/female, 2 years)                 | 75 mg/kg bodyweight Animal: rat, Animal sex: female, Remarks on results: other:Effect type: carcinogenicity (migrated information)  |
| Reproductive toxicity   | : Suspected of damaging fertility or the unborn child.  |
| <b>phthalic anhydride (85-44-9)</b>                           |   |
| NOAEL (animal/male, F0/P)                                     | 3570 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Generation: all major organs incl. reproductive organs were examined (migrated information)  |
| NOAEL (animal/female, F0/P)                                   | 1785 mg/kg bodyweight Animal: mouse, Animal sex: female, Remarks on results: other:Generation: all major organs incl. reproductive organs were examined (migrated information)  |
| STOT-single exposure  | : Not classified  |
| <b>styrene (100-42-5)</b>                                     |   |
| STOT-single exposure  | May cause respiratory irritation.   |
| <b>phthalic anhydride (85-44-9)</b>                           |   |
| STOT-single exposure  | May cause respiratory irritation.   |
| <b>1,4-naphthoquinone (130-15-4)</b>                          |   |
| STOT-single exposure  | May cause respiratory irritation.   |
| <b>1-methoxy-2-propanol (107-98-2)</b>                        |   |
| STOT-single exposure  | May cause drowsiness or dizziness.  |
| <b>Xylene (1330-20-7)</b>                                     |   |
| STOT-single exposure  | May cause respiratory irritation.   |
| STOT-repeated exposure  | : Causes damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).   |
| <b>styrene (100-42-5)</b>                                     |   |
| LOAEL (oral, rat, 90 days)                                    | 2000 mg/kg bodyweight Animal: rat   |
| LOAEC (inhalation, rat, vapour, 90 days)                      | 0.21 mg/l air Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)  |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| <b>styrene (100-42-5)</b>                               |   |
|---|---|
| NOAEL (oral, rat, 90 days)                              | 1000 mg/kg bodyweight Animal: rat   |
| NOAEL (subchronic, oral, animal/male, 90 days)          | 10 mg/kg bodyweight Animal: mouse, Animal sex: male   |
| STOT-repeated exposure                                  | Causes damage to organs (hearing sense) through prolonged or repeated exposure (if inhaled).  |
| <b>phthalic anhydride (85-44-9)</b>                     |   |
| LOAEL (oral, rat, 90 days)                              | 2500 mg/kg bodyweight Animal: rat, Animal sex: male   |
| <b>ethanediol; ethylene glycol (107-21-1)</b>           |   |
| STOT-repeated exposure                                  | May cause damage to organs through prolonged or repeated exposure.  |
| <b>1-methoxy-2-propanol (107-98-2)</b>                  |   |
| LOAEL (oral, rat, 90 days)                              | 2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)  |
| NOAEL (oral, rat, 90 days)                              | 919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)   |
| NOAEL (dermal, rat/rabbit, 90 days)                     | > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)  |
| <b>dipropylene glycol monomethyl ether (34590-94-8)</b> |   |
| NOAEL (oral, rat, 90 days)                              | 1000 mg/kg bodyweight Animal: rat, Guideline: other:KANPOGYO No.700, YAKUHATSU No. 1039.61, and KIKYKU No. 1014.  |
| NOAEL (dermal, rat/rabbit, 90 days)                     | 2850 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)  |
| <b>Xylene (1330-20-7)</b>                               |   |
| LOAEL (oral, rat, 90 days)                              | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
| STOT-repeated exposure                                  | May cause damage to organs through prolonged or repeated exposure.  |
| <b>ethylbenzene (100-41-4)</b>                          |   |
| NOAEL (oral, rat, 90 days)                              | 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)  |
| STOT-repeated exposure                                  | May cause damage to organs (hearing sense) through prolonged or repeated exposure.  |
| Aspiration hazard                                       | : Not classified  |
| <b>TOPSTOP GOLD EASY SANDING STOPPER</b>                |   |
| Viscosity, kinematic                                    | > 20.5 mm <sup>2</sup> /s   |

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

|  |   |
|--|---|
| Ecology - general  | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified  |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long-term (chronic) : Not classified

| <b>styrene (100-42-5)</b> |  |
|---------------------------|--|
| LC50 - Fish [1]           | 10 mg/l Test organisms (species): Pimephales promelas  |
| EC50 - Crustacea [1]      | 4.7 mg/l Test organisms (species): Daphnia magna   |
| EC50 72h - Algae [1]      | 4.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| EC50 96h - Algae [1]      | 6.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| ErC50 algae               | 4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)          |
| LOEC (chronic)            | 2.06 mg/l Test organisms (species): Daphnia magna Duration: '21 d'   |
| NOEC (chronic)            | 1.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'   |

| <b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b> |  |
|--|--|
| LC50 - Fish [1]  | 155 mg/l Test organisms (species): other:Japanese Medaka   |
| EC50 - Crustacea [1]   | 19.3 mg/l Test organisms (species): Daphnia magna  |
| EC50 - Crustacea [2]   | 27.8 mg/l Test organisms (species): Daphnia magna  |
| EC50 72h - Algae [1]   | > 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| ErC50 algae  | 61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)   |
| NOEC (chronic)   | ≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'   |

### 12.2. Persistence and degradability

| <b>styrene (100-42-5)</b>     |  |
|-------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Chemical oxygen demand (COD)  | 2.8 g O <sub>2</sub> /g substance                          |
| ThOD                          | 3.07 g O <sub>2</sub> /g substance                         |
| BOD (% of ThOD)               | 0.42 (Literature study)                                    |

| <b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b> |                                   |
|--|-----------------------------------|
| Persistence and degradability  | Biodegradability: not applicable. |
| Chemical oxygen demand (COD)   | Not applicable (inorganic)        |
| ThOD   | Not applicable (inorganic)        |

### 12.3. Bioaccumulative potential

| <b>styrene (100-42-5)</b>                       |   |
|---|---|
| BCF - Fish [1]                                  | 74 (Calculated value)   |
| Partition coefficient n-octanol/water (Log Pow) | 2.96 (Practical experience/observation, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Bioaccumulative potential                       | Low potential for bioaccumulation (BCF < 500).  |

| <b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b> |                      |
|--|----------------------|
| Bioaccumulative potential  | Not bioaccumulative. |



# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.4. Mobility in soil

#### styrene (100-42-5)

|  |                                       |
|--|---------------------------------------|
| Surface tension  | No data available in the literature   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.55 (log Koc, Estimated value)       |
| Ecology - soil   | Low potential for adsorption in soil. |

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7)

|                |                                     |
|----------------|-------------------------------------|
| Ecology - soil | Low potential for mobility in soil. |
|----------------|-------------------------------------|

### 12.5. Results of PBT and vPvB assessment

#### Component

|  |   |
|--|---|
| styrene (100-42-5)   | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII |

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number or ID number

UN-No. (ADR) : Not regulated  
UN-No. (IMDG) : Not regulated  
UN-No. (IATA) : Not regulated  
UN-No. (ADN) : Not regulated  
UN-No. (RID) : Not regulated

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not regulated  
Proper Shipping Name (IMDG) : Not regulated  
Proper Shipping Name (IATA) : Not regulated  
Proper Shipping Name (ADN) : Not regulated  
Proper Shipping Name (RID) : Not regulated

### 14.3. Transport hazard class(es)

**ADR**  
Transport hazard class(es) (ADR) : Not regulated

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### IMDG

Transport hazard class(es) (IMDG) : Not regulated

### IATA

Transport hazard class(es) (IATA) : Not regulated

### ADN

Transport hazard class(es) (ADN) : Not regulated

### RID

Transport hazard class(es) (RID) : Not regulated

## 14.4. Packing group

Packing group (ADR) : Not regulated

Packing group (IMDG) : Not regulated

Packing group (IATA) : Not regulated

Packing group (ADN) : Not regulated

Packing group (RID) : Not regulated

## 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

## 14.6. Special precautions for user

### Overland transport

Not regulated

### Transport by sea

Not regulated

### Air transport

Not regulated

### Inland waterway transport

Not regulated

### Rail transport

Not regulated

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

| EU restriction list (REACH Annex XVII) |               |  |
|--|---------------|--|
| Reference code                         | Applicable on | Entry title or description   |
| 3(a)                                   | styrene       | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| EU restriction list (REACH Annex XVII) |               |  |
|--|---------------|--|
| Reference code                         | Applicable on | Entry title or description   |
| 3(b)                                   | styrene       | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10  |
| 3(c)                                   | styrene       | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1  |
| 40.                                    | styrene       | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not. |

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 221 g/l

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Indication of changes:

Modified.

| Indication of changes |   |          |                                    |
|-----------------------|---|----------|------------------------------------|
| Section               | Changed item  | Change   | Comments                           |
|                       | Indication of changes   | Added    |                                    |
|                       | Revision date   | Modified |                                    |
| 1.2                   | Industrial/Professional use spec                                | Added    |                                    |
| 2.1                   | Adverse physicochemical, human health and environmental effects | Modified |                                    |
| 6.1                   | Emergency procedures  | Modified |                                    |
| 7.1                   | Precautions for safe handling                                   | Modified |                                    |
| 9.1                   |   | Removed  | VOC regulatory uninherited/removed |

### Abbreviations and acronyms:

|     |   |
|-----|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road             |
| ATE | Acute Toxicity Estimate   |
| BLV | Biological limit value  |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

|         |   |
|---------|---|
| CAS-No. | Chemical Abstract Service number  |
| CLP     | Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008                       |
| DMEL    | Derived Minimal Effect level  |
| DNEL    | Derived-No Effect Level   |
| EC50    | Median effective concentration  |
| EC-No.  | European Community number   |
| EN      | European Standard   |
| IATA    | International Air Transport Association   |
| IMDG    | International Maritime Dangerous Goods  |
| LC50    | Median lethal concentration   |
| LD50    | Median lethal dose  |
| LOAEL   | Lowest Observed Adverse Effect Level  |
| NOAEC   | No-Observed Adverse Effect Concentration  |
| NOAEL   | No-Observed Adverse Effect Level  |
| NOEC    | No-Observed Effect Concentration  |
| OEL     | Occupational Exposure Limit   |
| PBT     | Persistent Bioaccumulative Toxic  |
| PNEC    | Predicted No-Effect Concentration   |
| REACH   | Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 |
| RID     | Regulations concerning the International Carriage of Dangerous Goods by Rail                      |
| SDS     | Safety Data Sheet   |
| vPvB    | Very Persistent and Very Bioaccumulative  |
| WGK     | Water Hazard Class  |

### Full text of H- and EUH-statements:

|                                  |   |
|----------------------------------|---|
| Acute Tox. 4 (Inhalation)        | Acute toxicity (inhal.), Category 4                               |
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4                     |
| Aquatic Chronic 3                | Hazardous to the aquatic environment — Chronic Hazard, Category 3 |
| Asp. Tox. 1                      | Aspiration hazard, Category 1                                     |
| Carc. 2                          | Carcinogenicity, Category 2                                       |
| Eye Irrit. 2                     | Serious eye damage/eye irritation, Category 2                     |
| Flam. Liq. 3                     | Flammable liquids, Category 3                                     |
| H226                             | Flammable liquid and vapour.                                      |
| H304                             | May be fatal if swallowed and enters airways.                     |
| H315                             | Causes skin irritation.   |
| H319                             | Causes serious eye irritation.                                    |
| H332                             | Harmful if inhaled.   |
| H335                             | May cause respiratory irritation.                                 |

# TOPSTOP GOLD EASY SANDING STOPPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Full text of H- and EUH-statements: |  |
|-------------------------------------|--|
| H351                                | Suspected of causing cancer.   |
| H361                                | Suspected of damaging fertility or the unborn child.                                       |
| H361d                               | Suspected of damaging the unborn child.  |
| H372                                | Causes damage to organs through prolonged or repeated exposure.                            |
| H412                                | Harmful to aquatic life with long lasting effects.   |
| Repr. 2                             | Reproductive toxicity, Category 2  |
| Skin Irrit. 2                       | Skin corrosion/irritation, Category 2  |
| STOT RE 1                           | Specific target organ toxicity — Repeated exposure, Category 1                             |
| STOT SE 3                           | Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation |

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).