



TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 2/23/2017 Revision date: 11/10/2017 Supersedes: 2/23/2017 Version: 1.1

DRIVING SURFACE PERFECTION

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)
Vaporizer : Aerosol
Product group : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only
Function or use category : Aerosol

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

U-POL LIMITED
Denington Road, Wellingborough
Northants, NN8 2QH - UK
T +44 (0) 1933 230310 - F +44 (0) 1933 425797
technical.department@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - +44 (0) 870 8200418 (24 hrs)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazardous ingredients :

ethyl methyl ketone; Solvent naphtha (petroleum), light aromatic; toluene; n-butyl acetate; methyl acetate; Acetone

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing fume, spray, vapours.
P280 - Wear protective gloves, protective clothing, eye protection.
P305 - IF IN EYES: Rinse first with plenty of water and if necessary take medical advice
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene), reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|--------|--|
| methyl acetate | (CAS-No.) 79-20-9 (EC-No.) 201-185-2 (EC Index-No.) 607-021-00-X (REACH-no) 01-2119459211-47 | 5 - 23 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| Acetone | (CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49 | 5 - 23 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| xylene (Note C) | (CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32 | < 23 | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 |
| ethyl methyl ketone | (CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43 | < 5 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| 2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit | (CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 | < 5 | Flam. Liq. 3, H226 |
| Solvent naphtha (petroleum), light aromatic | (EC-No.) 918-668-5 | < 5 | Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |
| cyclohexanone | (CAS-No.) 108-94-1 (EC-No.) 203-631-1 (EC Index-No.) 606-010-00-7 (REACH-no) 01-2119453616-35 | < 5 | Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 |
| 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve | (CAS-No.) 111-76-2 (EC-No.) 203-905-0 (EC Index-No.) 603-014-00-0 (REACH-no) 01-2119475108-36 | < 5 | Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 |
| reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) | (EC-No.) 400-830-7 (EC Index-No.) 607-176-00-3 | < 5 | Skin Sens. 1, H317 Aquatic Chronic 2, H411 |
| reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | (CAS-No.) 1065336-91-5 (EC-No.) 915-687-0 (REACH-no) 01-2119491304-40 | < 5 | Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| ethylbenzene substance with a Community workplace exposure limit | (CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35 | < 5 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE 2, H373 Asp. Tox. 1, H304 |

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | | | |
|--|--|-----|--|
| toluene substance with a Community workplace exposure limit | (CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51 | < 5 | Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 |
|--|--|-----|--|

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Repeated exposure may cause skin dryness or cracking. |
| Symptoms/effects after eye contact | : Eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|------------------------------|----------------------------------|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. |
|------------------------------|----------------------------------|

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| Fire hazard | : Extremely flammable aerosol. |
| Explosion hazard | : Pressurised container: May burst if heated. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Advice for firefighters

| | |
|--------------------------------|--|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
|--------------------------------|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

| | |
|----------------------|---|
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, fume, spray. Avoid contact with skin and eyes. |
|----------------------|---|

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|---|
| Methods for cleaning up | : Mechanically recover the product. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-------------------------------|---|
| Precautions for safe handling | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, fume, spray. Avoid contact with skin and eyes. Wear personal protective equipment. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| ethyl methyl ketone (78-93-3) | | |
|-------------------------------|---------------------------------|---|
| EU | Local name | Butanone |
| EU | IOELV TWA (mg/m ³) | 600 mg/m ³ |
| EU | IOELV TWA (ppm) | 200 ppm |
| EU | IOELV STEL (mg/m ³) | 900 mg/m ³ |
| EU | IOELV STEL (ppm) | 300 ppm |
| United Kingdom | Local name | Butan-2-one (methyl ethyl ketone) |
| United Kingdom | WEL TWA (mg/m ³) | 600 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 200 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 899 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 300 ppm |
| United Kingdom | Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2) |
| xylene (1330-20-7) | | |
| EU | Local name | Xylene, mixed isomers, pure |
| EU | IOELV TWA (mg/m ³) | 221 mg/m ³ |
| EU | IOELV TWA (ppm) | 50 ppm |
| EU | IOELV STEL (mg/m ³) | 442 mg/m ³ |
| EU | IOELV STEL (ppm) | 100 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | Xylene, o-,m-,p- or mixed isomers |
| United Kingdom | WEL TWA (mg/m ³) | 220 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 50 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 441 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 100 ppm |
| United Kingdom | Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2) |
| ethylbenzene (100-41-4) | | |
| EU | Local name | Ethylbenzene |
| EU | IOELV TWA (mg/m ³) | 442 mg/m ³ |
| EU | IOELV TWA (ppm) | 100 ppm |
| EU | IOELV STEL (mg/m ³) | 884 mg/m ³ |
| EU | IOELV STEL (ppm) | 200 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | Ethylbenzene |
| United Kingdom | WEL TWA (mg/m ³) | 441 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 100 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 552 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 125 ppm |
| United Kingdom | Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| toluene (108-88-3) | | |
| EU | Local name | Toluène |
| EU | IOELV TWA (mg/m ³) | 192 mg/m ³ |
| EU | IOELV TWA (ppm) | 50 ppm |
| EU | IOELV STEL (mg/m ³) | 384 mg/m ³ |

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| toluene (108-88-3) | | |
|--|---------------------------------|---|
| EU | IOELV STEL (ppm) | 100 ppm |
| EU | Notes | Peau |
| United Kingdom | Local name | Toulene |
| United Kingdom | WEL TWA (mg/m ³) | 191 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 50 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 384 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 100 ppm |
| United Kingdom | Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| cyclohexanone (108-94-1) | | |
| EU | Local name | Cyclohexanone |
| EU | IOELV TWA (mg/m ³) | 40.8 mg/m ³ |
| EU | IOELV TWA (ppm) | 10 ppm |
| EU | IOELV STEL (mg/m ³) | 81.6 mg/m ³ |
| EU | IOELV STEL (ppm) | 20 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | Cyclohexanone |
| United Kingdom | WEL TWA (mg/m ³) | 41 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 10 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 82 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 20 ppm |
| United Kingdom | Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2) |
| 2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2) | | |
| EU | Local name | 2-Butoxyethanol |
| EU | IOELV TWA (mg/m ³) | 98 mg/m ³ |
| EU | IOELV TWA (ppm) | 20 ppm |
| EU | IOELV STEL (mg/m ³) | 246 mg/m ³ |
| EU | IOELV STEL (ppm) | 50 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | 2-Butoxyethanol |
| United Kingdom | WEL TWA (mg/m ³) | 123 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 25 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 246 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 50 ppm |
| United Kingdom | Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2) |
| 2-methoxy-1-methylethyl acetate (108-65-6) | | |
| EU | Local name | 2-Methoxy-1-methylethylacetate |
| EU | IOELV TWA (mg/m ³) | 275 mg/m ³ |
| EU | IOELV TWA (ppm) | 50 ppm |
| EU | IOELV STEL (mg/m ³) | 550 mg/m ³ |
| EU | IOELV STEL (ppm) | 100 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | 1-Methoxypropyl acetate |
| United Kingdom | WEL TWA (mg/m ³) | 274 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 50 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 548 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 100 ppm |
| United Kingdom | Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| methyl acetate (79-20-9) | | |
| United Kingdom | Local name | Methyl acetate |

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| methyl acetate (79-20-9) | | |
|--------------------------|--------------------------------|------------------------|
| United Kingdom | WEL TWA (mg/m ³) | 616 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 200 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 770 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 250 ppm |
| Acetone (67-64-1) | | |
| EU | Local name | Acetone |
| EU | IOELV TWA (mg/m ³) | 1210 mg/m ³ |
| EU | IOELV TWA (ppm) | 500 ppm |
| United Kingdom | Local name | Acetone |
| United Kingdom | WEL TWA (mg/m ³) | 1210 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 500 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 3620 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 1500 ppm |

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : Liquid |
| Colour | : Black. |
| Odour | : No data available |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : -60 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Log Pow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : Pressurised container: May burst if heated. |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

VOC content : 675 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

| | |
|-----------|---------|
| Vaporizer | Aerosol |
|-----------|---------|

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

Solvent naphtha (petroleum), light aromatic

| | |
|-------------------------------|---|
| Persistence and degradability | May cause long-term adverse effects in the environment. |
|-------------------------------|---|

12.3. Bioaccumulative potential

Solvent naphtha (petroleum), light aromatic

| | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |
|---------------------------|------------------|

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.






TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

| ADR | IMDG | IATA | ADN | RID |
|--|---|---|--|---|
| 14.1. UN number | | | | |
| 1950 | 1950 | 1950 | 1950 | 1950 |
| 14.2. UN proper shipping name | | | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable | AEROSOLS | AEROSOLS |
| Transport document description | | | | |
| UN 1950 AEROSOLS, 2.1, (D) | UN 1950 AEROSOLS, 2.1 | UN 1950 Aerosols, flammable, 2.1 | UN 1950 AEROSOLS, 2.1 | UN 1950 AEROSOLS, 2.1 |
| 14.3. Transport hazard class(es) | | | | |
| 2.1 | 2.1 | 2.1 | 2.1 | 2.1 |
|  |  |  |  |  |
| 14.4. Packing group | | | | |
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment : No | Dangerous for the environment : No Marine pollutant : No | Dangerous for the environment : No | Dangerous for the environment : No | Dangerous for the environment : No |
| No supplementary information available | | | | |

14.6. Special precautions for user

- Overland transport

| | |
|---|----------------------|
| Classification code (ADR) | : 5F |
| Special provisions (ADR) | : 190, 327, 344, 625 |
| Limited quantities (ADR) | : 11 |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P207, LP02 |
| Special packing provisions (ADR) | : PP87, RR6, L2 |
| Mixed packing provisions (ADR) | : MP9 |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Packages (ADR) | : V14 |
| Special provisions for carriage - Loading, unloading and handling (ADR) | : CV9, CV12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Tunnel restriction code (ADR) | : D |

- Transport by sea

| | |
|-----------------------------------|-------------------------------|
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 959 |
| Limited quantities (IMDG) | : SP277 |
| Excepted quantities (IMDG) | : E0 |
| Packing instructions (IMDG) | : P207, LP02 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D |
| EmS-No. (Spillage) | : S-U |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |

- Air transport

| | |
|--|---------|
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|---------------------------------|--------------------|
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

- Inland waterway transport

| | |
|-----------------------------------|----------------------|
| Classification code (ADN) | : 5F |
| Special provisions (ADN) | : 190, 327, 344, 625 |
| Limited quantities (ADN) | : 1 L |
| Excepted quantities (ADN) | : E0 |
| Equipment required (ADN) | : PP, EX, A |
| Ventilation (ADN) | : VE01, VE04 |
| Number of blue cones/lights (ADN) | : 1 |

- Rail transport

| | |
|---|----------------------|
| Classification code (RID) | : 5F |
| Special provisions (RID) | : 190, 327, 344, 625 |
| Limited quantities (RID) | : 1L |
| Excepted quantities (RID) | : E0 |
| Packing instructions (RID) | : P207, LP02 |
| Special packing provisions (RID) | : PP87, RR6, L2 |
| Mixed packing provisions (RID) | : MP9 |
| Transport category (RID) | : 2 |
| Special provisions for carriage – Packages (RID) | : W14 |
| Special provisions for carriage - Loading, unloading and handling (RID) | : CW9, CW12 |
| Colis express (express parcels) (RID) | : CE2 |
| Hazard identification number (RID) | : 23 |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

VOC content : 675 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

| | |
|-------------------------------------|---|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aerosol 1 | Aerosol, Category 1 |
| Aquatic Acute 1 | Hazardous to the aquatic environment — Acute Hazard, Category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment — Chronic Hazard, Category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment — Chronic Hazard, Category 2 |

TRIM #11 GLOSS BLACK AEROSOL (TRIMGB/AL)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | | |
|---------------|---|-----------------------|
| Asp. Tox. 1 | Aspiration hazard, Category 1 | |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 | |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 | |
| Flam. Liq. 2 | Flammable liquids, Category 2 | |
| Flam. Liq. 3 | Flammable liquids, Category 3 | |
| Repr. 2 | Reproductive toxicity, Category 2 | |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 | |
| Skin Sens. 1 | Skin sensitisation, Category 1 | |
| Skin Sens. 1A | Skin sensitisation, category 1A | |
| STOT RE 2 | Specific target organ toxicity — Repeated exposure, Category 2 | |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis | |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation | |
| H222 | Extremely flammable aerosol. | |
| H225 | Highly flammable liquid and vapour. | |
| H226 | Flammable liquid and vapour. | |
| H229 | Pressurised container: May burst if heated. | |
| H302 | Harmful if swallowed. | |
| H304 | May be fatal if swallowed and enters airways. | |
| H312 | Harmful in contact with skin. | |
| H315 | Causes skin irritation. | |
| H317 | May cause an allergic skin reaction. | |
| H318 | Causes serious eye damage. | |
| H319 | Causes serious eye irritation. | |
| H332 | Harmful if inhaled. | |
| H335 | May cause respiratory irritation. | |
| H336 | May cause drowsiness or dizziness. | |
| H361d | Suspected of damaging the unborn child | |
| H373 | May cause damage to organs through prolonged or repeated exposure. | |
| H400 | Very toxic to aquatic life. | |
| H410 | Very toxic to aquatic life with long lasting effects. | |
| H411 | Toxic to aquatic life with long lasting effects. | |
| EUH066 | Repeated exposure may cause skin dryness or cracking. | |
| EUH208 | Contains reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene), reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction. | |
| Aerosol 1 | H222;H229 | On basis of test data |
| Eye Irrit. 2 | H319 | Calculation method |
| STOT SE 3 | H336 | Calculation method |

UPOL SDS EU (no product code)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.