



DRIVING SURFACE PERFECTION

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations
Issue date: 4/05/2017 Revision date: 20/12/2021 Supersedes: 11/07/2019 Version: 3.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Trade name : TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL
Product code : TRIMGW/AL

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Topcoat

1.4. Details of manufacturer or importer

Supplier

U-POL Australia Pty Limited Ltd
Unit A, 16 - 20 Cassola Place
Penrith NSW 2750
Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.co.au - www.u-pol.com

Supplier

U-POL New Zealand Limited Ltd
c/o Lindsay & Associates Unit H, 12 Amara Place, East Tamaki
Manukau City Auckland 2013
New Zealand
T + 612 4731 2655 - F + 612 4731 2611
info@u-pol.co.nz - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

| | |
|--|-----------|
| Aerosol, Category 1 | H222;H229 |
| Serious eye damage/eye irritation, Category 2A | H319 |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis | H336 |

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)



Signal word (GHS AU)

: Danger

Contains

: methyl acetate (30 – 60 %); n-butyl acetate (10 – 30 %); hydrocarbons, C9, aromatics (< 10 %)

Hazard statements (GHS AU)

: H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

P261 - Avoid breathing vapours, spray, fume.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective gloves.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Unknown acute toxicity (GHS AU) : 32.5% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

| Name | CAS-No. | % | Classification according to the model Work Health and Safety Regulations (WHS Regulations) |
|---|------------|---------|--|
| methyl acetate | 79-20-9 | 30 – 60 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| n-butyl acetate | 123-86-4 | 10 – 30 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| hydrocarbons, C9, aromatics | 64742-95-6 | < 10 | Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 |
| Other substances (not contributing to the classification of this product) | - | 52.65 | - |

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

| n-butyl acetate (123-86-4) | |
|--|---|
| Australia - Occupational Exposure Limits | |
| Local name | n-Butyl acetate |
| OES TWA [1] | 713 mg/m ³ |
| OES TWA [2] | 150 ppm |
| OES STEL | 950 mg/m ³ |
| OES STEL [ppm] | 200 ppm |
| Regulatory reference | Workplace exposure standards for airborne contaminants (2019) |

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| n-butyl acetate (123-86-4) | |
|--|--|
| New Zealand - Occupational Exposure Limits | |
| Local name | n-Butyl acetate |
| WES-TWA (OEL TWA) [1] | 713 mg/m ³ |
| WES-TWA (OEL TWA) [2] | 150 ppm |
| WES-STEL (OEL STEL) | 950 mg/m ³ |
| WES-STEL (OEL STEL) [ppm] | 200 ppm |
| Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| methyl acetate (79-20-9) | |
| Australia - Occupational Exposure Limits | |
| Local name | Methyl acetate |
| OES TWA [1] | 606 mg/m ³ |
| OES TWA [2] | 200 ppm |
| OES STEL | 757 mg/m ³ |
| OES STEL [ppm] | 250 ppm |
| Regulatory reference | Workplace exposure standards for airborne contaminants (2019) |
| New Zealand - Occupational Exposure Limits | |
| Local name | Methyl acetate |
| WES-TWA (OEL TWA) [1] | 606 mg/m ³ |
| WES-TWA (OEL TWA) [2] | 200 ppm |
| WES-STEL (OEL STEL) | 757 mg/m ³ |
| WES-STEL (OEL STEL) [ppm] | 250 ppm |
| Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance : aerosol.
Colour : Black

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| | |
|---|---|
| Odour | : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Fruity odour Mild odour Ether-like odour Odourless Almost odourless Aromatic odour Pleasant odour Petroleum-like odour Sweet odour Peppermint odour Acetone odour Commercial/unpurified substance: unpleasant odour |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point / Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : No data available |
| Relative density | : No data available |
| Density | : Density: 0.782 g/cm ³ |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Explosive properties | : Pressurised container: May burst if heated. |
| Explosive limits | : No data available |
| Minimum ignition energy | : No data available |
| VOC content | : 650 g/l |
| VOC content - Regulatory | : No data available |
| Percent Solids | : 14.56 wt% |

SECTION 10: Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | : Extremely flammable aerosol. Pressurised container: May burst if heated. |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : No dangerous reactions known under normal conditions of use. |
| Conditions to avoid | : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. |
| Incompatible materials | : No additional information available |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

n-butyl acetate (123-86-4)

| | |
|---------------------------------|---|
| LD50 oral rat | 10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | 23.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat) |
| LC50 Inhalation - Rat [ppm] | 390 ppm/4h |
| LC50 Inhalation - Rat (Vapours) | > 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours) |
| ATE AU (oral) | 10760 mg/kg bodyweight |
| ATE AU (gases) | 390 ppmv/4h |
| ATE AU (vapours) | 23.4 mg/l/4h |
| ATE AU (dust,mist) | 23.4 mg/l/4h |

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| | |
|--|--|
| methyl acetate (79-20-9) | |
| LD50 oral rat | 6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat | 49 mg/l |
| ATE AU (oral) | 6482 mg/kg bodyweight |
| ATE AU (dust,mist) | 49 mg/l/4h |
| hydrocarbons, C9, aromatics (64742-95-6) | |
| LD50 oral rat | 8400 ml/kg |
| LD50 dermal rabbit | 3160 mg/kg bodyweight (OECD Guideline 402 (Acute Dermal Toxicity), rat, male/female) |
| LC50 Inhalation - Rat [ppm] | 3400 ppm/4h |
| LC50 Inhalation - Rat (Vapours) | > 5 mg/l/4h |
| Unknown acute toxicity (GHS AU) | : 32.5% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours)) |
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause drowsiness or dizziness. |
| n-butyl acetate (123-86-4) | |
| STOT-single exposure | May cause drowsiness or dizziness. |
| methyl acetate (79-20-9) | |
| STOT-single exposure | May cause drowsiness or dizziness. |
| hydrocarbons, C9, aromatics (64742-95-6) | |
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. |
| STOT-repeated exposure | : Not classified |
| methyl acetate (79-20-9) | |
| LOAEC (inhalation, rat, vapour, 90 days) | 2000 mg/l |
| NOAEC (inhalation, rat, vapour, 90 days) | 1057 mg/m³ |
| hydrocarbons, C9, aromatics (64742-95-6) | |
| NOAEL (oral, rat, 90 days) | 600 mg/kg bodyweight/day |
| NOAEC (inhalation, rat, vapour, 90 days) | 900 – 1800 mg/m³ |
| Aspiration hazard | : Not classified |
| TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL | |
| Vaporizer | aerosol |

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

12.1. Ecotoxicity

| | |
|---|---|
| Ecology - general | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified |

n-butyl acetate (123-86-4)

| | |
|--|--|
| LC50 - Fish [1] | 18 mg/l Test organisms (species): Pimephales promelas |
| LC50 - Fish [2] | 62 mg/l (Leuciscus idus, static system) |
| EC50 - Crustacea [1] | 44 mg/l Test organisms (species): Daphnia sp. |
| ErC50 algae | 397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP) |
| NOEC (chronic) | 23 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic crustacea | 23 mg/l |
| Partition coefficient n-octanol/water (Log Pow) | 2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |

methyl acetate (79-20-9)

| | |
|--|--|
| LC50 - Fish [1] | 250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) |
| EC50 - Crustacea [1] | 1026.7 mg/l Test organisms (species): Daphnia magna |
| BCF - Fish [1] | < 1 (Pisces, Literature study) |
| Partition coefficient n-octanol/water (Log Pow) | 0.18 (Experimental value, 20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |

hydrocarbons, C9, aromatics (64742-95-6)

| | |
|----------------------|---------------------------------|
| LC50 - Fish [1] | 9.22 mg/l (Oncorhynchus mykiss) |
| EC50 - Crustacea [1] | 6.14 mg/l 48 h, Daphnia magna |
| ErC50 algae | 2.9 mg/l |

12.2. Persistence and degradability

n-butyl acetate (123-86-4)

| | |
|-------------------------------|------------------------------------|
| Persistence and degradability | Readily biodegradable in water. |
| ThOD | 2.21 g O ₂ /g substance |
| BOD (% of ThOD) | 0.46 |

methyl acetate (79-20-9)

| | |
|-------------------------------|---------------------------------|
| Persistence and degradability | Readily biodegradable in water. |
|-------------------------------|---------------------------------|

hydrocarbons, C9, aromatics (64742-95-6)

| | |
|-------------------------------|---------------------------------|
| Persistence and degradability | Readily biodegradable in water. |
|-------------------------------|---------------------------------|

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)

| | |
|--|---|
| Partition coefficient n-octanol/water (Log Pow) | 2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

methyl acetate (79-20-9)

| | |
|--|--|
| BCF - Fish [1] | < 1 (Pisces, Literature study) |
| Partition coefficient n-octanol/water (Log Pow) | 0.18 (Experimental value, 20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

12.4. Mobility in soil

n-butyl acetate (123-86-4)

| | |
|--|---|
| Surface tension | 61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions) |
| Partition coefficient n-octanol/water (Log Pow) | 2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |

methyl acetate (79-20-9)

| | |
|--|--|
| Surface tension | 24 mN/m (20 °C) |
| Partition coefficient n-octanol/water (Log Pow) | 0.18 (Experimental value, 20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |
| Ecology - soil | Highly mobile in soil. |

12.5. Other adverse effects

| | |
|-----------------------|---------------------------------------|
| Ozone | : Not classified |
| Other adverse effects | : No additional information available |

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

| | |
|---|-------|
| Fluorinated greenhouse gases | False |
| n-butyl acetate (123-86-4) | |
| Fluorinated greenhouse gases | False |
| methyl acetate (79-20-9) | |
| Fluorinated greenhouse gases | False |
| hydrocarbons, C9, aromatics (64742-95-6) | |
| Fluorinated greenhouse gases | False |

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1
Danger labels (ADG) : 2.1
:



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1
:



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1
:



14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950
Special provision (ADG) : 63, 190, 277, 327, 344
Limited quantities (ADG) : See SP 277
Packing instructions (ADG) : P207, LP02
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515
Group standard : Aerosols

2-methoxy-1-methylethyl acetate (108-65-6)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001219 |
|----------------------|-----------|

phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)

Hazardous Substances and New Organisms Act

| | |
|----------------------|--|
| HSNO Approval Number | HSR001545(dilution) HSR001571(dilution) |
|----------------------|--|

solvent naphtha (petroleum), light aromatic (64742-95-6)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001503 |
|----------------------|-----------|

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

n-butyl acetate (123-86-4)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001091 |
|----------------------|-----------|

2-phenoxyethanol (122-99-6)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR003045 |
|----------------------|-----------|

toluene (108-88-3)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001227 |
|----------------------|-----------|

cyclohexanone (108-94-1)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001112 |
|----------------------|-----------|

butyl glycolether (111-76-2)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001154 |
|----------------------|-----------|

methyl acetate (79-20-9)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001188 |
|----------------------|-----------|

LPG, liquefied, under pressure (68476-85-7)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001009 |
|----------------------|-----------|

hydrocarbons, C9, aromatics (64742-95-6)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001503 |
|----------------------|-----------|

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 20/12/2021

Classification

| | |
|---------------|-----------|
| Aerosol 1 | H222;H229 |
| Eye Irrit. 2A | H319 |
| STOT SE 3 | H336 |

TRIM #11 GLOSS WHITE HIGH BUILD TOPCOAT AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| Full text of H-statements | |
|---------------------------|--|
| Aerosol 1 | Aerosol, Category 1 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation, Category 2A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation |
| H225 | Highly flammable liquid and vapour |
| H226 | Flammable liquid and vapour |
| H304 | May be fatal if swallowed and enters airways |
| H319 | Causes serious eye irritation |
| H335 | May cause respiratory irritation |
| H336 | May cause drowsiness or dizziness |

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.