



# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

DRIVING SURFACE PERFECTION

Date of issue:04/05/2017

Revision date:03/05/2019

Supersedes: 14/11/2017

Version: 2.1

### SECTION 1: Identification : Product identifier and chemical identity

#### 1.1. Product identifier

Product form : Mixture  
Trade name : TRIM #11 MATT BLACK AEROSOL  
Product code : TRIMMB/AL

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

#### 1.4. Supplier's details

##### Supplier

U-POL AUSTRALIA PTY LIMITED  
Unit A, 16 - 20 Cassola Place  
Penrith, NSW 2750 - Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com.au](http://www.u-pol.com.au)

##### Supplier

U-POL NEW ZEALAND LIMITED  
c/o Lindsay & Associates  
Unit H, 12 Amara Place, East Tamaki  
Manukau City 2013 - New Zealand  
T + 612 4731 2655 - F + 612 4731 2611  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazards identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1 H222  
Serious eye damage/eye irritation, Category 2A H319  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

#### 2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger

Contains : methyl acetate (5 - 23 %); acetone (5 - 23 %); n-butyl acetate (5 - 23 %); ethyl methyl ketone (< 5 %); toluene (< 5 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing vapours, fume, spray.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

Unknown acute toxicity (GHS AU) : 15% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
methyl acetate ( )	79-20-9	5 - 23	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
acetone ( )	67-64-1	5 - 23	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
n-butyl acetate ( )	123-86-4	5 - 23	Flam. Liq. 3, H226 STOT SE 3, H336
ethyl methyl ketone ( )	78-93-3	< 5	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Eye Irrit. 2A, H319 STOT SE 3, H336
C22-30 chlorinated paraffin (chlorination: 42-48%) ( )	63449-39-8	< 5	Not classified
toluene ( )	108-88-3	< 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)		100 - 100	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Symptoms caused by exposure

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
- Explosion hazard : Pressurised container: May burst if heated.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

- Avoid release to the environment.

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

## SECTION 7: Handling and storage, including how the chemical may be safely used

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters - exposure standards

ethyl methyl ketone (78-93-3)		
Australia	Local name	Methyl ethyl ketone (MEK) (2-Butanone)
Australia	TWA (mg/m <sup>3</sup> )	445 mg/m <sup>3</sup>
Australia	TWA (ppm)	150 ppm
Australia	STEL (mg/m <sup>3</sup> )	890 mg/m <sup>3</sup>
Australia	STEL (ppm)	300 ppm
New Zealand	Local name	Methyl ethyl ketone (2-Butanone) (MEK)
New Zealand	TWA (mg/m <sup>3</sup> )	445 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	150 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	890 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	300 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

toluene (108-88-3)		
Australia	Local name	Toluene
Australia	TWA (mg/m <sup>3</sup> )	191 mg/m <sup>3</sup>
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m <sup>3</sup> )	574 mg/m <sup>3</sup>
Australia	STEL (ppm)	150 ppm
Australia	Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
New Zealand	Local name	Toluene (Toluol)
New Zealand	TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	50 ppm
New Zealand	Remark (NZ)	skin (Skin absorption)
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 8th Edition

n-butyl acetate (123-86-4)		
Australia	Local name	n-Butyl acetate
Australia	TWA (mg/m <sup>3</sup> )	713 mg/m <sup>3</sup>
Australia	TWA (ppm)	150 ppm
Australia	STEL (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
Australia	STEL (ppm)	200 ppm
New Zealand	Local name	n-Butyl acetate
New Zealand	TWA (mg/m <sup>3</sup> )	713 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	150 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	200 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

methyl acetate (79-20-9)		
Australia	Local name	Methyl acetate
Australia	TWA (mg/m <sup>3</sup> )	606 mg/m <sup>3</sup>
Australia	TWA (ppm)	200 ppm
Australia	STEL (mg/m <sup>3</sup> )	757 mg/m <sup>3</sup>
Australia	STEL (ppm)	250 ppm
New Zealand	Local name	Methyl acetate
New Zealand	TWA (mg/m <sup>3</sup> )	606 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	200 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	757 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	250 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

acetone (67-64-1)		
Australia	Local name	Acetone
Australia	TWA (mg/m <sup>3</sup> )	1185 mg/m <sup>3</sup>
Australia	TWA (ppm)	500 ppm
Australia	STEL (mg/m <sup>3</sup> )	2375 mg/m <sup>3</sup>
Australia	STEL (ppm)	1000 ppm
New Zealand	Local name	Acetone
New Zealand	TWA (mg/m <sup>3</sup> )	1185 mg/m <sup>3</sup>
New Zealand	TWA (ppm)	500 ppm
New Zealand	STEL (mg/m <sup>3</sup> )	2375 mg/m <sup>3</sup>
New Zealand	STEL (ppm)	1000 ppm
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 9th Edition

### Exposure limit values for the other components

#### 8.2. Monitoring

No additional information available

#### 8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

#### 8.4. Personal protective equipment

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment  
Environmental exposure controls : Avoid release to the environment.

### SECTION 9: Physical and chemical properties

Physical state : Liquid  
Appearance :  
Colour : No data available  
Odour : No data available  
Odour threshold : No data available  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point / Freezing point : Melting point : Not applicable  
Boiling point : No data available  
Flash point : -60 °C  
Auto-ignition temperature : No data available

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density : 0.732 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 660 g/l
VOC content - Regulatory	: No data available

### SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated. Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>ethyl methyl ketone (78-93-3)</b>	
LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male/female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
<b>toluene (108-88-3)</b>	
LD50 oral rat	5580 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral (one dose))
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Other, 24 h, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (Vapours - mg/l/4h)	25.7 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 - 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male/female, Experimental value, Dermal)
LC50 inhalation rat (ppm)	390 ppm/4h
LC50 inhalation rat (Vapours - mg/l/4h)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)
<b>methyl acetate (79-20-9)</b>	
LD50 oral rat	6482 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	49 mg/l
<b>acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
<b>C22-30 chlorinated paraffin (chlorination: 42-48%) (63449-39-8)</b>	
LD50 oral rat	> 11700 mg/kg (EPA OPP 81-1 (Acute Oral Toxicity), rat, male/female)
LD50 dermal rabbit	> 13900 mg/kg
Unknown acute toxicity (GHS AU)	: 15% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

<b>methyl acetate (79-20-9)</b>	
LOAEC (inhalation, rat, vapour, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapour, 90 days)	1057 mg/m <sup>3</sup>

Aspiration hazard : Not classified

<b>TRIM #11 MATT BLACK AEROSOL</b>	
Vaporizer	Aerosol

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

<b>ethyl methyl ketone (78-93-3)</b>	
LC50 fish 1	2993 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	308 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Log Koc	1.53 (log Koc, Calculated value)

<b>toluene (108-88-3)</b>	
LC50 fish 1	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value)
BCF fish 1	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Log Pow	2.73 (Experimental value, 20 °C)

<b>n-butyl acetate (123-86-4)</b>	
LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
LC50 fish 2	62 mg/l (Leuciscus idus, static system)
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)
NOEC chronic crustacea	23 mg/l
BCF fish 1	15.3 (Calculated value)
Log Pow	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	1.268 - 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)

<b>methyl acetate (79-20-9)</b>	
LC50 fish 1	250 - 350 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1026.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	< 1 (Pisces, Literature study)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

<b>acetone (67-64-1)</b>	
LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)

### 12.2. Persistence and degradability

<b>ethyl methyl ketone (78-93-3)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance

<b>toluene (108-88-3)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.69

<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

<b>methyl acetate (79-20-9)</b>	
Persistence and degradability	Readily biodegradable in water. Inherently biodegradable.

<b>acetone (67-64-1)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)

### 12.3. Bioaccumulative potential

<b>ethyl methyl ketone (78-93-3)</b>	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>toluene (108-88-3)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>n-butyl acetate (123-86-4)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>methyl acetate (79-20-9)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>acetone (67-64-1)</b>	
BCF fish 1	See section 12.1 on ecotoxicology
BCF other aquatic organisms 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Not bioaccumulative.

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 12.4. Mobility in soil

<b>ethyl methyl ketone (78-93-3)</b>	
Surface tension	0.024 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.
<b>toluene (108-88-3)</b>	
Surface tension	27.73 N/m (25 °C)
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.
<b>n-butyl acetate (123-86-4)</b>	
Surface tension	0.0163 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.
<b>methyl acetate (79-20-9)</b>	
Surface tension	0.024 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil.
<b>acetone (67-64-1)</b>	
Surface tension	0.0237 N/m
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

<b>TRIM #11 MATT BLACK AEROSOL</b>	
Fluorinated greenhouse gases	False
<b>ethyl methyl ketone (78-93-3)</b>	
Fluorinated greenhouse gases	False
<b>toluene (108-88-3)</b>	
Fluorinated greenhouse gases	False
<b>n-butyl acetate (123-86-4)</b>	
Fluorinated greenhouse gases	False
<b>methyl acetate (79-20-9)</b>	
Fluorinated greenhouse gases	False
<b>acetone (67-64-1)</b>	
Fluorinated greenhouse gases	False
<b>C22-30 chlorinated paraffin (chlorination: 42-48%) (63449-39-8)</b>	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

### 14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable



# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### 14.3. Transport hazard class(es)

#### ADG

Transport hazard class(es) (ADG) : 2.1  
Danger labels (ADG) : 2.1



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1



#### IATA

Transport hazard class(es) (IATA) : 2.1  
Hazard labels (IATA) : 2.1



### 14.4. Packing group

Packing group (ADG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Marine pollutant : No

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344  
Limited quantities (ADG) : See SP 277  
Packing instructions (ADG) : P207, LP02  
Special packing provisions (ADG) : PP87, L2

### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

### Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.8. Hazchem or Emergency Action Code

Hazchemcode : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

#### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515  
Group standard : Aerosols

#### ethylbenzene (100-41-4)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001151

#### 2-phenoxyethanol (122-99-6)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR003045

### 15.2. International agreements

No additional information available

## SECTION 16: Any other relevant information

Revision date : 03/05/2019

Classification:

Flam. Aerosol 1	H222
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements:

Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.

# TRIM #11 MATT BLACK AEROSOL

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

H373	May cause damage to organs through prolonged or repeated exposure.
------	--

SDS Australia U-POL

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.*