



DRIVING SURFACE PERFECTION

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
SDS ID: RLB17K-R-US-SDS  
Issue date: 5/9/2016 Revision date: 1/5/2022 Supersedes: 11/16/2021 Version: 5.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC  
Product code : RLB17/1  
UP Number : UP0824  
Other means of identification : Component of: UP5025, UP5041, UP5045, UP0825

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coatings and paints, thinners, paint removers  
Recommended use : Coating

#### 1.3. Supplier

U-POL US Inc Inc.  
108 Commerce Way  
Easton, Pennsylvania, PA 18083  
United States  
T 1-800-340-7824 - F 1-800-787-5150  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 2	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Skin sensitization, Category 1	May cause an allergic skin reaction
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity — Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	May cause damage to organs through prolonged or repeated exposure

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger  
Hazard statements (GHS US) : Highly flammable liquid and vapor  
Causes skin irritation  
May cause an allergic skin reaction  
Causes serious eye irritation

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : May cause drowsiness or dizziness  
Suspected of causing cancer  
May cause damage to organs through prolonged or repeated exposure  
: If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe vapors, fume, spray.  
Avoid breathing fume, spray, vapors.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear eye protection, protective clothing, protective gloves, face protection.  
If on skin: Wash with plenty of water.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
Call a doctor if you feel unwell.  
Get medical advice/attention if you feel unwell.  
If skin irritation occurs: Get medical advice/attention.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
Wash contaminated clothing before reuse.  
In case of fire: Use foam, dry sand, extinguishing powder to extinguish.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
acetone	CAS-No.: 67-64-1	5 – 23	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
reaction mass of ethylbenzene, m-xylene and p-xylene	-	5 – 23	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
n-butyl acetate	CAS-No.: 123-86-4	< 23	Flam. Liq. 3, H226 STOT SE 3, H336
methyl acetate	CAS-No.: 79-20-9	5 – 23	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
kieselguhr, soda ash flux calcined	CAS-No.: 68855-54-9	< 5	STOT RE 2, H373
carbon black	CAS-No.: 1333-86-4	< 5	Carc. 2, H351
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: 1065336-91-5	< 5	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: 104810-48-2	< 5	Skin Sens. 1A, H317 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, fume, spray. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, fume, spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Storage temperature	: < 25 °C
Storage area	: Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

No additional information available

#### reaction mass of ethylbenzene, m-xylene and p-xylene

No additional information available

#### acetone (67-64-1)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Acetone
ACGIH OEL TWA [ppm]	250 ppm
ACGIH OEL STEL [ppm]	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021

##### USA - ACGIH - Biological Exposure Indices

Local name	ACETONE
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2021

##### USA - OSHA - Occupational Exposure Limits

Local name	Acetone
OSHA PEL (TWA) [1]	2400 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

#### carbon black (1333-86-4)

##### USA - ACGIH - Occupational Exposure Limits

Local name	Carbon black
ACGIH OEL TWA	3 mg/m <sup>3</sup> (Inhalable fraction)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2021

##### USA - OSHA - Occupational Exposure Limits

Local name	Carbon black
------------	--------------

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>carbon black (1333-86-4)</b>	
OSHA PEL (TWA) [1]	3.5 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>kieselguhr, soda ash flux calcined (68855-54-9)</b>	
No additional information available	
<b>n-butyl acetate (123-86-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	n-Butyl acetate
ACGIH OEL TWA [ppm]	50 ppm
ACGIH OEL STEL [ppm]	150 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	n-Butyl-acetate
OSHA PEL (TWA) [1]	710 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>methyl acetate (79-20-9)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Methyl acetate
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2021
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Methyl acetate
OSHA PEL (TWA) [1]	610 mg/m <sup>3</sup>
OSHA PEL (TWA) [2]	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)</b>	
No additional information available	
<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>	
No additional information available	

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Gas mask. Gloves. Protective clothing. Safety glasses.

#### Materials for protective clothing:

Impermeable clothing

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous. Liquid.
Color	: Black
Odor	: Characteristic odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 56 °C Acetone
Flash point	: -17 °C Acetone
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.117 (1.06 – 1.1) g/cm <sup>3</sup>
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 4476.276 mm <sup>2</sup> /s
Viscosity, dynamic	: 5000 (4500 – 6500) cP
Explosion limits	: No data available
Explosive properties	: No data available

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties : No data available

### 9.2. Other information

VOC content : 428.5 g/l  
As Packaged Regulatory VOC : 228 g/l (1.9 lbs/gal)  
As Packaged Actual VOC : 151.1 g/l (1.26 lbs/gal)  
As Applied Regulatory VOC : 199 g/l (1.7 lbs/gal)  
As Applied Actual VOC : 119 g/l (0.99 lbs/gal)  
Percent Solids : 61.66 wt%  
Percent Solids : 49.23 vol %  
Volatiles : 38.3 wt%  
Water Content : 0 wt%  
Water Content : 0 vol %  
Exempt Compounds by weight : 24.8 wt%  
Exempt Compounds by volume : 33.7 vol %  
% EPA HAPS : 8.00 wt%

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

reaction mass of ethylbenzene, m-xylene and p-xylene	
LD50 oral rat	3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral), rat, male)
LD50 dermal rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight



# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
ATE US (gases)	6350 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Weight of evidence, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE US (oral)	5800 mg/kg body weight
<b>carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))
<b>kieselguhr, soda ash flux calcined (68855-54-9)</b>	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 2.6 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	23.4 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Inhalation (mixture of vapour and aerosol), 14 day(s))
LC50 Inhalation - Rat [ppm]	390 ppm/4h
ATE US (oral)	10760 mg/kg body weight
ATE US (gases)	390 ppmV/4h
ATE US (vapors)	23.4 mg/l/4h
ATE US (dust, mist)	23.4 mg/l/4h
<b>methyl acetate (79-20-9)</b>	
LD50 oral rat	6482 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l
ATE US (oral)	6482 mg/kg body weight
ATE US (vapors)	49 mg/l/4h
ATE US (dust, mist)	49 mg/l/4h

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)</b>	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)
ATE US (vapors)	5800 mg/l/4h
ATE US (dust, mist)	5800 mg/l/4h
<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,
ATE US (oral)	3230 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>carbon black (1333-86-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
<b>acetone (67-64-1)</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
STOT-single exposure	May cause respiratory irritation.
<b>acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>methyl acetate (79-20-9)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
LOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day ( OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>kieselguhr, soda ash flux calcined (68855-54-9)</b>	
NOAEL (oral, rat, 90 days)	3737.9 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>methyl acetate (79-20-9)</b>	
LOAEC (inhalation, rat, vapor, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapor, 90 days)	1057 mg/m <sup>3</sup>
Aspiration hazard	: Not classified
Viscosity, kinematic	: 4476.276 mm <sup>2</sup> /s
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
<b>acetone (67-64-1)</b>	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>carbon black (1333-86-4)</b>	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

<b>methyl acetate (79-20-9)</b>	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna

### **reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)**

LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

## 12.2. Persistence and degradability

<b>acetone (67-64-1)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance

<b>carbon black (1333-86-4)</b>	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>kieselguhr, soda ash flux calcined (68855-54-9)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>methyl acetate (79-20-9)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>12.3. Bioaccumulative potential</b>	
<b>acetone (67-64-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Bioaccumulative potential	Not bioaccumulative.
<b>carbon black (1333-86-4)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>kieselguhr, soda ash flux calcined (68855-54-9)</b>	
Bioaccumulative potential	No test data of component(s) available.
<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>methyl acetate (79-20-9)</b>	
BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-48-2)</b>	
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

<b>12.4. Mobility in soil</b>	
<b>acetone (67-64-1)</b>	
Surface tension	23300 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
<b>carbon black (1333-86-4)</b>	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.
<b>n-butyl acetate (123-86-4)</b>	
Surface tension	61.3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methyl acetate (79-20-9)	
Surface tension	24 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

### 14.1. UN number

DOT NA No : UN1263  
UN-No. (TDG) : UN1263  
UN-No. (IMDG) : 1263  
UN-No. (IATA) : 1263

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Paint  
Proper Shipping Name (TDG) : PAINT  
Proper Shipping Name (IMDG) : PAINT  
Proper Shipping Name (IATA) : Paint

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 3  
Hazard labels (DOT) : 3

#### TDG

Transport hazard class(es) (TDG) : 3  
Hazard labels (TDG) : 3

#### IMDG

Transport hazard class(es) (IMDG) : 3  
Hazard labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

Hazard labels (IATA) : 3



### 14.4. Packing group

Packing group (DOT) : II  
Packing group (TDG) : II  
Packing group (IMDG) : II  
Packing group (IATA) : II

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

**DOT**  
UN-No.(DOT) : UN1263

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
- 367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package.
- 383 - Packages containing toy plastic or paper caps for toy pistols described as "UN0349, Articles, explosive, n.o.s. (Toy caps), 1.4S" or "NA0337, Toy caps, 1.4S" are not subject to the subpart E (labeling) requirements of this part when offered for transportation by motor vehicle, rail freight, cargo vessel, and cargo aircraft and, notwithstanding the packing method assigned in §173.62 of this subchapter, in conformance with the following conditions:
- B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
- B131 - When transported by highway, rail, or cargo vessel, waste Paint and Paint related material (UN1263; PG II and PG III), when in plastic or metal inner packagings of not more than 26.5 L (7 gallons), are excepted from the marking requirements in §172.301(a) and (c) and the labeling requirements in §172.400(a), when further packed in the following specification and non-specification bulk outer packagings and under the following conditions:
- a. Primary receptacles must conform to the general packaging requirements of subpart B of part 173 of this subchapter and may not leak. If they do leak, they must be overpacked in packagings conforming to the specification requirements of part 178 of this subchapter or in salvage packagings conforming to the requirements in §173.12 of this subchapter.
- b. Primary receptacles must be further packed in non-specification bulk outer packagings such as cubic yard boxes, plastic rigid-wall bulk containers, dump trailers, and roll-off containers. Bulk outer packagings must be liquid tight through design or by the use of lining materials.
- c. Primary receptacles may also be further packed in specification bulk outer packagings. Authorized specification bulk outer packagings are UN11G fiberboard intermediate bulk containers (IBC) and UN13H4 woven plastic, coated and with liner flexible intermediate bulk containers (FIBCs) meeting the Packing Group II performance level and lined with a plastic liner of at least 6 mil thickness.
- d. All inner packagings placed inside bulk outer packagings must be blocked and braced to prevent movement during transportation that could cause the container to open or fall over. Specification IBCs and FIBCs are to be secured to a pallet.
- IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
- T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
- TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
- TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150



# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L  
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### TDG

UN-No. (TDG) : UN1263  
TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20% nitrocellulose if the nitrocellulose contains not more than 12.6% nitrogen (by dry mass), 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment:  
(a) "PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material;  
(b) "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable;  
(c) "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and  
(d) "PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material.  
Explosive Limit and Limited Quantity Index : 5 L  
Excepted quantities (TDG) : E2  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L  
Emergency Response Guide (ERG) Number : 128

### IMDG

Special provision (IMDG) : 163, 367  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
Packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP8, TP28  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER  
Stowage category (IMDG) : B  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

### IATA

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
Special provision (IATA) : A3, A72, A192

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ERG code (IATA) : 3L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
reaction mass of ethylbenzene, m-xylene and p-xylene		Present	Active	
acetone	67-64-1	Present	Active	
carbon black	1333-86-4	Present	Active	
kieselguhr, soda ash flux calcined	68855-54-9	Present	Active	
n-butyl acetate	123-86-4	Present	Active	
methyl acetate	79-20-9	Present	Active	

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### acetone (67-64-1)

CERCLA RQ 5000 lb

#### n-butyl acetate (123-86-4)

CERCLA RQ 5000 lb

### 15.2. International regulations

#### CANADA

##### reaction mass of ethylbenzene, m-xylene and p-xylene

Listed on the Canadian DSL (Domestic Substances List)

##### acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

##### carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

##### kieselguhr, soda ash flux calcined (68855-54-9)

Listed on the Canadian DSL (Domestic Substances List)

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### n-butyl acetate (123-86-4)

Listed on the Canadian DSL (Domestic Substances List)

### methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

#### acetone (67-64-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### kieselguhr, soda ash flux calcined (68855-54-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### n-butyl acetate (123-86-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations



#### WARNING:

This product can expose you to carbon black, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
acetone(67-64-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
kieselguhr, soda ash flux calcined(68855-54-9)	U.S. - Pennsylvania - RTK (Right to Know) List
n-butyl acetate(123-86-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
methyl acetate(79-20-9)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

# RAPTOR PROTECTIVE COATING - BLACK BASE 1.7 VOC

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 01/05/2022

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).