

DRIVING SURFACE PERFECTION"

TECHNICAL DATA SHEET

BLEND#9



FADE OUT REDUCER AEROSOL

Version 2.0

TECHNICAL DATA SHEET & PROCESS GUIDE

A specially formulated blend of solvents for fast and effective blending of clearcoats. Produce seamless transitions on blend panels of clearcoats and solid colors for a virtually invisible repair. Ultra fine, soft spray generates immediate results. Ideal for both single and multi-panel repairs.

- Invisible blend finish
- · For use with all coatings
- Suitable for SMART repairs
- · Convenient aerosol application means no waste, less mess, no clean-up and no gun required.
- Reduces polishing time.

APPLICATION GUIDE

Mixing Shake

 \square Shake the aerosol can for at least 2 minutes before use.

Application

- Sand blend area with sanding soap or P800 1200 grit sandpaper to prepare blend area.
- Holding the aerosol approximately 10" from the panel, apply a light mist coat over the bled area of the freshly applied clearcoat or topcoat.
- Apply 2-3 light coats of BLEND#9 immediately after clearcoat is applied to blend edge.
- · Follow the clearcoat or topcoat manufacturers instructions for flash off and drying.

STORAGE & VOC INFORMATION

Shelf Life

2 years subject to proper storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To maximize the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use to clear the nozzle. If the nozzle becomes blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature 41°F - 77°F

Recommended Application Temperature 68°F

VOC Information

Order Code	Format	Color	MIR
UP0874	450ml Aerosol	Clear	N/A

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local distributor or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL US, Inc.	US Sales	Rest of the World Sales	Technical
108 Commerce Way	T: (610) 746 7081	T: +44 (0)20 8492 5900	T: +44 (0)1933 230 310
Stockertown, PA 18083	F: (610) 743 8654	F: +44 (0)20 8150 5605	F: +44 (0)1933 425 797
WWW.U-POL.COM	sales-us@u-pol.com	sales@u-pol.com	technicaldepartment@u-pol.com