

Safety Data Sheet RLSBAL-R-US-SDS

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 06/01/2018

Revision date: 06/21/2018

Supersedes: 06/01/2018

Version: 2.0

1550	Je uale. 00/01/2010	Revision date: 00/21/2018	Supersedes. 00/01/2018	version. 2.0
SECTION 1: Identification				
1.1. Identification				
Product form	: Mixture			
Trade name	: RAPTOR 2k	PROTECTIVE COATING SEP	IA BROWN AEROSOL	
UP Number	UP4888			
1.2. Recommended use and restric	tions on use			
Use of the substance/mixture	: Coatings and	d paints, thinners, paint remove	rs	
Recommended use	: Coating			
Restrictions on use	: Consumer u	ses: Private households (= gene	eral public = consumers)	
1.3. Supplier				
Supplier U-POL US Inc 108 Commerce Way Easton, PA 18040 - United States T 1-800-340-7824 - F 1-800-787-5150 technicalsupport@u-pol.com - www.u-pol.co	<u>om</u>			
1.4. Emergency telephone number				
Emergency number	: CHEMTREC	- 1-800-424-9300		
SECTION 2: Hazard(s) identification	tion			
2.1. Classification of the substance	or mixture			
GHS US classification				
Flammable aerosol Category 1 Serious eye damage/eye irritation Category Skin sensitization, Category 1	2 Cau	emely flammable aerosol ses serious eye irritation cause an allergic skin reaction		
2.2. GHS Label elements, including	precautionary state	ments		
GHS US labeling				
Hazard pictograms (GHS US)				
Signal word (GHS US)	: Danger			
Hazard statements (GHS US)	May cause a	ammable aerosol an allergic skin reaction ous eye irritation		
Precautionary statements (GHS US)	Keep out of Keep away f smoking. Pressurized Avoid breath Wear eye pr Protect from Dispose of c	wice is needed, have product co reach of children. rom heat, hot surfaces, sparks, container: Do not pierce or burr ing vapors, spray, fume. otection, protective gloves, prot sunlight. Do not expose to temp ontents/container to hazardous gional, national and/or internation	open flames and other ignition n, even after use. ective clothing. peratures exceeding 50 °C/12 or special waste collection po	2 °F.
2.3. Other hazards which do not re-		gional, national and/or internation		

2.3. Other hazards which do not result in classification

2.4. Unknown acute toxicity (GHS US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable 3.2. Mixtures

Name	Product identifier	%	GHS US classification
acetone	(CAS-No.) 67-64-1	5 – 23	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
hexamethylene diisocyanate oligomers	(CAS-No.) 28182-81-2	5 – 23	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
n-butyl acetate	(CAS-No.) 123-86-4	< 23	Flam. Liq. 3, H226 STOT SE 3, H336
reaction mass of ethylbenzene, m-xylene and p-xylene		< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
kieselguhr, soda ash flux calcined	(CAS-No.) 68855-54-9	< 5	STOT RE 2, H373
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α - 3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert- butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		< 5	Skin Sens. 1A, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5	< 5	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
carbon black	(CAS-No.) 1333-86-4	< 5	Carc. 2, H351

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures				
4.1. Description of first aid measures				
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.			
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.			
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.			
First-aid measures after eye contact	 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. 			
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.			
4.2. Most important symptoms and effe	ects (acute and delayed)			
Symptoms/effects after skin contact	: May cause an allergic skin reaction.			
Symptoms/effects after eye contact	: Eye irritation.			
4.3. Immediate medical attention and s	4.3. Immediate medical attention and special treatment, if necessary			
Treat symptomatically.				
SECTION 5: Fire-fighting measures				
5.1. Suitable (and unsuitable) extinguis	shing media			
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.			
5.2. Specific hazards arising from the o	chemical			
Fire hazard	: Extremely flammable aerosol.			
Explosion hazard	: Pressurized container: may burst if heated.			
Reactivity	: Extremely flammable aerosol. Pressurized container: may burst if heated.			
5.3. Special protective equipment and	precautions for fire-fighters			
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTI	SECTION 6: Accidental release measures				
6.1.	Personal precautions, protective equip	oment and emergency procedures			
6.1.1. Emerger	For non-emergency personnel ncy procedures :	No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable			
-		protective equipment may intervene. Avoid breathing fume, vapors, spray.			
6.1.2.	For emergency responders				
	e equipment :	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".			
6.2.	Environmental precautions				
Avoid rel	lease to the environment. Notify authorities	if product enters sewers or public waters.			
6.3.	Methods and material for containment	and cleaning up			
Methods	for cleaning up :	Mechanically recover the product. Notify authorities if product enters sewers or public waters.			
Other inf	formation :	Dispose of materials or solid residues at an authorized site.			
6.4.	Reference to other sections				
For furth	er information refer to section 13.				
SECTI	ON 7: Handling and storage				
7.1.	Precautions for safe handling				
Precautio	ons for safe handling :	Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing vapors, fume, spray.			
Hygiene	measures :	Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.			
7.2.	Conditions for safe storage, including	any incompatibilities			
Storage	conditions :	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool.			

8.1. Control parameters

acetone (67-64-1)				
ACGIH	Local name	Acetone		
ACGIH	ACGIH OEL TWA [ppm]	250 ppm		
ACGIH	ACGIH OEL STEL [ppm]	500 ppm		
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI		
ACGIH	Regulatory reference	ACGIH 2021		
OSHA	OSHA PEL (TWA) [1]	2400 mg/m ³		
OSHA	OSHA PEL (TWA) [2]	1000 ppm		
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
kieselguhr, soda ash flux calcined (68855-54-9)				
Not applicable	Not applicable			
reaction mass of ethylbenzene, m-xylene and p-xylene				
Not applicable				
n-butyl acetate (123-86-4)				
ACGIH	Local name	n-Butyl acetate		
	•			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-butyl acetate (123-86-4)		
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	ACGIH OEL STEL [ppm]	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	710 mg/m³
OSHA	OSHA PEL (TWA) [2]	150 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Not applicable

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5) Not applicable

hexamethylene diisocyanate oligomers (28182-81-2)

Not applicable		
carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	3.5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

- Appropriate engineering controls
- Environmental exposure controls
- : Ensure good ventilation of the work station.

: Avoid release to the environment.

Individual protection measures/Personal protective equipment

Hand protection:

8.3.

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical	and chemical properties	
9.1. Information on b	asic physical and chemical properties	
Physical state	: Liquid	
07/04/0004		1/10

Safety Data Sheet

	, march 20, 2012 / Raiob and Rogan		
Appearance	: aerosol.		
Color	: brown		
Odor	: characteristic		
Odor threshold	: No data available		
рН	: No data available		
Melting point	: Not applicable		
Freezing point	: No data available		
Boiling point	: No data available		
Flash point	: No data available		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: Extremely flammable aero	sol.	
Vapor pressure	: No data available		
Relative vapor density at 20 °C	: No data available		
Relative density	: No data available		
Density	: 0.964 g/cm ³		
Solubility	: No data available		
Partition coefficient n-octanol/water (Log Pow)	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
No data availableViscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
Explosion limits	: No data available		
Explosion limits Explosive properties	: Pressurized container: ma	v hurst if hosted	
	: No data available	y buist il neateu.	
Oxidizing properties	. No data avaliable		
9.2. Other information			
As Packaged Regulatory VOC	: 501 g/l (4.1 lb/gal)		
As Packaged Actual VOC	: 444 g/l (3.7 lb/gal)		
As Applied Regulatory VOC	: 501 g/l (4.1 lb/gal)		
As Applied Actual VOC	: 444 g/l (3.7 lb/gal)		
Water Content	0 wt%		
Volatiles	: 55.4 wt%		
% EPA HAPS	: 3.7 wt%		
Percent Solids	: 44.56 wt%		
Percent Solids	: 27.62 vol %		
Maximum Incremental Reactivity (MIR)	: 0.8		
MIR EPA Aerosol Category	: Non-Flat Coating - NFP 1.4		
MIR CARB Aerosol Category	: Nonflat Coating - General C	coatings - NFP 0.95	
SECTION 10: Stability and reactivity			
10.1. Reactivity			
Extremely flammable aerosol. Pressurized conta	ainer: may hurst if heated		
10.2. Chemical stability			
Stable under normal conditions.			
10.3. Possibility of hazardous reactions			
No dangerous reactions known under normal co	onditions of use.		
10.4. Conditions to avoid			
Avoid contact with hot surfaces. Heat. No flames	s, no sparks. Eliminate all source	es of ignition.	
10.5. Incompatible materials			
No additional information available			
07/01/2021	EN (English US)	SDS ID: RLSBAL-R-US-SDS	5/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6.	Hazardous	decomposition	products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	on
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
,	
acetone (67-64-1) LD50 oral rat	5000 mailer had susialt Arimal at Arimal any famale
	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
kieselguhr, soda ash flux calcined (68855-54-	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 2.6 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
reaction mass of ethylbenzene, m-xylene and	l p-xylene
LD50 oral rat	3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral), rat, male)
LD50 dermal rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	6350 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
ATE US (oral)	10760 mg/kg body weight
ATE US (dermal)	14112 mg/kg body weight
ATE US (gases)	390 ppmV/4h
reaction mass of α -3-(3-(2H-benzotriazol-2-yl) benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphen hydroxyphenyl)propionyloxypoly(oxyethylen	-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H- yl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- e)
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)
ATE US (vapors)	5800 mg/l/4h
ATE US (dust, mist)	5800 mg/l/4h
reaction mass of bis(1.2.2.6.6-pentamethyl-4-	piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)
LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,
ATE US (oral)	3230 mg/kg body weight
hexamethylene diisocyanate oligomers (2818	
LD50 oral rat	> 2500 mg/kg (OECD Test Guideline 423, rat, female)
LD50 dermal rat	> 2000 mg/kg (OECD Test Guideline 423, 1at, 1ethale) > 2000 mg/kg (OECD Test Guideline 402, rat, male/female)
	4500 ppmV/4h
ATE US (gases)	11 mg/l/4h
ATE US (vapors) ATE US (dust, mist)	0.39 mg/l/4h
	0.09 mg/r41

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)			
LD50 oral rat	> 8000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)		
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))		
Skin corrosion/irritation	: Not classified		
Serious eye damage/irritation	: Causes serious eye irritation.		
Respiratory or skin sensitization	: May cause an allergic skin reaction.		
Germ cell mutagenicity	Not classified		
Carcinogenicity	: Not classified		
reaction mass of ethylbenzene, m-xyler	ie and p-xylene		
IARC group	2B - Possibly carcinogenic to humans		
carbon black (1333-86-4)			
IARC group	2B - Possibly carcinogenic to humans		
Reproductive toxicity	: Not classified		
STOT-single exposure	: Not classified		
acetone (67-64-1)			
STOT-single exposure	May cause drowsiness or dizziness.		
reaction mass of ethylbenzene, m-xyler	ie and p-xylene		
STOT-single exposure	May cause respiratory irritation.		
n-butyl acetate (123-86-4)			
STOT-single exposure	May cause drowsiness or dizziness.		
hexamethylene diisocyanate oligomers	(28182-81-2)		
STOT-single exposure	May cause respiratory irritation.		
STOT-repeated exposure	: Not classified		
kieselguhr, soda ash flux calcined (688	55-54-9)		
NOAEL (oral,rat,90 days)	3737.9 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
reaction mass of ethylbenzene, m-xyler			
LOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)		
NOAEL (oral,rat,90 days)	150 mg/kg bodyweight/day (OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard	: Not classified		
Viscosity, kinematic	: No data available		
Symptoms/effects after skin contact	: May cause an allergic skin reaction.		
Symptoms/effects after eye contact	: Eye irritation.		
SECTION 12: Ecological information	tion		
12.1. Toxicity			
Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.		
acetone (67-64-1)			
LC50 - Fish [1]	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental		
	value, Nominal concentration)		
LOEC (obrania)	> 70 mg/l Test arganisms (aposiss); Danhais magna Duration; '21 d'		

LOEC (chronic)

> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Safety Data Sheet

acetone (67-64-1)			
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
reaction mass of ethylbenzene, m-xylene	and p-xylene		
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)		
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia		
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'		
n-butyl acetate (123-86-4)			
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas		
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.		
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)		
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic crustacea	23 mg/l		
hydroxyphenyl)propionyloxypoly(oxyeth LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value,		
EC50 - Crustacea [1]	Nominal concentration) 4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)		
ErC50 algae	 > 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration) 		
carbon black (1333-86-4)			
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)		
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)		
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)		
2.2. Persistence and degradability			
acetone (67-64-1)			
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance		
Chemical oxygen demand (COD)	1.92 g O₂/g substance		
ThOD	22 g O ₂ /g substance		

2.2 g O₂/g substance	
0.872 (20 day(s), Literature study)	
9)	
Biodegradability: not applicable.	
Not applicable	
Not applicable	
Not applicable	
Readily biodegradable in water.	
2.21 g O₂/g substance	
0.46	

carbon black (1333-86-4)		
Persistence and degradability Biodegradability in soil: not applicable. Biodegradability: not applicable.		
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	

Safety Data Sheet

acetone (67-64-1)			
BCF - Fish [1]	0.69 (Pisces)		
BCF - Other aquatic organisms [1]	3 (BCFWIN, Calculated value)		
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)		
Bioaccumulative potential	Not bioaccumulative.		
kieselguhr, soda ash flux calcined (68855-54	-9)		
Bioaccumulative potential	No test data of component(s) available.		
n-butyl acetate (123-86-4)			
BCF - Fish [1]	15.3 (Calculated value)		
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
hydroxyphenyl)propionyloxypoly(oxyethylen			
BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)		
BCF - Fish [1] Partition coefficient n-octanol/water (Log Pow)			
Partition coefficient n-octanol/water (Log Pow)	value)		
	value)		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 2.4. Mobility in soil	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 12.4. Mobility in soil acetone (67-64-1)	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C) Not bioaccumulative.		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 2.4. Mobility in soil acetone (67-64-1) Surface tension Ecology - soil	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C) Not bioaccumulative. 0.0237 N/m		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 2.4. Mobility in soil acetone (67-64-1) Surface tension Ecology - soil n-butyl acetate (123-86-4)	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C) Not bioaccumulative. 0.0237 N/m No (test)data on mobility of the substance available.		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 2.4. Mobility in soil acetone (67-64-1) Surface tension Ecology - soil n-butyl acetate (123-86-4) Surface tension Organic Carbon Normalized Adsorption	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C) Not bioaccumulative. 0.0237 N/m		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 2.4. Mobility in soil acetone (67-64-1) Surface tension Ecology - soil n-butyl acetate (123-86-4) Surface tension	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C) Not bioaccumulative. 0.0237 N/m No (test)data on mobility of the substance available. 0.0163 N/m (20 °C)		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 2.4. Mobility in soil acetone (67-64-1) Surface tension Ecology - soil n-butyl acetate (123-86-4) Surface tension Organic Carbon Normalized Adsorption Coefficient (Log Koc) Ecology - soil	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C) Not bioaccumulative. 0.0237 N/m No (test)data on mobility of the substance available. 0.0163 N/m (20 °C) 1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)		
Partition coefficient n-octanol/water (Log Pow) carbon black (1333-86-4) Bioaccumulative potential 2.4. Mobility in soil acetone (67-64-1) Surface tension Ecology - soil n-butyl acetate (123-86-4) Surface tension Organic Carbon Normalized Adsorption Coefficient (Log Koc)	value) 4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C) Not bioaccumulative. 0.0237 N/m No (test)data on mobility of the substance available. 0.0163 N/m (20 °C) 1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)		

SECTION 13: Disposal considerat	tions
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
SECTION 14: Transport informati	on
Department of Transportation (DOT) In accordance with DOT	
Transport document description (DOT)	: UN1950 Aerosols, 2.1
UN-No.(DOT)	: UN1950
Proper Shipping Name (DOT)	: Aerosols
Class (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
Emergency Response Guide (ERG) Number	: 126
Other information	: No supplementary information available.
Transportation of Dangerous Goods	
Transport document description (TDG)	: UN1950 AEROSOLS (flammable), 2.1
UN-No. (TDG)	: UN1950
Proper Shipping Name (TDG)	: AEROSOLS
TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gas
TDG Special Provisions	 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Transport by sea	
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1
UN-No. (IMDG)	: 1950
Proper Shipping Name (IMDG)	: AEROSOLS
Class (IMDG)	: 2 - Gases
Air transport	
Transport document description (IATA)	: UN 1950 Aerosols, flammable, 2.1
UN-No. (IATA)	: 1950
Proper Shipping Name (IATA)	: Aerosols, flammable
Class (IATA)	: 2 - Gases
SECTION 15: Regulatory information	

SECTION 15: Regulatory information

15.1. US Federal regulations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

acetone (67-64-1)			
Listed on the United States TSCA (Toxic Sub	stances Control Act) invento	v	
CERCLA RQ	5000 lb	5	
kieselguhr, soda ash flux calcined (68855-			
Listed on the United States TSCA (Toxic Sub			
, , , , , , , , , , , , , , , , , , ,	,	y	
reaction mass of ethylbenzene, m-xylene a			
Listed on the United States TSCA (Toxic Subs	stances Control Act) invento	У	-
n-butyl acetate (123-86-4)			
Listed on the United States TSCA (Toxic Subs	,	у	
CERCLA RQ	5000 lb		
reaction mass of α-3-(3-(2H-benzotriazol-2- benzotriazol-2-yl)-5-tert-butyl-4-hydroxyph hydroxyphenyl)propionyloxypoly(oxyethyl	enyl)propionyl-ω-3-(3-(2H-	henyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3- penzotriazol-2-yl)-5-tert-butyl-4-	3-(2H-
Listed on the United States TSCA (Toxic Sub	stances Control Act) invento	у	
EPA TSCA Regulatory Flag	name but is considered regardless of the amou PMN - PMN - indicates	polymeric substance containing no free-radical initiator in it to cover the designated polymer made with any free-radic nt used. a commenced PMN substance. ubstance exempt from reporting under the Chemical Data	al initiator
reaction mass of bis(1,2,2,6,6-pentamethyl	-4-piperidyl) sebacate and	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (106	5336-91-5)
Listed on the United States TSCA (Toxic Sub	stances Control Act) invento	У	
hexamethylene diisocyanate oligomers (28	3182-81-2)		
Listed on the United States TSCA (Toxic Sub	stances Control Act) invento	у	
EPA TSCA Regulatory Flag	XU - XU - indicates a s Rule, (40 CFR 711).	ubstance exempt from reporting under the Chemical Data	Reporting
carbon black (1333-86-4)			
Listed on the United States TSCA (Toxic Sub	stances Control Act) invento	у	
15.2. International regulations			
CANADA			
acetone (67-64-1)			
Listed on the Canadian DSL (Domestic Subst	ances List)		
kieselguhr, soda ash flux calcined (68855-	54-9)		
Listed on the Canadian DSL (Domestic Subst	•		
reaction mass of ethylbenzene, m-xylene a	and n-xylene		
Listed on the Canadian DSL (Domestic Subst			
n-butyl acetate (123-86-4)			
Listed on the Canadian DSL (Domestic Subst	ances List)		
Υ.	,		
reaction mass of α-3-(3-(2H-benzotriazol-2- benzotriazol-2-yl)-5-tert-butyl-4-hydroxyph hydroxyphenyl)propionyloxypoly(oxyethyl	enyl)propionyl-ω-3-(3-(2H-	henyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3- penzotriazol-2-yl)-5-tert-butyl-4-	3-(2H-
Listed on the Canadian DSL (Domestic Subst	ances List)		
reaction mass of bis(1,2,2,6,6-pentamethyl	-4-piperidyl) sebacate and	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (106	5336-91-5)
Listed on the Canadian DSL (Domestic Subst			,
hexamethylene diisocyanate oligomers (28	3182-81-2)		
Listed on the Canadian DSL (Domestic Subst	•		
, , , , , , , , , , , , , , , , , , ,			
carbon black (1333-86-4)	in the second se		
Listed on the Canadian DSL (Domestic Subst	andes Lisij		
EU-Regulations No additional information available			
07/01/2021	EN (English US)	SDS ID: RLSBAL-R-US-SDS	11/1:

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

This product can expose you to carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
carbon black(1333-86- 4)	Х					

Component	State or local regulations
kieselguhr, soda ash flux calcined(68855-54-9)	U.S Pennsylvania - RTK (Right to Know) List
n-butyl acetate(123-86-4)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S. – New York City – Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
acetone(67-64-1)	U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City – Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List
carbon black(1333-86-4)	U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date	: 06/21/2018
NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA reactivity	: 3 - Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction but that require a strong initiating source or must be heated under confinement before initiation.

Indication of cha Section	Changed item	Change	Comments
000000			
	Supersedes	Added	
	Revision date	Modified	
	Precautionary statements (GHS US)	Modified	
	Hazard pictograms (GHS US)	Modified	
	Hazard statements (GHS US)	Modified	
2.1	GHS-US classification	Modified	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3	Composition/Information on	Modified	
	ingredients		

SDS US GHS (GHS HazCom2012)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.