

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Product Reference code:according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Ref. (EU): UPEGF-SDS Issue date: 30/03/2015 Revision date: 17/11/2022 Supersedes version of: 17/03/2022 Version: 5.1

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form Trade name UFI Product code Type of product Product group	<ul> <li>Mixture</li> <li>EXTRA GOLD FINE POLYESTER FILLER</li> <li>N891-Q0DP-G00X-9XJY</li> <li>UPEGF/BL, UPEGF/2, DIS/UPEGF</li> <li>Fillers</li> <li>Bodyfiller</li> </ul>
Product group	: Bodyfiller

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category Use of the substance/mixture Function or use category Industrial use,Professional useFillers, putties, plasters, modelling clay

: Fillers

#### 1.2.2. Uses advised against

No additional information available

#### **1.3. Details of the supplier of the safety data sheet**

#### Manufacturer

U-POL Limited Ltd Denington Road GB– NN8 2QH Wellingborough – Northamptonshire United Kingdom T +44 (0) 1933 230310 technicalsupport@u-pol.com Importer U-POL Netherlands B.V. B.V. Hoorgoorddreef 15 NL– 1101BA Amsterdam Netherlands T +31 20 240 2216 technicalsupport@u-pol.com - www.u-pol.com

#### 1.4. Emergency telephone number

Emergency number

: CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours (www.gpoutofhours.h scni.net)

SECTION 2: Hazards identification		
2.1. Classification of the substance or mixture		
Classification according to Regulation (EC) No. 1272/2008 [CLP]		
Skin corrosion/irritation, Category 2	H315	
Serious eye damage/eye irritation, Category 2	H319	
Reproductive toxicity, Category 2	H361	
Specific target organ toxicity — Repeated exposure, Category 1	H372	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

Suspected of damaging the unborn child. Causes damage to organs (hearing organs) through prolonged or repeated exposure (inhalation). Causes skin irritation. Causes serious eye irritation.

#### 2.2. Label elements Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (CLP) GHS07 GHS08 Signal word (CLP) : Danger styrene Contains : Hazard statements (CLP) : H315 - Causes skin irritation. H319 - Causes serious eye irritation. H361 - Suspected of damaging fertility or the unborn child. H372 - Causes damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled). Precautionary statements (CLP) : P201 - Obtain special instructions before use. P264 - Wash hands thoroughly after handling. P280 - Wear eye protection, protective clothing, protective gloves. P308+P313 - IF exposed or concerned: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
styrene (100-42-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures			
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene (Note D)	CAS-No.: 100-42-5 EC-No.: 202-851-5 EC Index-No.: 601-026-00-0 REACH-no: 01-2119457861- 32	10 – 20	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu m]$	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379- 17	1 – 2.5	Carc. 2, H351

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.	
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.	
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects after skin contact	: Irritation.	
Symptoms/effects after eye contact	: Eye irritation.	
4.3. Indication of any immediate medical attention and special treatment needed		

Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Water spray. Dry powder. Foam.	
5.2. Special hazards arising from the substance or mixture		
Hazardous decomposition products in case of fire	: Toxic fumes may be released.	
5.3. Advice for firefighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Remove ignition sources. No open flames. No smoking.	
6.1.1. For non-emergency personnel		
Protective equipment	: Safety glasses. Protective clothing. Gloves.	
Emergency procedures	: Ventilate spillage area. Do not breathe vapours, fume. Avoid contact with skin and eyes.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for contain	ment and cleaning up	
For containment	: Contain released product, collect/pump into suitable containers. Collect spillage.	
Methods for cleaning up	<ul> <li>Mechanically recover the product. Notify authorities if product enters sewers or public waters.</li> </ul>	
Other information	: Dispose of materials or solid residues at an authorized site.	
6.4. Reference to other sections		

For further information refer to section 13.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
	<ul> <li>Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapours, fume. Avoid contact with skin and eyes.</li> <li>Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.</li> </ul>	
7.2. Conditions for safe storage, including any incompatibilities		
Storage temperature:Storage area:	Store locked up. Store in a well-ventilated place. Keep cool. < 25 °C Store in a well-ventilated place. Keep only in original container.	

7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

styrene (100-42-5)	
Ireland - Occupational Exposure Limits	
Local name	Styrene [Phenylethylene, Vinyl benzene]
OEL TWA [1]	85 mg/m³
OEL TWA [2]	20 ppm

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

styrene (100-42-5)		
OEL STEL	170 mg/m³	
OEL STEL [ppm]	40 ppm	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Styrene	
WEL TWA (OEL TWA) [1]	430 mg/m <sup>3</sup>	
WEL TWA (OEL TWA) [2]	100 ppm	
WEL STEL (OEL STEL)	1080 mg/m³	
WEL STEL (OEL STEL) [ppm]	250 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Ireland - Occupational Exposure Limits		
Local name	Titanium dioxide	
OEL TWA [1]	10 mg/m³ total inhalable dust 4 mg/m³ respirable dust	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Titanium dioxide	
WEL TWA (OEL TWA) [1]	10 mg/m³ 4 mg/m³	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

#### 8.1.2. Recommended monitoring procedures

No additional information available

## 8.1.3. Air contaminants formed

## No additional information available

### 8.1.4. DNEL and PNEC

styrene (100-42-5)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	289 mg/m³
Acute - local effects, inhalation	306 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	406 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	85 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	174.25 mg/m³
Acute - local effects, inhalation	182.75 mg/m³
Long-term - systemic effects,oral	2.1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	10.2 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day

## Safety Data Sheet

styrene (100-42-5)	
PNEC (Water)	
PNEC aqua (freshwater)	0.028 mg/l
PNEC aqua (marine water)	0.014 mg/l
PNEC aqua (intermittent, freshwater)	0.04 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.614 mg/kg dwt
PNEC sediment (marine water)	0.307 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.2 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	5 mg/l
phthalic anhydride (85-44-9)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	10 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	32.2 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	8.6 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	5 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	1 mg/l
PNEC aqua (marine water)	0.1 mg/l
PNEC aqua (intermittent, freshwater)	5.6 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.8 mg/kg dwt
PNEC sediment (marine water)	0.38 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.173 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
ethanediol; ethylene glycol (107-21-1)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	106 mg/kg bodyweight/day
Long-term - local effects, inhalation	35 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, dermal	53 mg/kg bodyweight/day
Long-term - local effects, inhalation	7 mg/m <sup>3</sup>
	-

## Safety Data Sheet

ethanediol; ethylene glycol (107-21-1)		
PNEC (Water)		
PNEC aqua (freshwater)	10 mg/l	
PNEC aqua (marine water)	1 mg/l	
PNEC aqua (intermittent, freshwater)	10 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	37 mg/kg dwt	
PNEC sediment (marine water)	3.7 mg/kg dwt	
PNEC (Soil)		
PNEC soil	1.53 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	199.5 mg/l	
1-methoxy-2-propanol (107-98-2)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	553.5 mg/m³	
Acute - local effects, inhalation	553.5 mg/m³	
Long-term - systemic effects, dermal	183 mg/m <sup>3</sup>	
Long-term - systemic effects, inhalation	369 mg/m <sup>3</sup>	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	33 mg/kg bw/day	
Long-term - systemic effects, inhalation	43.9 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	78 mg/kg bw/day	
PNEC (Water)		
PNEC aqua (freshwater)	10 mg/l	
PNEC aqua (marine water)	1 mg/l	
PNEC aqua (intermittent, freshwater)	100 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	52.3 mg/kg dwt	
PNEC sediment (marine water)	5.2 mg/kg dwt	
PNEC (Soil)		
PNEC soil	4.59 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
dipropylene glycol monomethyl ether (34590-94-8)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	283 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	308 mg/m <sup>3</sup>	
DNEL/DMEL (General population)	·	
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	

## Safety Data Sheet

dipropylene glycol monomethyl ether (34590-94-8)		
Long-term - systemic effects, inhalation	37.2 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	121 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	19 mg/l	
PNEC aqua (marine water)	1.9 mg/l	
PNEC aqua (intermittent, freshwater)	190 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	70.2 mg/kg dwt	
PNEC sediment (marine water)	7.02 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.74 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	4168 mg/l	
Xylene (1330-20-7)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	289 mg/m <sup>3</sup>	
Acute - local effects, inhalation	289 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	77 mg/m <sup>3</sup>	
Long-term - local effects, inhalation	77 mg/m <sup>3</sup>	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	174 mg/m <sup>3</sup>	
Acute - local effects, inhalation	174 mg/m <sup>3</sup>	
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	14.8 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day	
Long-term - local effects, inhalation	65.3 mg/m <sup>3</sup>	
PNEC (Water)		
PNEC aqua (freshwater)	0.327 mg/l	
PNEC aqua (marine water)	0.327 mg/l	
PNEC aqua (intermittent, freshwater)	0.327 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	12.46 mg/kg dwt	
PNEC sediment (marine water)	12.46 mg/kg dwt	
PNEC (Soil)	·	
PNEC soil	2.31 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	6.58 mg/l	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	293 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	77 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	15 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.1 mg/l	
PNEC aqua (marine water)	0.01 mg/l	
PNEC aqua (intermittent, freshwater)	0.1 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	13.7 mg/kg dwt	
PNEC sediment (marine water)	1.37 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.68 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	0.02 g/kg food	
PNEC (STP)		
PNEC sewage treatment plant	9.6 mg/l	

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

## Eye protection:

Safety glasses

Eye protection			
Type         Field of application         Characteristics         Standard			
Safety glasses	Dust	clear	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Protective gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR), Polyvinylalcohol (PVA), Viton	6 (> 480 minutes)	0.4		EN 374-3

#### Other skin protection

#### Materials for protective clothing:

Impermeable clothing

#### 8.2.2.3. Respiratory protection

#### **Respiratory protection:**

[In case of inadequate ventilation] wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
Breathing apparatus, Gas filters	Type A - High-boiling (>65 °C) organic compounds	Vapour protection	EN 140, EN 136, EN 143, EN 145, EN 149

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and	9.1. Information on basic physical and chemical properties		
Physical state	: Solid		
Colour	: Beige.		
Appearance	: Paste.		
Odour	: aromatic.		
Odour threshold	: Not available		
Melting point	: Not available		
Freezing point	: Not applicable		
Boiling point	: Not available		
Flammability	: Non flammable.		
Explosive limits	: Not applicable		
Lower explosion limit	: Not applicable		
Upper explosion limit	: Not applicable		
Flash point	: 32 °C (does not sustain combustion)		
Auto-ignition temperature	: Not applicable		
Decomposition temperature	: Not available		
рН	: Not available		
pH solution	: Not available		
Viscosity, kinematic	: > 20.5 mm²/s		

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 1.81 (1.79 – 1.83) g/cm <sup>3</sup>
Relative density	: Not applicable
Relative vapour density at 20 °C	: Not applicable
Particle size	: Not available
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle aggregation state	: Not available
Particle agglomeration state	: Not available
Particle specific surface area	: Not available
Particle dustiness	: Not available
9.2. Other information	
9.2.1. Information with regard to physical haza	rd classes
Not sustained combustibility	: Yes

#### 9.2.2. Other safety characteristics

VOC content : 221 g/l

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** 

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

**10.5. Incompatible materials** 

No additional information available

**10.6. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (dermal)	Not classified Not classified Not classified
styrene (100-42-5)	
LD50 oral rat	5000 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	11.8 mg/l (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours))

## Safety Data Sheet

oxirane, 2-methyl-, polymer with oxirane, mono[(diethylamino)alkyl] ether (68511-96-6)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000	
iron(III) oxide (1309-37-1)		
LD50 oral rat	> 10000 mg/kg bodyweight (Rat, Male, Experimental value, Oral)	
bisphenol-A-(epichlorhydrin), epoxy resin (25	068-38-6)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))	
phthalic anhydride (85-44-9)		
LD50 oral rat	1530 mg/kg bodyweight Animal: rat, Animal sex: male	
LD50 dermal rabbit	> 3160 mg/kg (Rabbit, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 2.14 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)	
1,4-naphthoquinone (130-15-4)		
LD50 oral rat	190 mg/kg bodyweight (Rat, Literature study, Oral)	
LD50 dermal rat	202 mg/kg	
LC50 Inhalation - Rat (Vapours)	0.046 mg/l/4h	
ethanediol; ethylene glycol (107-21-1)		
LD50 oral rat	7712 mg/kg bodyweight Animal: rat	
LD50 dermal	> 3500 mg/kg bodyweight (Mouse, Male / female, Experimental value, Dermal)	
LC50 Inhalation - Rat	> 2.5 mg/l (6 h, Rat, Male / female, Experimental value, Inhalation (aerosol))	
1-methoxy-2-propanol (107-98-2)		
LD50 oral rat	4016 mg/kg bodyweight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	13 g/kg	
dipropylene glycol monomethyl ether (34590-	94-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rat	> 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
Xylene (1330-20-7)		
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male	
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)	

## Safety Data Sheet

ethylbenzene (100-41-4)		
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)	
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))	
barium sulfate (7727-43-7)		
LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, Rat, Read-across, Dermal)	
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
LD50 oral rat	<ul> <li>&gt; 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline</li> <li>425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100</li> <li>(Acute Oral Toxicity)</li> </ul>	
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))	
dolomite (16389-88-1)		
LD50 oral rat	> 2000 mg/kg (OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), rat, female, Experimental value)	
talc (14807-96-6)		
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	> 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))	
magnesium carbonate (546-93-0)		
LD50 oral rat	<ul> <li>&gt; 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline</li> <li>420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)</li> </ul>	
Calcium carbonate (1317-65-3)		
LD50 oral rat	6450 mg/kg (Rat, Literature study, Oral)	
Serious eye damage/irritation:Respiratory or skin sensitisation:Germ cell mutagenicity:	Causes skin irritation. Causes serious eye irritation. Not classified Not classified Not classified.	
styrene (100-42-5)		
IARC group	2B - Possibly carcinogenic to humans	
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans	
bisphenol-A-(epichlorhydrin), epoxy resin (25	068-38-6)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)	

## Safety Data Sheet

bisphenol-A-(epichlorhydrin), epoxy resin (25068-38-6)		
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)	
phthalic anhydride (85-44-9)		
NOAEL (chronic, oral, animal/male, 2 years)	3570 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)	
NOAEL (chronic, oral, animal/female, 2 years)	1785 mg/kg bodyweight Animal: mouse, Animal sex: female, Remarks on results: other:Effect type: carcinogenicity (migrated information)	
ethanediol; ethylene glycol (107-21-1)		
NOAEL (chronic, oral, animal/male, 2 years)	1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)	
barium sulfate (7727-43-7)		
NOAEL (chronic, oral, animal/male, 2 years)	60 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)	
NOAEL (chronic, oral, animal/female, 2 years)	75 mg/kg bodyweight Animal: rat, Animal sex: female, Remarks on results: other:Effect type: carcinogenicity (migrated information)	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
phthalic anhydride (85-44-9)		
NOAEL (animal/male, F0/P)	3570 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Generation: all major orans incl. reproductive organs were examined (migrated information)	
NOAEL (animal/female, F0/P)	1785 mg/kg bodyweight Animal: mouse, Animal sex: female, Remarks on results: other:Generation: all major orans incl. reproductive organs were examined (migrated information)	
STOT-single exposure	Not classified	
styrene (100-42-5)		
STOT-single exposure	May cause respiratory irritation.	
phthalic anhydride (85-44-9)		
STOT-single exposure	May cause respiratory irritation.	
1,4-naphthoquinone (130-15-4)		
STOT-single exposure	May cause respiratory irritation.	
1-methoxy-2-propanol (107-98-2)		
STOT-single exposure	May cause drowsiness or dizziness.	
Xylene (1330-20-7)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure	: Causes damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).	
styrene (100-42-5)		
LOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight Animal: rat	
LOAEC (inhalation, rat, vapour, 90 days)	0.21 mg/l air Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

styrene (100-42-5)		
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat	
NOAEL (subchronic, oral, animal/male, 90 days)	10 mg/kg bodyweight Animal: mouse, Animal sex: male	
STOT-repeated exposure	Causes damage to organs (hearing sense) through prolonged or repeated exposure (if inhaled).	
phthalic anhydride (85-44-9)		
LOAEL (oral, rat, 90 days)	2500 mg/kg bodyweight Animal: rat, Animal sex: male	
ethanediol; ethylene glycol (107-21-1)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
1-methoxy-2-propanol (107-98-2)		
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)	
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	
dipropylene glycol monomethyl ether (34590	-94-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:KANPOGYO No.700, YAKUHATSU No. 1039.61, and KIKYKU No. 1014.	
NOAEL (dermal, rat/rabbit, 90 days)	2850 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)	
Xylene (1330-20-7)		
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
ethylbenzene (100-41-4)		
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)	
STOT-repeated exposure	May cause damage to organs (hearing sense) through prolonged or repeated exposure.	
Aspiration hazard :	Not classified	
EXTRA GOLD FINE POLYESTER FILLER		
Viscosity, kinematic	> 20.5 mm <sup>2</sup> /s	
11.2. Information on other hazards		

No additional information available

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long-term : (chronic)	Not classified
styrene (100-42-5)	
LC50 - Fish [1]	10 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	4.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	6.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
LOEC (chronic)	2.06 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	1.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

styrene (100-42-5)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Chemical oxygen demand (COD)	2.8 g O <sub>2</sub> /g substance	
ThOD	3.07 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	0.42 (Literature study)	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	

### 12.3. Bioaccumulative potential

styrene (100-42-5)	
BCF - Fish [1]	74 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.96 (Practical experience/observation, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil	
styrene (100-42-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.55 (log Koc, Estimated value)
Ecology - soil	Low potential for adsorption in soil.
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Ecology - soil	Low potential for mobility in soil.

#### 12.5. Results of PBT and vPvB assessment

Component	
styrene (100-42-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Regional legislation (waste) Waste treatment methods	<ul><li>Disposal must be done according to official regulations.</li><li>Dispose of contents/container in accordance with licensed collector's sorting instructions.</li></ul>
SECTION 14: Transport information	
In accordance with ADR / IMDG / IATA / ADN / RID	
14.1. UN number or ID number	
UN-No. (ADR) UN-No. (IMDG) UN-No. (IATA) UN-No. (ADN) UN-No. (RID)	<ul> <li>Not regulated</li> <li>Not regulated</li> <li>Not regulated</li> <li>Not regulated</li> <li>Not regulated</li> </ul>
14.2. UN proper shipping name	
Proper Shipping Name (ADR) Proper Shipping Name (IMDG) Proper Shipping Name (IATA) Proper Shipping Name (ADN)	<ul> <li>Not regulated</li> <li>Not regulated</li> <li>Not regulated</li> <li>Not regulated</li> <li>Not regulated</li> </ul>

## 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)

Proper Shipping Name (RID)

: Not regulated

: Not regulated

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	lion (EC) 1907/2008 amended b	
IMDG Transport hazard class(es) (I	IMDG) :	Not regulated
IATA Transport hazard class(es) (I	IATA) :	Not regulated
ADN Transport hazard class(es) (a	ADN) :	Not regulated
<b>RID</b> Transport hazard class(es) (I	RID) :	Not regulated
14.4. Packing group		
Packing group (ADR) Packing group (IMDG) Packing group (IATA) Packing group (ADN) Packing group (RID)	:	Not regulated Not regulated Not regulated Not regulated Not regulated
14.5. Environmental haz	zards	
Dangerous for the environme Marine pollutant Other information	:	No No No supplementary information available
14.6. Special precaution	ns for user	
Overland transport Not regulated		
Transport by sea Not regulated		
Air transport Not regulated		
Inland waterway transport Not regulated		
Rail transport Not regulated		
14.7. Maritime transport in bulk according to IMO instruments		
Not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and	environmental regulat	ions/legislation specific for the substance or mixture
15.1.1. EU-Regulations		
EU restriction list (REA	CH Annex XVII)	
Reference code	Applicable on	Entry title or description
3(a)	styrene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or

and 2, 2.15 types A to F

categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	styrene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	styrene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	styrene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content

: 221 g/l

#### 15.1.2. National regulations

No additional information available

**15.2. Chemical safety assessment** 

No chemical safety assessment has been carried out

#### **SECTION 16: Other information**

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

## Safety Data Sheet

Abbreviations and acronyms:	
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

### Safety Data Sheet

#### according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.